

Appendix 4B

Material Volume Calculations



Client Greensource
Project Number 22635
Project Name Ballinlee WF
Project Manager Aileen O'Connor

Description:

Tables populated from EIAR Calculations Tab and inserted into EIAR chapters

Table: Permanent Land Use Requirements

| equirements | | |
|--|---|--|
| Description | Unit | Quantity |
| Wind turbine hardstand area for vehicle during construction and operational phase 1797m2 | m2 | 30549 |
| Existing, new and upgraded access tracks both founded and floated required for construction and operational phases. 10.8km x 5.5m | m2 | 59400 |
| Compound including fences, grid connection access tracks & attenuation for operational phase | m2 | 9350 |
| Compound + maintenace compound including attenuation for operational phase | m2 | 3500 |
| Permanent met mast + vehicle hardstand for operational phase | m2 | 806 |
| 9 No. permanent deposition areas throughout site | m2 | 43627 |
| Permanent sediment settlement ponds used for the operational phase throughout the site each pond is 24m2 and is sized to treat an area of 2400m2 | m2 | 2400 |
| | Description Wind turbine hardstand area for vehicle during construction and operational phase 1797m2 Existing, new and upgraded access tracks both founded and floated required for construction and operational phases. 10.8km x 5.5m Compound including fences, grid connection access tracks & attenuation for operational phase Compound + maintenace compound including attenuation for operational phase Permanent met mast + vehicle hardstand for operational phase 9 No. permanent deposition areas throughout site Permanent sediment settlement ponds used for the operational phase throughout the site each pond is 24m2 and | Description Unit Wind turbine hardstand area for vehicle during construction and operational phase 1797m2 m2 Existing, new and upgraded access tracks both founded and floated required for construction and operational phases. m2 10.8km x 5.5m m2 Compound including fences, grid connection access tracks & attenuation for operational phase m2 Compound + maintenace compound including attenuation for operational phase m2 Permanent met mast + vehicle hardstand for operational phase m2 9 No. permanent deposition areas throughout site m2 Permanent sediment settlement ponds used for the operational phase throughout the site each pond is 24m2 and m2 |

Table: Temporary Land Use Requirements

| Table. Telliporary Land Ose N | is a facility of the second of | | |
|-------------------------------|--|------|----------|
| Item | Description | Unit | Quantity |
| Construction Compound | 3 No. Temporary construction compounds to be installed/removed as part of the construction phase Site compound No1. 4750m2 Site compound No2. 4750m2 Site compound No3. 1375m2 | m2 | 10875 |
| Borrow Pit | 2 No. temporary borrow pits for site won aggregate, to be infilled as part of construction phase Northern Borrow Pit 35200m2 Southern Borrow Pit 25500m2 | m2 | 60700 |
| Sediment Settlement Ponds | Temprary sediment settlement ponds used for the construction phase throughout the site each pond is 24m2 and is sized to treat an area of 2400m2 | m2 | 1440 |
| Wind Turbine Construction | Wind turbine blade set down area 2x 80m2 and the wind turbine crane hardstand area 2x 174m2 | m2 | 8636 |
| Deposition Areas | 2 No. temporary material deposition areas adjacent to borrow pits Northern deposition area 21000m2 Southern deposition area 22750m2 | m2 | 43750 |

Table: Summary of Approximate Aggregate and Reinforced Steel Quantities

| Table out the state of the stat | | |
|--|--------|----------|
| Item | Unit | Quantity |
| Total volume of aggregate required (including site won and imported) | m3 | 167592 |
| Site won aggregate from onsite borrow pit | m3 | 99852 |
| Total volume of site won aggregate required | m3 | 99852 |
| Imported stone for turbine bases | m3 | 16905 |
| Imported stone for turbine hardstand | m3 | 7548 |
| Imported stone for access tracks | m3 | 9801 |
| Imported stone for temporary compound | m3 | 1320 |
| Imported stone for substation area | m3 | 10362 |
| Imported stone for independent power provider | m3 | 5313 |
| mported stone for met mast area | m3 | 532 |
| mported stone for internal cable route | m3 | 1203 |
| mported stone for external cable route | m3 | 14755 |
| Total volume of imported aggregate required | m3 | 67740 |
| Concrete for turbine bases | m3 | 19097 |
| Concrete for substation | m3 | 63 |
| Concrete for independent power provider | m3 | 66 |
| Concrete for met mast | m3 | 12 |
| Concrete for internal cable route | m3 | 4922 |
| Concrete for external cable route | m3 | 11426 |
| Total volume concrete required | m3 | 35586 |
| Reinforced steel for turbine bases | tonnes | 2865 |
| Reinforced steel for substation | tonnes | 8 |
| | | |

| Reinforced steel for independent power provider | tonnes | 8 |
|---|--------|------|
| Reinforced steel for met mast | tonnes | 1 |
| Total volume of imported steel reinforcement required | tonnes | 2882 |

Table: Excavation and Material Volumes

| ltem | Unit | Quantity |
|---|--------|----------|
| Total Excavation Volume | m3 | 321758 |
| Excavated Material from the Wind Farm Site | m3 | 296918 |
| Excavated Material from External Grid Route | m3 | 24840 |
| Total Aggregate Volume | m3 | 167592 |
| Imported Aggregate | m3 | 67740 |
| Site Won Aggregate | m3 | 99852 |
| Total Concrete Volume | m3 | 35586 |
| Total Reinforcement Volume | Tonnes | 2882 |