

NOTES:

GENERAL

1. Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
2. All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / microcrosing.
3. Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
4. All drainage management features shown should be read in conjunction with relevant typical detail drawings.

POLLUTION PREVENTION

5. Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving watercourses.
6. Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
7. Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
8. Direct discharge of untreated track drainage to watercourses shall not be permitted.
9. DO NOT pump water direct to watercourses.
10. DO NOT strip vegetation from existing ditches unless absolutely necessary.
11. If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be bunded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE

12. Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations
13. Settlement/attenuation ponds are retained following completion of construction activities.
14. Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
15. Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
16. Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
17. Swale breakouts to be installed at regular intervals (every c. 80m).


WATERCOURSE & TRACK DRAINAGE CROSSINGS

18. The minimum pipe diameter for any track drainage crossing shall be 450mm.
19. All HDPE pipes shall be twinwall type, BBA HAPAS approved.
20. All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
21. Refer to Watercourse Crossing Schedule for min. soffit levels.

MAINTENANCE

22. The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
23. Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.


Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m
1	Attenuated discharge overland by level spreader	1022	2	14	6 x 3 x 0.8



- LEGEND**
- EIAR Boundary
 - Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
 - Hydrology Features & Constraints**
 - Water Feature Constraints**
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features**
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing

TREATED CLEAN WATER TO BE DISCHARGED OVERLAND BY LEVEL SPREADER, ATTENUATED TO GREENFIELD (QBAR) EQUIVALENT RATE.

Basin 1



CARRIGEEN RENEWABLE ENERGY DEVELOPMENT - PERMANENT DRAINAGE				
DESCRIPTION LAYOUT SHEET 1				
PROJECT / FIGURE NO. M02232-01_DNG_1				
DRAWN BY	SCALE	REVISION	DATE	
DH	1:2000	1	26/03/2026	

DRAWING COPYRIGHT MCCLOY CONSULTING LTD. ALL RIGHTS RESERVED.

BACKGROUND MAP CONTAINS OPENSTREETMAP DATA © OSM CONTRIBUTORS (2026)

PLANNING DESIGN

NOTES:

GENERAL

1. Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
2. All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / microcrosing.
3. Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
4. All drainage management features shown should be read in conjunction with relevant typical detail drawings.

POLLUTION PREVENTION

5. Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving watercourses.
6. Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
7. Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
8. Direct discharge of untreated track drainage to watercourses shall not be permitted.
9. DO NOT pump water direct to watercourses.
10. DO NOT strip vegetation from existing ditches unless absolutely necessary.
11. If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be bunded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE

12. Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations
13. Settlement/attenuation ponds are retained following completion of construction activities.
14. Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
15. Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
16. Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
17. Swale breakouts to be installed at regular intervals (every c. 80m).


WATERCOURSE & TRACK DRAINAGE CROSSINGS

18. The minimum pipe diameter for any track drainage crossing shall be 450mm.
19. All HDPE pipes shall be twinwall type, BBA HAPAS approved.
20. All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
21. Refer to Watercourse Crossing Schedule for min. soffit levels.

MAINTENANCE

22. The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
23. Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.


Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m
2	Attenuated discharge to watercourse	7072	6.2	126	21 x 5 x 1.2
3	Attenuated discharge to watercourse	224	2	2	2 x 1.5 x 0.6



LEGEND

- EIAR Boundary
- Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
- Hydrology Features & Constraints**
 - Water Feature Constraints**
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features**
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing

Watercourse Crossing Ref	Min. Soffit (mOD)	Description
WX01	66.72	Clear span bridge or bottomless culvert



IE +353 (0) 1 5138963
 UK +44 (0) 28 9084 8694
 E: info@mcclloyconsulting.com
 W: www.mcclloyconsulting.com


CARRIGEEN RENEWABLE ENERGY DEVELOPMENT - PERMANENT DRAINAGE				
DESCRIPTION LAYOUT SHEET 2				
PROJECT / FIGURE NO. M02232-01_DNG_2				
DRAWN BY	SCALE	REVISION	DATE	
DH	1:2000	1	26/03/2026	

DRAWING COPYRIGHT MCCLOY CONSULTING LTD. ALL RIGHTS RESERVED.

BACKGROUND MAP CONTAINS OPENSTREETMAP DATA © OSM CONTRIBUTORS (2026)

PLANNING DESIGN

Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m
4	Attenuated discharge to watercourse	152	2	1	2 x 1 x 0.6
5	Attenuated discharge to watercourse	234	2	2	2 x 1.5 x 0.6
6	Attenuated discharge to watercourse	5165	4.5	96	16 x 5 x 1.2



LEGEND

- EIAR Boundary
- Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
- Hydrology Features & Constraints**
 - Water Feature Constraints
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing

Watercourse Crossing Ref	Min. Soffit (mOD)	Description
WX02	66.62	Clear span bridge or bottomless culvert

NOTES:

GENERAL

- Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
- All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / microcrosing.
- Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
- All drainage management features shown should be read in conjunction with relevant typical detail drawings.

POLLUTION PREVENTION

- Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving watercourses.
- Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
- Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
- Direct discharge of untreated track drainage to watercourses shall not be permitted.
- DO NOT pump water direct to watercourses.
- DO NOT strip vegetation from existing ditches unless absolutely necessary.
- If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be banded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE


- Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations
- Settlement/attenuation ponds are retained following completion of construction activities.
- Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
- Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
- Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
- Swale breakouts to be installed at regular intervals (every c. 80m).

WATERCOURSE & TRACK DRAINAGE CROSSINGS

- The minimum pipe diameter for any track drainage crossing shall be 450mm.
- All HDPE pipes shall be twinwall type, BBA HAPAS approved.
- All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
- Refer to Watercourse Crossing Schedule for min. soffit levels.

MAINTENANCE

- The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
- Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.



IE +353 (0) 1 5138963
UK +44 (0) 28 9084 8694
E: info@mcclloyconsulting.com
W: www.mcclloyconsulting.com

CARRIGEEN RENEWABLE ENERGY DEVELOPMENT - PERMANENT DRAINAGE				
DESCRIPTION				
LAYOUT SHEET 3				
PROJECT / FIGURE NO.				
M02232-01_DNG_3				
DRAWN BY	SCALE	REVISION	DATE	
DH	1:2000	1	26/03/2026	

DRAWING COPYRIGHT MCCLOY CONSULTING LTD. ALL RIGHTS RESERVED.

BACKGROUND MAP CONTAINS OPENSTREETMAP DATA © OSM CONTRIBUTORS (2026)

PLANNING DESIGN

NOTES:

GENERAL
 1. Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
 2. All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / microcrosing.
 3. Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
 4. All drainage management features shown should be read in conjunction with relevant typical detail drawings.


POLLUTION PREVENTION
 5. Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving watercourses.
 6. Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
 7. Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
 8. Direct discharge of untreated track drainage to watercourses shall not be permitted.
 9. DO NOT pump water direct to watercourses.
 10. DO NOT strip vegetation from existing ditches unless absolutely necessary.
 11. If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be banded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE
 12. Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations
 13. Settlement/attenuation ponds are retained following completion of construction activities.
 14. Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
 15. Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
 16. Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
 17. Swale breakouts to be installed at regular intervals (every c. 80m).

WATERCOURSE & TRACK DRAINAGE CROSSINGS
 18. The minimum pipe diameter for any track drainage crossing shall be 450mm.
 19. All HDPE pipes shall be twinwall type, BBA HAPAS approved.
 20. All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
 21. Refer to Watercourse Crossing Schedule for min. soffit levels.

MAINTENANCE
 22. The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
 23. Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.


Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m
7	Attenuated discharge overland by level spreader	4626	4.1	84	14 x 5 x 1.2
8	Attenuated discharge to watercourse	1000	2	12	5 x 3 x 0.8
9	Attenuated discharge to watercourse	6141	5.4	114	19 x 5 x 1.2



LEGEND

- EIAR Boundary
- Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
- Hydrology Features & Constraints**
 - Water Feature Constraints**
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features**
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing

Watercourse Crossing Ref	Min. Soffit (mOD)	Description
WX03	66	Clear span bridge or bottomless culvert



NOTES:

GENERAL

1. Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
2. All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / microsting.
3. Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
4. All drainage management features shown should be read in conjunction with relevant typical detail drawings.

POLLUTION PREVENTION

5. Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving watercourses.
6. Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
7. Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
8. Direct discharge of untreated track drainage to watercourses shall not be permitted.
9. DO NOT pump water direct to watercourses.
10. DO NOT strip vegetation from existing ditches unless absolutely necessary.
11. If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be bunded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE

12. Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations
13. Settlement/attenuation ponds are retained following completion of construction activities.
14. Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
15. Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
16. Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
17. Swale breakouts to be installed at regular intervals (every c. 80m).


WATERCOURSE & TRACK DRAINAGE CROSSINGS

18. The minimum pipe diameter for any track drainage crossing shall be 450mm.
19. All HDPE pipes shall be twinwall type, BBA HAPAS approved.
20. All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
21. Refer to Watercourse Crossing Schedule for min. soffit levels.

MAINTENANCE

22. The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
23. Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.


Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m
10	Attenuated discharge overland by level spreader	681	2	6	4 x 2 x 0.8



LEGEND

- EIAR Boundary
- Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
- Hydrology Features & Constraints**
 - Water Feature Constraints**
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features**
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing

Watercourse Crossing Ref	Min. Soffit (mOD)	Description
WX04	65.8	Clear span bridge or bottomless culvert



IE +353 (0) 1 5138963
 UK +44 (0) 28 9084 8694
 E: info@mcclloyconsulting.com
 W: www.mcclloyconsulting.com

CARRIGEEN RENEWABLE ENERGY DEVELOPMENT - PERMANENT DRAINAGE				
DESCRIPTION LAYOUT SHEET 6				
PROJECT / FIGURE NO. M02232-01_DNG_5				
DRAWN BY	SCALE	REVISION	DATE	
DH	1:2000	1	26/03/2026	

DRAWING COPYRIGHT MCCLOY CONSULTING LTD. ALL RIGHTS RESERVED.

BACKGROUND MAP CONTAINS OPENSTREETMAP DATA © OSM CONTRIBUTORS (2026)

PLANNING DESIGN

NOTES:

GENERAL

1. Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
2. All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / microtopography TO GREENFIELD (QBAR) EQUIVALENT RATE.
3. Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
4. All drainage management features shown should be read in conjunction with relevant typical detail drawings.

POLLUTION PREVENTION

5. Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving watercourses.
6. Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
7. Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
8. Direct discharge of untreated track drainage to watercourses shall not be permitted.
9. DO NOT pump water direct to watercourses.
10. DO NOT strip vegetation from existing ditches unless absolutely necessary.
11. If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be banded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE

12. Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations.
13. Settlement/attenuation ponds are retained following completion of construction activities.
14. Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
15. Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
16. Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
17. Swale breakouts to be installed at regular intervals (every c. 80m).


WATERCOURSE & TRACK DRAINAGE CROSSINGS

18. The minimum pipe diameter for any track drainage crossing shall be 450mm.
19. All HDPE pipes shall be twinwall type, BBA HAPAS approved.
20. All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
21. Refer to Watercourse Crossing Schedule for min. soffit levels.

MAINTENANCE

22. The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
23. Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.

Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m.
8	Attenuated discharge to watercourse	1000	2	12	5 x 3 x 0.8
9	Attenuated discharge to watercourse	6141	5.4	114	19 x 5 x 1.2
11	Attenuated discharge overland by level spreader	6068	5.3	108	18 x 5 x 1.2



LEGEND

- EIAR Boundary
- Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
- Hydrology Features & Constraints**
 - Water Feature Constraints**
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features**
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing

Watercourse Crossing Ref	Min. Soffit (mOD)	Description
WX03	66	Clear span bridge or bottomless culvert



CARRIGEEN RENEWABLE ENERGY DEVELOPMENT - PERMANENT DRAINAGE			
DESCRIPTION			
LAYOUT SHEET 4			
PROJECT / FIGURE NO.			
M02232-01_DNG_6			
DRAWN BY	SCALE	REVISION	DATE
DH	1:2000	1	26/03/2026

DRAWING COPYRIGHT MCCLOY CONSULTING LTD. ALL RIGHTS RESERVED.

BACKGROUND MAP CONTAINS OPENSTREETMAP DATA © OSM CONTRIBUTORS (2026)

PLANNING DESIGN

NOTES:

GENERAL

1. Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
2. All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / microcrosing.
3. Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
4. All drainage management features shown should be read in conjunction with relevant typical detail drawings.

POLLUTION PREVENTION

5. Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving watercourses.
6. Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
7. Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
8. Direct discharge of untreated track drainage to watercourses shall not be permitted.
9. DO NOT pump water direct to watercourses.
10. DO NOT strip vegetation from existing ditches unless absolutely necessary.
11. If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be banded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE


12. Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations
13. Settlement/attenuation ponds are retained following completion of construction activities.
14. Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
15. Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
16. Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
17. Swale breakouts to be installed at regular intervals (every c. 80m).

WATERCOURSE & TRACK DRAINAGE CROSSINGS


18. The minimum pipe diameter for any track drainage crossing shall be 450mm.
19. All HDPE pipes shall be twinwall type, BBA HAPAS approved.
20. All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
21. Refer to Watercourse Crossing Schedule for min. soffit levels.

MAINTENANCE

22. The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
23. Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.



Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m
11	Attenuated discharge overland by level spreader	6068	5.3	108	18 x 5 x 1.2



- LEGEND**
- EIAR Boundary
 - Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
 - Hydrology Features & Constraints**
 - Water Feature Constraints**
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features**
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing

IE +353 (0) 1 5138963
 UK +44 (0) 28 9084 8694
 E: info@mcclloyconsulting.com
 W: www.mcclloyconsulting.com

CARRIGEEN RENEWABLE ENERGY DEVELOPMENT - PERMANENT DRAINAGE				
DESCRIPTION LAYOUT SHEET 7				
PROJECT / FIGURE NO. M02232-01_DNG_7				
DRAWN BY	SCALE	REVISION	DATE	
DH	1:2000	1	26/03/2026	

DRAWING COPYRIGHT MCCLOY CONSULTING LTD. ALL RIGHTS RESERVED.

BACKGROUND MAP CONTAINS OPENSTREETMAP DATA © OSM CONTRIBUTORS (2026)

PLANNING DESIGN

576500 576600 576700 576800 576900 577000

NOTES:

GENERAL

1. Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
2. All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / microcrosing.
3. Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
4. All drainage management features shown should be read in conjunction with relevant typical detail drawings.

POLLUTION PREVENTION

5. Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving watercourses.
6. Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
7. Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
8. Direct discharge of untreated track drainage to watercourses shall not be permitted.
9. DO NOT pump water direct to watercourses.
10. DO NOT strip vegetation from existing ditches unless absolutely necessary.
11. If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be banded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE

12. Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations
13. Settlement/attenuation ponds are retained following completion of construction activities.
14. Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
15. Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
16. Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
17. Swale breakouts to be installed at regular intervals (every c. 80m).


WATERCOURSE & TRACK DRAINAGE CROSSINGS

18. The minimum pipe diameter for any track drainage crossing shall be 450mm.
19. All HDPE pipes shall be twinwall type, BBA HAPAS approved.
20. All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
21. Refer to Watercourse Crossing Schedule for min. soffit levels.

MAINTENANCE

22. The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
23. Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.


Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m
12	Attenuated discharge overland by level spreader	5366	4.7	96	16 x 5 x 1.2
13	Attenuated discharge to watercourse	6390	5.6	114	19 x 5 x 1.2
14	Attenuated discharge to watercourse	1820	2	30	10 x 3 x 1



LEGEND

- EIAR Boundary
- Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
- Hydrology Features & Constraints**
 - Water Feature Constraints**
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features**
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing

Watercourse Crossing Ref	Min. Soffit (mOD)	Description
WX05	68.4	Clear span bridge or bottomless culvert




IE +353 (0) 1 5138963
 UK +44 (0) 28 9084 8694
 E: info@mcclloyconsulting.com
 W: www.mcclloyconsulting.com

CARRIGEEN RENEWABLE ENERGY DEVELOPMENT - PERMANENT DRAINAGE				
DESCRIPTION LAYOUT SHEET 8				
PROJECT / FIGURE NO. M02232-01_DNG_8				
DRAWN BY	SCALE	REVISION	DATE	
DH	1:2000	1	26/03/2026	


DRAWING COPYRIGHT MCCLOY CONSULTING LTD. ALL RIGHTS RESERVED.

BACKGROUND MAP CONTAINS OPENSTREETMAP DATA © OSM CONTRIBUTORS (2026)

PLANNING DESIGN



Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m
13	Attenuated discharge to watercourse	6390	5.6	114	19 x 5 x 1.2
14	Attenuated discharge to watercourse	1820	2	30	10 x 3 x 1
15	Attenuated discharge overland by level spreader	333	2	2	2 x 1.5 x 0.8



LEGEND

- EIAR Boundary
- Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
- Hydrology Features & Constraints**
 - Water Feature Constraints**
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features**
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing

Watercourse Crossing Ref	Min. Soffit (mOD)	Description
WX05	68.4	Clear span bridge or bottomless culvert

NOTES:

GENERAL

- Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
- All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / microcrosing.
- Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
- All drainage management features shown should be read in conjunction with relevant typical detail drawings.

POLLUTION PREVENTION

- Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving watercourses.
- Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
- Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
- Direct discharge of untreated track drainage to watercourses shall not be permitted.
- DO NOT pump water direct to watercourses.
- DO NOT strip vegetation from existing ditches unless absolutely necessary.
- If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be banded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE

- Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations
- Settlement/attenuation ponds are retained following completion of construction activities.
- Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
- Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
- Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
- Swale breakouts to be installed at regular intervals (every c. 80m).

WATERCOURSE & TRACK DRAINAGE CROSSINGS

- The minimum pipe diameter for any track drainage crossing shall be 450mm.
- All HDPE pipes shall be twinwall type, BBA HAPAS approved.
- All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
- Refer to Watercourse Crossing Schedule for min. soffit levels.

MAINTENANCE

- The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
- Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.

REGULAR CROSS DRAINAGE CULVERTS (EVERY C. 40 M) TO FLOATED TRACK TO PRESERVE PEAT HYROLOGY.

NEW WATERCOURSE CROSSING TO ALLOW FOR ACCESS TRACK. CULVERT SIZED TO OPW SECTION 50 STANDARDS. REFER TO WATERCOURSE CROSSING SCHEDULE.

TREATED CLEAN WATER TO BE DISCHARGED TO WATERCOURSE. ATTENUATED TO GREENFIELD (QBAR) EQUIVALENT RATE.

TREATED CLEAN WATER TO BE DISCHARGED TO WATERCOURSE. ATTENUATED TO GREENFIELD (QBAR) EQUIVALENT RATE.

TREATED CLEAN WATER TO BE DISCHARGED OVERLAND BY LEVEL SPREADER. ATTENUATED TO GREENFIELD (QBAR) EQUIVALENT RATE.

REGULAR CROSS DRAINAGE CULVERTS (EVERY C. 40 M) TO FLOATED TRACK TO PRESERVE PEAT HYROLOGY.

CARRIGEEN RENEWABLE ENERGY DEVELOPMENT - PERMANENT DRAINAGE

DESCRIPTION LAYOUT SHEET 9

PROJECT / FIGURE NO. M02232-01_DNG_9

DRAWN BY	SCALE	REVISION	DATE
DH	1:2000	1	26/03/2026

DRAWING COPYRIGHT MCCLOY CONSULTING LTD. ALL RIGHTS RESERVED.

BACKGROUND MAP CONTAINS OPENSTREETMAP DATA © OSM CONTRIBUTORS (2026)



IE +353 (0) 1 5138963
 UK +44 (0) 28 9084 8694
 E: info@mcclloyconsulting.com
 W: www.mcclloyconsulting.com

PLANNING DESIGN

NOTES:

GENERAL

1. Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
2. All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / microcrosing.
3. Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
4. All drainage management features shown should be read in conjunction with relevant typical detail drawings.

POLLUTION PREVENTION

5. Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving watercourses.
6. Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
7. Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
8. Direct discharge of untreated track drainage to watercourses shall not be permitted.
9. DO NOT pump water direct to watercourses.
10. DO NOT strip vegetation from existing ditches unless absolutely necessary.
11. If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be banded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE

12. Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations
13. Settlement/attenuation ponds are retained following completion of construction activities.
14. Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
15. Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
16. Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
17. Swale breakouts to be installed at regular intervals (every c. 80m).


WATERCOURSE & TRACK DRAINAGE CROSSINGS

18. The minimum pipe diameter for any track drainage crossing shall be 450mm.
19. All HDPE pipes shall be twinwall type, BBA HAPAS approved.
20. All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
21. Refer to Watercourse Crossing Schedule for min. soffit levels.


MAINTENANCE

22. The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
23. Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.

Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m
16	Attenuated discharge overland by level spreader	717	2	8	4 x 2 x 1



- LEGEND**
- EIAR Boundary
 - Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
 - Hydrology Features & Constraints**
 - Water Feature Constraints**
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features**
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing



IE +353 (0) 1 5138963
 UK +44 (0) 28 9084 8694
 E: info@mcclloyconsulting.com
 W: www.mcclloyconsulting.com

CARRIGEEN RENEWABLE ENERGY DEVELOPMENT - PERMANENT DRAINAGE				
DESCRIPTION LAYOUT SHEET 10				
PROJECT / FIGURE NO. M02232-01_DNG_10				
DRAWN BY	SCALE	REVISION	DATE	
DH	1:2000	1	26/03/2026	

DRAWING COPYRIGHT MCCLOY CONSULTING LTD. ALL RIGHTS RESERVED.

BACKGROUND MAP CONTAINS OPENSTREETMAP DATA © OSM CONTRIBUTORS (2026)

PLANNING DESIGN

NOTES:

GENERAL

1. Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
2. All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / micro-siting.
3. Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
4. All drainage management features shown should be read in conjunction with relevant typical detail drawings.

POLLUTION PREVENTION

5. Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving (QBAR) watercourses.
6. Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
7. Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
8. Direct discharge of untreated track drainage to watercourses shall not be permitted.
9. DO NOT pump water direct to watercourses.
10. DO NOT strip vegetation from existing ditches unless absolutely necessary.
11. If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be banded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE

12. Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations
13. Settlement/attenuation ponds are retained following completion of construction activities.
14. Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
15. Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
16. Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
17. Swale breakouts to be installed at regular intervals (every c. 80m).


WATERCOURSE & TRACK DRAINAGE CROSSINGS

18. The minimum pipe diameter for any track drainage crossing shall be 450mm.
19. All HDPE pipes shall be twinwall type, BBA HAPAS approved.
20. All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
21. Refer to Watercourse Crossing Schedule for min. soffit levels.

MAINTENANCE

22. The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
23. Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.


Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m
17	Attenuated discharge to watercourse	12003	10.5	221	23 x 8 x 1.2
18	Attenuated discharge to watercourse	995	2	12	5 x 3 x 0.8
19	Attenuated discharge to watercourse	6643	5.8	120	20 x 5 x 1.2



LEGEND

- EIAR Boundary
- Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
- Hydrology Features & Constraints**
 - Water Feature Constraints**
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features**
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing

Watercourse Crossing Ref	Min. Soffit (mOD)	Description
WX06	68.19	Clear span bridge or bottomless culvert



IE +353 (0) 1 5138963
 UK +44 (0) 28 9084 8694
 E: info@mcclloyconsulting.com
 W: www.mcclloyconsulting.com

CARRIGEEN RENEWABLE ENERGY DEVELOPMENT - PERMANENT DRAINAGE				
DESCRIPTION LAYOUT SHEET 11				
PROJECT / FIGURE NO. M02232-01_DNG_11				
DRAWN BY	SCALE	REVISION	DATE	
DH	1:2000	1	26/03/2026	

DRAWING COPYRIGHT MCCLOY CONSULTING LTD. ALL RIGHTS RESERVED.

BACKGROUND MAP CONTAINS OPENSTREETMAP DATA © OSM CONTRIBUTORS (2026)

PLANNING DESIGN

NOTES:

GENERAL

- Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
- All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / microcrosing.
- Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
- All drainage management features shown should be read in conjunction with relevant typical detail drawings.

POLLUTION PREVENTION

- Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving watercourses.
- Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
- Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
- Direct discharge of untreated track drainage to watercourses shall not be permitted.
- DO NOT pump water direct to watercourses.
- DO NOT strip vegetation from existing ditches unless absolutely necessary.
- If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be banded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE

- Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations
- Settlement/attenuation ponds are retained following completion of construction activities.
- Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
- Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
- Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
- Swale breakouts to be installed at regular intervals (every c. 80m).


WATERCOURSE & TRACK DRAINAGE CROSSINGS

- The minimum pipe diameter for any track drainage crossing shall be 450mm.
- All HDPE pipes shall be twinwall type, BBA HAPAS approved.
- All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
- Refer to Watercourse Crossing Schedule for min. soffit levels.


MAINTENANCE

- The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
- Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.

Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m
19	Attenuated discharge to watercourse	6643	5.8	120	20 x 5 x 1.2



- LEGEND**
- EIAR Boundary
 - Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
 - Hydrology Features & Constraints**
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features**
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing



CARRIGEEN RENEWABLE ENERGY DEVELOPMENT - PERMANENT DRAINAGE			
DESCRIPTION		LAYOUT SHEET 12	
PROJECT / FIGURE NO.		M02232-01_DNG_12	
DRAWN BY	SCALE	REVISION	DATE
DH	1:2000	1	26/03/2026

DRAWING COPYRIGHT MCCLOY CONSULTING LTD. ALL RIGHTS RESERVED.

BACKGROUND MAP CONTAINS OPENSTREETMAP DATA © OSM CONTRIBUTORS (2026)

PLANNING DESIGN

NOTES:

GENERAL

1. Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
2. All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / microcrosing.
3. Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
4. All drainage management features shown should be read in conjunction with relevant typical detail drawings.

POLLUTION PREVENTION

5. Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving watercourses.
6. Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
7. Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
8. Direct discharge of untreated track drainage to watercourses shall not be permitted.
9. DO NOT pump water direct to watercourses.
10. DO NOT strip vegetation from existing ditches unless absolutely necessary.
11. If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be banded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE

12. Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations
13. Settlement/attenuation ponds are retained following completion of construction activities.
14. Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
15. Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
16. Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
17. Swale breakouts to be installed at regular intervals (every c. 80m).


WATERCOURSE & TRACK DRAINAGE CROSSINGS

18. The minimum pipe diameter for any track drainage crossing shall be 450mm.
19. All HDPE pipes shall be twinwall type, BBA HAPAS approved.
20. All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
21. Refer to Watercourse Crossing Schedule for min. soffit levels.


MAINTENANCE

22. The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
23. Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.

Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m
20	Attenuated discharge overland by level spreader	6289	5.5	114	19 x 5 x 1.2



- LEGEND**
- EIAR Boundary
 - Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
 - Hydrology Features & Constraints**
 - Water Feature Constraints**
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features**
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing




IE +353 (0) 1 5138963
 UK +44 (0) 28 9084 8694
 E: info@mccloyconsulting.com
 W: www.mccloyconsulting.com

CARRIGEEN RENEWABLE ENERGY DEVELOPMENT - PERMANENT DRAINAGE				
DESCRIPTION LAYOUT SHEET 13				
PROJECT / FIGURE NO. M02232-01_DNG_13				
DRAWN BY	SCALE	REVISION	DATE	
DH	1:2000	1	26/03/2026	


DRAWING COPYRIGHT MCCLOY CONSULTING LTD. ALL RIGHTS RESERVED.

BACKGROUND MAP CONTAINS OPENSTREETMAP DATA © OSM CONTRIBUTORS (2026)

PLANNING DESIGN



Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m
21	Attenuated discharge overland by level spreader	1331	2	21	7 x 3 x 1
22	Attenuated discharge overland by level spreader	6374	5.6	114	19 x 5 x 1.2



LEGEND

- EIAR Boundary
- Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
- Hydrology Features & Constraints**
 - Water Feature Constraints**
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features**
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing

NOTES:

GENERAL

- Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
- All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / micro-siting.
- Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
- All drainage management features shown should be read in conjunction with relevant typical detail drawings.

POLLUTION PREVENTION

- Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving watercourses.
- Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
- Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
- Direct discharge of untreated track drainage to watercourses shall not be permitted.
- DO NOT pump water direct to watercourses.
- DO NOT strip vegetation from existing ditches unless absolutely necessary.
- If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be banded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE

- Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations
- Settlement/attenuation ponds are retained following completion of construction activities.
- Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
- Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
- Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
- Swale breakouts to be installed at regular intervals (every c. 80m).

WATERCOURSE & TRACK DRAINAGE CROSSINGS

- The minimum pipe diameter for any track drainage crossing shall be 450mm.
- All HDPE pipes shall be twinwall type, BBA HARAS approved.
- All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
- Refer to Watercourse Crossing Schedule for min. soffit levels.

MAINTENANCE

- The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
- Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.


IE +353 (0) 1 5138963
UK +44 (0) 28 9084 8694
E: info@mcclloyconsulting.com
W: www.mcclloyconsulting.com

CARRIGEEN RENEWABLE ENERGY DEVELOPMENT - PERMANENT DRAINAGE				
DESCRIPTION LAYOUT SHEET 14				
PROJECT / FIGURE NO. M02232-01_DNG_14				
DRAWN BY	SCALE	REVISION	DATE	
DH	1:2000	1	26/03/2026	

DRAWING COPYRIGHT MCCLOY CONSULTING LTD. ALL RIGHTS RESERVED.

BACKGROUND MAP CONTAINS OPENSTREETMAP DATA © OSM CONTRIBUTORS (2026)

PLANNING DESIGN



Basin	Outfall	Drained Area sqm	Disch. Rate lps	Vol cu.m	Dims (LxWxD) m
23	Attenuated discharge overland by level spreader	5537	4.9	102	17 x 5 x 1.2



NOTES:

GENERAL

1. Drawings are for planning and are not intended for construction and should not be used as such. For avoidance of doubt, surface water management design is intended to be further developed post-consent of the planning application.
2. All locations of suds features identified are approximate and to be refined on an observational basis dependant on local topography and track alignment / microsting.
3. Additional temporary drainage / mitigation will be provided during the construction phase on an observational basis.
4. All drainage management features shown should be read in conjunction with relevant typical detail drawings.

POLLUTION PREVENTION

5. Temporary or permanent drainage / silt management features including settlement features and drainage crossings should be installed prior to or in parallel with construction of new access roads / hardstanding to prevent the conveyance of silts to receiving watercourses.
6. Interim measures to be employed in all instances where work carried out is likely to cause adverse environmental impacts through increased silt loadings being generated during the construction phase.
7. Oil fuel should be stored within containment and cement should be mixed within compound / containment, tools washed in the same area and water recycled (in the cement mix).
8. Direct discharge of untreated track drainage to watercourses shall not be permitted.
9. DO NOT pump water direct to watercourses.
10. DO NOT strip vegetation from existing ditches unless absolutely necessary.
11. If water pollution is identified the following steps should be adhered to:
STOP - Work in the immediate area should be stopped and the source of the pollution identified
CONTAIN - The source of the pollution should be bunded using a suitable method. Natural watercourses should be temporarily diverted around the source of pollution.
NOTIFY - The relevant authorities and Client/Developer should be notified immediately to ensure that measures can be implemented downstream to protect fish habitat and other sensitive areas.

TRACK / INFRASTRUCTURE DRAINAGE


12. Temporary upslope cutoff / diversion drainage to be installed in advance of main earthworks in areas indicated in order to minimise surface water ingress to excavations
13. Settlement/attenuation ponds are retained following completion of construction activities.
14. Batters of swales to have dimensions as per separately issued typical detail drawing. Swale to be re-vegetated with local species.
15. Slopes of swales to be vegetated or protected from erosion until vegetation has been established. Stripped vegetative layer from excavations to be stored locally and used to line slopes and base of swale. Vegetative layer to be placed into swale after construction of the swale.
16. Clean stone check dams to be installed in all drainage channels in order to promote settlement of suspended solids and control flow rates. Check dams generally to be locally won well graded stone. Aggregate size for stone check dams to be typically 5-40mm clean stone. On steep sections small stone to be anchored through the placement of 100mm stone on the downhill face of the check dam
17. Swale breakouts to be installed at regular intervals (every c. 80m).

WATERCOURSE & TRACK DRAINAGE CROSSINGS

18. The minimum pipe diameter for any track drainage crossing shall be 450mm.
19. All HDPE pipes shall be twinwall type, BBA HAPAS approved.
20. All watercourse crossings to be installed min. 0.15m below existing bed level and to suit existing stream channel gradients.
21. Refer to Watercourse Crossing Schedule for min. soffit levels.

MAINTENANCE

22. The level of silt in runoff during construction is to be monitored visually and excessive silt levels in any area to be temporarily managed through use of silt fences / constructed settlement features.
23. Build-up of silt levels at check dams to be removed and disposed of. Silt levels at check dams to be visually inspected as part of an ongoing maintenance programme during the construction phase. Where check dams become clogged with silt or vegetation, stone check dam to be removed and replaced subsequent to the removal of silt.



- LEGEND**
- EIAR Boundary
 - Infrastructure**
 - Existing Roads to be Upgraded
 - Proposed Floated Sections
 - Proposed Infrastructure
 - Cut
 - Fill
 - Hydrology Features & Constraints**
 - Water Feature Constraints
 - Major Watercourses
 - Minor Watercourses
 - Other Ephemeral / Minor Drainage
 - Watercourse Buffers
 - Permanent Drainage Features
 - Dirty Track Drainage Pipe
 - Clean Drainage Pipes
 - Swale / Track Drainage with Check Dams & Breakouts
 - Attenuation Basin
 - Flow Control with Outlet to Watercourse
 - Flow Control with Outlet to Level Spreader (Discharge Overland)
 - Proposed Watercourse Crossing

IE +353 (0) 1 5138963
 UK +44 (0) 28 9084 8694
 E: info@mcclloyconsulting.com
 W: www.mcclloyconsulting.com

CARRIGEEN RENEWABLE ENERGY DEVELOPMENT - PERMANENT DRAINAGE			
DESCRIPTION		LAYOUT SHEET 15	
PROJECT / FIGURE NO.		M02232-01_DNG_15	
DRAWN BY	SCALE	REVISION	DATE
DH	1:2000	1	26/03/2026

DRAWING COPYRIGHT MCCLOY CONSULTING LTD. ALL RIGHTS RESERVED.

BACKGROUND MAP CONTAINS OPENSTREETMAP DATA © OSM CONTRIBUTORS (2026)

PLANNING DESIGN