



APPENDIX 8-4

WATER QUALITY LABORATORY REPORTS



Rialtas na hÉireann
Government of Ireland



Arna chomhchistiú ag
an Aontas Eorpach
Co-funded by the
European Union



Tionól Reigiúnach
Oirthir agus Lár-Tíre
Eastern and Midland
Regional Assembly



Fáilte
Ireland



Comhairle Contae
Ros Comáin
Roscommon
County Council



The Hodson Bay Waterfront Park Project is co-funded by the Government of Ireland and the European Union through the EU Just Transition Fund

McCarthy Keville & O'Sullivan Ltd
2nd Floor
H91VW84
Tuam Road
Galway
Ireland



4225



Attention : Colin Fitzgerald
Date : 2nd December, 2025
Your reference : 241220-F
Our reference : Test Report 25/19348 Batch 1
Location : Hodson Bay
Date samples received : 20th November, 2025
Status : Final Report
Issue : 202512021145

Four samples were received for analysis on 20th November, 2025 of which four were scheduled for analysis. Please find attached our Test Report which should be read with notes at the end of the report and should include all sections if reproduced. Interpretations and opinions are outside the scope of any accreditation, and all results relate only to samples supplied.

All analysis is carried out on as received samples and reported on a dry weight basis unless stated otherwise. Results are not surrogate corrected.

The greenhouse gas emissions generated (in Carbon – Co2e) to obtain the results in this report are estimated as:

Scope 1&2 emissions - 13.322 kg of CO2

Scope 1&2&3 emissions - 31.482 kg of CO2

Authorised By:



Phil Sommerton BSc
Senior Technical Account Manager

Please include all sections of this report if it is reproduced

Element Materials Technology

Client Name: McCarthy Keville & O'Sullivan Ltd
Reference: 241220-F
Location: Hodson Bay
Contact: Colin Fitzgerald
EMT Job No: 25/19348

Report : Liquid

Liquids/products: V=40ml vial, G=glass bottle, P=plastic bottle
H=H₂SO₄, Z=ZnAc, N=NaOH, HN=HNO₃

EMT Sample No.	1-10	11-20	21-30	31-40							Please see attached notes for all abbreviations and acronyms		
Sample ID	SW01	SW02	SW03	SW04									
Depth													
COC No / misc													
Containers	V H H N Z P BOD G	V H H N Z P BOD G	V H H N Z P BOD G	V H H N Z P BOD G									
Sample Date	18/11/2025 11:00	18/11/2025 11:20	18/11/2025 11:40	18/11/2025 12:00									
Sample Type	Surface Water	Surface Water	Surface Water	Surface Water									
Batch Number	1	1	1	1									
Date of Receipt	20/11/2025	20/11/2025	20/11/2025	20/11/2025							LOD/LOR	Units	Method No.
Dissolved Arsenic #	3.1	3.6	<2.5	<2.5							<2.5	ug/l	TM30/PM14
Dissolved Barium #	39	39	39	39							<3	ug/l	TM30/PM14
Dissolved Beryllium	<0.5	<0.5	<0.5	<0.5							<0.5	ug/l	TM30/PM14
Dissolved Boron	27	19	21	22							<12	ug/l	TM30/PM14
Dissolved Cadmium #	<0.5	<0.5	<0.5	<0.5							<0.5	ug/l	TM30/PM14
Dissolved Calcium #	52.4	51.8	52.2	52.1							<0.2	mg/l	TM30/PM14
Total Dissolved Chromium #	<1.5	<1.5	<1.5	<1.5							<1.5	ug/l	TM30/PM14
Dissolved Copper #	<7	<7	<7	<7							<7	ug/l	TM30/PM14
Dissolved Lead #	<5	<5	<5	<5							<5	ug/l	TM30/PM14
Dissolved Magnesium #	4.1	4.1	4.1	4.1							<0.1	mg/l	TM30/PM14
Dissolved Mercury #	<1	<1	<1	<1							<1	ug/l	TM30/PM14
Dissolved Nickel #	<2	<2	<2	<2							<2	ug/l	TM30/PM14
Dissolved Potassium #	2.3	2.2	2.2	2.3							<0.1	mg/l	TM30/PM14
Dissolved Selenium #	<3	<3	<3	<3							<3	ug/l	TM30/PM14
Dissolved Sodium #	8.8	8.6	9.0	8.7							<0.1	mg/l	TM30/PM14
Dissolved Vanadium #	<1.5	<1.5	<1.5	<1.5							<1.5	ug/l	TM30/PM14
Dissolved Zinc #	<3	<3	3	3							<3	ug/l	TM30/PM14
Pesticides													
Organochlorine Pesticides													
Aldrin	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Alpha-HCH (BHC)	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Beta-HCH (BHC)	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Delta-HCH (BHC)	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Dieldrin	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Endosulphan I	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Endosulphan II	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Endosulphan sulphate	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Endrin	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Gamma-HCH (BHC)	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Heptachlor	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Heptachlor Epoxide	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
o,p'-Methoxychlor	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
p,p'-DDE	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
p,p'-DDT	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
p,p'-Methoxychlor	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
p,p'-TDE	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30

Element Materials Technology

Client Name: McCarthy Keville & O'Sullivan Ltd
Reference: 241220-F
Location: Hodson Bay
Contact: Colin Fitzgerald
EMT Job No: 25/19348

Report : Liquid

Liquids/products: V=40ml vial, G=glass bottle, P=plastic bottle
H=H₂SO₄, Z=ZnAc, N=NaOH, HN=HNO₃

EMT Sample No.	1-10	11-20	21-30	31-40							Please see attached notes for all abbreviations and acronyms		
Sample ID	SW01	SW02	SW03	SW04									
Depth													
COC No / misc													
Containers	V H H N Z P BOD G	V H H N Z P BOD G	V H H N Z P BOD G	V H H N Z P BOD G									
Sample Date	18/11/2025 11:00	18/11/2025 11:20	18/11/2025 11:40	18/11/2025 12:00									
Sample Type	Surface Water	Surface Water	Surface Water	Surface Water									
Batch Number	1	1	1	1									
Date of Receipt	20/11/2025	20/11/2025	20/11/2025	20/11/2025							LOD/LOR	Units	Method No.
Pesticides													
Organophosphorus Pesticides													
Azinphos methyl	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Diazinon	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Dichlorvos	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Disulfoton	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Ethion	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Ethyl Parathion (Parathion)	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Fenitrothion	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Malathion	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Methyl Parathion	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Mevinphos	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
MTBE #	<5	<5	<5	<5							<5	ug/l	TM36/PM12
Benzene #	<5	<5	<5	<5							<5	ug/l	TM36/PM12
Toluene #	<5	<5	<5	<5							<5	ug/l	TM36/PM12
Ethylbenzene #	<5	<5	<5	<5							<5	ug/l	TM36/PM12
m/p-Xylene #	<5	<5	<5	<5							<5	ug/l	TM36/PM12
o-Xylene #	<5	<5	<5	<5							<5	ug/l	TM36/PM12
TPH CWG													
Aliphatics													
>C5-C6 #	<10	<10	<10	<10							<10	ug/l	TM36/PM12
>C6-C8 #	<10	<10	<10	<10							<10	ug/l	TM36/PM12
>C8-C10 #	<10	<10	<10	<10							<10	ug/l	TM36/PM12
>C10-C12 #	<5	<5	<5	<5							<5	ug/l	TM5/PM16/PM30
>C12-C16 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
>C16-C21 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
>C21-C35 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
Total aliphatics C5-35 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
Aromatics													
>C5-EC7 #	<10	<10	<10	<10							<10	ug/l	TM36/PM12
>EC7-EC8 #	<10	<10	<10	<10							<10	ug/l	TM36/PM12
>EC8-EC10 #	<10	<10	<10	<10							<10	ug/l	TM36/PM12
>EC10-EC12 #	<5	<5	<5	<5							<5	ug/l	TM5/PM16/PM30
>EC12-EC16 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
>EC16-EC21 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
>EC21-EC35 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
Total aromatics C5-35 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
Total aliphatics and aromatics(C5-35) #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
Fluoride	<0.3	<0.3	<0.3	<0.3							<0.3	mg/l	TM173/PM0
Sulphate as SO ₄ #	13.6	13.6	13.4	13.4							<0.5	mg/l	TM38/PM0

Element Materials Technology

Client Name: McCarthy Keville & O'Sullivan Ltd
Reference: 241220-F
Location: Hodson Bay
Contact: Colin Fitzgerald
EMT Job No: 25/19348

Report : Liquid

Liquids/products: V=40ml vial, G=glass bottle, P=plastic bottle
H=H₂SO₄, Z=ZnAc, N=NaOH, HN=HNO₃

[illegible]

Client Name:	McCarthy Keville & O'Sullivan Ltd
Reference:	241220-F
Location:	Hodson Bay
Contact:	Colin Fitzgerald

[illegible]

Please note that only samples that are deviating are mentioned in this report. If no samples are listed it is because none were deviating. Only analyses which are accredited are recorded as deviating if set criteria are not met.

It is a requirement under ISO 17025 that we inform clients if samples are deviating i.e. outside what is expected. A deviating sample indicates that the sample 'may' be compromised but not necessarily will be compromised. The result is still accredited and our analytical reports will still show accreditation on the relevant analytes.

NOTES TO ACCOMPANY ALL SCHEDULES AND REPORTS

EMT Job No.: 25/19348

SOILS and ASH

Please note we are only MCERTS accredited (UK soils only) for sand, loam and clay and any other matrix is outside our scope of accreditation.

Where an MCERTS report has been requested, you will be notified within 48 hours of any samples that have been identified as being outside our MCERTS scope. As validation has been performed on clay, sand and loam, only samples that are predominantly these matrices, or combinations of them will be within our MCERTS scope. If samples are not one of a combination of the above matrices they will not be marked as MCERTS accredited.

It is assumed that you have taken representative samples on site and require analysis on a representative subsample. Stones will generally be included unless we are requested to remove them.

All samples will be discarded one month after the date of reporting, unless we are instructed to the contrary. Asbestos samples are retained for 6 months.

If you have not already done so, please send us a purchase order if this is required by your company.

Where appropriate please make sure that our detection limits are suitable for your needs, if they are not, please notify us immediately.

All analysis is reported on a dry weight basis unless stated otherwise. Limits of detection for analyses carried out on as received samples are not moisture content corrected. Results are not surrogate corrected. Samples are dried at 35°C ±5°C unless otherwise stated. Moisture content for CEN Leachate tests are dried at 105°C ±5°C. Ash samples are dried at 35°C ±5°C.

Where Mineral Oil is quoted, this refers to Total Aliphatics C10-C40.

Where a CEN 10:1 ZERO Headspace VOC test has been carried out, a 10:1 ratio of water to wet (as received) soil has been used.

% Asbestos in Asbestos Containing Materials (ACMs) is determined by reference to HSG 264 The Survey Guide - Appendix 2 : ACMs in buildings listed in order of ease of fibre release.

Sufficient amount of sample must be received to carry out the testing specified. Where an insufficient amount of sample has been received the testing may not meet the requirements of our accredited methods, as such accreditation may be removed.

Negative Neutralization Potential (NP) values are obtained when the volume of NaOH (0.1N) titrated (pH 8.3) is greater than the volume of HCl (1N) to reduce the pH of the sample to 2.0 - 2.5. Any negative NP values are corrected to 0.

The calculation of Pyrite content assumes that all oxidisable sulphides present in the sample are pyrite. This may not be the case. The calculation may be an overestimate when other sulphides such as Barite (Barium Sulphate) are present.

WATERS

Please note we are not a UK Drinking Water Inspectorate (DWI) Approved Laboratory .

ISO17025 accreditation applies to surface water and groundwater and usually one other matrix which is analysis specific, any other liquids are outside our scope of accreditation.

As surface waters require different sample preparation to groundwaters the laboratory must be informed of the water type when submitting samples.

Where Mineral Oil is quoted, this refers to Total Aliphatics C10-C40.

STACK EMISSIONS

Where an MCERTS report has been requested, you will be notified within 48 hours of any samples that have been identified as being outside our MCERTS scope. As validation for Dioxins and Furans and Dioxin like PCBs has been performed on XAD-2 Resin, only samples which use this resin will be within our MCERTS scope.

Where appropriate please make sure that our detection limits are suitable for your needs, if they are not, please notify us immediately.

DEVIATING SAMPLES

All samples should be submitted to the laboratory in suitable containers with sufficient ice packs to sustain an appropriate temperature for the requested analysis. The temperature of sample receipt is recorded on the confirmation schedules in order that the client can make an informed decision as to whether testing should still be undertaken.

SURROGATES

Surrogate compounds are added during the preparation process to monitor recovery of analytes. However low recovery in soils is often due to peat, clay or other organic rich matrices. For waters this can be due to oxidants, surfactants, organic rich sediments or remediation fluids. Acceptable limits for most organic methods are 70 - 130% and for VOCs are 50 - 150%. When surrogate recoveries are outside the performance criteria but the associated AQC passes this is assumed to be due to matrix effect. Results are not surrogate corrected.

DILUTIONS

A dilution suffix indicates a dilution has been performed and the reported result takes this into account. No further calculation is required.

BLANKS

Where analytes have been found in the blank, the sample will be treated in accordance with our laboratory procedure for dealing with contaminated blanks.

NOTE

Data is only reported if the laboratory is confident that the data is a true reflection of the samples analysed. Data is only reported as accredited when all the requirements of our Quality System have been met. In certain circumstances where all the requirements of the Quality System have not been met, for instance if the associated AQC has failed, the reason is fully investigated and documented. The sample data is then evaluated alongside the other quality control checks performed during analysis to determine its suitability. Following this evaluation, provided the sample results have not been effected, the data is reported but accreditation is removed. It is a requirement of our Accreditation Body for data not reported as accredited to be considered indicative only, but this does not mean the data is not valid.

Where possible, and if requested, samples will be re-extracted and a revised report issued with accredited results. Please do not hesitate to contact the laboratory if further details are required of the circumstances which have led to the removal of accreditation.

Laboratory records are kept for a period of no less than 6 years.

REPORTS FROM THE SOUTH AFRICA LABORATORY

Any method number not prefixed with SA has been undertaken in our UK laboratory unless reported as subcontracted.

Measurement Uncertainty

Measurement uncertainty defines the range of values that could reasonably be attributed to the measured quantity. This range of values has not been included within the reported results. Uncertainty expressed as a percentage can be provided upon request.

Customer Provided Information

Sample ID and depth is information provided by the customer.

Age of Diesel

The age of release estimation is based on the nC17/pristane ratio only as prescribed by Christensen and Larsen (1993) and Kaplan, Galperin, Alimi et al., (1996).

Age estimation should be treated with caution as it can be influenced by site specific factors of which the laboratory are not aware.

Tentatively Identified Compounds (TICs)

Where Tentatively Identified Compounds (TICs) are reported, up to 10 Tentatively Identified Compounds will be listed where there is found to be a greater than 80% match with the NIST library. The reported concentration is determined semi-quantitatively, with a matrix specific limit of detection.

Note, other compounds may be present but are not reported.

ABBREVIATIONS and ACRONYMS USED

#	ISO17025 (UKAS Ref No. 4225) accredited - UK.
SA	ISO17025 (SANAS Ref No.T0729) accredited - South Africa
B	Indicates analyte found in associated method blank.
DR	Dilution required.
M	MCERTS accredited.
NA	Not applicable
NAD	No Asbestos Detected.
ND	None Detected (usually refers to VOC and/SVOC TICs).
NDP	No Determination Possible
SS	Calibrated against a single substance
SV	Surrogate recovery outside performance criteria. This may be due to a matrix effect.
W	Results expressed on as received basis.
+	AQC failure, accreditation has been removed from this result, if appropriate, see 'Note' on previous page.
>>	Results above quantitative calibration range. The result should be considered the minimum value and is indicative only. The actual result could be significantly higher.
*	Analysis subcontracted to an Element Materials Technology approved laboratory.
CO	Suspected carry over
LOD/LOR	Limit of Detection (Limit of Reporting) in line with ISO 17025 and MCERTS
ME	Matrix Effect
NFD	No Fibres Detected
BS	AQC Sample
LB	Blank Sample
N	Client Sample
TB	Trip Blank Sample
OC	Outside Calibration Range
AA	x3 Dilution

EMT Job No: 25/19348

Test Method No.	Description	Prep Method No. (if appropriate)	Description	ISO 17025 (UKAS/ANAS)	MCERTS (UK soils only)	Analysis done on As Received (AR) or Dried (AD)	Reported on dry weight basis
TM5	Modified 8015B v2:1996 method for the determination of solvent Extractable Petroleum Hydrocarbons (EPH) within the range C8-C40 by GC/FID. For waters the solvent extracts dissolved phase plus a sheen if present.	PM16/PM30	Fractionation into aliphatic and aromatic fractions using a Rapid Trace SPE/Water samples are extracted with solvent using a magnetic stirrer to create a vortex.	Yes			
TM5/TM36	please refer to TM5 and TM36 for method details	PM12/PM16/PM30	please refer to PM16/PM30 and PM12 for method details	Yes			
TM30	Determination of Trace Metals by ICP-OES (Inductively Coupled Plasma-Optical Emission Spectrometry); WATERS by Modified USEPA Method 200.7, Rev. 4.4, 1994; Modified EPA Method 6010B, Rev.2, Dec 1996; Modified BS EN ISO 11885:2009: SOILS by Modified USEP 6010B, Rev.2, Dec.1996; Modified EPA Method 3050B, Rev.2, Dec.1996	PM14	Preparation of waters and leachates for metals by ICP OES/ICP MS. Samples are filtered for Dissolved metals, and remain unfiltered for Total metals then acidified				
TM30	Determination of Trace Metals by ICP-OES (Inductively Coupled Plasma-Optical Emission Spectrometry); WATERS by Modified USEPA Method 200.7, Rev. 4.4, 1994; Modified EPA Method 6010B, Rev.2, Dec 1996; Modified BS EN ISO 11885:2009: SOILS by Modified USEP 6010B, Rev.2, Dec.1996; Modified EPA Method 3050B, Rev.2, Dec.1996	PM14	Preparation of waters and leachates for metals by ICP OES/ICP MS. Samples are filtered for Dissolved metals, and remain unfiltered for Total metals then acidified	Yes			
TM34	Turbidity by 2100P Turbidity Meter. complies with EPA 180.1 1993	PM0	No preparation is required.				
TM36	Modified US EPA method 8015B v2:1996. Determination of Gasoline Range Organics (GRO) in the carbon chain range of C4-12 by headspace GC-FID. MTBE by GC/FID co-elutes with 3-methylpentane if present and therefore can give a false positive. Positive MTBE results will be re-run using GC-MS to double check, when requested.	PM12	Modified US EPA method 5021A v2:2014. Preparation of solid and liquid samples for GC headspace analysis.	Yes			
TM37	Modified method - TSS: USEPA 100.2 (1993), EN612:2009 and APHA SM 2540D:1999 22nd Edition; VSS: USEPA 1684 (Jan 2001), USEPA 160.4 (1971) and SMEWW 2540E:1999 22nd Edition. Gravimetric determination of Total Suspended Solids (TSS) and Volatile Suspended Solids (VSS). Sample is filtered through a 1.5um pore size glass fibre filter and the resulting residue is dried and weighed at 105°C for TSS and 550°C for VSS.	PM0	No preparation is required.	Yes			
TM38	Soluble Ion analysis using Discrete Analyser. Modified US EPA methods: Chloride 325.2 (1978), Sulphate 375.4 (Rev.2 1993), o-Phosphate 365.2 (Rev.2 1993), TON 353.1 (Rev.2 1993), Nitrite 354.1 (1971), Hex Cr 7196A (1992), NH4+ 350.1 (Rev.2 1993) - All anions comparable to BS ISO 15923-1: 2013	PM0	No preparation is required.	Yes			
TM38/TM125	Total Nitrogen/Organic Nitrogen by calculation	PM0	No preparation is required.				
TM57	Modified US EPA Method 410.4. (Rev. 2.0 1993) Comparable with ISO 15705:2002. Chemical Oxygen Demand is determined by hot digestion with Potassium Dichromate and measured spectrophotometrically.	PM0	No preparation is required.	Yes			

EMT Job No: 25/19348

Test Method No.	Description	Prep Method No. (if appropriate)	Description	ISO 17025 (UKAS/S ANAS)	MCERTS (UK soils only)	Analysis done on As Received (AR) or Dried (AD)	Reported on dry weight basis
TM58	APHA SMEWW 5210B:1999 22nd Edition. Comparable with ISO 5815:1989. Measurement of Biochemical Oxygen Demand. When cBOD (Carbonaceous BOD) is requested a nitrification inhibitor is added which prevents the oxidation of reduced forms of nitrogen, such as am	PM0	No preparation is required.	Yes			
TM60	TC/TOC analysis of Waters by High Temperature Combustion followed by NDIR detection. Based on the following modified standard methods: USEPA 9060A (2002), APHA SMEWW 5310B:1999 22nd Edition, ASTM D 7573, and USEPA 415.1.	PM0	No preparation is required.	Yes			
TM73	Modified US EPA methods 150.1 (1982) and 9045D Rev. 4 - 2004) and BS1377-3:1990. Determination of pH by Metrohm automated probe analyser.	PM0	No preparation is required.	Yes			
TM75	Modified US EPA method 310.1 (1978). Determination of Alkalinity by Metrohm automated titration analyser.	PM0	No preparation is required.	Yes			
TM76	Modified US EPA method 120.1 (1982). Determination of Specific Conductance by Metrohm automated probe analyser.	PM0	No preparation is required.	Yes			
TM89	Modified USEPA method OIA-1667 (1999). Determination of cyanide by Flow Injection Analyser. Where WAD cyanides are required a Ligand displacement step is carried out before analysis.	PM0	No preparation is required.	Yes			
TM107	Determination of Sulphide/Thiocyanate by Skalar Continuous Flow Analyser	PM0	No preparation is required.				
TM149	Determination of Pesticides by Large Volume Injection on GC Triple Quad MS, based upon USEPA method 8270D v5:2014	PM30	Water samples are extracted with solvent using a magnetic stirrer to create a vortex.				
TM173	Analysis of fluoride by ISE (Ion Selective Electrode) using modified ISE method 9214 - 340.2 (EPA 1998)	PM0	No preparation is required.				

McCarthy Keville & O'Sullivan Ltd
2nd Floor
H91VW84
Tuam Road
Galway
Ireland



4225



Attention : Colin Fitzgerald
Date : 10th February, 2026
Your reference : 241220-F
Our reference : Test Report 26/1342 Batch 1
Location : Hodson Bay
Date samples received : 29th January, 2026
Status : Final Report
Issue : 202602101216

Four samples were received for analysis on 29th January, 2026 of which four were scheduled for analysis. Please find attached our Test Report which should be read with notes at the end of the report and should include all sections if reproduced. Interpretations and opinions are outside the scope of any accreditation, and all results relate only to samples supplied.

All analysis is carried out on as received samples and reported on a dry weight basis unless stated otherwise. Results are not surrogate corrected.

The greenhouse gas emissions generated (in Carbon – Co2e) to obtain the results in this report are estimated as:

Scope 1&2 emissions - 13.901 kg of CO2

Scope 1&2&3 emissions - 32.851 kg of CO2

Authorised By:



Phil Sommerton BSc

Senior Technical Account Manager

Please include all sections of this report if it is reproduced

Element Materials Technology

Client Name: McCarthy Keville & O'Sullivan Ltd
Reference: 241220-F
Location: Hodson Bay
Contact: Colin Fitzgerald
EMT Job No: 26/1342

Report : Liquid

Liquids/products: V=40ml vial, G=glass bottle, P=plastic bottle
H=H₂SO₄, Z=ZnAc, N=NaOH, HN=HNO₃

EMT Sample No.	1-11	12-22	23-33	34-44							Please see attached notes for all abbreviations and acronyms		
Sample ID	SW01	SW02	SW03	SW04									
Depth													
COC No / misc													
Containers	V H H N Z P BOD G	V H H N Z P BOD G	V H H N Z P BOD G	V H H N Z P BOD G									
Sample Date	27/01/2026 13:10	27/01/2026 12:10	27/01/2026 12:30	27/01/2026 13:00									
Sample Type	Surface Water	Surface Water	Surface Water	Surface Water									
Batch Number	1	1	1	1									
Date of Receipt	29/01/2026	29/01/2026	29/01/2026	29/01/2026							LOD/LOR	Units	Method No.
Dissolved Arsenic #	<2.5	<2.5	<2.5	<2.5							<2.5	ug/l	TM30/PM14
Dissolved Barium #	34	35	34	34							<3	ug/l	TM30/PM14
Dissolved Beryllium	<0.5	<0.5	<0.5	<0.5							<0.5	ug/l	TM30/PM14
Dissolved Boron	<12	<12	<12	<12							<12	ug/l	TM30/PM14
Dissolved Cadmium #	<0.5	<0.5	<0.5	<0.5							<0.5	ug/l	TM30/PM14
Dissolved Calcium #	58.8	59.3	56.1	57.2							<0.2	mg/l	TM30/PM14
Total Dissolved Chromium #	<1.5	<1.5	<1.5	<1.5							<1.5	ug/l	TM30/PM14
Dissolved Copper #	<7	<7	<7	<7							<7	ug/l	TM30/PM14
Dissolved Lead #	<5	<5	<5	<5							<5	ug/l	TM30/PM14
Dissolved Magnesium #	4.0	4.0	3.8	3.9							<0.1	mg/l	TM30/PM14
Dissolved Mercury #	<1	<1	<1	<1							<1	ug/l	TM30/PM14
Dissolved Nickel #	<2	<2	<2	<2							<2	ug/l	TM30/PM14
Dissolved Potassium #	2.0	2.0	2.0	1.9							<0.1	mg/l	TM30/PM14
Dissolved Selenium #	<3	<3	<3	<3							<3	ug/l	TM30/PM14
Dissolved Sodium #	8.4	8.3	8.4	8.0							<0.1	mg/l	TM30/PM14
Dissolved Vanadium #	<1.5	<1.5	<1.5	<1.5							<1.5	ug/l	TM30/PM14
Dissolved Zinc #	<3	4	22	4							<3	ug/l	TM30/PM14
Pesticides													
Organochlorine Pesticides													
Aldrin	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Alpha-HCH (BHC)	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Beta-HCH (BHC)	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Delta-HCH (BHC)	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Dieldrin	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Endosulphan I	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Endosulphan II	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Endosulphan sulphate	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Endrin	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Gamma-HCH (BHC)	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Heptachlor	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Heptachlor Epoxide	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
o,p'-Methoxychlor	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
p,p'-DDE	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
p,p'-DDT	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
p,p'-Methoxychlor	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
p,p'-TDE	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30

Element Materials Technology

Client Name: McCarthy Keville & O'Sullivan Ltd
Reference: 241220-F
Location: Hodson Bay
Contact: Colin Fitzgerald
EMT Job No: 26/1342

Report : Liquid

Liquids/products: V=40ml vial, G=glass bottle, P=plastic bottle
H=H₂SO₄, Z=ZnAc, N=NaOH, HN=HNO₃

EMT Sample No.	1-11	12-22	23-33	34-44							Please see attached notes for all abbreviations and acronyms		
Sample ID	SW01	SW02	SW03	SW04									
Depth													
COC No / misc													
Containers	V H H N Z P BOD G	V H H N Z P BOD G	V H H N Z P BOD G	V H H N Z P BOD G									
Sample Date	27/01/2026 13:10	27/01/2026 12:10	27/01/2026 12:30	27/01/2026 13:00									
Sample Type	Surface Water	Surface Water	Surface Water	Surface Water									
Batch Number	1	1	1	1									
Date of Receipt	29/01/2026	29/01/2026	29/01/2026	29/01/2026							LOD/LOR	Units	Method No.
Pesticides													
Organophosphorus Pesticides													
Azinphos methyl	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Diazinon	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Dichlorvos	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Disulfoton	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Ethion	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Ethyl Parathion (Parathion)	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Fenitrothion	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Malathion	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Methyl Parathion	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
Mevinphos	<0.01	<0.01	<0.01	<0.01							<0.01	ug/l	TM149/PM30
MTBE #	<5	<5	<5	<5							<5	ug/l	TM36/PM12
Benzene #	<5	<5	<5	<5							<5	ug/l	TM36/PM12
Toluene #	<5	<5	<5	<5							<5	ug/l	TM36/PM12
Ethylbenzene #	<5	<5	<5	<5							<5	ug/l	TM36/PM12
m/p-Xylene #	<5	<5	<5	<5							<5	ug/l	TM36/PM12
o-Xylene #	<5	<5	<5	<5							<5	ug/l	TM36/PM12
TPH CWG													
Aliphatics													
>C5-C6 #	<10	<10	<10	<10							<10	ug/l	TM36/PM12
>C6-C8 #	<10	<10	<10	<10							<10	ug/l	TM36/PM12
>C8-C10 #	<10	<10	<10	<10							<10	ug/l	TM36/PM12
>C10-C12 #	<5	<5	<5	<5							<5	ug/l	TM5/PM16/PM30
>C12-C16 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
>C16-C21 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
>C21-C35 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
Total aliphatics C5-35 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
Aromatics													
>C5-EC7 #	<10	<10	<10	<10							<10	ug/l	TM36/PM12
>EC7-EC8 #	<10	<10	<10	<10							<10	ug/l	TM36/PM12
>EC8-EC10 #	<10	<10	<10	<10							<10	ug/l	TM36/PM12
>EC10-EC12 #	<5	<5	<5	<5							<5	ug/l	TM5/PM16/PM30
>EC12-EC16 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
>EC16-EC21 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
>EC21-EC35 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
Total aromatics C5-35 #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
Total aliphatics and aromatics(C5-35) #	<10	<10	<10	<10							<10	ug/l	TM5/PM16/PM30
Fluoride	<0.3	<0.3	<0.3	<0.3							<0.3	mg/l	TM173/PM0
Sulphate as SO ₄ #	11.8	11.9	11.5	11.4							<0.5	mg/l	TM38/PM0

Element Materials Technology

Client Name: McCarthy Keville & O'Sullivan Ltd
Reference: 241220-F
Location: Hodson Bay
Contact: Colin Fitzgerald
EMT Job No: 26/1342

Report : Liquid

Liquids/products: V=40ml vial, G=glass bottle, P=plastic bottle
H=H₂SO₄, Z=ZnAc, N=NaOH, HN=HNO₃

[illegible]

Client Name: McCarthy Keville & O'Sullivan Ltd
Reference: 241220-F
Location: Hodson Bay
Contact: Colin Fitzgerald

[illegible]

Please note that only samples that are deviating are mentioned in this report. If no samples are listed it is because none were deviating. Only analyses which are accredited are recorded as deviating if set criteria are not met.

It is a requirement under ISO 17025 that we inform clients if samples are deviating i.e. outside what is expected. A deviating sample indicates that the sample 'may' be compromised but not necessarily will be compromised. The result is still accredited and our analytical reports will still show accreditation on the relevant analytes.

NOTES TO ACCOMPANY ALL SCHEDULES AND REPORTS

EMT Job No.: 26/1342

SOILS and ASH

Please note we are only MCERTS accredited (UK soils only) for sand, loam and clay and any other matrix is outside our scope of accreditation.

Where an MCERTS report has been requested, you will be notified within 48 hours of any samples that have been identified as being outside our MCERTS scope. As validation has been performed on clay, sand and loam, only samples that are predominantly these matrices, or combinations of them will be within our MCERTS scope. If samples are not one of a combination of the above matrices they will not be marked as MCERTS accredited.

It is assumed that you have taken representative samples on site and require analysis on a representative subsample. Stones will generally be included unless we are requested to remove them.

All samples will be discarded one month after the date of reporting, unless we are instructed to the contrary. Asbestos samples are retained for 6 months.

If you have not already done so, please send us a purchase order if this is required by your company.

Where appropriate please make sure that our detection limits are suitable for your needs, if they are not, please notify us immediately.

All analysis is reported on a dry weight basis unless stated otherwise. Limits of detection for analyses carried out on as received samples are not moisture content corrected. Results are not surrogate corrected. Samples are dried at 35°C ±5°C unless otherwise stated. Moisture content for CEN Leachate tests are dried at 105°C ±5°C. Ash samples are dried at 35°C ±5°C.

Where Mineral Oil is quoted, this refers to Total Aliphatics C10-C40.

Where a CEN 10:1 ZERO Headspace VOC test has been carried out, a 10:1 ratio of water to wet (as received) soil has been used.

% Asbestos in Asbestos Containing Materials (ACMs) is determined by reference to HSG 264 The Survey Guide - Appendix 2 : ACMs in buildings listed in order of ease of fibre release.

Sufficient amount of sample must be received to carry out the testing specified. Where an insufficient amount of sample has been received the testing may not meet the requirements of our accredited methods, as such accreditation may be removed.

Negative Neutralization Potential (NP) values are obtained when the volume of NaOH (0.1N) titrated (pH 8.3) is greater than the volume of HCl (1N) to reduce the pH of the sample to 2.0 - 2.5. Any negative NP values are corrected to 0.

The calculation of Pyrite content assumes that all oxidisable sulphides present in the sample are pyrite. This may not be the case. The calculation may be an overestimate when other sulphides such as Barite (Barium Sulphate) are present.

WATERS

Please note we are not a UK Drinking Water Inspectorate (DWI) Approved Laboratory .

ISO17025 accreditation applies to surface water and groundwater and usually one other matrix which is analysis specific, any other liquids are outside our scope of accreditation.

As surface waters require different sample preparation to groundwaters the laboratory must be informed of the water type when submitting samples.

Where Mineral Oil is quoted, this refers to Total Aliphatics C10-C40.

STACK EMISSIONS

Where an MCERTS report has been requested, you will be notified within 48 hours of any samples that have been identified as being outside our MCERTS scope. As validation for Dioxins and Furans and Dioxin like PCBs has been performed on XAD-2 Resin, only samples which use this resin will be within our MCERTS scope.

Where appropriate please make sure that our detection limits are suitable for your needs, if they are not, please notify us immediately.

DEVIATING SAMPLES

All samples should be submitted to the laboratory in suitable containers with sufficient ice packs to sustain an appropriate temperature for the requested analysis. The temperature of sample receipt is recorded on the confirmation schedules in order that the client can make an informed decision as to whether testing should still be undertaken.

SURROGATES

Surrogate compounds are added during the preparation process to monitor recovery of analytes. However low recovery in soils is often due to peat, clay or other organic rich matrices. For waters this can be due to oxidants, surfactants, organic rich sediments or remediation fluids. Acceptable limits for most organic methods are 70 - 130% and for VOCs are 50 - 150%. When surrogate recoveries are outside the performance criteria but the associated AQC passes this is assumed to be due to matrix effect. Results are not surrogate corrected.

DILUTIONS

A dilution suffix indicates a dilution has been performed and the reported result takes this into account. No further calculation is required.

BLANKS

Where analytes have been found in the blank, the sample will be treated in accordance with our laboratory procedure for dealing with contaminated blanks.

NOTE

Data is only reported if the laboratory is confident that the data is a true reflection of the samples analysed. Data is only reported as accredited when all the requirements of our Quality System have been met. In certain circumstances where all the requirements of the Quality System have not been met, for instance if the associated AQC has failed, the reason is fully investigated and documented. The sample data is then evaluated alongside the other quality control checks performed during analysis to determine its suitability. Following this evaluation, provided the sample results have not been effected, the data is reported but accreditation is removed. It is a requirement of our Accreditation Body for data not reported as accredited to be considered indicative only, but this does not mean the data is not valid.

Where possible, and if requested, samples will be re-extracted and a revised report issued with accredited results. Please do not hesitate to contact the laboratory if further details are required of the circumstances which have led to the removal of accreditation.

Laboratory records are kept for a period of no less than 6 years.

REPORTS FROM THE SOUTH AFRICA LABORATORY

Any method number not prefixed with SA has been undertaken in our UK laboratory unless reported as subcontracted.

Measurement Uncertainty

Measurement uncertainty defines the range of values that could reasonably be attributed to the measured quantity. This range of values has not been included within the reported results. Uncertainty expressed as a percentage can be provided upon request.

Customer Provided Information

Sample ID and depth is information provided by the customer.

Age of Diesel

The age of release estimation is based on the nC17/pristane ratio only as prescribed by Christensen and Larsen (1993) and Kaplan, Galperin, Alimi et al., (1996).

Age estimation should be treated with caution as it can be influenced by site specific factors of which the laboratory are not aware.

Tentatively Identified Compounds (TICs)

Where Tentatively Identified Compounds (TICs) are reported, up to 10 Tentatively Identified Compounds will be listed where there is found to be a greater than 80% match with the NIST library. The reported concentration is determined semi-quantitatively, with a matrix specific limit of detection.

Note, other compounds may be present but are not reported.

ABBREVIATIONS and ACRONYMS USED

#	ISO17025 (UKAS Ref No. 4225) accredited - UK.
SA	ISO17025 (SANAS Ref No.T0729) accredited - South Africa
B	Indicates analyte found in associated method blank.
DR	Dilution required.
M	MCERTS accredited.
NA	Not applicable
NAD	No Asbestos Detected.
ND	None Detected (usually refers to VOC and/SVOC TICs).
NDP	No Determination Possible
SS	Calibrated against a single substance
SV	Surrogate recovery outside performance criteria. This may be due to a matrix effect.
W	Results expressed on as received basis.
+	AQC failure, accreditation has been removed from this result, if appropriate, see 'Note' on previous page.
>>	Results above quantitative calibration range. The result should be considered the minimum value and is indicative only. The actual result could be significantly higher.
*	Analysis subcontracted to an Element Materials Technology approved laboratory.
CO	Suspected carry over
LOD/LOR	Limit of Detection (Limit of Reporting) in line with ISO 17025 and MCERTS
ME	Matrix Effect
NFD	No Fibres Detected
BS	AQC Sample
LB	Blank Sample
N	Client Sample
TB	Trip Blank Sample
OC	Outside Calibration Range
AA	x2 Dilution
AB	x3 Dilution

EMT Job No: 26/1342

Test Method No.	Description	Prep Method No. (if appropriate)	Description	ISO 17025 (UKAS/ANAS)	MCERTS (UK soils only)	Analysis done on As Received (AR) or Dried (AD)	Reported on dry weight basis
TM5	Modified 8015B v2:1996 method for the determination of solvent Extractable Petroleum Hydrocarbons (EPH) within the range C8-C40 by GC/FID. For waters the solvent extracts dissolved phase plus a sheen if present.	PM16/PM30	Fractionation into aliphatic and aromatic fractions using a Rapid Trace SPE/Water samples are extracted with solvent using a magnetic stirrer to create a vortex.	Yes			
TM5/TM36	please refer to TM5 and TM36 for method details	PM12/PM16/PM30	please refer to PM16/PM30 and PM12 for method details	Yes			
TM30	Determination of Trace Metals by ICP-OES (Inductively Coupled Plasma-Optical Emission Spectrometry); WATERS by Modified USEPA Method 200.7, Rev. 4.4, 1994; Modified EPA Method 6010B, Rev.2, Dec 1996; Modified BS EN ISO 11885:2009: SOILS by Modified USEP 6010B, Rev.2, Dec.1996; Modified EPA Method 3050B, Rev.2, Dec.1996	PM14	Preparation of waters and leachates for metals by ICP OES/ICP MS. Samples are filtered for Dissolved metals, and remain unfiltered for Total metals then acidified				
TM30	Determination of Trace Metals by ICP-OES (Inductively Coupled Plasma-Optical Emission Spectrometry); WATERS by Modified USEPA Method 200.7, Rev. 4.4, 1994; Modified EPA Method 6010B, Rev.2, Dec 1996; Modified BS EN ISO 11885:2009: SOILS by Modified USEP 6010B, Rev.2, Dec.1996; Modified EPA Method 3050B, Rev.2, Dec.1996	PM14	Preparation of waters and leachates for metals by ICP OES/ICP MS. Samples are filtered for Dissolved metals, and remain unfiltered for Total metals then acidified	Yes			
TM34	Turbidity by 2100P Turbidity Meter. complies with EPA 180.1 1993	PM0	No preparation is required.				
TM36	Modified US EPA method 8015B v2:1996. Determination of Gasoline Range Organics (GRO) in the carbon chain range of C4-12 by headspace GC-FID. MTBE by GC/FID co-elutes with 3-methylpentane if present and therefore can give a false positive. Positive MTBE results will be re-run using GC-MS to double check, when requested.	PM12	Modified US EPA method 5021A v2:2014. Preparation of solid and liquid samples for GC headspace analysis.	Yes			
TM37	Modified methods: TSS: USEPA 100.2 (1993), EN612:2009 and APHA SM 2540D:1999 22nd Edition; VSS: USEPA 1684 (Jan 2001), USEPA 160.4 (1971) and SMEWW 2540E:1999 22nd Edition. Gravimetric determination of Total Suspended Solids (TSS) and Volatile Suspended Solids (VSS). Sample is filtered through a 1.5um pore size glass fibre filter and the resulting residue is dried and weighed at 105°C for TSS and 550°C for VSS.	PM0	No preparation is required.	Yes			
TM38	Soluble Ion analysis using Discrete Analyser. Modified US EPA methods: Chloride 325.2 (1978), Sulphate 375.4 (Rev.2 1993), o-Phosphate 365.2 (Rev.2 1993), TON 353.1 (Rev.2 1993), Nitrite 354.1 (1971), Hex Cr 7196A (1992), NH4+ 350.1 (Rev.2 1993) - All anions comparable to BS ISO 15923-1: 2013	PM0	No preparation is required.	Yes			
TM38/TM125	Total Nitrogen/Organic Nitrogen by calculation	PM0	No preparation is required.				
TM57	Modified US EPA Method 410.4. (Rev. 2.0 1993) Comparable with ISO 15705:2002. Chemical Oxygen Demand is determined by hot digestion with Potassium Dichromate and measured spectrophotometrically.	PM0	No preparation is required.	Yes			

EMT Job No: 26/1342

Test Method No.	Description	Prep Method No. (if appropriate)	Description	ISO 17025 (UKAS/ANAS)	MCERTS (UK soils only)	Analysis done on As Received (AR) or Dried (AD)	Reported on dry weight basis
TM58	APHA SMEWW 5210B:1999 22nd Edition. Comparable with ISO 5815:1989. Measurement of Biochemical Oxygen Demand. When cBOD (Carbonaceous BOD) is requested a nitrification inhibitor is added which prevents the oxidation of reduced forms of nitrogen, such as am	PM0	No preparation is required.	Yes			
TM60	TC/TOC analysis of Waters by High Temperature Combustion followed by NDIR detection. Based on the following modified standard methods: USEPA 9060A (2002), APHA SMEWW 5310B:1999 22nd Edition, ASTM D 7573, and USEPA 415.1.	PM0	No preparation is required.	Yes			
TM73	Modified US EPA methods 150.1 (1982) and 9045D Rev. 4 - 2004) and BS1377-3:1990. Determination of pH by Metrohm automated probe analyser.	PM0	No preparation is required.	Yes			
TM75	Modified US EPA method 310.1 (1978). Determination of Alkalinity by Metrohm automated titration analyser.	PM0	No preparation is required.	Yes			
TM76	Modified US EPA method 120.1 (1982). Determination of Specific Conductance by Metrohm automated probe analyser.	PM0	No preparation is required.	Yes			
TM89	Modified USEPA method OIA-1667 (1999). Determination of cyanide by Flow Injection Analyser. Where WAD cyanides are required a Ligand displacement step is carried out before analysis.	PM0	No preparation is required.	Yes			
TM107	Determination of Sulphide/Thiocyanate by Skalar Continuous Flow Analyser	PM0	No preparation is required.				
TM149	Determination of Pesticides by Large Volume Injection on GC Triple Quad MS, based upon USEPA method 8270D v5:2014	PM30	Water samples are extracted with solvent using a magnetic stirrer to create a vortex.				
TM173	Analysis of fluoride by ISE (Ion Selective Electrode) using modified ISE method 9214 - 340.2 (EPA 1998)	PM0	No preparation is required.				

McCarthy Keville & O'Sullivan Ltd
2nd Floor
H91VW84
Tuam Road
Galway
Ireland



Attention :	Bébhinn Anders
Date :	20th April, 2026
Your reference :	291220-F
Our reference :	Test Report 26/5392 Batch 1
Location :	Hodson Bay
Date samples received :	9th April, 2026
Status :	Final Report
Issue :	202604201354

Four samples were received for analysis on 9th April, 2026 of which four were scheduled for analysis. Please find attached our Test Report which should be read with notes at the end of the report and should include all sections if reproduced. Interpretations and opinions are outside the scope of any accreditation, and all results relate only to samples supplied.

All analysis is carried out on as received samples and reported on a dry weight basis unless stated otherwise. Results are not surrogate corrected.

The greenhouse gas emissions generated (in Carbon – Co2e) to obtain the results in this report are estimated as:

Scope 1&2 emissions - 8.688 kg of CO2

Scope 1&2&3 emissions - 20.532 kg of CO2

Authorised By:



Bruce Leslie
Project Manager

Please include all sections of this report if it is reproduced

Element Materials Technology

Client Name: McCarthy Keville & O'Sullivan Ltd
Reference: 291220-F
Location: Hodson Bay
Contact: Bébhinn Anders
EMT Job No: 26/5392

Report : Liquid

Liquids/products: V=40ml vial, G=glass bottle, P=plastic bottle
H=H₂SO₄, Z=ZnAc, N=NaOH, HN=HNO₃

EMT Sample No.	1-11	12-22	23-33	34-44							Please see attached notes for all abbreviations and acronyms		
Sample ID	SW01	SW02	SW03	SW04									
Depth													
COC No / misc													
Containers	V H H N Z P BOD G	V H H N Z P BOD G	V H H N Z P BOD G	V H H N Z P BOD G									
Sample Date	07/04/2026	07/04/2026	07/04/2026	07/04/2026									
Sample Type	Surface Water	Surface Water	Surface Water	Surface Water									
Batch Number	1	1	1	1									
Date of Receipt	09/04/2026	09/04/2026	09/04/2026	09/04/2026							LOD/LOR	Units	Method No.
Dissolved Arsenic	<2.5	<2.5	<2.5	<2.5							<2.5	ug/l	TM30/PM14
Dissolved Barium	35	37	38	37							<3	ug/l	TM30/PM14
Dissolved Beryllium	<0.5	<0.5	<0.5	<0.5							<0.5	ug/l	TM30/PM14
Dissolved Boron	<12	<12	<12	<12							<12	ug/l	TM30/PM14
Dissolved Cadmium	<0.5	<0.5	<0.5	<0.5							<0.5	ug/l	TM30/PM14
Dissolved Calcium	63.9	63.8	63.5	63.1							<0.2	mg/l	TM30/PM14
Total Dissolved Chromium	<1.5	<1.5	<1.5	<1.5							<1.5	ug/l	TM30/PM14
Dissolved Copper	<7	<7	<7	<7							<7	ug/l	TM30/PM14
Dissolved Lead	<5	<5	<5	<5							<5	ug/l	TM30/PM14
Dissolved Magnesium	4.3	4.3	4.2	4.2							<0.1	mg/l	TM30/PM14
Dissolved Mercury	<1	<1	<1	<1							<1	ug/l	TM30/PM14
Dissolved Nickel	<2	<2	<2	<2							<2	ug/l	TM30/PM14
Dissolved Potassium	1.8	1.9	1.9	1.8							<0.1	mg/l	TM30/PM14
Dissolved Selenium	<3	<3	<3	<3							<3	ug/l	TM30/PM14
Dissolved Sodium	8.0	7.8	8.0	7.7							<0.1	mg/l	TM30/PM14
Dissolved Vanadium	<1.5	<1.5	<1.5	<1.5							<1.5	ug/l	TM30/PM14
Dissolved Zinc	<3	4	<3	3							<3	ug/l	TM30/PM14
Fluoride	<0.3	<0.3	<0.3	<0.3							<0.3	mg/l	TM173/PM0
Sulphate as SO ₄	10.8	10.9	11.0	10.4							<0.5	mg/l	TM38/PM0
Chloride	14.3	13.5	14.1	13.4							<0.3	mg/l	TM38/PM0
Nitrate as N	0.74	0.86	0.89	0.68							<0.05	mg/l	TM38/PM0
Nitrite as N	0.007	0.011	0.010	0.007							<0.006	mg/l	TM38/PM0
Ortho Phosphate as P	<0.03	<0.03	<0.03	<0.03							<0.03	mg/l	TM38/PM0
Total Oxidised Nitrogen as N	0.7	0.9	0.9	0.7							<0.2	mg/l	TM38/PM0
Ammoniacal Nitrogen as N	<0.03	0.04	<0.03	<0.03							<0.03	mg/l	TM38/PM0
Total Alkalinity as CaCO ₃	180	156	184	160							<1	mg/l	TM75/PM0
Sulphide	<10	<10	<10	<10							<10	ug/l	TM107/PM0
BOD (Settled)	<2 _{AA}	<2 _{AA}	<2 _{AA}	<3 _{AB}							<1	mg/l	TM58/PM0
COD (Settled)	28	27	29	31							<7	mg/l	TM57/PM0
Dissolved Organic Carbon	10	10	10	10							<2	mg/l	TM60/PM0
Electrical Conductivity @25C	375	360	362	363							<2	uS/cm	TM76/PM0
pH	8.14	8.21	8.20	8.29							<0.01	pH units	TM73/PM0
Total Organic Carbon	9	9	10	10							<2	mg/l	TM60/PM0
Total Nitrogen	1.7	1.9	1.8	1.7							<0.5	mg/l	TM38/PM125/PM0
Total Suspended Solids	<10	<10	<10	<10							<10	mg/l	TM37/PM0
Turbidity	4.1	6.2	2.8	9.6							<0.1	NTU	TM34/PM0

Client Name: McCarthy Keville & O'Sullivan Ltd

Reference: 291220-F

Location: Hodson Bay

Contact: Bébhinn Anders

[illegible]

Please note that only samples that are deviating are mentioned in this report. If no samples are listed it is because none were deviating. Only analyses which are accredited are recorded as deviating if set criteria are not met.

It is a requirement under ISO 17025 that we inform clients if samples are deviating i.e. outside what is expected. A deviating sample indicates that the sample 'may' be compromised but not necessarily will be compromised. The result is still accredited and our analytical reports will still show accreditation on the relevant analytes.

NOTES TO ACCOMPANY ALL SCHEDULES AND REPORTS

EMT Job No.: 26/5392

SOILS and ASH

Please note we are only MCERTS accredited (UK soils only) for sand, loam and clay and any other matrix is outside our scope of accreditation.

Where an MCERTS report has been requested, you will be notified within 48 hours of any samples that have been identified as being outside our MCERTS scope. As validation has been performed on clay, sand and loam, only samples that are predominantly these matrices, or combinations of them will be within our MCERTS scope. If samples are not one of a combination of the above matrices they will not be marked as MCERTS accredited.

It is assumed that you have taken representative samples on site and require analysis on a representative subsample. Stones will generally be included unless we are requested to remove them.

All samples will be discarded one month after the date of reporting, unless we are instructed to the contrary. Asbestos samples are retained for 6 months.

If you have not already done so, please send us a purchase order if this is required by your company.

Where appropriate please make sure that our detection limits are suitable for your needs, if they are not, please notify us immediately.

All analysis is reported on a dry weight basis unless stated otherwise. Limits of detection for analyses carried out on as received samples are not moisture content corrected. Results are not surrogate corrected. Samples are dried at 35°C ±5°C unless otherwise stated. Moisture content for CEN Leachate tests are dried at 105°C ±5°C. Ash samples are dried at 35°C ±5°C.

Where Mineral Oil is quoted, this refers to Total Aliphatics C10-C40.

Where a CEN 10:1 ZERO Headspace VOC test has been carried out, a 10:1 ratio of water to wet (as received) soil has been used.

% Asbestos in Asbestos Containing Materials (ACMs) is determined by reference to HSG 264 The Survey Guide - Appendix 2 : ACMs in buildings listed in order of ease of fibre release.

Sufficient amount of sample must be received to carry out the testing specified. Where an insufficient amount of sample has been received the testing may not meet the requirements of our accredited methods, as such accreditation may be removed.

Negative Neutralization Potential (NP) values are obtained when the volume of NaOH (0.1N) titrated (pH 8.3) is greater than the volume of HCl (1N) to reduce the pH of the sample to 2.0 - 2.5. Any negative NP values are corrected to 0.

The calculation of Pyrite content assumes that all oxidisable sulphides present in the sample are pyrite. This may not be the case. The calculation may be an overestimate when other sulphides such as Barite (Barium Sulphate) are present.

WATERS

Please note we are not a UK Drinking Water Inspectorate (DWI) Approved Laboratory .

ISO17025 accreditation applies to surface water and groundwater and usually one other matrix which is analysis specific, any other liquids are outside our scope of accreditation.

As surface waters require different sample preparation to groundwaters the laboratory must be informed of the water type when submitting samples.

Where Mineral Oil is quoted, this refers to Total Aliphatics C10-C40.

STACK EMISSIONS

Where an MCERTS report has been requested, you will be notified within 48 hours of any samples that have been identified as being outside our MCERTS scope. As validation for Dioxins and Furans and Dioxin like PCBs has been performed on XAD-2 Resin, only samples which use this resin will be within our MCERTS scope.

Where appropriate please make sure that our detection limits are suitable for your needs, if they are not, please notify us immediately.

DEVIATING SAMPLES

All samples should be submitted to the laboratory in suitable containers with sufficient ice packs to sustain an appropriate temperature for the requested analysis. The temperature of sample receipt is recorded on the confirmation schedules in order that the client can make an informed decision as to whether testing should still be undertaken.

SURROGATES

Surrogate compounds are added during the preparation process to monitor recovery of analytes. However low recovery in soils is often due to peat, clay or other organic rich matrices. For waters this can be due to oxidants, surfactants, organic rich sediments or remediation fluids. Acceptable limits for most organic methods are 70 - 130% and for VOCs are 50 - 150%. When surrogate recoveries are outside the performance criteria but the associated AQC passes this is assumed to be due to matrix effect. Results are not surrogate corrected.

DILUTIONS

A dilution suffix indicates a dilution has been performed and the reported result takes this into account. No further calculation is required.

BLANKS

Where analytes have been found in the blank, the sample will be treated in accordance with our laboratory procedure for dealing with contaminated blanks.

NOTE

Data is only reported if the laboratory is confident that the data is a true reflection of the samples analysed. Data is only reported as accredited when all the requirements of our Quality System have been met. In certain circumstances where all the requirements of the Quality System have not been met, for instance if the associated AQC has failed, the reason is fully investigated and documented. The sample data is then evaluated alongside the other quality control checks performed during analysis to determine its suitability. Following this evaluation, provided the sample results have not been effected, the data is reported but accreditation is removed. It is a requirement of our Accreditation Body for data not reported as accredited to be considered indicative only, but this does not mean the data is not valid.

Where possible, and if requested, samples will be re-extracted and a revised report issued with accredited results. Please do not hesitate to contact the laboratory if further details are required of the circumstances which have led to the removal of accreditation.

Laboratory records are kept for a period of no less than 6 years.

REPORTS FROM THE SOUTH AFRICA LABORATORY

Any method number not prefixed with SA has been undertaken in our UK laboratory unless reported as subcontracted.

Measurement Uncertainty

Measurement uncertainty defines the range of values that could reasonably be attributed to the measured quantity. This range of values has not been included within the reported results. Uncertainty expressed as a percentage can be provided upon request.

Customer Provided Information

Sample ID and depth is information provided by the customer.

Age of Diesel

The age of release estimation is based on the nC17/pristane ratio only as prescribed by Christensen and Larsen (1993) and Kaplan, Galperin, Alimi et al., (1996).

Age estimation should be treated with caution as it can be influenced by site specific factors of which the laboratory are not aware.

Tentatively Identified Compounds (TICs)

Where Tentatively Identified Compounds (TICs) are reported, up to 10 Tentatively Identified Compounds will be listed where there is found to be a greater than 80% match with the NIST library. The reported concentration is determined semi-quantitatively, with a matrix specific limit of detection.

Note, other compounds may be present but are not reported.

ABBREVIATIONS and ACRONYMS USED

#	ISO17025 (UKAS Ref No. 4225) accredited - UK.
SA	ISO17025 (SANAS Ref No.T0729) accredited - South Africa
B	Indicates analyte found in associated method blank.
DR	Dilution required.
M	MCERTS accredited.
NA	Not applicable
NAD	No Asbestos Detected.
ND	None Detected (usually refers to VOC and/SVOC TICs).
NDP	No Determination Possible
SS	Calibrated against a single substance
SV	Surrogate recovery outside performance criteria. This may be due to a matrix effect.
W	Results expressed on as received basis.
+	AQC failure, accreditation has been removed from this result, if appropriate, see 'Note' on previous page.
>>	Results above quantitative calibration range. The result should be considered the minimum value and is indicative only. The actual result could be significantly higher.
*	Analysis subcontracted to an Element Materials Technology approved laboratory.
CO	Suspected carry over
LOD/LOR	Limit of Detection (Limit of Reporting) in line with ISO 17025 and MCERTS
ME	Matrix Effect
NFD	No Fibres Detected
BS	AQC Sample
LB	Blank Sample
N	Client Sample
TB	Trip Blank Sample
OC	Outside Calibration Range
AA	x2 Dilution
AB	x3 Dilution

EMT Job No: 26/5392

Test Method No.	Description	Prep Method No. (if appropriate)	Description	ISO 17025 (UKAS/ANAS)	MCERTS (UK soils only)	Analysis done on As Received (AR) or Dried (AD)	Reported on dry weight basis
TM30	Determination of Trace Metals by ICP-OES (Inductively Coupled Plasma-Optical Emission Spectrometry): WATERS by Modified USEPA Method 200.7, Rev. 4.4, 1994; Modified EPA Method 6010B, Rev.2, Dec 1996; Modified BS EN ISO 11885:2009: SOILS by Modified USEPA 6010B, Rev.2, Dec.1996; Modified EPA Method 3050B, Rev.2, Dec.1996	PM14	Preparation of waters and leachates for metals by ICP OES/ICP MS. Samples are filtered for Dissolved metals, and remain unfiltered for Total metals then acidified				
TM34	Turbidity by 2100P Turbidity Meter. complies with EPA 180.1 1993	PM0	No preparation is required.				
TM37	Modified methods - TSS: USEPA 100.2 (1969), EN612:2009 and APHA SMEWW 2540D:1999 22nd Edition; VSS: USEPA 1684 (Jan 2001), USEPA 160.4 (1971) and SMEWW 2540E:1999 22nd Edition. Gravimetric determination of Total Suspended Solids (TSS) and Volatile Suspended Solids (VSS). Sample is filtered through a 1.5um pore size glass fibre filter and the resulting residue is dried and weighed at 105°C for TSS and 550°C for VSS.	PM0	No preparation is required.				
TM38	Soluble Ion analysis using Discrete Analyser. Modified US EPA methods: Chloride 325.2 (1978), Sulphate 375.4 (Rev.2 1993), o-Phosphate 365.2 (Rev.2 1993), TON 353.1 (Rev.2 1993), Nitrite 354.1 (1971), Hex Cr 7196A (1992), NH4+ 350.1 (Rev.2 1993) - All anions comparable to BS ISO 15923-1: 2013I	PM0	No preparation is required.				
TM38/TM125	Total Nitrogen/Organic Nitrogen by calculation	PM0	No preparation is required.				
TM57	Modified US EPA Method 410.4. (Rev. 2.0 1993) Comparable with ISO 15705:2002. Chemical Oxygen Demand is determined by hot digestion with Potassium Dichromate and measured spectrophotometrically.	PM0	No preparation is required.				
TM58	APHA SMEWW 5210B:1999 22nd Edition. Comparable with ISO 5815:1989. Measurement of Biochemical Oxygen Demand. When cBOD (Carbonaceous BOD) is requested a nitrification inhibitor is added which prevents the oxidation of reduced forms of nitrogen, such as am	PM0	No preparation is required.				
TM60	TC/TOC analysis of Waters by High Temperature Combustion followed by NDIR detection. Based on the following modified standard methods: USEPA 9060A (2002), APHA SMEWW 5310B:1999 22nd Edition, ASTM D 7573, and USEPA 415.1.	PM0	No preparation is required.				
TM73	Modified US EPA methods 150.1 (1982) and 9045D Rev. 4 - 2004) and BS1377-3:1990. Determination of pH by Metrohm automated probe analyser.	PM0	No preparation is required.				
TM75	Modified US EPA method 310.1 (1978). Determination of Alkalinity by Metrohm automated titration analyser.	PM0	No preparation is required.				

EMT Job No: 26/5392

Test Method No.	Description	Prep Method No. (if appropriate)	Description	ISO 17025 (UKAS/S ANAS)	MCERTS (UK soils only)	Analysis done on As Received (AR) or Dried (AD)	Reported on dry weight basis
TM76	Modified US EPA method 120.1 (1982). Determination of Specific Conductance by Metrohm automated probe analyser.	PM0	No preparation is required.				
TM107	Determination of Sulphide/Thiocyanate by Skalar Continuous Flow Analyser	PM0	No preparation is required.				
TM173	Analysis of fluoride by ISE (Ion Selective Electrode) using modified ISE method 9214 - 340.2 (EPA 1998)	PM0	No preparation is required.				

McCarthy Keville & O'Sullivan Ltd
2nd Floor
H91VW84
Tuam Road
Galway
Ireland



4225



Attention : Colin Fitzgerald
Date : 27th May, 2026
Your reference : 241220-F
Our reference : Test Report 26/7251 Batch 1
Location : Hodson Bay
Date samples received : 12th May, 2026
Status : Final Report
Issue : 202605271018

Four samples were received for analysis on 12th May, 2026 of which four were scheduled for analysis. Please find attached our Test Report which should be read with notes at the end of the report and should include all sections if reproduced. Interpretations and opinions are outside the scope of any accreditation, and all results relate only to samples supplied.

All analysis is carried out on as received samples and reported on a dry weight basis unless stated otherwise. Results are not surrogate corrected.

The greenhouse gas emissions generated (in Carbon – Co2e) to obtain the results in this report are estimated as:

Scope 1&2 emissions - 8.688 kg of CO2

Scope 1&2&3 emissions - 20.532 kg of CO2

Authorised By:



Phil Sommerton BSc

Senior Technical Account Manager

Please include all sections of this report if it is reproduced

Element Materials Technology

Client Name: McCarthy Keville & O'Sullivan Ltd
Reference: 241220-F
Location: Hodson Bay
Contact: Colin Fitzgerald
EMT Job No: 26/7251

Report : Liquid

Liquids/products: V=40ml vial, G=glass bottle, P=plastic bottle
H=H₂SO₄, Z=ZnAc, N=NaOH, HN=HNO₃

EMT Sample No.	1-7	8-14	15-21	22-28							Please see attached notes for all abbreviations and acronyms		
Sample ID	SW01	SW02	SW03	SW04									
Depth													
COC No / misc													
Containers	V H HN Z P BOD G	V H HN Z P BOD G	V H HN Z P BOD G	V H HN Z P BOD G									
Sample Date	11/05/2026 12:00	11/05/2026 12:30	11/05/2026 13:00	11/05/2026 13:00									
Sample Type	Surface Water	Surface Water	Surface Water	Surface Water									
Batch Number	1	1	1	1									
Date of Receipt	12/05/2026	12/05/2026	12/05/2026	12/05/2026							LOD/LOR	Units	Method No.
Dissolved Arsenic #	<2.5	<2.5	<2.5	<2.5							<2.5	ug/l	TM30/PM14
Dissolved Barium #	39	34	35	41							<3	ug/l	TM30/PM14
Dissolved Beryllium	<0.5	<0.5	<0.5	<0.5							<0.5	ug/l	TM30/PM14
Dissolved Boron	<12	<12	<12	<12							<12	ug/l	TM30/PM14
Dissolved Cadmium #	<0.5	<0.5	<0.5	<0.5							<0.5	ug/l	TM30/PM14
Dissolved Calcium #	69.8	63.5	65.6	70.3							<0.2	mg/l	TM30/PM14
Total Dissolved Chromium #	<1.5	<1.5	<1.5	<1.5							<1.5	ug/l	TM30/PM14
Dissolved Copper #	<7	<7	<7	<7							<7	ug/l	TM30/PM14
Dissolved Lead #	<5	<5	<5	<5							<5	ug/l	TM30/PM14
Dissolved Magnesium #	4.5	4.2	4.3	4.2							<0.1	mg/l	TM30/PM14
Dissolved Mercury #	<1	<1	<1	<1							<1	ug/l	TM30/PM14
Dissolved Nickel #	<2	<2	<2	<2							<2	ug/l	TM30/PM14
Dissolved Potassium #	1.9	1.9	1.9	1.6							<0.1	mg/l	TM30/PM14
Dissolved Selenium #	<3	<3	<3	<3							<3	ug/l	TM30/PM14
Dissolved Sodium #	9.2	9.8	19.0	8.6							<0.1	mg/l	TM30/PM14
Dissolved Vanadium #	<1.5	<1.5	<1.5	<1.5							<1.5	ug/l	TM30/PM14
Dissolved Zinc #	<3	<3	<3	<3							<3	ug/l	TM30/PM14
Fluoride	1.9	<0.3	<0.3	<0.3							<0.3	mg/l	TM173/PM0
Sulphate as SO ₄ #	10.0	10.0	10.0	8.1							<0.5	mg/l	TM38/PM0
Chloride #	14.0	15.8	33.6	13.4							<0.3	mg/l	TM38/PM0
Nitrate as N #	0.24	0.66	0.57	0.32							<0.05	mg/l	TM38/PM0
Nitrite as N #	<0.006	<0.006	<0.006	<0.006							<0.006	mg/l	TM38/PM0
Ortho Phosphate as P #	<0.03	<0.03	<0.03	<0.03							<0.03	mg/l	TM38/PM0
Total Oxidised Nitrogen as N #	0.2	0.7	0.6	0.3							<0.2	mg/l	TM38/PM0
Ammoniacal Nitrogen as N #	<0.03	<0.03	<0.03	0.04							<0.03	mg/l	TM38/PM0
Total Alkalinity as CaCO ₃ #	188	168	176	198							<1	mg/l	TM75/PM0
Sulphide	<10	<10	<10	<10							<10	ug/l	TM107/PM0
BOD (Settled) #	<2 _{AA}	<2 _{AA}	<2 _{AA}	<3 _{AB}							<1	mg/l	TM58/PM0
COD (Settled) #	23	22	24	31							<7	mg/l	TM57/PM0
Dissolved Organic Carbon #	9	9	9	11							<2	mg/l	TM60/PM0
Electrical Conductivity @25C #	392	369	421	389							<2	uS/cm	TM76/PM0
pH #	8.14	8.30	8.49	7.92							<0.01	pH units	TM73/PM0
Total Organic Carbon #	8	9	9	11							<2	mg/l	TM60/PM0
Total Nitrogen	1.5	1.6	1.8	2.4							<0.5	mg/l	TM38/PM125/PM0
Total Suspended Solids #	<10	<10	<10	49							<10	mg/l	TM37/PM0
Turbidity	1.8	8.2	3.7	17.4							<0.1	NTU	TM34/PM0

Client Name: McCarthy Keville & O'Sullivan Ltd

Reference: 241220-F

Location: Hodson Bay

Contact: Colin Fitzgerald

[illegible]

Please note that only samples that are deviating are mentioned in this report. If no samples are listed it is because none were deviating. Only analyses which are accredited are recorded as deviating if set criteria are not met.

It is a requirement under ISO 17025 that we inform clients if samples are deviating i.e. outside what is expected. A deviating sample indicates that the sample 'may' be compromised but not necessarily will be compromised. The result is still accredited and our analytical reports will still show accreditation on the relevant analytes.

NOTES TO ACCOMPANY ALL SCHEDULES AND REPORTS

EMT Job No.: 26/7251

SOILS and ASH

Please note we are only MCERTS accredited (UK soils only) for sand, loam and clay and any other matrix is outside our scope of accreditation.

Where an MCERTS report has been requested, you will be notified within 48 hours of any samples that have been identified as being outside our MCERTS scope. As validation has been performed on clay, sand and loam, only samples that are predominantly these matrices, or combinations of them will be within our MCERTS scope. If samples are not one of a combination of the above matrices they will not be marked as MCERTS accredited.

It is assumed that you have taken representative samples on site and require analysis on a representative subsample. Stones will generally be included unless we are requested to remove them.

All samples will be discarded one month after the date of reporting, unless we are instructed to the contrary. Asbestos samples are retained for 6 months.

If you have not already done so, please send us a purchase order if this is required by your company.

Where appropriate please make sure that our detection limits are suitable for your needs, if they are not, please notify us immediately.

All analysis is reported on a dry weight basis unless stated otherwise. Limits of detection for analyses carried out on as received samples are not moisture content corrected. Results are not surrogate corrected. Samples are dried at 35°C ±5°C unless otherwise stated. Moisture content for CEN Leachate tests are dried at 105°C ±5°C. Ash samples are dried at 35°C ±5°C.

Where Mineral Oil is quoted, this refers to Total Aliphatics C10-C40.

Where a CEN 10:1 ZERO Headspace VOC test has been carried out, a 10:1 ratio of water to wet (as received) soil has been used.

% Asbestos in Asbestos Containing Materials (ACMs) is determined by reference to HSG 264 The Survey Guide - Appendix 2 : ACMs in buildings listed in order of ease of fibre release.

Sufficient amount of sample must be received to carry out the testing specified. Where an insufficient amount of sample has been received the testing may not meet the requirements of our accredited methods, as such accreditation may be removed.

Negative Neutralization Potential (NP) values are obtained when the volume of NaOH (0.1N) titrated (pH 8.3) is greater than the volume of HCl (1N) to reduce the pH of the sample to 2.0 - 2.5. Any negative NP values are corrected to 0.

The calculation of Pyrite content assumes that all oxidisable sulphides present in the sample are pyrite. This may not be the case. The calculation may be an overestimate when other sulphides such as Barite (Barium Sulphate) are present.

WATERS

Please note we are not a UK Drinking Water Inspectorate (DWI) Approved Laboratory .

ISO17025 accreditation applies to surface water and groundwater and usually one other matrix which is analysis specific, any other liquids are outside our scope of accreditation.

As surface waters require different sample preparation to groundwaters the laboratory must be informed of the water type when submitting samples.

Where Mineral Oil is quoted, this refers to Total Aliphatics C10-C40.

STACK EMISSIONS

Where an MCERTS report has been requested, you will be notified within 48 hours of any samples that have been identified as being outside our MCERTS scope. As validation for Dioxins and Furans and Dioxin like PCBs has been performed on XAD-2 Resin, only samples which use this resin will be within our MCERTS scope.

Where appropriate please make sure that our detection limits are suitable for your needs, if they are not, please notify us immediately.

DEVIATING SAMPLES

All samples should be submitted to the laboratory in suitable containers with sufficient ice packs to sustain an appropriate temperature for the requested analysis. The temperature of sample receipt is recorded on the confirmation schedules in order that the client can make an informed decision as to whether testing should still be undertaken.

SURROGATES

Surrogate compounds are added during the preparation process to monitor recovery of analytes. However low recovery in soils is often due to peat, clay or other organic rich matrices. For waters this can be due to oxidants, surfactants, organic rich sediments or remediation fluids. Acceptable limits for most organic methods are 70 - 130% and for VOCs are 50 - 150%. When surrogate recoveries are outside the performance criteria but the associated AQC passes this is assumed to be due to matrix effect. Results are not surrogate corrected.

DILUTIONS

A dilution suffix indicates a dilution has been performed and the reported result takes this into account. No further calculation is required.

BLANKS

Where analytes have been found in the blank, the sample will be treated in accordance with our laboratory procedure for dealing with contaminated blanks.

NOTE

Data is only reported if the laboratory is confident that the data is a true reflection of the samples analysed. Data is only reported as accredited when all the requirements of our Quality System have been met. In certain circumstances where all the requirements of the Quality System have not been met, for instance if the associated AQC has failed, the reason is fully investigated and documented. The sample data is then evaluated alongside the other quality control checks performed during analysis to determine its suitability. Following this evaluation, provided the sample results have not been effected, the data is reported but accreditation is removed. It is a requirement of our Accreditation Body for data not reported as accredited to be considered indicative only, but this does not mean the data is not valid.

Where possible, and if requested, samples will be re-extracted and a revised report issued with accredited results. Please do not hesitate to contact the laboratory if further details are required of the circumstances which have led to the removal of accreditation.

Laboratory records are kept for a period of no less than 6 years.

Date

The dates of the performance of laboratory activity are available on request.

Measurement Uncertainty

Measurement uncertainty defines the range of values that could reasonably be attributed to the measured quantity. This range of values has not been included within the reported results. Uncertainty expressed as a percentage can be provided upon request.

Customer Provided Information

Sample ID and depth is information provided by the customer.

Age of Diesel

The age of release estimation is based on the nC17/pristane ratio only as prescribed by Christensen and Larsen (1993) and Kaplan, Galperin, Alimi et al., (1996).

Age estimation should be treated with caution as it can be influenced by site specific factors of which the laboratory are not aware.

Tentatively Identified Compounds (TICs)

Where Tentatively Identified Compounds (TICs) are reported, up to 10 Tentatively Identified Compounds will be listed where there is found to be a greater than 80% match with the NIST library. The reported concentration is determined semi-quantitatively, with a matrix specific limit of detection.

Note, other compounds may be present but are not reported.

ABBREVIATIONS and ACRONYMS USED

#	ISO17025 (UKAS Ref No. 4225) accredited - UK.
SA	ISO17025 (SANAS Ref No.T0729) accredited - South Africa
B	Indicates analyte found in associated method blank.
DR	Dilution required.
M	MCERTS accredited.
NA	Not applicable
NAD	No Asbestos Detected.
ND	None Detected (usually refers to VOC and/SVOC TICs).
NDP	No Determination Possible
SS	Calibrated against a single substance
SV	Surrogate recovery outside performance criteria. This may be due to a matrix effect.
W	Results expressed on as received basis.
+	AQC failure, accreditation has been removed from this result, if appropriate, see 'Note' on previous page.
>>	Results above quantitative calibration range. The result should be considered the minimum value and is indicative only. The actual result could be significantly higher.
*	Analysis subcontracted to an Element Materials Technology approved laboratory.
CO	Suspected carry over
LOD/LOR	Limit of Detection (Limit of Reporting) in line with ISO 17025 and MCERTS
ME	Matrix Effect
NFD	No Fibres Detected
BS	AQC Sample
LB	Blank Sample
N	Client Sample
TB	Trip Blank Sample
OC	Outside Calibration Range
AA	x2 Dilution
AB	x3 Dilution

EMT Job No: 26/7251

Test Method No.	Description	Prep Method No. (if appropriate)	Description	ISO 17025 (UKAS/ANAS)	MCERTS (UK soils only)	Analysis done on As Received (AR) or Dried (AD)	Reported on dry weight basis
TM30	Determination of Trace Metals by ICP-OES (Inductively Coupled Plasma-Optical Emission Spectrometry): WATERS by Modified USEPA Method 200.7, Rev. 4.4, 1994; Modified EPA Method 6010B, Rev.2, Dec 1996; Modified BS EN ISO 11885:2009: SOILS by Modified USEP 6010B, Rev.2, Dec.1996; Modified EPA Method 3050B, Rev.2, Dec.1996	PM14	Preparation of waters and leachates for metals by ICP OES/ICP MS. Samples are filtered for Dissolved metals, and remain unfiltered for Total metals then acidified				
TM30	Determination of Trace Metals by ICP-OES (Inductively Coupled Plasma-Optical Emission Spectrometry): WATERS by Modified USEPA Method 200.7, Rev. 4.4, 1994; Modified EPA Method 6010B, Rev.2, Dec 1996; Modified BS EN ISO 11885:2009: SOILS by Modified USEP 6010B, Rev.2, Dec.1996; Modified EPA Method 3050B, Rev.2, Dec.1996	PM14	Preparation of waters and leachates for metals by ICP OES/ICP MS. Samples are filtered for Dissolved metals, and remain unfiltered for Total metals then acidified	Yes			
TM34	Turbidity by 2100P Turbidity Meter. complies with EPA 180.1 1993	PM0	No preparation is required.				
TM37	Modified Methods - TSS: USEPA 100.2 (1993); EN612:2003 and APHA SMEWW 2540D:1999 22nd Edition; VSS: USEPA 1684 (Jan 2001), USEPA 160.4 (1971) and SMEWW 2540E:1999 22nd Edition. Gravimetric determination of Total Suspended Solids (TSS) and Volatile Suspended Solids (VSS). Sample is filtered through a 1.5um pore size glass fibre filter and the resulting residue is dried and weighed at 105°C for TSS and 550°C for VSS.	PM0	No preparation is required.	Yes			
TM38	Soluble Ion analysis using Discrete Analyser. Modified US EPA methods: Chloride 325.2 (1978), Sulphate 375.4 (Rev.2 1993), o-Phosphate 365.2 (Rev.2 1993), TON 353.1 (Rev.2 1993), Nitrite 354.1 (1971), Hex Cr 7196A (1992), NH4+ 350.1 (Rev.2 1993) - All anions comparable to BS ISO 15923-1: 2013	PM0	No preparation is required.	Yes			
TM38/TM125	Total Nitrogen/Organic Nitrogen by calculation	PM0	No preparation is required.				
TM57	Modified US EPA Method 410.4. (Rev. 2.0 1993) Comparable with ISO 15705:2002. Chemical Oxygen Demand is determined by hot digestion with Potassium Dichromate and measured spectrophotometrically.	PM0	No preparation is required.	Yes			
TM58	APHA SMEWW 5210B:1999 22nd Edition. Comparable with ISO 5815:1989. Measurement of Biochemical Oxygen Demand. When cBOD (Carbonaceous BOD) is requested a nitrification inhibitor is added which prevents the oxidation of reduced forms of nitrogen, such as am	PM0	No preparation is required.	Yes			
TM60	TC/TOC analysis of Waters by High Temperature Combustion followed by NDIR detection. Based on the following modified standard methods: USEPA 9060A (2002), APHA SMEWW 5310B:1999 22nd Edition, ASTM D 7573, and USEPA 415.1.	PM0	No preparation is required.	Yes			
TM73	Modified US EPA methods 150.1 (1982) and 9045D Rev. 4 - 2004) and BS1377-3:1990. Determination of pH by Metrohm automated probe analyser.	PM0	No preparation is required.	Yes			

EMT Job No: 26/7251

Test Method No.	Description	Prep Method No. (if appropriate)	Description	ISO 17025 (UKAS/ANAS)	MCERTS (UK soils only)	Analysis done on As Received (AR) or Dried (AD)	Reported on dry weight basis
TM75	Modified US EPA method 310.1 (1978). Determination of Alkalinity by Metrohm automated titration analyser.	PM0	No preparation is required.	Yes			
TM76	Modified US EPA method 120.1 (1982). Determination of Specific Conductance by Metrohm automated probe analyser.	PM0	No preparation is required.	Yes			
TM107	Determination of Sulphide/Thiocyanate by Skalar Continuous Flow Analyser	PM0	No preparation is required.				
TM173	Analysis of fluoride by ISE (Ion Selective Electrode) using modified ISE method 9214 - 340.2 (EPA 1998)	PM0	No preparation is required.				