

Ownership BoundaryDevelopment BoundaryPermitted Pinewoods Wind FarmFolio Not Related to Proposed DevelopmentArea of FillArea of CutPermitted Laois - Kilkenny Grid Reinforcement Project 110kV Overhead LineSubstation Access TrackSubstation Buildings & Footpath150mm thick top layer of permeable compound stone consisting of 50mm single sized crushed Linestone3m Embankment	
Permitted Pinewoods Wind Farm Folio Not Related to Proposed Development Area of Fill Area of Cut Permitted Laois - Kilkenny Grid Reinforcement Project 110kV Overhead Line Substation Access Track Substation Buildings & Footpath 150mm thick top layer of permeable compound stone consisting of 50mm single sized crushed Limestone	
<ul> <li>Folio Not Related to Proposed Development</li> <li>Area of Fill</li> <li>Area of Cut</li> <li>Permitted Laois - Kilkenny Grid Reinforcement Project 110kV Overhead Line</li> <li>Substation Access Track</li> <li>Substation Buildings &amp; Footpath</li> <li>150mm thick top layer of permeable compound stone consisting of 50mm single sized crushed Limestone</li> </ul>	
Area of Fill Area of Cut Permitted Laois - Kilkenny Grid Reinforcement Project 110kV Overhead Line Substation Access Track Substation Buildings & Footpath 150mm thick top layer of permeable compound stone consisting of 50mm single sized crushed Limestone	
Area of Cut Permitted Laois - Kilkenny Grid Reinforcement Project 110kV Overhead Line Substation Access Track Substation Buildings & Footpath 150mm thick top layer of permeable compound stone consisting of 50mm single sized crushed Limestone	
Permitted Laois - Kilkenny Grid Reinforcement Project 110kV Overhead Line Substation Access Track Substation Buildings & Footpath 150mm thick top layer of permeable compound stone consisting of 50mm single sized crushed Limestone	
Project 110kV Overhead Line Substation Access Track Substation Buildings & Footpath 150mm thick top layer of permeable compound stone consisting of 50mm single sized crushed Limestone	
Substation Buildings & Footpath 150mm thick top layer of permeable compound stone consisting of 50mm single sized crushed Limestone	
150mm thick top layer of permeable compound stone consisting of 50mm single sized crushed Limestone	
compound stone consisting of 50mm single sized crushed Limestone	
3m Embankment	
800mm High Earth Berm	
600mm High Stone Berm	
Concrete Equipment Plinths	
2.95m High Palisade Fence	00-
Concrete Post & Rail Fence	00-
Post & Wire Stockproof Fence	-00-
100mm Ø uPVC Foul Water Pipe	
150mm Ø uPVC Storm Water Pipe	
Foul Water AJ	<b>A.J.</b>
Foul Water Manhole	(MH)
Storm Water AJ	<b>A.J.</b>
Storm Water Manhole	(MH)
Existing 1m Contours	<del>249.0</del>
Proposed Levels	- <del> </del>
	1

C.M.P.

S.C.

J.B.