


TREE PLANTING DETAIL A (clear or multi-stemmed trees)

- Q31/505 The tree pit should be excavated to allow adequate earance between the root ends (when fully spread) and the side
- of the pit.

 Care is to be the tree pit to 1200x1200x1000mm depth. Care is to be the pit damage existing landscape finishes (topsoil, mulch, plants, grass lawns etc); protection from foot damage is to be provided by the use of boards.
- Fork the bottom and sides of the pit to break up the sub-soil. Q31/586 Back-fill with 1200mm³ multi-purpose grade topsoil to BS:3882 as shown to the level of the roots. Scarify pit sides, and ensure pit bottom is slightly raised.
- Q31/515 On heavy wet soils, provide a min 150mm depth of clean gravel or broken stone, with no fines, graded 40 to 20 mm with a geotextile filter membrane on top to aid drainage.
- Mix the dug soil with a slow-release fertiliser and an approved soil ameliorant.
- 6. Stakes and rail to be half-round 150mm diameter planed finish. Drive in the stakes so that they are a minimum of 300mm below the bottom of the pit, and 650mm above the ground level. The stakes and rail are to be sweet chestnut or peeled larch poles, pointed at one end, preserved to resist rot for their intended lifespan, and strong enough to take galvanised screws without splitting.
- Plant the tree, ensuring that the original depth is maintained and the soil is carefully firmed back up to the existing ground level.
- Secure the rail to the stakes with 2 no. galvanised screws per stake. Secure the tree to the rail with 2 no rainbow type rubber tree ties,
- screw-fixed to rails. Secure ties to allow for movement but to prevent damage to trunk. Q31/512 Install irrigation/ventilation pipe, woven coil pipe wrapped 1.5 times to encircle rootball with plastic cover cap. Watering filler
- cap to finish slightly above mulch level. 11. Spread Q37/430 75mm depth medium-grade bark mulch over around the tree, and maintain it until the spring following the first
- growing season (1200mmØ where tree is in lawn surfacing). 12. Protect the tree base and stem from damage by using a bamboo or hessian wrap tree guard to 2m height.
- 13. The stakes and rail are to be removed as soon as the tree is anchored securely by its own roots (generally at the start of the third growing season after planting.
- 14. Q31/510 wherever the installed rootball will be within 3.0 m of an existing underground service route and 2.0m of a building or paving foundation, install a tree pit root barrier, geotextile or cylinder type as appropriate. Top of root barrier to finish 75mm below finished soil level, installation with sides vertical.



TREE STAKE END ELEVATION


PLANED RAIL SECURED WITH 2NR GALVANISED SCREWS

PLANED VERTICAL STAKE

STAKES AND RAIL TO BE HALF-ROUND 150MM DIAMETER PLANED FINISH

SHRUB/TRANSPLANT PLANTING DETAIL

- All shrub/transplant planting beds to Q31/315 300/450mm depth of quality approved multi-purpose grade topsoil to BS: 3882 or as otherwise specified.
- Break up the soil in the base of each pit. Mix the dug soil with a slow release fertiliser and a
- specified soil ameliorant. Planting is to be carried out to the densities
- specified. Once planted, back-fill with the remaining soil and firm as before.
- Top-dress the planting area with a Q37/430 75mm depth of medium-grade bark mulch, and maintain it until the spring following the first growing season. Mulch to finish 25mm below adjacent surfacing.



WOODEN EDGING

Tanalised pressure-treated larch timber edging board, 50x150mm variable lengths, secured with 50x50x400mm tanalised pressure-treated larch timber posts at 1000mm c/cs, fixed to edging with 2 no. galvanised screws 80mm long.

LAWN SURFACING DETAIL

- Excavate lawn areas to 100mm depth and break up base of lawn area to ensure free drainage.
- Q31/315 Back-fill with min. 150mm depth multi-purpose grade topsoil to BS:3882 to lawn areas.
- Seed bed: Reduce to fine, firm tilth with good crumb structure, depth: 25mm.
- Surface preparation: Rake to a true, even surface, friable and lightly firmed but not over compacted. Remove surface stones/earth clods exceeding: general areas: 40mm, fine lawn areas:
- Seed with Q30/310 grass seed mix or surface with Q30/410 turf as specified.
- Q30/428 Compost dressing, 20mm

GENERAL NOTES (cont.)

Plant Material (cont).

- 3. All plants to be planted at the same depth as previously grown.
- 4. Sufficient soil must be removed from the planting pit to allow the roots to fully spread. Care must be taken with root systems - with dry, damaged roots being carefully pruned.

Planting:

(refer to Plant Schedule for species, sizes and planting densities)

- 3. All shrubs to be pit-planted. General pit dimensions to be 300mm depth and back-filled with previously cultivated, excavated material. Back-filling to be done in layers of 150mm depth; at each stage the filling is to be firmly consolidated.
- 4. All trees to be pit-planted. Standard tree pits to be a minimum size of 1200x1200x1000mm. Semi-mature trees to agreed dimensions dependent on rootball size. Remove the full depth of topsoil and set aside for re-use.

Mulching:

1. All planting areas to receive a full even 75mm thickness of medium-grade pulverised bark mulch graded from 40mm down, sample to be provided for approval. During subsequent weeding/maintenance do not incorporate the mulch into the underlying soil. Care must also be taken against mulch becoming so dry as to become a fire hazard. If necessary, the areas must be dampened down.

Grass: (refer to Site Preparation Notes)

- 1. Bring top 100mm of topsoil (see above) to a fine tilth, ensuring there are no stones over 25mm diameter
- 2. Spray areas with an approved herbicide at manufacturer's recommended
- 3. Incorporate an approved pre-seeding slow release granular fertiliser at 50g/m² and work into top 50mm of topsoil.
- 4. Sow an approved low maintenance grass seed mix in two operations at a
- rate of 25gs/m² (350kh/Ha). 5. Harrow and roll seed bed lightly after sowing.

Drawn LP


3 plants per m2 or as otherwise specified

GENERAL NOTES


Clearance:

Planting Density: 4 per m²

All shrub planting to follow 1m grid in straight parallel staggered rows to specified centres as shown.




Planting Density: 3 per m² All shrub planting to follow 1m grid in straight parallel staggered rows




Planting Density: 2 per m²

All shrub planting to follow 1m grid in straight parallel staggered rows to specified centres as shown.



Planting Density: 1 per m²

All shrub planting to follow 1m grid in straight parallel staggered rows to specified centres as shown.



manufacturer's instructions Site Preparation:

1. Following herbicide treatment (duration depending on herbicide type) the entire area shall be cultivated to a medium tilth prior to topsoil being spread. All topsoil shall comply with the following:

1. All rubble, stone over 50mm, general rubbis and builders' debris to be

cleared from the proposed planting areas and carried off site to an

2. The planting area shall be treated with an approved herbicide. Any

chemicals to be approved by the landscape architect and applied to

approved tip on prior to any excavation/cultivation works.

- All imported topsoil to be multi-purpose grade to BS:3882.
- Soil shall have an acidity reading of between pH 8.0 and 7.0.
- Stone content shall be over 5%, but not exceeding 20% stones by dry weight.
- Minimum size of stone to be 20mm Ø on largest size.
- Soil make-up: 16-27% clay: 0-70% sand; 20-40% silt and fibrous
- 2. Topsoil to be free of grass, pernicious weeds and weed seed. 3. After all topsoil spread and prior to planting to be cultivated to a
- medium tilth and then turned over to a minimum of 300mm. Incorporate an approved peat-free planting compost at a rate of 20LT/m² to a minimum depth of 100mm. Incorporate an approved slow-release granular fertiliser at the manufacturer's recommended
- 4. Topsoil to be spread to a minimum depth of 300mm to shrub and transplant planting areas and 150mm to grass seed bed.

Plant Material

- 1. All plant material shall be pest and disease free.
- 2. All planting to be carried out during the period of late October to

CHARTERED LANDSCAPE ARCHITECTS 68 Pearse Street Dublin 2 tel: 01 6775670 Client The Ardee Partnership Project Residential Dev at Bridgegate, Rathgory & Mulladrillen, Ardee Title Planting details Date Issued 2021-10-19 Drg No 20-547-SDA-PD-DR-300 Scale nts @ A3

Purpose Planning

STEPHEN **DIAMOND** ASSOCIATES