

Energy Statement

SHD at Holybanks, Swords

March 2022

Waterman Moylan Consulting Engineers Limited

Block S, EastPoint Business Park, Alfie Byrne Road, Dublin 3
www.watermangroup.com



Client Name: Cairn Homes Properties Ltd
Document Reference: 17-088r.016
Project Number: 17-088

Quality Assurance – Approval Status

This document has been prepared and checked in accordance with
Waterman Group's IMS (BS EN ISO 9001: 2015, BS EN ISO 14001: 2015)

Issue	Date	Prepared by	Checked by	Approved by
1	15-10-2020	A.Brophy	N. Coughlan	N. Coughlan
2	17-12-2021	N. Coughlan	N. Coughlan	N. Coughlan
3	23-03-2021	N. Coughlan	N. Coughlan	N. Coughlan

Comments

Disclaimer

This report has been prepared by Waterman Moylan, with all reasonable skill, care and diligence within the terms of the Contract with the Client, incorporation of our General Terms and Condition of Business and taking account of the resources devoted to us by agreement with the Client.

We disclaim any responsibility to the Client and others in respect of any matters outside the scope of the above.

This report is confidential to the Client and we accept no responsibility of whatsoever nature to third parties to whom this report, or any part thereof, is made known. Any such party relies on the report at its own risk.

Content

- 1. Introduction.....7**
- 2. Building Regulations Part L 2021 - Dwellings9**
 - 2.1 Regulation 8 Part (a)9
 - 2.2 Regulation 8 Part (b)9
 - 2.3 Regulation 8 Part (c)9
 - 2.4 Regulation 8 Parts (d & e).....10
 - 2.5 Regulation 8 Parts (f)10
- 3. Building Regulations Part L 2021 (Building Other than Dwellings)11**
 - 3.1 Regulation L5 Parts (a)11
 - 3.2 Regulation L5 Parts (b)11
 - 3.3 Regulation L5 Parts (c)11
 - 3.4 Regulation L5 Parts (d)12
 - 3.5 Regulation L5 Parts (e)12
 - 3.6 Regulation L5 Parts (f)13
 - 3.7 Regulation L5 Parts (g)13
 - 3.8 Regulation L5 Parts (h)13
 - 3.9 Regulation L5 Parts (i)13
- 4. Building Fabric.....14**
 - 4.1 Elemental U-Values14
 - 4.2 Air Permeability14
 - 4.3 Thermal Bridging.....15
- 5. Heat Sources & Renewable Energy Options – Dwellings16**
 - 5.1 Houses16
 - 5.1.1 Air Source Heat Pumps16
 - 5.2 Apartments16
 - 5.2.1 Option 1 - District Heating16
 - 5.2.2 Option 2 - Individual Plant – Exhaust Air Heat Pumps17
 - 5.2.3 Option 3 - Individual Plant – Electric Heaters, Hot Water Heat Pumps & PV Panels....17
 - 5.3 Ventilation Design18
 - 5.3.1 Traditional Natural Ventilation Approach18
 - 5.3.2 Whole House Mechanical Heat Recovery Ventilation (MHRV)18
 - 5.3.3 Mechanical Whole House Extract (MEV)18
- 6. Heat Sources & Renewable Energy Options – Creche & Amenity Areas20**
 - 6.1 Gas Fired Boilers with Solar Panels.20
 - 6.2 Air Source Heat Pumps20

7. Proposed Solutions for the Development.....	22
7.1 Dwellings.....	22
7.2 Creche & Amenity Areas.....	22

1. Introduction

The proposed scheme will consist of the development of the existing 13.4 Ha vacant site adjacent to the Glen Ellan Road in Swords to provide a total of 621 no. residential units comprising a mix of housing typologies, duplexes and apartments. The proposal also includes the provision of public open space, vehicular access, surface level car parking, basement carparking including bicycle parking, plant and storage, all associated ancillary works including site development works, and hard and soft landscaping. The detailed breakdown of the scheme including the residential units is as follows:

- 118 no. houses comprising: 8 no. 1-storey, 1-bed maisonette units; 99 no. 2-storey, 3-bed units (18 no. mid-terrace and 81 no. semi-detached) and 11 no. 2-storey, 4-bed units (semi-detached).
- 349 no. apartment units (137 no. 1-bed units, 201 no. 2-bed units, and 11 no. 3-bed units) provided within 2 no. blocks ranging in height from 1 no. to 7 no. storeys (over basement level) to the south side of the site along Glen Ellan Road. A single level basement has been provided for Block B and an under-croft area is provided within Block A incorporating parking areas, waste management areas, plant rooms and other ancillary services.
- 154 no. duplex units that are arranged within 14 no. 3-storey blocks comprising of 77 no. 2-bed units (ground floor) and 77 no. 3-bed units.
- Apartments and duplexes are provided with balconies/terraces along all elevations and dedicated services / bin store areas.
- The development will also provide for an ancillary childcare facility (506.5 sq.m), and residential amenity facilities (573 sq.m) including gym, concierge, meeting room and multi-purpose room within the ground floor of Block B.
- Provision of 705 no. car parking spaces, 856 no. bicycle parking spaces and 21 no. motorbike parking spaces (within basement, under-croft and at surface levels);
- The landscape proposal includes extensive public open space (10,008 sq.m.), in addition to a new public park measuring 29,400 sq.m as an extension of Broadmeadow Riverside Park to the north of the site.
- Principal vehicular access to the site is from Glen Ellan Road, with an additional new secondary site entrance provided from Jugback Lane/Terrace. New pedestrian connections are provided to the site from Jugback Lane/Terrace, Glen Ellan Road and the proposed Broadmeadow Riverside Park extension to the north of the site. Further, a segregated pedestrian/cycle path is proposed along a central green spine, connecting Glen Ellan Road in the south with Broadmeadow Riverside Park extension in the north.
- Junction and road improvement works are proposed to the Glen Ellan / Balheary Road junction and R132/R125 Seatown West Roundabout. This will include widening of Balheary Road (South), upgrade works to cycle/pedestrian facilities and for the partial signalisation of R132/R125 junction. The application also contains proposals to upgrade existing Irish Water infrastructure including the construction of a stormwater storage tank and overflow outfall gravity sewer to the Broadmeadow River.

- All associated site development works above and below ground including hard and soft landscaping, roads/footpaths/cycle paths, play areas, public art, boundary treatments, lighting, SuDs, pumping station, EV charging points, green roofs, ESB substations and services to facilitate the development.
- As part of the proposed development, temporary permission (3 no. years) is sought for a single-storey Marketing Suite and associated signage (including hoarding) during the development construction stage.

This report identifies the energy standards with which the proposed development will have to comply and also sets out the overall strategy that will be adopted to achieve these energy efficiency targets.

The dwellings will be required to minimise overall energy use and to incorporate an adequate proportion of renewable energy in accordance with Building Regulations Part L 2021, Conservation of Energy & Fuel (hereinafter referred to as “Part L 2021 Dwellings”).

The creche and amenity spaces will be designed to meet the requirements of Building Regulations Part L 2021, Buildings Other than Dwellings (hereinafter referred to as “*Part L 2021 BOTD*”).

2. Building Regulations Part L 2021 - Dwellings

Compliance with Building Regulations Part L 2021 Dwellings is broken down into six distinct categories, known as Regulation 8; parts (a) to (f).

A summary of each of these parts as listed in Technical Guidance Document Part L 2021 Dwellings is provided below together with a description of what is required to demonstrate compliance and suggested routes to meeting the required standards.

2.1 Regulation 8 Part (a)

The regulation requires that:

Providing that the energy performance of the building is such as to limit the calculated primary energy consumption and related carbon dioxide (CO₂) to that of a nearly zero energy building within the meaning of the Directive insofar as is reasonably

Part (a) is the overarching compliance target which stipulates the required overall reduction in energy consumption and carbon emissions for new dwellings.

This requires that the energy consumption and carbon emissions of every dwelling is assessed using the DEAP software and that reductions of 70% in energy consumption and 65% in carbon emissions are achieved. The baseline against which this reduction is to be measured is considered to be a dwelling which is constructed to perfectly comply with the 2005 version of Building Regulations Part L.

The ratio of the energy consumed by the proposed dwelling to a similar dwelling constructed to 2005 energy efficiency standards is referred to as the “Energy Performance Co-efficient”

2.2 Regulation 8 Part (b)

The regulation requires that:

Providing that, the nearly zero or very low amount of energy required is covered to a very significant extent by energy from renewable sources, including energy from renewable sources produced on-site or nearby;

This requires that the all new dwellings are provided with a renewable energy source. The regulations state that 20% of the total energy consumed within the dwelling must be provided from renewable thermal sources (solar thermal, biomass, heat pumps) or renewable electrical sources (Photovoltaic, Micro-wind).

In practical terms, for a multiple unit development, this requirement is usually met by incorporating PV panels at roof level, incorporating air source heat pump technology or by adding an element of biomass or micro-CHP to a district heating scheme.

Where CHP is included, the renewable energy is considered to be the waste heat which is generated as a by-product of the electricity produced. Specific calculation methods are set out within *Part L 2021 Dwellings* which detail how compliance should be demonstrated.

2.3 Regulation 8 Part (c)

The regulation requires that:

Limiting heat loss and, where appropriate, availing of heat gain through the fabric of the building;

This requires that the fabric of the building is designed to minimise heat loss from the building and that the air permeability of the structure limits the unwanted passage of air into the building.

Typical compliant U-Values are as follows.

Pitched roof	0.16 W/m ² K
Flat roof	0.20 W/m ² K
Walls	0.18 W/m ² K
Floor	0.18 W/m ² K
Windows	1.4 W/m ² K

The u-values of individual elements can be relaxed if required provided that compensatory measures are taken on other elements and that the overall area weighted u-value for the entire dwelling is the same as it would have been if all individual elements had complied.

The thermal bridging details of junctions in the envelope of the building (floor-wall; wall-window; wall-roof, etc) must also be designed and constructed in accordance with the guidance set out in Limiting Thermal Bridging and Air Infiltration – Acceptable Construction Details

Every dwelling must also be subjected to an air pressure test to determine the air tightness. All dwellings must achieve and **air tightness of less than 5m³/m²/hour** when tested at 50 Pascals. In multiple dwelling developments with repeating house/apartment types, testing can be conducted on a representative sample of units in accordance with Table 1.5.4.3 of *Part L 2021 Dwellings*

2.4 Regulation 8 Parts (d & e)

The regulation requires that:

Providing and commissioning energy efficient space and water heating systems with efficient heat sources and effective controls;

Providing that all oil and gas fired boilers shall meet a minimum seasonal efficiency of 90%;

These require that gas or oil-fired boilers are at least 90% efficient and that heating controls allow independent time control of the heating (2 zones for dwellings larger than 100m²) and hot water. Heating in each zone should also be controlled by room thermostats (in the case of heating) and cylinder stats (in the case of hot water).

2.5 Regulation 8 Parts (f)

The regulation requires that:

Providing to the dwelling owner sufficient information about the building, the fixed building services and their maintenance requirements so that the building can be operated in such a manner as to use no more fuel and energy than is reasonable.

This requires that information is provided to the dwelling owner which relates to the effective and efficient operation of the systems installed in that house. Instructions on how to control the heating & hot water systems based on time and temperature requirements.

3. Building Regulations Part L 2021 (Building Other than Dwellings)

Compliance with Building Regulations Part L 2021 BOTD is broken down into seven distinct categories, known as Regulation L5 parts (a) to (i).

A summary of each of these parts as listed in Technical Guidance *Document L 2021 BOTD* is provided below together with a description of what is required to demonstrate compliance and suggested routes to meeting the required standards.

3.1 Regulation L5 Parts (a)

The regulation requires that:

(a) providing that the energy performance of the building is such as to limit the calculated primary energy consumption and related Carbon Dioxide (CO₂) emissions to a Nearly Zero Energy Building level insofar as is reasonably practicable, when both energy consumption and Carbon Dioxide emissions are calculated using the Non-domestic Energy Assessment Procedure (NEAP) published by Sustainable Energy Authority of Ireland;

Part (a) is the overarching compliance target which stipulates the required overall reduction in energy consumption and carbon emissions for new commercial buildings.

This requires that the energy consumption and carbon emissions of every building is assessed using the SBEM software and that the energy consumption and carbon emissions associated with the building being assessed are in line with the required standards.

3.2 Regulation L5 Parts (b)

The regulation requires that:

providing that, the nearly zero or very low amount of energy required is covered to a very significant extent by energy from renewable sources produced on-site or nearby.

This requires that Renewable Energy Technologies are provided. This to be reflected by Renewable Energy Ratio (RER) which is the ratio of the primary energy from renewable energy sources to total primary energy as defined and calculated in NEAP. RER for commercial buildings was as follows

- Where the MPEPC of 1.0 and MPCPC of 1.15 is achieved an RER of 0.20
- Where an EPC of 0.9 and a CPC of 1.04 is achieved an RER of 0.10

3.3 Regulation L5 Parts (c)

The regulation requires that:

limiting the heat loss and, where appropriate, availing of the heat gains through the fabric of the building.

This requires that the fabric of the building is designed to minimise heat loss from the building and that the air permeability of the structure limits the unwanted passage of air into the building.

Typical compliant U-Values are as follows.

Pitched roof	0.16 W/m ² K
Flat roof	0.20 W/m ² K
Walls	0.21 W/m ² K
Floor	0.21 W/m ² K
Windows	1.6 W/m ² K

The u-values of individual elements can be relaxed if required provided that compensatory measures are taken on other elements and that the overall area weighted u-value for the entire building is the same as it would have been if all individual elements had complied.

The thermal bridging details of junctions in the envelope of the building (floor-wall; wall-window; wall-roof, etc) must also be designed and constructed in accordance with Acceptable Construction Details and/or certified details for all key junctions.

Building must also be subjected to an air pressure test to determine the air tightness and must achieve an air tightness of less than 5m³/m²/hour when tested at 50 Pascals.

3.4 Regulation L5 Parts (d)

The regulation requires that:

providing and commissioning energy efficient space heating and cooling systems, heating and cooling equipment, water heating systems, and ventilation systems, with effective controls.

This requires that heat- generators should be designed and installed so that they operate efficiently over the range of loading likely to be encountered. This means that gas or oil-fired boilers are at least 86% efficient for output less than 70kW and 93% efficient for output over 70kW. Space and water heating systems should be effectively controlled so as to limit energy use by these systems.

Additionally, buildings should be designed and constructed in such way that there is no requirement for excessive installed capacity of Air Conditioning and Mechanical Ventilation for cooling purposes and the ventilating and cooling systems installed are energy efficient and are capable of being controlled to achieve optimum energy efficiency.

3.5 Regulation L5 Parts (e)

The regulation requires that:

ensuring that the building is appropriately designed to limit need for cooling and, where air-conditioning or mechanical ventilation is installed, that installed systems are energy efficient, appropriately sized and adequately controlled.

This requires that the glazed elements of the proposed building are design to limit solar gain to acceptable levels. Design approaches that are often adopted to address this requirement include reducing total glazing areas, introducing internal or external shading devices or using specifically selected solar control glazing to reduce the solar gain.

3.6 Regulation L5 Parts (f)

The regulation requires that:

limiting the heat loss from pipes, ducts and vessels used for the transport or storage of heated water or air.

this requires that hot water storage vessels, pipes and ducts associated with the provision of heating and hot water in a building should be insulated to limit heat loss, except where the heat flow through the wall of the pipe, duct or vessel is always useful in conditioning the surrounding space.

3.7 Regulation L5 Parts (g)

The regulation requires that:

limiting the heat gains by chilled water and refrigerant vessels, and by pipes and ducts that serve air conditioning systems.

this requires that storage vessels for chilled water and refrigerant, and pipes and ducts that serve air-conditioning systems should be insulated to limit heat gain from the surrounding environment.

3.8 Regulation L5 Parts (h)

The regulation requires that:

providing energy efficient artificial lighting systems and adequate control of these systems.

this requires that artificial lighting systems shall be designed and controlled so as to ensure the efficient use of energy for this purpose. Lighting controls should encourage the maximum use of daylight and help avoiding unnecessary artificial lighting.

3.9 Regulation L5 Parts (i)

The regulation requires that:

providing to the building owner or occupants sufficient information about the building, the fixed building services, controls and their maintenance requirements so that the building can be operated in such a manner as to use no more fuel and energy than is reasonable.

This requires that information is provided to the dwelling owner which relates to the effective and efficient operation of the systems installed in that house. Instructions on how to control the heating & hot water systems based on time and temperature requirements.

4. Building Fabric

Before considering efficient building services or renewable energy systems, the form and fabric of a building must be assessed and optimised so as to reduce the energy demand for heating, lighting and ventilation. Target performance levels have been identified by the design team and are presented below.

4.1 Elemental U-Values

The U-Value of a building element is a measure of the amount of heat energy that will pass through the constituent element of the building envelope. Increasing the insulation levels in each element will reduce the heat lost during the heating season and this in turn will reduce the consumption of fuel and the associated carbon emissions and operating costs.

It is the intention of the design team to exceed the requirements of the building regulations. Target U-Values are identified below.

U-Values	Range of Target Values Proposed	Part L 2021 (Dwellings) Compliant Values	Part L 2021 (BOTD) Compliant Values
Floor	0.10 to 0.18 W/m ² K	0.18W/m ² K	0.21W/m ² K
Roof (Flat)	0.12 to 0.20 W/m ² K	0.20 W/m ² K	0.20 W/m ² K
Roof (Pitched)	0.10 to 0.16 W/m ² K	0.16 W/m ² K	0.16 W/m ² K
Walls	0.10 to 0.18 W/m ² K	0.18 W/m ² K	0.21 W/m ² K
Windows	0.9 to 1.4 W/m ² K	1.4W/m ² K	1.6W/m ² K

4.2 Air Permeability

A major consideration in reducing the heat losses in a building is the air infiltration. This essentially relates to the ingress of cold outdoor air into the building and the corresponding displacement of the heated internal air. This incoming cold air must be heated if comfort conditions are to be maintained. In a traditionally constructed building, infiltration can account for 30 to 40 percent of the total heat loss, however construction standards continue to improve in this area.

With good design and strict on-site control of building techniques, infiltration losses can be significantly reduced, resulting in equivalent savings in energy consumption, emissions and running costs.

In order to ensure that a sufficient level of air tightness is achieved, air permeability testing will be specified in tender documents, with the responsibility being placed on the main contractor to carry out testing and achieve the targets identified in the tender documents.

A design air permeability target of **3 m³/m²/hr** has been identified for the apartments and houses on the site. As set in Part L 2021 BOTD target air tightness for Creche and Amenity areas will be **5 m³/m²/hr**.

The air permeability testing will be carried out in accordance with BS EN 13829:2001 'Determination of air permeability of buildings, fan pressurisation method' and CIBSE TM23: 2000 'Testing buildings for air leakage'

4.3 Thermal Bridging

Thermal bridges occur at junctions between planar elements of the building fabric and are typically defined as areas where heat can escape the building fabric due to a lack of continuity of the insulation in the adjoin elements.

Careful design and detailing of the manner in which insulation is installed at these junctions can reduce the rate at which the heat escapes. Standard good practice details are available and are known as Acceptable Construction Details (ACDs). Adherence to these details is known to reduce the rate at which heat is lost.

The rate at which heat is lost is quantified by the Thermal Bridging Factor of the dwelling and measured in W/m^2K . The Thermal Bridging Factor is used in the overall dwelling Part L calculation, this value can be entered in three different ways:

0.15 W/m^2K	Used where the ACDs are not adhered to
0.08 W/m^2K	Used where the ACDs are fully adhered to
< 0.08 W/m^2K	Used where the thermal details are thermally modelled and considered to perform better than the ACDs

It is intended that the ACDS will be complied with or thermal modelling will be carried out for all thermal bridges on the dwellings within proposed development and that the resultant Thermal Bridging Factor will be in the range of 0.04 W/m^2K to 0.08 W/m^2K .

5. Heat Sources & Renewable Energy Options – Dwellings

All new dwellings must have a portion of their annual energy demand provided by renewable energy sources. This can be thermal energy such as **solar thermal collection**, **biomass boilers** or **heat pumps** or it can be electrical energy as generated by **photovoltaic solar panels** or **wind turbines**.

The minimum renewable energy contributions for dwellings as required by Part L 2021 Dwellings is defined as the Renewable Energy Ratio (RER) which is the ratio of the primary energy from renewable energy sources to total primary energy. In order to meet the requirements of *Part L 2021 Dwellings*, the RER is required to be a minimum 20%.

In order to determine the most efficient and effective means of complying with the requirements of *Part L 2021 Dwellings*, a detailed assessment of the various renewable energy systems available will be conducted during the detailed design stage. A range of possible solutions will be assessed in terms of their technical suitability; ease of operation for end-users; operating costs to be borne by end users and capital costs of the plant and equipment required.

The most common approach to meeting the required standards is set out below.

5.1 Houses

5.1.1 Air Source Heat Pumps

Air source heat pumps (ASHPs) utilise grid supplied electricity to extract thermal energy from a heat source, in this case, the external ambient air. While the electricity consumed is obviously not renewable energy, the efficiency at which a heat pump operates allows a significant portion of the heat delivered to be considered as renewable energy. The amount of heat considered to be renewable is determined by the efficiency of the heat pump and the “primary energy conversion factor” for grid supplied electricity. Typically, approximately 40% to 50% of the heat supplied is considered to be renewable energy.

Air source heat pumps require an indoor and an outdoor component. The outdoor unit is the evaporator which extracts the thermal energy from the ambient air while the indoor unit typically includes the heating buffer tanks and the hot water cylinder for the dwelling. The outdoor unit is typically located in the back garden of a dwelling.

In recent years, the design of ASHPs has improved bringing about higher efficiencies and reduced costs. This, in turn, has led to an increase use of this technology in large scale housing developments. Certified seasonal efficiencies of some models can exceed 500% meaning that the use of this technology can easily deliver compliance with current Part L requirements.

5.2 Apartments

5.2.1 Option 1 - District Heating

This approach would involve the generation of heat in a central location on the site and the distribution of this heat to each apartment via a network district heating pipework. The central plant used to generate the heat could include Air Source Heat Pumps, Combined Heat and Power (CHP) plant and high efficiency gas fired condensing boilers.

A CHP unit uses gas as its energy source to create electricity which can be utilised within the proposed development. This process of creating electricity results in the generation of “waste heat” which can then be used to meet a proportion of the heating and hot water demands of the housing development. Since the

waste heat is captured it can be considered to be renewable energy and therefore contributes towards the overall 20% renewable energy requirement.

The Air Source Heat Pumps (ASHPs) utilise grid supplied electricity to extract thermal energy from a heat source, in this case, the external ambient air. While the electricity consumed is not considered renewable energy, the efficiency at which a heat pump operates allows a significant portion of the heat delivered to be considered as renewable energy. The amount of heat considered to be renewable is determined by the efficiency of the heat pump and the “primary energy conversion factor” for grid supplied electricity. Typically, approximately 40% to 50% of the heat supplied is considered to be renewable energy.

In order to meet the heating and hot water demands of the apartments in the proposed developments a district heating plant centre will be provided in each half of the development. Each plant centre will be capable of generating approximately 750kW to 1MW of heat energy. In this arrangement, the CHP would typically be sized to provide up to 30% of the total annual energy consumption, heat pumps would provide 30 to 40% and the remaining energy demand will be met by the gas fired boilers.

Heating pipework will be installed throughout the scheme to distribute the heat generated in the plant room throughout the apartment development, serving each apartment via a heat interface unit (HIU). The HIU will both control and meter the consumption of heat and hot water within each individual dwelling allowing occupants to set the times they need space heating and ensuring they are charged accordingly.

Heat Recovery Ventilation would then be provided in order meet the ventilation needs of the apartments. Air is extracted from wet rooms and supplied to living spaces via a central unit which contains supply and extract fans and a heat exchanger. This system recovers the heat from the warm air being extracted from the dwelling and uses the heat recovered to raise the temperature of the incoming air stream leading to improved overall efficiency.

5.2.2 Option 2 - Individual Plant – Exhaust Air Heat Pumps

Exhaust Air heat pumps (EAHPs) operate in a very similar manner to air source heat pumps and utilise grid supplied electricity to extract thermal energy from a heat source, in this case, the internal air within the apartment. The internal air is extracted from kitchens and wet rooms and is drawn into the heat pump via ductwork in the ceiling void. The heat pump extracts heat from this air before expelling it from the apartment.

There are a number of manufacturers offering products of this type and the certified seasonal efficiencies of some models can exceed 450% in heating mode and 170% to 190% in hot water mode. These efficiencies can deliver *Part L 2021 Dwellings* compliance in most circumstances but in some instances may need supplementary PV panels in order to meet the required energy targets.

There is no requirement for a separate Mechanical Extract Ventilation (MEV) systems when an exhaust air heat pump is used as the heat pump draws the air from all wet rooms in the same manner as an MEV system would. The fan will run continuously to ensure that the minimum ventilation rates are maintained and the supply air to the dwelling is provided through trickle vents in each habitable room.

5.2.3 Option 3 - Individual Plant – Electric Heaters, Hot Water Heat Pumps & PV Panels

This approach includes the provision of electric storage & convector heaters in the living & sleeping areas to meet all of the space heating requirements with electric towel rads provided in main bathrooms and en-suites.

The hot water demand is met by a hot water heat pump which utilise grid supplied electricity to extract thermal energy from a heat source in a similar manner to an Exhaust Air Heat Pump. The heat pump is ducted directly to the external façade through insulated supply & exhaust ductwork and uses external air for the hot water needs. It can use up to 3 times less electricity than direct acting water heaters and produces renewable energy to aid Part L compliance.

Heat Recovery Ventilation would then be provided in order to meet the ventilation needs of the apartments. Air is extracted from wet rooms and supplied to living spaces via a central unit which contains supply and extract fans and a heat exchanger. This system recovers the heat from the warm air being extracted from the dwelling and uses the heat recovered to raise the temperature of the incoming air stream leading to improved overall efficiency.

PV panels are also then needed to improve the overall renewable energy contribution and improve the overall energy performance of the dwellings. Generally, 1 or 2 PV panels will be required for each apartment.

5.3 Ventilation Design

The provision of a well-designed ventilation for dwellings and commercial building is vitally important in order to control the odours and moisture levels and to provide an adequate supply of fresh air to the dwelling.

Three different options are generally considered for schemes of this nature. These are as follows: -

5.3.1 Traditional Natural Ventilation Approach

This approach operates with intermittent extract fans in wet rooms and background ventilation provided in accordance with the guidance of Technical Guidance Document F (TGD-F)

In the DEAP calculation used for Part L compliance, the number of “intermittent fans and passive vents” entered in the calculation is typically one (fan) per wet room and one (passive vent) per habitable room.

5.3.2 Whole House Mechanical Heat Recovery Ventilation (MHRV)

Where MHRV are used, air is extracted from wet rooms and supplied to living spaces via a central unit which contains supply and extract fans and a heat exchanger. This system recovers the heat from the warm air being extracted from the dwelling and using the heat recovered to raise the temperature of the incoming air stream leading to improved overall efficiency.

The system also has the benefit of eliminating the requirement for trickle ventilation as it runs continuously, thereby increasing the benefits of an airtight construction. It is also possible to incorporate a humidity control function into the fans which will result in a system which is capable of varying supply and extract rates in accordance with the humidity levels in the dwelling.

In the DEAP calculation used for Part L compliance, the number of “intermittent fans and passive vents” entered in the calculation will only need to take account of the kitchen extract fan and therefore only 1 “intermittent fans and passive vents” will be entered in the software.

5.3.3 Mechanical Whole House Extract (MEV)

MEV systems are similar to MHRV systems in that they extract air from all wet rooms using a central extract fan which runs continuously however there is no supply air provided by the system and there is no heat recovery. In order to supply air to the dwelling trickle vents are required but the total free area required is typically 60% to 70% less than that which is required using the traditional ventilation approach. As with MHRV it is possible to incorporate a humidity control function into the fan which will result in a system which is capable of varying air extract rates in accordance with the humidity levels in the dwelling.

In the DEAP calculation used for Part L compliance, the number of “intermittent fans and passive vents” entered in the calculation will only need to take account of the kitchen extract fan and therefore only 1 “intermittent fans and passive vents” will be entered in the software. The trickle vents provided in the windows can be ignored since their area is less than 3,500mm²

Of the three systems outlined above, the MEV systems are the most likely to be adopted for the dwellings within scheme.

6. Heat Sources & Renewable Energy Options – Creche & Amenity Areas

All new commercial buildings must have a portion of their annual energy demand provided by renewable energy sources. This can be thermal energy such as **solar thermal collection, biomass boilers or heat pumps** or it can be electrical energy as generated by **photovoltaic solar panels** or **wind turbines**.

The minimum renewable energy contributions for a development of this nature is defined in Part L 2021 BOTD L5 Part (b) and is measured by the Renewable Energy Ratio (RER). This is the ratio of the primary energy from renewable energy sources to total primary energy demands of the building. Depending on the overall performance of the building, as measured by the EPC and CPC the required renewable energy contribution is either 20% or 10%

In order to determine the most efficient and effective means of complying with the requirements of Part L 2021 BOTD Part (b) a detailed assessment of the various renewable energy systems available will be conducted during the design stage using the SBEM calculation methodology. A range of possible solutions are described below in Sections 6.1 to 6.6 . Each of these will need to be assessed in terms of their technical suitability; ease of operation for end-users; operating costs to be borne by end users and capital costs of the plant and equipment required.

The most common approach to meeting the required standards are set out below.

6.1 Gas Fired Boilers with Solar Panels.

The use of natural gas to provide heating and hot water to commercial buildings is very common due to its convenience and to low fuel prices. There is existing Gas Networks Ireland infrastructure in the vicinity of the proposed development.

Both Solar PV and Solar Thermal Collection harvest the sun's energy to provide a renewable energy source for the building. In the case of PV, the sun's energy is converted into electrical energy which offsets the use of grid electricity while in the case of solar thermal collection it is converted into thermal energy which is used to heat domestic hot water within the building.

The use of PV panels has become the a very common approach for achieving Part L compliance as the quantity of panels provided can be tailored specifically to ensure minimum targets are compliant with regulations L5 (a) and (b).

6.2 Air Source Heat Pumps

Air source heat pumps (ASHPs) utilise grid supplied electricity to extract thermal energy from a heat source, in this case, the external ambient air. While the electricity consumed is obviously not renewable energy, the efficiency at which a heat pump operates allows a significant portion of the heat delivered to be considered as renewable energy. The amount of heat considered to be renewable is determined by the efficiency of the heat pump and the "primary energy conversion factor" for grid supplied electricity. Typically, approximately 40% to 50% of the heat supplied is considered to be renewable energy.

Air source heat pumps require an indoor and an outdoor component. The outdoor unit is the evaporator which extracts the thermal energy from the ambient air while the indoor unit typically includes the heating buffer tanks. The outdoor unit is typically located at roof level.

In recent years, the design of ASHPs has improved bringing about higher efficiencies and reduced costs. This, in turn, has led to an increase use of this technology in commercial developments. The heat pump can be utilised to meet the heating and cooling demand.

7. Proposed Solutions for the Development

The preceding sections of this report set out the regulatory requirements with which the scheme will have to comply while identifying a number of technologies and design approaches that may be utilised to achieve compliance.

The building fabric standards and the technology solutions discussed will all be assessed in greater detail during the detailed design stage of the project. A cost benefit analysis of all these available solutions will be carried out to determine the correct balance between an efficient building envelope and the most appropriate combination of technology and renewable energy systems.

The proposed approach to achieving Part L Compliance will be based on a combination of the solutions below once a detailed analysis has been completed at detailed design stage. A final decision will be made once capital costs, renewable targets and regulation compliance have all been compared to find the most appropriate solution:

7.1 Dwellings

The most likely overall solution that will be implemented will include the following measures

- Exceed minimum U-Value standards by 20% to 30%
- Achieve air tightness standards of $3\text{m}^3/\text{m}^2/\text{hr}$.
- Ensure thermal bridging details are design to achieve thermal bridging factors of $0.08\text{W}/\text{m}^2\text{K}$ or less
- Install centralised mechanical ventilation systems to ensure adequate ventilation rates are achieved in the dwelling which maximising the benefits of the airtight construction.
- Install Air Source Heat Pumps in houses to meet NZEB requirements.
- Install Exhaust Air Heat Pumps in apartments to meet NZEB requirements.

7.2 Creche & Amenity Areas

The most likely overall solution that will be implemented will include the following measures

- Exceed minimum U-Value standards by 20% to 30%,
- Achieve air tightness standards of $5\text{m}^3/\text{m}^2/\text{hr}$
- Provide an air source heat pump to meet Part L renewable contribution requirements

UK and Ireland Office Locations



