



- TYPE A COLUMN DETAILS**
- HEIGHT : 6m
 - BRACKET LENGTH : Post-top
 - INCLINATION : 5 Degrees
 - COLUMN QUANTITY : 146
- LANTERN DETAILS**
- AVERAGE WATTAGE (CLO) : 16w LED
 - MAKE & MODEL : C.U.Phosco E950-28-P4A-730-C600
- TYPE B COLUMN DETAILS**
- HEIGHT : 5m ABACUS Raise & lower type
 - BRACKET LENGTH : Post-top
 - INCLINATION : 0 Degrees
 - COLUMN QUANTITY : 28
- LANTERN DETAILS**
- AVERAGE WATTAGE (CLO) : 8w LED
 - MAKE & MODEL : C.U.Phosco E950-28-R3P-730-C250
- TYPE C COLUMN DETAILS**
- HEIGHT : 6m
 - BRACKET LENGTH : Post-top
 - INCLINATION : 0 Degrees
 - COLUMN QUANTITY : 25
- LANTERN DETAILS**
- AVERAGE WATTAGE (CLO) : 18w LED
 - MAKE & MODEL : C.U.Phosco E950-28-F2A-730-C700
- TYPE D COLUMN DETAILS**
- HEIGHT : 6m
 - BRACKET LENGTH : Post-top
 - INCLINATION : 0 Degrees
 - COLUMN QUANTITY : 11
- LANTERN DETAILS**
- AVERAGE WATTAGE (CLO) : 22w LED
 - MAKE & MODEL : C.U.Phosco E950-28-R2P-730-SD0500
- TYPE F COLUMN DETAILS**
- HEIGHT : 8m
 - BRACKET LENGTH : Post-top
 - INCLINATION : 0 Degrees
 - COLUMN QUANTITY : 18
- LANTERN DETAILS**
- AVERAGE WATTAGE (CLO) : 49w LED
 - MAKE & MODEL : C.U.Phosco P863-128-F2B-730-W3-375

TYPE E & G are existing columns with various lantern types

NOTES:
 All LED lanterns must have Constant Light Output (CLO).
 Automatically dimmed to 75% each night from 12 midnight to 6am.
 All lanterns to have Twin NEMA sockets fitted.
 Electronic Photocells switched at 35/18lux.
 All columns, luminaires, cable and pillars, shall comply with Local Authority General Specification for Public Lighting.
 No trees to be located within falling distance of PHL columns.
 Minimum set-back of columns is 800mm from face of kerb.



NOTES
 THIS DRAWING IS THE INTELLECTUAL PROPERTY OF Sabre LIGHTING DESIGN DEPT. AND IS COPYRIGHT © AND CAN NOT BE USED WITHOUT PRIOR CONSENT.

NO ACCOUNT IS TAKEN FOR THE BLOCKING EFFECT CAUSED BY BUILDINGS, TREES ETC. THE CALCULATION SHOWN BY THIS DRAWING ASSUMES THAT THE WHOLE AREA BEING CONSIDERED IS IN THE SAME PLANE, I.E. THERE ARE NO CHANGES IN GRADIENT OR ELEVATION.

This drawing layout is based on calculated lighting levels, produced by Sabre Electrical Services Ltd., using Lighting Really software. Any alterations to the layout or luminaire type used for the lighting design calculations, will require a revised lighting design to be carried-out. A redesign may require approval from the Local Authority Public Lighting Dept. prior to any alterations/modifications being implemented on site.

Sabre
 ELECTRICAL SERVICES LTD.
 Specialist Contractors
 PUBLIC LIGHTING - FLOOD LIGHTING - SPORTS LIGHTING

UNIT 11,
 BELLVUE INDUSTRIAL ESTATE,
 FINGLAS,
 DUBLIN 11.
 E-MAIL: graham@sabrelighting.ie PH: 01-811 0875

-	?	GS	CHK	-----
-	?	GS	CHK	-----
-	?	GS	CHK	-----
-	?	GS	CHK	-----
-	?	GS	CHK	-----
-	?	GS	CHK	-----
-	?	GS	CHK	-----
A	Client name updated	GS	CHK	05-09-22
REV	DESCRIPTION	INTS	CHK'D	DATE

CLIENT/CUSTOMER
 Arnub Limited & Aspect Homes Limited

PROJECT
 Hickey's Lane Ashbourne

TITLE
 Public Lighting ISOLUX

DRAWN G.S. SCALE 1:500@a1 DATE 01-09-22

DRAWING NUMBER SES 11822 Sheet 4 ISSUE 2

BASE DRAWING NUMBER edit
 DRAWING ORIGIN edit

DO NOT SCALE FROM THIS DRAWING