



OCSC

O'CONNOR | SUTTON | CRONIN


Multidisciplinary
Consulting Engineers

ENGINEERING SERVICES REPORT

**Development at Emmet Road, Dublin 8
For Dublin City Council**

PROJECT NO. B967

28 September 2022



ENGINEERING SERVICES REPORT

**Development at Emmet Road, Dublin 8
For Dublin City Council**

PROJECT NO. B967

28 September 2022

ENGINEERING SERVICES REPORT

for

Development at Emmet Road,

Inchicore, Dublin 8



OCSC

O'CONNOR | SUTTON | CRONIN

Multidisciplinary
Consulting Engineers

NOTICE

This document has been produced by O'Connor Sutton Cronin & Associates for its client, *Dublin City Council*. It may not be used for any purpose other than that specified by any other person without the written permission of the authors.



DOCUMENT CONTROL & HISTORY

OCSC Job No.: B967	Project Code	Originator	Zone Volume	Level	File Type	Role Type	Number	Status / Suitability Code	Revision
	B967	OCSC	XX	XX	RP	C	0006	S4	P04
Rev.	Status	Authors	Checked		Authorised		Issue Date		
P04	S4	MK	IC		PH		28.09.2022		
P03	S4	MK	IC		PH		21.09.2022		
P02	S3	MK	IC		PH		19.07.2022		
P01	S3	RP	MK		AH		12.03.2021		

ENGINEERING SERVICES REPORT

TABLE OF CONTENTS

PAGE

1 INTRODUCTION	1
1.1 Appointment.....	1
1.2 Administrative Jurisdiction	1
1.3 Site Location	1
1.4 Existing Site Overview	3
1.5 Proposed Development Context	4
2 SCOPE OF SERVICES REPORT	7
3 SURFACE WATER DRAINAGE.....	9
3.1 Design Guidelines Overview	9
3.2 Surface Water Design Strategy Overview	10
3.3 Consultation	10
3.4 Existing Site Drainage	10
3.4.1 Existing Site Catchment Area.....	10
3.4.2 Existing Surface Water Drainage Infrastructure	11
3.4.3 Diversions of Existing Drainage Infrastructure	12
3.4.4 Existing Site Rainfall Runoff	13
3.5 Proposed Surface Water Drainage Design Strategy.....	15
3.5.1 Proposed Surface Water Strategy Overview	15
3.5.2 Climate Change Allowance	15
3.5.3 Proposed Surface Water Management Plan	15
3.5.3.1 Green Roofs	17
3.5.3.2 Bioretention Systems / Rain Gardens.....	18
3.5.3.3 SuDS Tree Pits.....	18
3.5.3.4 Pervious Paving	19
3.5.3.5 Filter Drains	20
3.5.3.6 Trapped Road Gullies	20

3.5.3.7	Underground Pipe Network	20
3.5.3.8	Silt Traps	21
3.5.3.9	Geocellular Storage Systems	21
3.5.3.10	Flow Control Device.....	22
3.6	Proposed Surface Water Network Detailed Design	23
3.6.1	Software Design Criteria.....	23
3.6.2	Proposed Surface Water Catchment Area.....	24
3.6.3	Proposed Development Rainfall Runoff	24
3.6.4	Proposed Surface Water Pipe Network Design	26
3.7	Proposed Surface Water Attenuation Storage	26
3.8	Surface Water Outfall Location	27
3.9	Water Quality	27
3.10	Maintenance.....	28
3.11	Surface Water Impact Assessment	29
3.12	Criterion 1 – River Water Quality Protection	29
3.13	Criterion 2 – River Regime Protection	29
3.14	Criterion 3 – Level of Service (Flooding) Site	30
3.14.1	Sub-Criterion 3.1	30
3.14.2	Sub-Criterion 3.2	30
3.14.3	Sub-Criterion 3.3	31
3.14.4	Sub-Criterion 3.4	31
3.15	Criterion 4 – River Flood Protection	31
4	WASTEWATER DRAINAGE	33
4.1	Overview	33
4.2	Existing Wastewater Drainage	33
4.3	Consultation	35
4.4	Proposed Wastewater Drainage Strategy	35
4.5	Wastewater Network Design Calculations.....	35
4.6	Taking In Charge.....	36
5	POTABLE WATER SUPPLY	37

5.1	Overview	37
5.2	Consultation	37
5.3	Existing Watermain Infrastructure	37
5.4	Decommissioning of Existing Watermain	39
5.5	Connection to the Existing Network.....	40
5.6	Water Meters.....	40

APPENDICES

APPENDIX A.	EXISTING DRAINAGE INFRASTRUCTURE RECORDS
APPENDIX B.	RETURN PERIOD RAINFALL DEPTHS
APPENDIX C.	Q_{BAR} RUNOFF CALCULATIONS
APPENDIX D.	SURFACE WATER DESIGN CALCULATIONS
APPENDIX E.	WASTEWATER DESIGN CALCULATIONS
APPENDIX F.	IRISH WATER CONFIRMATION OF FEASIBILITY

1 INTRODUCTION

1.1 Appointment

O'Connor Sutton Cronin & Associates (OCSC) have been appointed by *Dublin City Council* to carry out the design of the Civil Engineering services (surface water, wastewater drainage and watermain) associated with the development proposed comprising c.578nr. residential units, along with supporting community facilities, retail, and a neighbourhood (supermarket) centre at Emmet Road, Inchicore, Dublin 8.

1.2 Administrative Jurisdiction

The proposed development is located in the jurisdiction of Dublin City Council (DCC), and therefore the engineering services design was carried out with reference to the following:

- Dublin City Council Development Plan (2016 – 2022);
- Dublin City Council Draft Development Plan (2022 – 2028);
- Greater Dublin Strategic Drainage Study (GDSDS);
- The Planning System and Flood Risk Management Guidelines for Planning Authorities, 2009 (Department of Environment, Heritage and Local Government and the Office of Public Works).

1.3 Site Location

The subject site is located at Emmet Road, in the heart of Inchicore, Dublin 8, as shown in *Figure 1.1 – Site Location*.

Inchicore is a suburb of Dublin located approximately 5km to the west of Dublin city centre. Inchicore is primarily a residential area comprising predominantly of 2 storey early to mid-20th century housing stock with some medium rise apartments developments of both social and private built in more recent decades.

The proposed development site is immediately bound by:

- Emmet Road, to the north;
- Saint Michael's Estate and the pedestrian link to the Emmet Road next to Saint Michael's Catholic Church, to the east;
- Saint Vincent Street West, to the west;
- Goldenbridge cemetery, to the south.




Figure 1.1 - Site Location (www.myplan.ie)

1.4 Existing Site Overview

The overall development site area is approximately **3.8-hectares** (9.4 acres) and is currently zoned by Dublin City Council for **Z14, Strategic Development and Regeneration Areas**. This area does not include the section of Emmet Road associated with proposed watermain upgrade, as advised by Irish Water.

The site is graded naturally towards the northeast corner of the site. For context, the highest part of the site, located in the southwest corner of the site, has an existing level of approximately +27.5m AOD; with the lowest typical level being in the order of +22.2m AOD located in the northeast corner of the site.

The site currently comprises of a mixture of brownfield areas which previously housed the Saint Michael's Estate development together with the current existing buildings/structures:

- St Michael's Parish Community Centre (to be demolished);
- Eve Tuiscint Health Centre (to be demolished);
- Inchicore Community Sports Centre (to be retained);
- Boundary wall to the north western corner of the site (to be retained).

There are a number of existing structures outside of the site that are of importance. These include:

- Inchicore Primary Care Centre to the east of the site;
- Inchicore Community Centre;
- Richmond Barracks to the east of the site.

The locations of the above building relative to the site are shown in *Figure 1.2* over.




Figure 1.2 – Aerial Overview of the Site

1.5 Proposed Development Context

The proposed scheme consists of a mixed-use development with a strong emphasis on residential units in addition to commercial, retail and community facilities together with all associated infrastructure including roads, footpaths, services and landscaping.



The development will comprise 578 no. apartments, consisting of 110 no. studio apartments, 172 no. 1 bedroom apartments, 250 no. 2 bedroom apartments (including 10 no. duplex apartments) and 46 no. 3 bedroom apartments (all apartments to have balconies or terraces), community facilities Library/Community Hub, Creche, Supermarket, 5 no. units (retail/café/restaurant/class 2 financial services floorspace) & 2 no. Café units), a public plaza fronting onto Emmet Road and the installation of a new watermain c 200m in length along Emmet Road to the junction with Tyrconnell Road/Grattan Crescent. The proposal includes works to a protected structure (8705 - Richmond/Keogh Barracks, relating to works to rubble stone boundary walls).

2 SCOPE OF SERVICES REPORT

This Engineering Services Report was prepared by reviewing the available data from the Local Authority sources and national bodies *i.e.*, Dublin City Council, Irish Water, The OPW, and the wider Design Team.

The following services are addressed within this report, with respect to the proposed development:

- Surface Water Drainage;
- Wastewater Drainage;
- Potable Water Supply.

An assessment on potential flood risks associated with, and as a result of, the proposed development is provided under separate cover, as part of this application. Refer to document **B967-OCSC-XX-XX-RP-C-0007** for details of the Site-Specific Flood Risk Assessment.

The proposed design, for the aforementioned services, have been carried out in accordance with the following technical guidelines and information:

- Dublin City Development Plan (2016 – 2022);
- Dublin City Council Draft Development Plan (2022 – 2028);
- Greater Dublin Strategic Drainage Study, 2005 (GDSDS);
- Greater Dublin Regional Code of Practice for Drainage Works v6.0, 2006 (GDR COP);
- Irish Water Code of Practice for Wastewater, IW-CDS-5030-03 (Revision 2 – July 2020);
- Irish Water Code of Practice for Water Supply, IW-CDS-5020-03 (Revision 2 – July 2020);
- The Building Regulations – Technical Guidance Document Part H;
- BE EN 752 – Drainage Outside Buildings;
- BS 7533-13 – Guide for Design of Permeable Pavements;
- The Office of Public Works, the Planning System and Flood Risk Management, 2009;
- DECLG website www.myplan.ie;
- Architectural drawings;

- Topographical survey of the proposed site;
- Dublin City Council's and Irish Water's Drainage and Watermain Records.

Members of the wider design team cover all other elements of the application pertaining to roads, traffic, sustainability, landscaping, planning, ecological, and architectural detail.

This report should be read in conjunction with the set of OCSC Civil Engineering design drawings that accompany this submission.

3 SURFACE WATER DRAINAGE

3.1 Design Guidelines Overview

Any planning permission sought on the subject lands are required to adhere to the Local Authority requirements *i.e.*, the Dublin City Development Plan, and as such, the Greater Dublin Strategic Drainage Study (Dublin City Council, 2005).

New development must ensure that a comprehensive Sustainable Drainage System (SuDS), is incorporated into the development. SuDS requires that post development run-off rates be maintained at equivalent, or lower, levels than pre-development levels. Thus, the development must be able to retain, within its boundaries, surface water volumes from extreme rainfall events up to a 1 in 100-year rainfall event, more commonly expressed as a 1.0% AEP (Annual Exceedance Probability), *while also allowing for an additional climate change factor of **20%** increase in rainfall intensity* in accordance with the Dublin City Development Plan (2016 - 2022), which is carried forward in the new Draft Development Plan.

Any new development must also have the physical capacity to retain surface water volumes as directed under the Greater Dublin Strategic Drainage Strategy (GDSDS) and, if necessary, release these attenuated surface water volumes to an outfall at a controlled flow rate, not greater than the greenfield runoff equivalent.

A further component of the SuDS protocol is to increase the overall water quality of surface water runoff before it enters a natural watercourse or a public sewer, which ultimately discharges to a water body. This is to ensure the highest possible standard of surface water quality.

The surface water strategy for the proposed development is to include a number of Sustainable Drainage Systems, prior to discharging an attenuated flow to the existing storm sewers located adjacent to the eastern boundary of the development site. Development discharge rates are to be restricted to the greenfield runoff equivalent.

SuDS are designed in accordance with best practice and the CIRIA C753, 2015 (The SuDS Manual) guidance material, and DCC's SuDS Design and Evaluation Guide.

3.2 Surface Water Design Strategy Overview

The proposed development is to be served by a gravity surface water drainage network that is to be divided into two sub-catchments, as a result of the natural topography and other site constraints, with attenuated surface water runoff, generated within the new development site boundary, ultimately discharging to the existing 225mm-diameter concrete storm sewer at the western of the development site and 375mm-diameter concrete storm sewer at the eastern of the development site.

Sustainable Drainage Systems are to be provided, wherever practicable, and these are discussed in more detail in *Section 3.5*, with discharge rates from site being restricted to the greenfield equivalent runoff rate, for design rainfall events up to, and including, the 1% AEP, in accordance with both the current and draft Dublin City Development Plan and the GDSDS.

3.3 Consultation

The applicant has been involved in several stakeholder meetings and workshops with Dublin City Council, some of which included members from the drainage, landscaping and roads departments; in which, the design strategy and approach was discussed in detail.

3.4 Existing Site Drainage

3.4.1 Existing Site Catchment Area

As detailed in *Section 1.4*, the existing c.3.8-hectares (9.4 acres) site is a mixture of brownfield areas, the site is currently graded to lower levels in the south-west to north-east direction. The site therefore naturally drains to the Emmet Road located at northern boundary of the site, before ultimately discharging to the Camac River located to the north of the Emmet Road.

3.4.2 Existing Surface Water Drainage Infrastructure

The site and its surroundings are well served by dedicate/separate storm drainage network, as indicated in **Figure 3.1**. Refer to the **Appendix A** for the Existing Drainage Infrastructure Records.

Two main storm drains are identified serving the site. The first is a 225mm-diameter concrete sewer which travels along the western boundary of the site. This sewer later becomes a 300mm-diameter sewer before travelling in a westerly direction along Thomas Davis Street West. The Irish Water records drawings indicate that this sewer previously gathered storm drainage from Saint Michael's Estate. However, the drawings from the demolition of Saint Michael's Estate and the result of the GPR survey indicate that these connections may have been removed. It is noted that there are discrepancies between the findings of the GPR survey and the record drawings in terms of the plan location and alignment of this sewer - this will need to be further reviewed/verified on site. It is also noted that the sewer passes onto the site in a number of locations. Thus, a permanent diversion of same may be required to facilitate the development.

The second dedicated storm sewer is a 375mm-diameter concrete sewer which travels along Saint Michael's Estate to the eastern boundary of the site. This sewer later becomes a 450mm-diameter sewer before travelling under Emmet Road and to the rear of Richmond Park to discharge to the Camac River. Again, the Irish Water Record drawings indicate that this sewer previously gathered storm drainage from Saint Michael's Estate. However, the drawings from the demolition of the Saint Michael's Estate and the results of the GPR survey indicate that these connections may have been removed.



Sections of the existing public drainage infrastructure that is located at St Michael's Estate and St Vincent's Street West are to be relocated from within the development boundary to the public road area, so as to facilitate the new development layout, including planting of significant trees, as part of the landscaping proposal.

Further details of the sections of drainage infrastructure to be decommissioned and relocated is indicated on the drainage detailed design layout drawing **B967-OCSC-ZZ-GF-DR-C-0500**.

3.4.4 Existing Site Rainfall Runoff

The mixed nature of the current site, with vast areas of grassed lands together with existing buildings and hard surfaced areas provides a varied rainfall runoff response. Thus, there is a mixture of areas currently with infiltration, albeit with poor water acceptance performance, along with other areas that are positively drained to the existing storm drainage system.

The soil value can be calculated from *Figure 1.4.18 (institute of Hydrology, 1978)* which shows the various soil types. The soil classifications are also available from the *Wallingford Procedure, Volume 3, Maps, "Winter rain acceptance potential"*. The equation was first published in FSSR 16, 1985. Refer to *Figure 3.2* for the "Soil" value in MicroDrainage that consider the SPR value and it can be obtained at *Greater Dublin Strategic Drainage Study – Regional Drainage Policies Volume 2 – New Development* at section 6.7.2.

SOIL	SPR value (% runoff)
1	0.1
2	0.3
3	0.37
4	0.47
5	0.53

Figure 3.2– SPR Values for Soil (Excerpt from GDSDS: Table 6.7)

A site investigation, carried out in the October 2020 on behalf of the client, confirmed that the existing ground is unsuitable for infiltration, with poor water acceptance characteristics. A **Soil Type 4**, consistent with the confirmed soil material found on site was therefore applied in runoff calculations. A copy of the Site Investigation is provided as part of the Environmental Impact Assessment Report, submitted under separate cover as part of this application.

The Standard Annual Average Rainfall (SAAR) equivalent of **720mm**, as received from Met Éireann for the subject site, was used to determine the rainfall runoff rate. Refer to the **Appendix B** for the Return Period Rainfall Depths for Sliding Durations from Met Éireann.

Using the ICPSuDS Input, {Flood Studies Report (FSR)} Method, the rainfall runoff discharging from the total site area that is to be developed (i.e. 3.8 ha), in its existing condition, has been calculated at greenfield runoff rate, **QBAR_{RURAL} = 5.0 l/s/ha** (i.e. 19 l/s).

Refer to **Figure 3.3** for an excerpt of the results from the MicroDrainage Runoff Calculator, which also provides the calculated QBAR runoff rate along with the discharge rate for varying Annual Recurrence Intervals (ARI). Refer to the **Appendix C** for the QBAR runoff calculations.

Region	QBAR (l/s)	Q (2yrs) (l/s)	Q (1 yrs) (l/s)	Q (30 yrs) (l/s)	Q (100 yrs) (l/s)
Ireland East	5.0	4.8	4.2	8.1	9.5
Ireland South	5.0	4.8	4.2	7.9	9.2
Ireland West	5.0	4.8	4.2	7.7	8.9
Ireland Greater Dublin	5.0	4.6	4.2	10.6	13.0

Figure 3.3 - Existing Site Runoff Calculator Results (MicroDrainage Excerpt)

3.5 Proposed Surface Water Drainage Design Strategy

3.5.1 Proposed Surface Water Strategy Overview

It is proposed to separate the surface water and wastewater drainage networks, which will serve the proposed development, and provide independent connections to the adjacent watercourse and local wastewater sewer network, respectively.

Refer to *Section 4* for details of the proposed wastewater drainage design.

Refer to detailed drawing **B967-OCSC-ZZ-GF-DR-C-0500** for the proposed drainage network layout, which is to serve the proposed development.

3.5.2 Climate Change Allowance

The proposed surface water network has been designed to allow for an additional 20% increase in rainfall intensity, to allow for Climate Change projections, in accordance with both the current and draft Dublin City Development Plan and the GDSDS.

All discussion within this report, with regards to surface water network design calculation and results, include for the allowance of an increase of 20% in rainfall intensity, as required.

3.5.3 Proposed Surface Water Management Plan

The proposed surface water network is to be split into three main gravity surface water catchments, as follows:

- Catchment A: Road and paving alongside Goldenbridge Cemetery;
- Catchment B: 2nr. Residential Blocks & associated paving / landscaping;
- Catchment C: Commercial area, and associated paving / landscaping.

Each catchment is to be separated into smaller sub-catchments, to best manage the rainfall runoff and provide treatment and attenuation at source, wherever practicable. Each catchment will also have its own independent outfall to the public surface water infrastructure, along St. Michael's Estate,

which will each discharge treated flows that are attenuated to greenfield equivalent rates.




Figure 3.4 - Proposed Surface Water (SW) Drainage Drawing

The new development's surface water drainage network will comprise a sustainable drainage system that is heavily integrated with the landscape features, wherever practicable. The sustainable drainage systems reduce the runoff volume discharging from site, as well as improving the water quality.

The typical traditional and Sustainable Drainage Systems (SuDS) provided, all of which have been designed in accordance with CIRIA C753, the SuDS Manual, and the design guidance material listed in *Section 2* of this report, are listed and detailed in order of general sequence within the drainage network, as follows:

3.5.3.1 Green Roofs

Extensive green roofs are to be considered for use, where large flat roofs are to be provided. Green roofs are designed to intercept and retain initial rainfall, which reduces the volume and rate at which it enters the surface water network.




Figure 3.5 - Typical Green Roof Build-up (DCC SuDS GUIDE)

Significant green roof has been provided across the development, which comprises both extensive green roof along with isolated intensive green roof areas, in addition to an intensively landscaped podium area within the Commercial building. The combined extent of both the intensive and extensive roof areas are in accordance with the draft DCC Development Plan, and the requirements set out in the supplementary Dublin City Council Green Blue Roof Guide, 2021.

All roof area within the residential blocks shall discharge to the landscaping features within the central open space areas, for further treatment and attenuation.

The roof area of the main commercial building shall discharge to the podium landscaping and paving base course, for further treatment and attenuation.

3.5.3.2 Bioretention Systems / Rain Gardens

Bioretention systems are shallow landscaped depressions that can reduce rates and volumes and treat pollution through the use of engineered soils and vegetation. They are particularly effective in delivering interception and attenuation and can also provide attractive landscape features that are self-irrigating and fertilising; habitat and biodiversity; and cooling of the local microclimate due to evapotranspiration.




Figure 3.6– Components of a bioretention system (DCC SuDS GUIDE)

The bioretention systems throughout the development shall typically receive direct runoff from the development's green and other roofs, for further treatment and attenuation.

3.5.3.3 SuDS Tree Pits

SuDS Tree Pits collect the rainfall runoff laterally from the surrounding landscaping and paving, which allows the trees to be watered every time it rains, with the growing medium also being used to store water before being released slowly to the adjacent surface water system.

These systems may also include cellular layer, at base or surround, in order to store additional rainfall.




Figure 3.7 - SuDS Tree Pit Illustration (DCC SuDS GUIDE)

3.5.3.4 Pervious Paving

Pervious paving and surfaces allow for rainfall runoff to be captured directly by a SuDS structure for interception, treatment, infiltration (where possible) and attenuation. There are several pervious surfaces available but all work by similar practice, with the surface allowing rainfall to pass through, with an open-graded base layer providing both structural strength to the surface, while also allowing for storage within the void content.

Filter drains can be provided under the structural layer of the pervious paving, at its low-point, in order to convey excess rainfall volumes.




Figure 3.8 - Pervious Paving Illustration (DCC SuDS GUIDE)

Attenuation and storage properties of pervious paving structures can be further optimised by providing flow controls, to hold back rainfall runoff and maximise the available storage within the structure.

3.5.3.5 Filter Drains

A filter drain is an open graded stone filled trench, which can also include a perforated pipe to assist distribution and conveyance of rainfall runoff along its length. Rainfall runoff can be stored within the void content of the stone trench, which should be wrapped in a fine geotextile to prevent fine sediment from entering the structure.




Figure 3.9 - Filter Drain Illustration (DCC SuDS GUIDE)

3.5.3.6 Trapped Road Gullies

All road gullies serving the proposed development are to be trapped, to help prevent sediment and gross pollutants from entering the surface water network, and thus improving the water quality discharging from site.

The grated covers are to have a minimum load classification of D400, for frequent vehicular traffic.




Figure 3.10 - Trapped Road Gully (Typical Detail)

3.5.3.7 Underground Pipe Network

A traditional gravity pipe and manhole network will be provided, to convey the collected rainfall runoff as far as the development's outfall. Manholes,

compliant with the GDSDS and GDR COP, are provided for maintenance access at branched connections, change in pipe size and gradient, and at intervals no greater than 90m distance.

3.5.3.8 Silt Traps

A manhole upstream of attenuation system is to contain a 600mm sump, below invert level of outlet pipe, in order to trap sediment and other gross pollutants, and prevent from entering the downstream watercourse; thus, improving the water quality discharging from site.




Figure 3.11 - Typical Detail of Silt Trap Manhole

3.5.3.9 Geocellular Storage Systems

Unlined proprietary geocellular storage units are to be provided for the attenuation of rainfall runoff for the catchment area.

These systems are to provide sufficient temporary storage volume for rainfall events up to, and including, the design 1% AEP rainfall event (including climate change). Typical geocellular storage systems comprise plastic cellular units of high porosity (typically >95%), structurally arranged in rows and layers, with a perforated distribution pipe through the centre.

These systems also allow for interception of initial rainfall to be provided at the base of the system, by elevating the outlet relative to the systems base.

Access chambers for inspection and maintenance are also to be provided.




Figure 3.12 - Typical Section of Geocellular System (CIRIA C753)

3.5.3.10 Flow Control Device

Flow Control devices are to be provided at strategic locations across the integrated sustainable drainage network. These are typically to be provided immediately downstream of SuDS structures, in order to maximise the treatment and storage benefits at source and within the SuDS structure.

A vortex-hydrobrake type flow control shall be provided at end-of-line manholes, to limit the catchment discharge rate to the greenfield equivalent rate.



Figure 3.13 - Vortex Hydro-Brake Flow Control Unit (Hydro International)

All other flow control devices within the development – typically located immediately downstream of a SuDS structure – are to comprise **protected orifices**, as the restricted flow will typically be in the order of 1.0 l/s, and therefore a small aperture will be present. This will minimise risk of blockage.




Figure 3.14 - Illustration of Protected Orifice (DCC SuDS Guide)

3.6 Proposed Surface Water Network Detailed Design

3.6.1 Software Design Criteria

The proposed surface water network has been designed in accordance with the regulations and guidelines outlined in *Section 2*, using MicroDrainage Network Design package, by Innovyze Inc., which simulates the performance of the integrated drainage network for varying rainfall return periods and storm durations.

The MicroDrainage Network Design software applies the Flood Studies Report (FSR) methodology for analysis of the rainfall profiles. However, the input design parameters that were used, as part of this design, were based on the available Flood Studies Update (FSU) data, *i.e.* the return period rainfall depths for sliding durations, which determine the **M₅₋₆₀** and **R** values, and the standard annual average rainfall (SAAR); as sourced from Met Éireann.

Figure 3.15 - Surface Water Network Design Criteria (MicroDrainage Excerpt)

3.6.2 Proposed Surface Water Catchment Area

The proposed development has been divided into three independent surface water networks, based on both the proposed development layout, natural topography, and resultant proposed finish levels. The northern catchment can be considered commercial, and the southern catchment can be considered residential. The total contributing drainage catchments are as follow:

- Catchment A (Southern Link Road) 0.2-hectares
- Catchment B (Residential Development) 1.5-hectares
- Catchment C (Commercial Development) 1.0-Hectares



Figure 3.16 – Surface Water Network Catchment Overview

Other areas outside of the above comprise footpath and landscaped areas alongside the adjacent public roads, and do not directly contribute to the new surface water drainage networks.

Refer to design layout drawings **B967-OCSC-ZZ-GF-DR-C-0500** and **B967-OCSC-ZZ-GF-DR-C-0526** for information.

3.6.3 Proposed Development Rainfall Runoff

It is proposed to reduce and restrict the rainfall runoff, discharging from the site of the proposed development, to the greenfield equivalent, $Q_{BAR_{RURAL}}$, runoff rate, as per the FSR ICP SuDS method, which is based on the IH124 method for catchments smaller than 25km^2 (25ha) in area.

This is to be achieved with the provision of a flow restrictor (Hydro-Brake Optimum by Hydro-International, or similar approved) prior to discharging to the existing storm sewers at the east and north eastern boundary of the site, with the appropriate measures of attenuation provided and sub-catchment management.

Sub-catchment flow-control devices and associated attenuation are also to be strategically provided, in order to maximise SuDS benefits and avail of the central open space for preliminary attenuation.

Refer to *Figure 3.3*, in *Section 3.4.3*, for an excerpt from the results MicroDrainage Runoff Calculator for the development catchment area (c.3.8-hectares), which indicates the greenfield equivalent, $Q_{BAR_{RURAL}}$, value of **19 l/s** (5 l/s/ha) along with the calculated runoff for varying Average Recurrence Intervals (ARI).

This maximum flow rate (i.e. greenfield equivalent) was incorporated into the integrated drainage network design for each contributing catchment, on a pro-rata basis *i.e.*:

- Catchment A: (0.2-hectares) 1.5 l/s
- Catchment B: (1.5-hectares) 9 l/s
- Catchment C: (1.0-hectares) 5 l/s

For the purpose of the surface water network design simulation, we have applied a runoff coefficient, C_v value, of 1.0 across the entire development, with a reduced percentage of permeability applied to the various surfaces. As such, and as outlined in DCC's SuDS Design and Evaluation Guideline that forms part of Dublin City Council's Draft Development Plan (2022 – 2028), an upper bound percentage impermeable value of 15% has been applied to all bio-retention and landscaping zones, which are to comprise free draining – clay soils.

The rainfall runoff at roof level has been applied to the design simulation software using Micro-drainage's built-in Green Roof calculator function.

3.6.4 Proposed Surface Water Pipe Network Design

The overall surface water drainage system, serving both catchments in the proposed development, is to consist of a gravity sewer network that will convey runoff from the roofs and paved areas to the outfall manhole, as illustrated on the detailed design drainage layout drawing (**B967-OCSC-ZZ-GF-DR-C-0500**) that accompanies this submission. The new gravity networks will discharge a controlled attenuated flow rate to both the existing public networks (Northern and Southern catchments) at the east and north-eastern boundary of the site, as outlined in *Section 3.5.3*.

The proposed piped-network has been designed in accordance with BS EN 752 and all new infrastructure is to be compliant with the requirements of the GDSDS and the GDR COP for Drainage Works, with minimum full-bore velocities of 1.0 m/s achieved throughout.

All main surface water carrier pipes have been designed to ensure no surcharging of the proposed drainage network for rainfall events up to, and including, the 1 in 5-year ARI (Average Recurrence Interval) event.

Refer to drawing **B967-OCSC-ZZ-GF-DR-C-0500** for the proposed drainage infrastructure layout.

3.7 Proposed Surface Water Attenuation Storage

Each proposed catchment is to attenuate its own rainfall runoff, prior to discharging to the same existing storm sewer in different locations. The primary function of the attenuation systems will be to temporarily store excessive rainfall runoff, during significant rainfall events, due to the restricted discharge rates (to greenfield equivalent runoff rates) from the development outfalls.

Attenuation and temporary storage has been strategically distributed across the development site and largely provided as part of the proposed SuDS structures, which comprise:

- Bio-retention / rain garden;
- Pervious paving with filter drain;

- Filter drain;
- Infiltration blanket;
- SuDS Tree Pits;
- Proprietary Cellular Storage.

A minimum total storage volume of **2,650m³** is to be provided across the entire development, within the aforementioned SuDS structures.

All attenuation systems have been designed to temporarily store the surface water runoff for design rainfall events up to, and including, the 1% AEP with a 20% increase in rainfall intensity, along with the associated integrated surface water drainage network.

3.8 Surface Water Outfall Location

There are 3nr. proposed outfall locations to the public surface water network, as illustrated on the detailed design drainage layout drawing (**B967-OCSC-ZZ-GF-DR-C-0500**) that accompanies this submission: each of which will discharge treated flows that are attenuated to the greenfield equivalent rate, as described earlier in this section.

The above is to ensure that there is no increase in flow rates and volumes, from the development site, being discharged to the receiving infrastructure; thus, causing no adverse impact on adjoining and other downstream properties.

3.9 Water Quality

The quality of the surface water discharging from site is to be improved through the following provisions, each of which is discussed in greater detail in *Section 3.5.3*:

- Green Roofs to cover minimum of 70% roof area;
- Bioretention system at open spaces;
- Intensive landscaping, where practical, to drain paving;
- Pervious Paving at car park areas;
- Filter Drains;

- Trapped road gullies on the road carriageway, to trap silt and gross pollutants;
- Silt trap to be provided on manhole immediately upstream of attenuation system, as a further preventative measure to trap silt and other gross pollutants;
- Attenuation facilities to allow for interception and infiltration.

All of the above sustainable drainage systems will provide significant treatment of the rainfall runoff across the new development site, resulting in increased water quality discharging from site ensuring a positive impact on the receiving watercourse i.e., the river Camac, which is in line with the proposals in the Water Framework Directive.

3.10 Maintenance

The proposed surface water drainage networks have been carefully designed to minimise risk of blockage throughout the network, mainly through the following provisions that limit and restrict the size of pollutants entering the network:

- Green Roof;
- Bioretention systems;
- Pervious Paving;
- Filter Drains.
- Trapped road gullies;
- Silt trap manhole;
- Protected Orifices for flow controls.

All SuDS structures, including bioretention systems, pervious paving, road gullies, silt trap, flow control device and attenuation system, should be inspected regularly and maintained, as appropriate and in accordance with manufacturer's recommendations and guidelines.

An appropriate inspection and maintenance schedule will be devised and implemented for the operational life of the proposed development.

3.11 Surface Water Impact Assessment

The design criteria for the drainage system are established in *GDSDS Volume 2, Section 6.3.4* and explained further in *GDSDS Volume 2, Appendix E*. There are four design criteria, each of which has been considered for the subject site:

- River Water Quality Protection;
- River Regime Protection;
- Level of Service (flooding) for the site and;
- River Flood Protection.

3.12 Criterion 1 – River Water Quality Protection

It is proposed that the overall drainage system, serving this development, will contain a range of surface water treatment methods, as outlined previously in *Section 3.5*, which will improve the quality of surface water being discharged from the proposed development to the River Camac.

Gross pollutants, sediments, hydrocarbons, and other impurities, will be removed at source with the following provisions:

- a) Bioretention systems in open spaces;
- b) Intensive landscaping, where practicable;
- c) Interception storage at attenuation systems;
- d) All road gullies and linear channel drains are to be trapped;
- e) Silt-trap prior to attenuation storage area.

3.13 Criterion 2 – River Regime Protection

Surface water discharge from the overall development will be restricted to an equivalent rural runoff rate of **5.0 l/s/ha**, as per GDSDS and Dublin City Council Development Plan (and the Draft Development Plan) requirements. Refer to *Section 3.4.3* for further details of the proposed development rainfall runoff calculations.

This will be achieved with the provision of a flow control devices (Hydro-Brake Optimum, by Hydro-International, or similar approved) upstream of the outfall manhole. Refer to *Section 3.5.3.7* for further details.

3.14 Criterion 3 – Level of Service (Flooding) Site

There are four sub-criteria for the required level of service, for a new development; as set out in the *GSDSDS Volume 2, Section 6.3.4 (Table 6.3)*.

- No flooding on site except where planned (30-year high intensity rainfall event);
- No internal property flooding (100-year high intensity rainfall event);
- No internal property flooding (100-year river event and critical duration for site) and;
- No flood routing off site except where specifically planned. (100-year high intensity rainfall event).

3.14.1 Sub-Criterion 3.1

The surface water drainage systems, serving the proposed development, have been designed to accommodate the 100-year return period rainfall event (including an allowance of 20% increase in rainfall intensity for climate change) without flooding. Therefore, the system has capacity for the 30-year return period rainfall event without flooding.

The performance of the proposed drainage system has been analysed for design rainfall events up to, and including, the 1% AEP event (including 20% climate change allowance) using the *MicroDrainage Network Design Software*, by Innovyze Inc. Refer to **Appendix D** for details of design criteria, calculations and results. The analyses indicate that no flooding will occur for design rainfall events up to, and including, the 1% AEP (Annual Exceedance Probability).

3.14.2 Sub-Criterion 3.2

The surface water drainage systems, serving the proposed development, are yet to be designed to accommodate the 100-year return period rainfall

event (including an allowance of 20% increase in rainfall intensity for climate change) without flooding.

The performance of the proposed drainage system in 100-year return period storm events (including 20% climate change allowance) has been analysed – Refer **Appendix D** for calculations. The analyses show that no flooding will occur in 100-year return period storm events.

3.14.3 Sub-Criterion 3.3

Details of the flood risk assessment associated with the proposed development is outlined in the Site-Specific Flood Risk Assessment (Document Nr. **B967-OCSC-XX-XX-RP-C-0007**), which is submitted under separate cover, as part of this application.

3.14.4 Sub-Criterion 3.4

The surface water drainage systems, serving the proposed development, are yet to be designed to accommodate the 100-year return period rainfall event (including an allowance of 20% increase in rainfall intensity for climate change) without flooding, so no flood routing off site will be experienced for such a rainfall event.

The performance of the proposed drainage system in 100-year return period storm events (including 20% climate change allowance) has been analysed – Refer **Appendix D** for calculations. The analyses show that no flooding will occur in 100-year return period storm events.

Details of the flood risk assessment associated with the proposed development is outlined in the Site-Specific Flood Risk Assessment (Document Nr. **B967-OCSC-XX-XX-RP-C-0007**), which is submitted under separate cover, as part of this application.

3.15 Criterion 4 – River Flood Protection

As outlined in *Section 3.14* (Criterion 2), the surface water runoff from the development's catchment will be limited to a maximum of **5.0 l/s/ha**.

Refer to *Section 3.4.3* and *Section 3.6* of this report for further details on the limiting discharge rates. The *GDSDS Volume 2, Appendix E* states that this practice ensures "*that sufficient stormwater runoff retention is achieved to protect the river during extreme events*".

Attenuation storage is to be provided for the 100-year return period rainfall event (including an increased 20% rainfall intensity; to allow for climate change). Discharge from site is to be achieved through the use of a vortex flow control device (e.g. Hydro-Brake Optimum, by Hydro-International, or similar approved), which will reduce the risk of blockage present with other flow devices.

Refer to **Appendix D** for details of hydraulic modelling calculations of attenuation and flow control facilities, as carried out using MicroDrainage software by Innovyze Inc.

4 WASTEWATER DRAINAGE

4.1 Overview

All proposed wastewater sewer design has been carried out in accordance with *Irish Water's Code of Practice for Wastewater Infrastructure (Revision 2 – July 2020)*. The proposed site is a mixture of brownfield areas, with no existing wastewater discharge to the public wastewater infrastructure.

The proposed development is to be served by a gravity wastewater drainage network ultimately discharging to the existing wastewater sewers located at western and eastern boundaries of the site.

4.2 Existing Wastewater Drainage

The proposed development site is well served by foul/combined sewers, as identified on the Irish Water Records reproduced as *Figure 4.1* and verified by GPR/Utilities survey.

Foul sewers are located to both the western and eastern boundaries of the site. There are 2nr. foul sewers located along Saint Vincent Street West. The sizes are not identified on the Irish Water Records, but the larger sewer been determined by topographical survey (by Apex Surveys in 2020) as a 375mm-diameter sewer becoming a 1600mm brick arch sewer. The second sewer is identified as a 300mm-diameter combined sewer that travels under the ground of the Pigeon Club onto Emmet Road. This has been labelled as a storm sewer on the utilities survey which may indicate the foul flow into same would have been from the Saint Michael's Estate buildings.

The foul sewer to the east of the site runs along Saint Michael's Estate. This consists of a 225mm-diameter travelling in a northern direction along the eastern boundary of the site. The sewer serves a number of adjoining developments including Richmond Barracks, Inchicore Primary Care Centre, Inchicore Community Sports Centre, Saint Michael's Parish Community Centre and Eve Tuiscint Health Centre amongst others. Both the record drawings and utilities survey confirm that this sewer becomes a combined sewer before discharging to the combined sewer along Emmet Road.

It is noted that there are a number of old connections from the site identified on the GPR survey.




Figure 4.1 – Irish Water Public Records (Excerpt)

Refer to **Appendix A** for details of Irish Water existing wastewater infrastructure records.

4.3 Consultation

A Pre-Connection Enquiry Form (***IW Ref Nr. CDS22003279***) was submitted to Irish Water, with Confirmation of Feasibility subsequently confirmed by Irish Water, without the requirement for any upgrades.

Refer to **Appendix F** for a copy of the Confirmation of Feasibility Letter.

4.4 Proposed Wastewater Drainage Strategy

It is proposed to separate the wastewater and surface water drainage networks, which will serve the proposed development, and provide independent connections to the adjacent local wastewater and surface water sewer network infrastructure, respectively. Refer to *Section 3* for details of the proposed surface water drainage design strategy.

The overall development is to be separated into three individual gravity wastewater catchments – based on the natural topography of the development site and the proposed finish levels across the new development – to serve each of the proposed blocks.

Each wastewater network is to discharge to the existing wastewater network that is located at St Michael's Estate.

The proposed wastewater network has been designed in accordance with the Building Regulations Part H, and *Irish Water's Code of Practice for Wastewater Infrastructure (Revision 2 – July 2020)*.

Refer to detailed drawing **B967-OCSC-ZZ-GF-DR-C-0500** for the proposed drainage network layout, which is to serve the proposed development.

4.5 Wastewater Network Design Calculations

Wastewater (volumetric) calculations have been complied in accordance with *Irish Water's Code of Practice Wastewater Infrastructure, IW-CDS-5030-03 (Revision 2 – July 2020)* and are included in **Appendix E**.

4.6 Taking In Charge

It is proposed that all new wastewater drainage infrastructure installed to serve the proposed development within the redline boundary **is not** to be offered to Irish Water for to be taken-in-charge and is to be managed by the new development's building management.

5 POTABLE WATER SUPPLY

5.1 Overview

All proposed potable water design has been carried out in accordance with *Irish Water's Code of Practice for Water Infrastructure, IW-CDS-5020-03 (Revision 2 – July 2020)*.

5.2 Consultation

A Pre-Connection Enquiry Form (***IW Ref Nr. CDS22003279***) was submitted to Irish Water, with Confirmation of Feasibility subsequently confirmed by Irish Water, subject to upgrading approximately 180m of existing watermain at Emmet Road, from 150mm to 200mm diameter.



Figure 5.1 - Section of Watermain Requiring Upgrade

Refer to **Appendix F** for a copy of the Confirmation of Feasibility Letter.

5.3 Existing Watermain Infrastructure

There are a number of existing watermain services identified on the Irish Water Record drawings as serving the Emmet Road site. These include:

- 3 inches asbestos pipe supply to Eve Tuiscint Health Centre and Pigeon Club grounds;
- 3 inches asbestos pipe supply to Saint Michael's Parish Community Centre and Inchicore Community Sports Centre;
- 4 inches asbestos pipe supply to northern portion of the original Saint Michael's Estate building. This main links a 4 inches asbestos pipe main

on Saint Vincent Street West and a 3 inches asbestos pipe supply on Saint Michael's Estate;

- 4 inches asbestos pipe supply to central portion of the original Saint Michael's Estate building. This main links a 4 inches pipe main on Saint Vincent Street West and 3 inches asbestos pipe supply on Saint Michael's Estate;
- 2 nr. 4 inches asbestos pipe feeds on the southern portion of the site. Again, there mains link watermains on Saint Vincent Street West and Saint Michael's Estate. Sections of these mains also supply Thornton Heights development;
- 150mm-diameter Ductile iron 1987 pipe at Saint Vincent Street West.

In addition to the above, the record drawings indicate a separate 110mm-diameter MOPVC supply along Bulfin Road and Saint Michael's Estate. This main is indicated to supply Inchicore Primary Care Centre and/or Richmond Barracks.

It is noted that the demolition drawings for Saint Michael's Estate indicate that a number of the above watermains may have been removed as part of the demolition works.




Figure 5.2 - Irish Water Public Records (Excerpt)

Refer to **Appendix A** for details of existing watermain infrastructure records.

5.4 Decommissioning of Existing Watermain

A large number of existing watermain infrastructure will require decommissioning in order to facilitate the new infill development. As part of

this, Irish Water may require diversions in place through or around the development.

5.5 Connection to the Existing Network

It is proposed to serve the proposed development by providing a new connection from the public infrastructure to a centralised water storage tank, located at the new Energy Centre adjacent to Richmond Barracks. From here, water will be metered and distributed to each block and individual units.

The proposed connection is to be carried out in accordance with *Irish Water's Code of Practice for Water Infrastructure (Revision 2 – July 2020)*, following a New Connection agreement with Irish Water, with a bulk water meter to be provided at the development's entrance, with separate metering provided for each individual development unit, as per Irish Water requirements.

Refer to detailed drawing **B967-OCSC-ZZ-GF-DR-C-0550** for the proposed watermain layout, which is to serve the proposed development.

In order to facilitate the proposed development Irish Water have advised to upgrade the existing 150mm ø watermain along Emmet Road to a 200mm ø pipe; refer Section 5.2 and appended Confirmation of Feasibility Letter for details.

5.6 Water Meters

A bulk water meter is to be provided at the location of the new connection from the public watermain, along with individual meters provided at the connection to each unit. All metering is to be provided in accordance with Irish Water's requirements. Taking In Charge

All new watermain infrastructure, installed to serve the proposed development after the bulk meter **is not** to be offered to Irish Water for to be taken-in-charge. The development's internal water infrastructure is to be managed and maintained by the building management.

APPENDIX A. EXISTING DRAINAGE INFRASTRUCTURE RECORDS

Appendix A

Existing Drainage Infrastructure Records

APPENDIX B. RETURN PERIOD RAINFALL DEPTHS

Appendix B

Return Period Rainfall Depths for Sliding Durations from Met Éireann

Met Eireann

Return Period Rainfall Depths for sliding Durations

Irish Grid: Easting: 312121, Northing: 233327,

DURATION	Interval		Years													
	6months,	1year,	2,	3,	4,	5,	10,	20,	30,	50,	75,	100,	150,	200,	250,	500,
5 mins	2.4,	3.5,	4.1,	5.0,	5.7,	6.2,	7.8,	9.7,	11.0,	12.8,	14.4,	15.7,	17.6,	19.2,	20.5,	N/A,
10 mins	3.4,	4.9,	5.7,	7.0,	7.9,	8.6,	10.9,	13.5,	15.3,	17.8,	20.0,	21.8,	24.6,	26.7,	28.5,	N/A,
15 mins	4.0,	5.8,	6.8,	8.3,	9.3,	10.1,	12.8,	15.9,	18.0,	20.9,	23.6,	25.7,	28.9,	31.4,	33.5,	N/A,
30 mins	5.2,	7.5,	8.8,	10.6,	11.9,	12.9,	16.2,	20.0,	22.5,	26.1,	29.2,	31.7,	35.6,	38.6,	41.1,	N/A,
1 hours	6.9,	9.8,	11.4,	13.7,	15.3,	16.5,	20.6,	25.1,	28.2,	32.5,	36.3,	39.2,	43.8,	47.4,	50.3,	N/A,
2 hours	9.2,	12.8,	14.7,	17.6,	19.6,	21.1,	26.1,	31.6,	35.3,	40.4,	45.0,	48.5,	53.9,	58.1,	61.6,	N/A,
3 hours	10.8,	14.9,	17.2,	20.4,	22.7,	24.4,	29.9,	36.2,	40.2,	46.0,	51.0,	54.9,	60.9,	65.5,	69.4,	N/A,
4 hours	12.1,	16.7,	19.1,	22.7,	25.1,	27.0,	33.0,	39.8,	44.2,	50.3,	55.8,	60.0,	66.4,	71.3,	75.4,	N/A,
6 hours	14.3,	19.5,	22.3,	26.3,	29.1,	31.2,	37.9,	45.5,	50.4,	57.2,	63.3,	67.9,	75.0,	80.4,	84.9,	N/A,
9 hours	16.8,	22.8,	25.9,	30.5,	33.6,	36.0,	43.6,	52.0,	57.5,	65.1,	71.7,	76.9,	84.7,	90.7,	95.6,	N/A,
12 hours	18.9,	25.4,	28.9,	33.9,	37.2,	39.8,	48.1,	57.2,	63.1,	71.3,	78.4,	83.9,	92.3,	98.7,	104.0,	N/A,
18 hours	22.2,	29.7,	33.6,	39.3,	43.1,	46.0,	55.2,	65.4,	72.0,	81.0,	89.0,	95.0,	104.2,	111.3,	117.1,	N/A,
24 hours	24.9,	33.2,	37.4,	43.6,	47.8,	50.9,	60.9,	71.9,	79.0,	88.8,	97.3,	103.8,	113.6,	121.2,	127.3,	148.6,
2 days	30.7,	40.0,	44.8,	51.7,	56.2,	59.6,	70.5,	82.2,	89.7,	99.9,	108.8,	115.5,	125.7,	133.4,	139.7,	161.2,
3 days	35.4,	45.6,	50.8,	58.2,	63.0,	66.7,	78.2,	90.6,	98.5,	109.2,	118.4,	125.4,	136.0,	143.9,	150.4,	172.5,
4 days	39.5,	50.4,	55.9,	63.8,	68.9,	72.8,	85.0,	98.0,	106.2,	117.3,	126.9,	134.1,	145.0,	153.2,	159.9,	182.5,
6 days	46.6,	58.8,	65.0,	73.6,	79.2,	83.5,	96.7,	110.7,	119.5,	131.4,	141.6,	149.3,	160.8,	169.4,	176.4,	200.1,
8 days	52.9,	66.2,	72.8,	82.2,	88.2,	92.8,	106.9,	121.8,	131.1,	143.7,	154.4,	162.5,	174.5,	183.5,	190.8,	215.5,
10 days	58.7,	73.0,	80.0,	90.0,	96.4,	101.2,	116.1,	131.8,	141.6,	154.8,	166.0,	174.3,	186.9,	196.2,	203.8,	229.3,
12 days	64.0,	79.2,	86.7,	97.2,	104.0,	109.0,	124.7,	141.1,	151.3,	165.0,	176.6,	185.3,	198.3,	208.0,	215.8,	242.1,
16 days	74.0,	90.8,	99.0,	110.5,	117.8,	123.3,	140.2,	157.9,	168.9,	183.5,	196.0,	205.2,	219.0,	229.3,	237.6,	265.3,
20 days	83.1,	101.3,	110.2,	122.6,	130.4,	136.3,	154.4,	173.2,	184.9,	200.4,	213.5,	223.2,	237.7,	248.5,	257.2,	286.2,
25 days	93.9,	113.7,	123.2,	136.6,	145.1,	151.4,	170.8,	190.9,	203.2,	219.7,	233.6,	243.9,	259.2,	270.6,	279.7,	310.2,

NOTES:

N/A Data not available

These values are derived from a Depth Duration Frequency (DDF) Model

For details refer to:

'Fitzgerald D. L. (2007), Estimates of Point Rainfall Frequencies, Technical Note No. 61, Met Eireann, Dublin',

Available for download at www.met.ie/climate/products/Estimation-of-Point-Rainfall-Frequencies_TN61.pdf

APPENDIX C. Q_{BAR} RUNOFF CALCULATIONS

O'Connor Sutton Cronin		Page 1
9 Prussia Street Dublin 7 Ireland	Emmet Road Development	
Date 01/06/2022	Designed by MK	
File	Checked by ZB	
XP Solutions		Source Control 2020.1

ICP SUDS Mean Annual Flood

Input

Return Period (years)	2	Soil	0.470
Area (ha)	3.800	Urban	0.000
SAAR (mm)	720	Region Number	User Defined

User Defined Growth Curve

Filename gdsds_Growth Curve.gcfx Description GDSDS

Return Period (years)	Growth Curve Factor
1	0.850
2	0.000
5	0.000
10	1.700
20	0.000
25	0.000
30	2.100
50	0.000
100	2.600
200	2.900
500	0.000
1000	0.000

Results 1/s

QBAR Rural 19.0
QBAR Urban 19.0

Q2 years 0.0

Q1 year 16.1
Q30 years 39.8
Q100 years 49.3

©1982-2020 Innovyze

APPENDIX D. SURFACE WATER DESIGN CALCULATIONS

- Design Criteria;
- Area Summary;
- Network Design & Results Table;
- Simulation Criteria;
- Hydrobrake / Controls & Storage Design;
- Summary of Results.

Appendix D

Surface Water Design Calculations

O'Connor Sutton Cronin		Page 1										
9 Prussia Street Dublin 7 Ireland		EMMET ROAD										
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Designed by EH Checked by MK										
XP Solutions		Network 2020.1.3										
STORM SEWER DESIGN by the Modified Rational Method												
Design Criteria for SW R												
Pipe Sizes IW Manhole Sizes IW												
FSR Rainfall Model - Scotland and Ireland												
Return Period (years) 5 Foul Sewage (l/s/ha) 0.000 Maximum Backdrop Height (m) 3.000												
M5-60 (mm) 16.500 Volumetric Runoff Coeff. 1.000 Min Design Depth for Optimisation (m) 0.750												
Ratio R 0.277 PIMP (%) 100 Min Vel for Auto Design only (m/s) 1.00												
Maximum Rainfall (mm/hr) 50 Add Flow / Climate Change (%) 20 Min Slope for Optimisation (1:X) 500												
Maximum Time of Concentration (mins) 30 Minimum Backdrop Height (m) 0.000												
Designed with Level Soffits												
Network Design Table for SW R												
PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	n	HYD SECT	DIA (mm)	Section Type	Auto Design
R.S1.000	17.512	0.175	100.1	0.040	5.00	0.0	0.600	o	150	Pipe/Conduit		
Network Results Table												
PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	E I.Area (ha)	E Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)		
R.S1.000	50.00	5.29	26.000	0.040	0.0	0.0	1.5	1.00	17.8	8.7		
©1982-2020 Innovyze												

9 Prussia Street
Dublin 7
Ireland

EMMET ROAD



Date 27/09/2022 12:53

Designed by EH

File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX

Checked by MK

XP Solutions

Network 2020.1.3

Network Design Table for SW R

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	n	HYD SECT	DIA (mm)	Section Type	Auto Design
R.S2.000	6.330	0.063	100.0	0.004	5.00	0.0	0.600	o	150	Pipe/Conduit	🟢	
R.S3.000	6.080	0.061	100.0	0.051	5.00	0.0	0.600	o	150	Pipe/Conduit	🟡	
R.S2.001	1.860	0.093	20.0	0.000	0.00	0.0	0.600	o	150	Pipe/Conduit	🟢	
R.S2.002	13.287	0.221	60.1	0.000	0.00	0.0	0.600	o	150	Pipe/Conduit	🟢	
R.S4.000	3.992	0.040	100.1	0.009	5.00	0.0	0.600	o	150	Pipe/Conduit	🟢	
R.S4.001	3.282	0.164	20.0	0.000	0.00	0.0	0.600	o	150	Pipe/Conduit	🟢	

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Flow (l/s)	Base Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
R.S2.000	50.00	5.10	25.853	0.004	0.00	0.0	0.1	1.00	17.8	0.8
R.S3.000	50.00	5.10	25.950	0.051	0.0	0.0	1.8	1.00	17.8	11.1
R.S2.001	50.00	5.12	25.790	0.055	0.0	0.0	2.0	2.26	40.0	11.9
R.S2.002	50.00	5.29	25.697	0.055	0.0	0.0	2.0	1.30	23.0	11.9
R.S4.000	50.00	5.07	25.917	0.009	0.0	0.0	0.3	1.00	17.7	2.0
R.S4.001	50.00	5.09	25.877	0.009	0.0	0.0	0.3	2.26	40.0	2.0

O'Connor Sutton Cronin			Page 4									
9 Prussia Street Dublin 7 Ireland		EMMET ROAD										
Date 27/09/2022 12:53		Designed by EH										
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK										
XP Solutions		Network 2020.1.3										
Network Design Table for SW R												
PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	n	HVD SECT	DIA (mm)	Section Type	Auto Design
R.S1.004	17.236	0.069	249.8	0.022	0.00	0.0		0.045	→ o →		Filter Drain	
R.S1.005	19.937	0.080	249.2	0.032	0.00	0.0		0.045	→ o →		Filter Drain	
R.S1.006	12.978	0.433	30.0	0.000	0.00	0.0	0.600			225	Pipe/Conduit	
R.S1.007	31.657	0.396	80.0	0.000	0.00	0.0	0.600			225	Pipe/Conduit	
R.S1.008	54.854	0.549	100.0	0.000	0.00	0.0	0.600			225	Pipe/Conduit	
R.S1.009	43.143	0.431	100.1	0.000	0.00	0.0	0.600			225	Pipe/Conduit	
R.S6.000	2.787	0.083	33.5	0.000	5.00	0.0	0.600			150	Pipe/Conduit	
R.S6.001	16.592	0.207	80.0	0.008	0.00	0.0	0.600			225	Pipe/Conduit	
Network Results Table												
PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)		
R.S1.004	46.30	10.01	24.865	0.129	2.0	0.0	4.7	0.21	50.8	28.2		
R.S1.005	43.19	11.56	24.796	0.161	2.0	0.0	5.4	0.21	50.8	32.5		
R.S1.006	50.00	5.09	24.716	0.000	2.0	0.0	0.3	2.40	95.3	2.0		
R.S1.007	50.00	5.45	24.283	0.000	2.0	0.0	0.4	1.46	58.2	2.4		
R.S1.008	50.00	6.15	23.888	0.000	2.0	0.0	0.4	1.31	52.0	2.4		
R.S1.009	50.00	6.70	23.339	0.000	2.0	0.0	0.4	1.31	52.0	2.4		
R.S6.000	50.00	5.03	26.000	0.000	0.0	0.0	0.0	1.74	30.8	0.0		
R.S6.001	50.00	5.22	25.650	0.008	0.0	0.0	0.3	1.46	58.2	1.7		
©1982-2020 Innovyze												

9 Prussia Street
Dublin 7
Ireland

EMMET ROAD



Date 27/09/2022 12:53

Designed by EH

File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX

Checked by MK

XP Solutions

Network 2020.1.3

Network Design Table for SW R

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	Base k (mm)	n	HYD SECT	DIA (mm)	Section Type	Auto Design
R.S7.000	3.378	0.082	41.0	0.000	5.00	0.0	0.600	o	150	Pipe/Conduit		🟢
R.S6.002	18.180	0.109	166.6	0.008	0.00	0.0	0.600	o	225	Pipe/Conduit		🟢
R.S8.000	8.075	0.081	100.1	0.007	5.00	0.0	0.600	o	150	Pipe/Conduit		🟢
R.S9.000	15.297	0.191	80.0	0.037	5.00	0.0	0.600	o	150	Pipe/Conduit		🟡
R.S6.003	13.020	0.078	166.6	0.005	0.00	0.0	0.600	o	225	Pipe/Conduit		🟢
R.S6.004	13.020	0.078	166.6	0.000	0.00	0.0	0.600	o	225	Pipe/Conduit		🟢

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap Flow (l/s)
R.S7.000	50.00	5.04	25.600	0.000	0.0	0.0	0.0	1.58	27.9
R.S6.002	50.00	5.52	25.443	0.015	0.0	0.0	0.6	1.01	40.2
R.S8.000	50.00	5.13	24.850	0.007	0.0	0.0	0.3	1.00	17.7
R.S9.000	50.00	5.23	25.150	0.037	0.0	0.0	1.3	1.12	19.9
R.S6.003	50.00	5.73	24.694	0.065	0.0	0.0	2.3	1.01	40.2
R.S6.004	50.00	5.95	24.616	0.065	0.0	0.0	2.3	1.01	40.2

O'Connor Sutton Cronin			Page 6									
9 Prussia Street Dublin 7 Ireland		EMMET ROAD										
Date 27/09/2022 12:53		Designed by EH										
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK										
XP Solutions		Network 2020.1.3										
Network Design Table for SW R												
PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	n	HYD SECT	DIA (mm)	Section Type	Auto Design
R.S10.000	3.925	0.039	100.7	0.000	5.00	0.0	0.600	o	150	Pipe/Conduit		
R.S10.001	3.925	0.039	100.7	0.011	0.00	0.0	0.600	o	150	Pipe/Conduit		
R.S10.002	2.084	0.052	40.0	0.006	0.00	0.0	0.600	o	75	Pipe/Conduit		
R.S10.003	11.862	0.079	150.0	0.000	0.00	0.0	0.600	o	225	Pipe/Conduit		
R.S10.004	24.048	0.160	150.0	0.017	0.00	0.0	0.600	o	225	Pipe/Conduit		
R.S10.005	12.664	0.084	150.0	0.002	0.00	0.0	0.600	o	225	Pipe/Conduit		
R.S11.000	4.869	0.049	99.4	0.004	5.00	0.0	0.600	o	225	Pipe/Conduit		
Network Results Table												
PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap Flow (l/s)	Flow (l/s)		
R.S10.000	50.00	5.07	24.750	0.000	0.0	0.0	0.0	1.00	17.7	0.0		
R.S10.001	50.00	5.13	24.200	0.011	0.0	0.0	0.4	1.00	17.7	2.5		
R.S10.002	50.00	5.03	24.161	0.000	2.0	0.0	0.3	1.01	4.5	2.0		
R.S10.003	50.00	5.22	23.959	0.000	2.0	0.0	0.4	1.07	42.4	2.4		
R.S10.004	50.00	5.60	23.880	0.017	2.0	0.0	1.0	1.07	42.4	6.1		
R.S10.005	50.00	5.79	23.720	0.019	2.0	0.0	1.1	1.07	42.4	6.6		
R.S11.000	50.00	5.06	24.300	0.004	0.0	0.0	0.1	1.31	52.2	0.9		
©1982-2020 Innovyze												

9 Prussia Street
Dublin 7
Ireland

EMMET ROAD



Date 27/09/2022 12:53

Designed by EH

File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX

Checked by MK

XP Solutions

Network 2020.1.3

Network Design Table for SW R

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	n	HYD SECT	DIA (mm)	Section Type	Auto Design
R.S16.001	4.246	0.028	150.0	0.000	0.00	0.0	0.600		o	150	Pipe/Conduit	
R.S16.002	2.875	0.019	150.0	0.000	0.00	0.0	0.600		o	75	Pipe/Conduit	
R.S16.003	24.940	0.416	60.0	0.020	0.00	0.0	0.600		o	225	Pipe/Conduit	
R.S19.000	3.701	0.046	80.5	0.000	5.00	0.0	0.600		o	150	Pipe/Conduit	
R.S16.004	12.470	0.125	99.8	0.008	0.00	0.0	0.600		o	225	Pipe/Conduit	
R.S20.000	3.816	0.047	81.2	0.000	5.00	0.0	0.600		o	150	Pipe/Conduit	

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
R.S16.001	50.00	5.64	25.249	0.026	0.0	0.0	0.9	0.82	14.5	5.5
R.S16.002	50.00	5.09	25.221	0.000	2.0	0.0	0.3	0.52	2.3	2.0
R.S16.003	50.00	5.34	25.051	0.020	2.0	0.0	1.1	1.69	67.3	6.7
R.S19.000	50.00	5.05	25.100	0.000	0.0	0.0	0.0	1.12	19.8	0.0
R.S16.004	50.00	5.50	24.250	0.028	2.0	0.0	1.4	1.31	52.0	8.4
R.S20.000	50.00	5.06	24.800	0.000	0.0	0.0	0.0	1.12	19.7	0.0

O'Connor Sutton Cronin			Page 14									
9 Prussia Street Dublin 7 Ireland		EMMET ROAD										
Date 27/09/2022 12:53		Designed by EH										
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK										
XP Solutions		Network 2020.1.3										
Network Design Table for SW R												
PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	n	HYD SECT	DIA (mm)	Section Type	Auto Design
R.S23.002	4.707	0.047	100.1	0.006	0.00	0.00	0.0	0.600	o	150	Pipe/Conduit	
R.S23.003	3.411	0.034	100.3	0.009	0.00	0.00	0.0	0.600	o	75	Pipe/Conduit	
R.S23.004	23.077	0.132	174.8	0.000	0.00	0.00	0.0	0.600	o	225	Pipe/Conduit	
R.S25.000	4.836	0.060	80.0	0.000	5.00	0.00	0.0	0.600	o	150	Pipe/Conduit	
R.S25.001	4.325	0.043	100.6	0.009	0.00	0.00	0.0	0.600	o	150	Pipe/Conduit	
R.S26.000	4.818	0.060	80.0	0.000	5.00	0.00	0.0	0.600	o	150	Pipe/Conduit	
R.S26.001	10.682	0.107	99.8	0.012	0.00	0.00	0.0	0.600	o	150	Pipe/Conduit	
Network Results Table												
PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add	Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)	
R.S23.002	50.00	5.26	23.823	0.074	0.00	0.0	2.7	1.00	17.7	16.1		
R.S23.003	50.00	5.09	23.776	0.000	2.0	0.0	0.3	0.63	2.8	2.0		
R.S23.004	50.00	5.48	23.592	0.000	2.0	0.0	0.4	0.99	39.2	2.4		
R.S25.000	50.00	5.07	25.400	0.000	0.00	0.0	0.0	1.12	19.9	0.0		
R.S25.001	50.00	5.14	24.500	0.009	0.00	0.0	0.3	1.00	17.7	2.0		
R.S26.000	50.00	5.07	24.900	0.000	0.00	0.0	0.0	1.12	19.9	0.0		
R.S26.001	50.00	5.25	24.500	0.012	0.00	0.0	0.4	1.01	17.8	2.6		
©1982-2020 Innovyze												

O'Connor Sutton Cronin			Page 16									
9 Prussia Street Dublin 7 Ireland			EMMET ROAD									
			Designed by EH Checked by MK Network 2020.1.3									
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX XP Solutions			Network Design Table for SW R									
PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k	n	HYD SECT	DIA (mm)	Section Type	Auto Design
R.S25.004	5.038	0.050	100.1	0.000	0.00	0.0	0.600	o	225	Pipe/Conduit		
R.S29.000	2.359	0.029	80.0	0.000	5.00	0.0	0.600	o	150	Pipe/Conduit		
R.S29.001	8.862	0.089	100.0	0.007	0.00	0.0	0.600	o	150	Pipe/Conduit		
R.S25.005	7.627	0.352	21.7	0.000	0.00	0.0	0.600	o	225	Pipe/Conduit		
R.S30.000	6.486	0.081	80.1	0.008	5.00	0.0	0.600	o	150	Pipe/Conduit		
R.S23.005	10.277	0.103	100.1	0.000	0.00	0.0	0.600	o	225	Pipe/Conduit		
Network Results Table												
PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul Flow (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)		
R.S25.004	50.00	5.36	24.055	0.010	2.0	0.0	0.8	1.31	51.9	4.6		
R.S29.000	50.00	5.03	24.900	0.000	0.0	0.0	0.0	1.12	19.9	0.0		
R.S29.001	50.00	5.18	24.871	0.007	0.0	0.0	0.3	1.00	17.8	1.6		
R.S25.005	50.00	5.40	24.005	0.017	2.0	0.0	1.0	2.82	112.2	6.2		
R.S30.000	50.00	5.10	24.350	0.008	0.0	0.0	0.3	1.12	19.9	1.8		
R.S23.005	50.00	5.61	23.460	0.026	4.0	0.0	1.7	1.31	51.9	10.4		
©1982-2020 Innovyze												

O'Connor Sutton Cronin			Page 18									
9 Prussia Street Dublin 7 Ireland		EMMET ROAD										
Date 27/09/2022 12:53		Designed by EH										
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK										
XP Solutions				Network 2020.1.3								
Network Design Table for SW R												
PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k	n	HYD SECT	DIA (mm)	Section Type	Auto Design
R.S31.003	2.496	0.025	100.1	0.000	0.00	0.0	0.600		o	150	Pipe/Conduit	
R.S31.004	2.251	0.028	80.4	0.000	0.00	0.0	0.600		o	75	Pipe/Conduit	
R.S23.006	27.764	0.277	100.2	0.012	0.00	0.0	0.600		o	150	Pipe/Conduit	
R.S22.008	12.580	0.126	100.1	0.012	0.00	0.0	0.600		o	150	Pipe/Conduit	
R.S6.008	9.223	0.061	150.0	0.006	0.00	0.0	0.600		o	225	Pipe/Conduit	
R.S34.000	10.466	0.105	99.7	0.011	5.00	0.0	0.600		o	150	Pipe/Conduit	
Network Results Table												
PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap Flow (l/s)	Flow (l/s)		
R.S31.003	50.00	5.51	23.608	0.076	0.0	0.0	2.7	1.00	17.7	16.5		
R.S31.004	50.00	5.05	23.584	0.000	2.0	0.0	0.3	0.71	3.1	2.0		
R.S23.006	50.00	5.46	23.357	0.000	3.0	0.0	0.5	1.00	17.7	3.0		
R.S22.008	50.00	5.67	23.080	0.012	5.0	0.0	1.4	1.00	17.7	8.5		
R.S6.008	50.00	5.81	22.754	0.017	12.0	0.0	3.0	1.07	42.4	18.1		
R.S34.000	50.00	5.17	23.700	0.011	0.0	0.0	0.4	1.01	17.8	2.5		
©1982-2020 Innovyze												

O'Connor Sutton Cronin			Page 21			
9 Prussia Street Dublin 7 Ireland		EMMET ROAD				
Date 27/09/2022 12:53		Designed by EH				
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK				
XP Solutions		Network 2020.1.3				
Area Summary for SW R						
Pipe Number	PIMP Type	PIMP Name	PIMP (%)	Gross Area (ha)	Imp. Area (ha)	Pipe Total (ha)
1.000	As Zoned	Default	90	0.043	0.039	0.039
		Bioretention / Planted	30	0.005	0.001	0.040
2.000	As Zoned	Default	90	0.001	0.001	0.001
		Bioretention / Planted	30	0.009	0.003	0.004
3.000	As Zoned	Default	90	0.057	0.051	0.051
		Grass (Lawn)	15	0.000	0.000	0.051
2.001	-	-	100	0.000	0.000	0.000
2.002	-	-	100	0.000	0.000	0.000
4.000	As Zoned	Default	90	0.009	0.008	0.008
		Bioretention / Planted	30	0.004	0.001	0.009
4.001	-	-	100	0.000	0.000	0.000
2.003	-	-	100	0.000	0.000	0.000
5.000	As Zoned	Default	90	0.025	0.022	0.022
		Bioretention / Planted	30	0.009	0.003	0.025
2.004	-	-	100	0.000	0.000	0.000
1.001	As Zoned	Default	90	0.022	0.020	0.020
		Bioretention / Planted	30	0.002	0.000	0.020
1.002	As Zoned	Default	90	0.025	0.022	0.022
		Bioretention / Planted	30	0.002	0.001	0.023
1.003	As Zoned	Default	90	0.024	0.022	0.022
		Bioretention / Planted	30	0.004	0.001	0.023
1.004	As Zoned	Default	90	0.024	0.022	0.022
		Bioretention / Planted	30	0.002	0.001	0.022
1.005	As Zoned	Default	90	0.023	0.021	0.021
		Bioretention / Planted	30	0.002	0.001	0.021
As Zoned		Default	90	0.009	0.008	0.029
		Bioretention / Planted	30	0.009	0.003	0.032
©1982-2020 Innovyze						

O'Connor Sutton Cronin			Page 22			
9 Prussia Street Dublin 7 Ireland		EMMET ROAD				
Date 27/09/2022 12:53		Designed by EH				
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK				
XP Solutions		Network 2020.1.3				
Area Summary for SW R						
Pipe Number	PIMP Type	PIMP Name	PIMP (%)	Gross Area (ha)	Imp. Area (ha)	Pipe Total (ha)
1.006	-		- 100	0.000	0.000	0.000
1.007	-		- 100	0.000	0.000	0.000
1.008	-		- 100	0.000	0.000	0.000
1.009	-		- 100	0.000	0.000	0.000
6.000	-		- 100	0.000	0.000	0.000
6.001	As Zoned	Default	90	0.005	0.005	0.005
		Bioretention / Planted	30	0.009	0.003	0.008
		Grass (Lawn)	15	0.001	0.000	0.008
7.000	-		- 100	0.000	0.000	0.000
6.002	As Zoned	Default	90	0.008	0.007	0.007
		Bioretention / Planted	30	0.002	0.001	0.008
8.000	As Zoned	Default	90	0.002	0.002	0.002
		Grass (Lawn)	15	0.040	0.006	0.007
9.000	As Zoned	Default	90	0.040	0.036	0.036
		Bioretention / Planted	30	0.000	0.000	0.036
		Grass (Lawn)	15	0.002	0.000	0.037
6.003	As Zoned	Grass (Lawn)	15	0.030	0.004	0.005
6.004	-		- 100	0.000	0.000	0.000
10.000	-		- 100	0.000	0.000	0.000
10.001	As Zoned	Default	90	0.004	0.004	0.004
		Bioretention / Planted	30	0.025	0.007	0.011
10.002	As Zoned	Default	90	0.001	0.001	0.001
		Bioretention / Planted	30	0.000	0.000	0.001
		Grass (Lawn)	15	0.033	0.005	0.006
10.003	-		- 100	0.000	0.000	0.000
10.004	As Zoned	Default	90	0.016	0.015	0.015
		Grass (Lawn)	15	0.017	0.003	0.017
©1982-2020 Innovyze						

O'Connor Sutton Cronin			Page 23			
9 Prussia Street Dublin 7 Ireland		EMMET ROAD				
Date 27/09/2022 12:53		Designed by EH				
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK				
XP Solutions		Network 2020.1.3				
Area Summary for SW R						
Pipe Number	PIMP Type	PIMP Name	PIMP (%)	Gross Area (ha)	Imp. Area (ha)	Pipe Total (ha)
10.005	As Zoned	Grass (Lawn)	15	0.014	0.002	0.002
11.000	As Zoned	Default	90	0.001	0.001	0.001
		Grass (Lawn)	15	0.020	0.003	0.004
6.005	-	-	100	0.000	0.000	0.000
12.000	-	-	100	0.000	0.000	0.000
13.000	-	-	100	0.000	0.000	0.000
13.001	As Zoned	Default	90	0.008	0.007	0.007
		Bioretention / Planted	30	0.023	0.007	0.014
12.001	As Zoned	Default	90	0.010	0.009	0.009
		Bioretention / Planted	30	0.007	0.002	0.011
12.002	-	-	100	0.000	0.000	0.000
12.003	As Zoned	Default	90	0.011	0.010	0.010
		Bioretention / Planted	30	0.008	0.002	0.013
14.000	-	-	100	0.000	0.000	0.000
12.004	-	-	100	0.000	0.000	0.000
6.006	-	-	100	0.000	0.000	0.000
15.000	-	-	100	0.000	0.000	0.000
15.001	As Zoned	Default	90	0.030	0.027	0.027
		Grass (Lawn)	15	0.000	0.000	0.027
15.002	-	-	100	0.000	0.000	0.000
16.000	-	-	100	0.000	0.000	0.000
17.000	-	-	100	0.000	0.000	0.000
17.001	As Zoned	Default	90	0.014	0.013	0.013
		Bioretention / Planted	30	0.020	0.006	0.019
		Grass (Lawn)	15	0.001	0.000	0.019
18.000	-	-	100	0.000	0.000	0.000
17.002	As Zoned	Default	90	0.004	0.004	0.004
©1982-2020 Innovyze						

O'Connor Sutton Cronin			Page 25			
9 Prussia Street Dublin 7 Ireland		EMMET ROAD				
Date 27/09/2022 12:53		Designed by EH				
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK				
XP Solutions		Network 2020.1.3				
Area Summary for SW R						
Pipe Number	PIMP Type	PIMP Name	PIMP (%)	Gross Area (ha)	Imp. Area (ha)	Pipe Total (ha)
21.007	As Zoned	Bioretention / Planted	30	0.003	0.001	0.003
		Default	90	0.006	0.005	0.005
21.008	As Zoned	Bioretention / Planted	30	0.000	0.000	0.005
		Default	90	0.016	0.014	0.014
21.009	-	Bioretention / Planted	30	0.003	0.001	0.015
22.000	As Zoned	-	100	0.000	0.000	0.000
		Default	90	0.011	0.010	0.010
22.001	As Zoned	Bioretention / Planted	30	0.013	0.004	0.014
		Default	90	0.005	0.004	0.004
22.002	As Zoned	Bioretention / Planted	30	0.002	0.000	0.005
		Default	90	0.004	0.003	0.003
22.003	As Zoned	Bioretention / Planted	30	0.004	0.001	0.004
		Default	90	0.005	0.004	0.004
22.004	As Zoned	Bioretention / Planted	30	0.000	0.000	0.004
		Default	90	0.005	0.005	0.005
22.005	As Zoned	Bioretention / Planted	30	0.007	0.002	0.007
		Default	90	0.005	0.004	0.004
22.006	As Zoned	Bioretention / Planted	30	0.000	0.000	0.004
		Default	90	0.003	0.003	0.003
22.007	-	Bioretention / Planted	30	0.006	0.002	0.004
		-	100	0.000	0.000	0.000
23.000	As Zoned	Roof (Std)	95	0.032	0.030	0.030
23.001	As Zoned	Default	90	0.008	0.007	0.007
		Bioretention / Planted	30	0.010	0.003	0.010
		Grass (Lawn)	15	0.000	0.000	0.010
24.000	As Zoned	Roof (Std)	95	0.029	0.028	0.028
23.002	As Zoned	Default	90	0.004	0.004	0.004
©1982-2020 Innovyze						

O'Connor Sutton Cronin			Page 26			
9 Prussia Street Dublin 7 Ireland		EMMET ROAD				
Date 27/09/2022 12:53		Designed by EH				
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK				
XP Solutions		Network 2020.1.3				
Area Summary for SW R						
Pipe Number	PIMP Type	PIMP Name	PIMP (%)	Gross Area (ha)	Imp. Area (ha)	Pipe Total (ha)
23.003	As Zoned	Bioretention / Planted	30	0.008	0.002	0.006
		Grass (Lawn)	15	0.002	0.000	0.006
		Default	90	0.007	0.006	0.006
23.004	-	Grass (Lawn)	15	0.018	0.003	0.009
		-	100	0.000	0.000	0.000
25.000	-	-	100	0.000	0.000	0.000
25.001	As Zoned	Default	90	0.009	0.008	0.008
		Bioretention / Planted	30	0.004	0.001	0.009
26.000	-	-	100	0.000	0.000	0.000
26.001	As Zoned	Default	90	0.008	0.007	0.007
		Bioretention / Planted	30	0.015	0.004	0.012
27.000	-	-	100	0.000	0.000	0.000
26.002	As Zoned	Default	90	0.003	0.003	0.003
		Bioretention / Planted	30	0.004	0.001	0.004
25.002	As Zoned	Default	90	0.001	0.001	0.001
		Grass (Lawn)	15	0.006	0.001	0.002
25.003	-	-	100	0.000	0.000	0.000
28.000	-	-	100	0.000	0.000	0.000
28.001	As Zoned	Default	90	0.009	0.008	0.008
		Bioretention / Planted	30	0.004	0.001	0.010
25.004	-	Grass (Lawn)	15	0.002	0.000	0.010
		-	100	0.000	0.000	0.000
		Default	90	0.006	0.006	0.006
29.000	-	-	100	0.000	0.000	0.000
29.001	As Zoned	Default	90	0.004	0.001	0.007
		Bioretention / Planted	30	0.004	0.001	0.007
25.005	-	Grass (Lawn)	15	0.002	0.000	0.007
		-	100	0.000	0.000	0.000
©1982-2020 Innovyze						

O'Connor Sutton Cronin			Page 27			
9 Prussia Street Dublin 7 Ireland		EMMET ROAD				
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Designed by EH Checked by MK				
XP Solutions		Network 2020.1.3				
Area Summary for SW R						
Pipe Number	PIMP Type	PIMP Name	PIMP (%)	Gross Area (ha)	Imp. Area (ha)	Pipe Total (ha)
30.000	As Zoned	Default	90	0.005	0.004	0.004
		Bioretention / Planted	30	0.000	0.000	0.004
		Grass (Lawn)	15	0.026	0.004	0.008
23.005	-	-	100	0.000	0.000	0.000
31.000	As Zoned	Default	90	0.001	0.000	0.000
		Roof (Std)	95	0.058	0.056	0.056
		Bioretention / Planted	30	0.000	0.000	0.056
31.001	As Zoned	Default	90	0.011	0.010	0.010
		Bioretention / Planted	30	0.010	0.003	0.013
		Grass (Lawn)	15	0.003	0.000	0.013
32.000	-	-	100	0.000	0.000	0.000
31.002	As Zoned	Default	90	0.003	0.002	0.002
		Bioretention / Planted	30	0.012	0.004	0.006
		Grass (Lawn)	15	0.004	0.001	0.007
33.000	-	-	100	0.000	0.000	0.000
31.003	-	-	100	0.000	0.000	0.000
31.004	-	-	100	0.000	0.000	0.000
23.006	As Zoned	Default	90	0.013	0.012	0.012
		Bioretention / Planted	30	0.001	0.000	0.012
22.008	As Zoned	Default	90	0.011	0.010	0.010
		Bioretention / Planted	30	0.005	0.001	0.012
6.008	As Zoned	Default	90	0.006	0.005	0.005
		Bioretention / Planted	30	0.002	0.000	0.006
34.000	As Zoned	Default	90	0.010	0.009	0.009
		Bioretention / Planted	30	0.008	0.002	0.011
34.001	As Zoned	Default	90	0.002	0.002	0.002
		Bioretention / Planted	30	0.003	0.001	0.003
©1982-2020 Innovyze						

O'Connor Sutton Cronin			Page 28			
9 Prussia Street Dublin 7 Ireland	EMMET ROAD					
	Designed by EH					
	Checked by MK					
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX XP Solutions			Network 2020.1.3			
Area Summary for SW R						
Pipe Number	PIMP Type	PIMP Name	PIMP (%)	Gross Area (ha)	Imp. Area (ha)	Pipe Total (ha)
34.002	-	-	100	0.000	0.000	0.000
34.003	-	-	100	0.000	0.000	0.000
34.004	As Zoned	Default	90	0.008	0.007	0.007
34.005	-	Bioretention / Planted	30	0.007	0.002	0.010
6.009	As Zoned	-	100	0.000	0.000	0.000
35.000	-	Default	90	0.026	0.023	0.023
35.001	As Zoned	Bioretention / Planted	30	0.010	0.003	0.027
35.002	-	-	100	0.000	0.000	0.000
35.003	As Zoned	Default	90	0.018	0.016	0.016
35.004	-	Pervious Paving	70	0.004	0.003	0.019
35.005	-	-	100	0.000	0.000	0.000
35.006	-	Default	90	0.009	0.008	0.008
35.007	-	Pervious Paving	70	0.034	0.024	0.031
35.008	-	Bioretention / Planted	30	0.006	0.002	0.033
35.009	-	Default	90	0.010	0.009	0.009
35.010	As Zoned	-	100	0.000	0.000	0.000
35.011	-	-	100	0.000	0.000	0.000
35.012	-	-	100	0.000	0.000	0.000
35.013	-	-	100	0.000	0.000	0.000
35.014	-	-	100	0.000	0.000	0.000
35.015	-	-	100	0.000	0.000	0.000
35.016	-	-	100	0.000	0.000	0.000
35.017	-	-	100	0.000	0.000	0.000
35.018	-	-	100	0.000	0.000	0.000
35.019	-	-	100	0.000	0.000	0.000
35.020	-	-	100	0.000	0.000	0.000
35.021	-	-	100	0.000	0.000	0.000
35.022	-	-	100	0.000	0.000	0.000
35.023	-	-	100	0.000	0.000	0.000
35.024	-	-	100	0.000	0.000	0.000
35.025	-	-	100	0.000	0.000	0.000
35.026	-	-	100	0.000	0.000	0.000
35.027	-	-	100	0.000	0.000	0.000
35.028	-	-	100	0.000	0.000	0.000
35.029	-	-	100	0.000	0.000	0.000
35.030	-	-	100	0.000	0.000	0.000
35.031	-	-	100	0.000	0.000	0.000
35.032	-	-	100	0.000	0.000	0.000
35.033	-	-	100	0.000	0.000	0.000
35.034	-	-	100	0.000	0.000	0.000
35.035	-	-	100	0.000	0.000	0.000
35.036	-	-	100	0.000	0.000	0.000
35.037	-	-	100	0.000	0.000	0.000
35.038	-	-	100	0.000	0.000	0.000
35.039	-	-	100	0.000	0.000	0.000
35.040	-	-	100	0.000	0.000	0.000
35.041	-	-	100	0.000	0.000	0.000
35.042	-	-	100	0.000	0.000	0.000
35.043	-	-	100	0.000	0.000	0.000
35.044	-	-	100	0.000	0.000	0.000
35.045	-	-	100	0.000	0.000	0.000
35.046	-	-	100	0.000	0.000	0.000
35.047	-	-	100	0.000	0.000	0.000
35.048	-	-	100	0.000	0.000	0.000
35.049	-	-	100	0.000	0.000	0.000
35.050	-	-	100	0.000	0.000	0.000
35.051	-	-	100	0.000	0.000	0.000
35.052	-	-	100	0.000	0.000	0.000
35.053	-	-	100	0.000	0.000	0.000
35.054	-	-	100	0.000	0.000	0.000
35.055	-	-	100	0.000	0.000	0.000
35.056	-	-	100	0.000	0.000	0.000
35.057	-	-	100	0.000	0.000	0.000
35.058	-	-	100	0.000	0.000	0.000
35.059	-	-	100	0.000	0.000	0.000
35.060	-	-	100	0.000	0.000	0.000
35.061	-	-	100	0.000	0.000	0.000
35.062	-	-	100	0.000	0.000	0.000
35.063	-	-	100	0.000	0.000	0.000
35.064	-	-	100	0.000	0.000	0.000
35.065	-	-	100	0.000	0.000	0.000
35.066	-	-	100	0.000	0.000	0.000
35.067	-	-	100	0.000	0.000	0.000
35.068	-	-	100	0.000	0.000	0.000
35.069	-	-	100	0.000	0.000	0.000
35.070	-	-	100	0.000	0.000	0.000
35.071	-	-	100	0.000	0.000	0.000
35.072	-	-	100	0.000	0.000	0.000
35.073	-	-	100	0.000	0.000	0.000
35.074	-	-	100	0.000	0.000	0.000
35.075	-	-	100	0.000	0.000	0.000
35.076	-	-	100	0.000	0.000	0.000
35.077	-	-	100	0.000	0.000	0.000
35.078	-	-	100	0.000	0.000	0.000
35.079	-	-	100	0.000	0.000	0.000
35.080	-	-	100	0.000	0.000	0.000
35.081	-	-	100	0.000	0.000	0.000
35.082	-	-	100	0.000	0.000	0.000
35.083	-	-	100	0.000	0.000	0.000
35.084	-	-	100	0.000	0.000	0.000
35.085	-	-	100	0.000	0.000	0.000
35.086	-	-	100	0.000	0.000	0.000
35.087	-	-	100	0.000	0.000	0.000
35.088	-	-	100	0.000	0.000	0.000
35.089	-	-	100	0.000	0.000	0.000
35.090	-	-	100	0.000	0.000	0.000
35.091	-	-	100	0.000	0.000	0.000
35.092	-	-	100	0.000	0.000	0.000
35.093	-	-	100	0.000	0.000	0.000
35.094	-	-	100	0.000	0.000	0.000
35.095	-	-	100	0.000	0.000	0.000
35.096	-	-	100	0.000	0.000	0.000
35.097	-	-	100	0.000	0.000	0.000
35.098	-	-	100	0.000	0.000	0.000
35.099	-	-	100	0.000	0.000	0.000
35.100	-	-	100	0.000	0.000	0.000
35.101	-	-	100	0.000	0.000	0.000
35.102	-	-	100	0.000	0.000	0.000
35.103	-	-	100	0.000	0.000	0.000
35.104	-	-	100	0.000	0.000	0.000
35.105	-	-	100	0.000	0.000	0.000
35.106	-	-	100	0.000	0.000	0.000
35.107	-	-	100	0.000	0.000	0.000
35.108	-	-	100	0.000	0.000	0.000
35.109	-	-	100	0.000	0.000	0.000
35.110	-	-	100	0.000	0.000	0.000
35.111	-	-	100	0.000	0.000	0.000
35.112	-	-	100	0.000	0.000	0.000
35.113	-	-	100	0.000	0.000	0.000
35.114	-	-	100	0.000	0.000	0.000
35.115	-	-	100	0.000	0.000	0.000
35.116	-	-	100	0.000	0.000	0.000
35.117	-	-	100	0.000	0.000	0.000
35.118	-	-	100	0.000	0.000	0.000
35.119	-	-	100	0.000	0.000	0.000
35.120	-	-	100	0.000	0.000	0.000
35.121	-	-	100	0.000	0.000	0.000
35.122	-	-	100	0.000	0.000	0.000
35.123	-	-	100	0.000	0.000	0.000
35.124	-	-	100	0.000	0.000	0.000
35.125	-	-	100	0.000	0.000	0.000
35.126	-	-	100	0.000	0.000	0.000
35.127	-	-	100	0.000	0.000	0.000
35.128	-	-	100	0.000	0.000	0.000
35.129	-	-	100	0.000	0.000	0.000
35.130	-	-	100	0.000	0.000	0.000
35.131	-	-	100	0.000	0.000	0.000
35.132	-	-	100	0.000	0.000	0.000
35.133	-	-	100	0.000	0.000	0.000
35.134	-	-	100	0.000	0.000	0.000
35.135	-	-	100	0.000	0.000	0.000
35.136	-	-	100	0.000	0.000	0.000
35.137	-	-	100	0.000	0.000	0.000
35.138	-	-	100	0.000	0.000	0.000
35.139	-	-	100	0.000	0.000	0.000
35.140	-	-	100	0.000	0.000	0.000
35.141	-	-	100	0.000	0.000	0.000
35.142	-	-	100	0.000	0.000	0.000
35.143	-	-	100	0.000	0.000	0.000
35.144	-	-	100	0.000	0.000	0.000
35.145	-	-	100	0.000	0.000	0.000
35.146	-	-	100	0.000	0.000	0.000
35.147	-	-	100	0.000	0.000	0.000
35.148	-	-	100	0.000	0.000	0.000
35.149	-	-	100	0.000	0.000	0.000
35.150	-	-	100	0.000	0.000	0.000
35.151	-	-	100	0.000	0.000	0.000
35.152	-	-	100	0.000	0.000	0.000
35.153	-	-	100	0.000	0.000	0.000
35.154	-	-	100	0.000	0.000	0.000
35.155	-	-	100	0.000	0.000	0.000
35.156	-	-	100	0.000	0.000	0.000
35.157	-	-	100	0.000	0.000	0.000
35.158	-	-	100	0.000	0.000	0.000
35.159	-	-	100	0.000	0.000	0.000
35.160	-	-	100	0.000	0.000	0.000
35.161	-	-	100	0.000	0.000	0.000
35.162	-	-	100	0.000	0.000	0.000
35.163	-	-	100	0.000	0.000	0.000
35.164	-	-	100	0.000	0.000	0.000
35.165	-	-	100	0.000	0.000	0.000
35.166	-	-	100	0.000	0.000	0.000
35.167	-	-	100	0.000	0.000	0.000
35.168	-	-	100	0.000	0.000	0.000
35.169	-	-	100	0.000	0.000	0.000
35.170	-	-	100	0.000	0.000	0.000
35.171	-	-	100	0.000	0.000	0.000
35.172	-	-	100	0.000	0.000	0.000
35.173	-	-	100	0.000	0.000	0.000
35.174	-	-	100	0.000	0.000	0.000
35.175	-	-	100	0.000	0.000	0.000

O'Connor Sutton Cronin		Page 29				
9 Prussia Street Dublin 7 Ireland	EMMET ROAD					
	Designed by EH Checked by MK					
Date 27/09/2022 12:53						
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX						
XP Solutions						
Network 2020.1.3						
Free Flowing Outfall Details for SW R						
Outfall Pipe Number	Outfall Name	C. Level (m)	I. Level (m)	Min I. Level (m)	D, L (mm)	W (mm)
R.S1.012	R.S	22.500	21.636	0.000	0	0
©1982-2020 Innovyze						

O'Connor Sutton Cronin

9 Prussia Street
Dublin 7
Ireland

Date 27/09/2022 12:53
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX
XP Solutions

EMMET ROAD

Designed by EH
Checked by MK
Network 2020.1.3



Online Controls for SW R

Hydro-Brake® Optimum Manhole: R.S3, DS/PN: R.S1.006, Volume (m³): 6.7

Unit Reference MD-SHE-0052-1500-1500-1500

Design Head (m) 1.500

Design Flow (l/s) 1.5

Flush-Flow™

Objective Minimise upstream storage

Application Surface

Sump Available Yes

Diameter (mm) 52

Invert Level (m) 24.716

Calculated Minimum Outlet Pipe Diameter (mm) 75

Suggested Manhole Diameter (mm) 1200

Control Points

Head (m)

Flow (l/s)

Design Point (Calculated)

Flush-Flow™

Control Points

Head (m)

Flow (l/s)

Kick-Flow®

Mean Flow over Head Range

0.9

1.1

Depth (m)

Flow (l/s)

Depth (m)

Flow (l/s)

Depth (m)

Flow (l/s)

0.100

1.0

0.600

1.0

1.600

1.5

2.600

1.9

5.000

2.6

7.500

3.1

0.200

1.1

0.800

1.1

1.800

1.6

3.000

2.1

5.500

2.7

8.000

3.2

0.300

1.1

1.000

1.2

2.000

1.7

3.500

2.2

6.000

2.8

8.500

3.3

0.400

1.0

1.200

1.4

2.200

1.8

4.000

2.3

6.500

2.9

9.000

3.4

0.500

0.9

1.400

1.4

2.400

1.9

4.500

2.5

7.000

3.0

9.500

3.5

The hydrological calculations have been based on the Head/Discharge relationship for the Hydro-Brake® Optimum as specified. Should another type of control device other than a Hydro-Brake Optimum® be utilised then these storage routing calculations will be invalidated

©1982-2020 Innovyze

O'Connor Sutton Cronin		Page 31	
9 Prussia Street Dublin 7 Ireland	EMMET ROAD		
	Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX	Designed by EH Checked by MK	
	Network 2020.1.3		
XP Solutions			
<u>Orifice Manhole: R.SHW A2, DS/PN: R.S12.002, Volume (m³): 0.6</u>			
Diameter (m) 0.018 Discharge Coefficient 0.600 Invert Level (m) 24.160			
<u>Orifice Manhole: R.SHW A3, DS/PN: R.S12.004, Volume (m³): 0.8</u>			
Diameter (m) 0.022 Discharge Coefficient 0.600 Invert Level (m) 23.875			
<u>Complex Manhole: R.SHW 3, DS/PN: R.S15.002, Volume (m³): 0.4</u>			
<u>Orifice</u>			
Diameter (m) 0.023 Discharge Coefficient 0.600 Invert Level (m) 24.222			
<u>Orifice</u>			
Diameter (m) 0.021 Discharge Coefficient 0.600 Invert Level (m) 23.880			
<u>Orifice Manhole: R.SHW 4, DS/PN: R.S16.006, Volume (m³): 2.3</u>			
Diameter (m) 0.021 Discharge Coefficient 0.600 Invert Level (m) 24.000			
<u>Hydro-Brake® Optimum Manhole: R.S15, DS/PN: R.S6.007, Volume (m³): 2.4</u>			
Unit Reference MD-SHE-0104-6000-1750-6000 Flush-Flow™ Calculated			
Design Head (m) 1.750 Objective Minimise upstream storage			
Design Flow (l/s) 6.0 Application Surface			
©1982-2020 Innovyze			

O'Connor Sutton Cronin			Page 32		
9 Prussia Street Dublin 7 Ireland		EMMET ROAD			
Date 27/09/2022 12:53		Designed by EH			
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK			
XP Solutions		Network 2020.1.3			
Hydro-Brake® Optimum Manhole: R.S15, DS/PN: R.S6.007, Volume (m³): 2.4					
Sump Available		Yes	Minimum Outlet Pipe Diameter (mm)	150	
Diameter (mm)		104	Suggested Manhole Diameter (mm)	1200	
Invert Level (m)		23.370			
Control Points		Head (m)	Flow (l/s)	Control Points	Head (m) Flow (l/s)
Design Point (Calculated)		1.750	6.0	Kick-Flo®	0.926 4.5
Flush-Flow™		0.456	5.6	Mean Flow over Head Range	- 5.0
The hydrological calculations have been based on the Head/Discharge relationship for the Hydro-Brake® Optimum as specified. Should another type of control device other than a Hydro-Brake Optimum® be utilised then these storage routing calculations will be invalidated					
Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)
0.100	3.5	0.600	5.5	1.600	5.8
0.200	5.0	0.800	5.1	1.800	6.1
0.300	5.4	1.000	4.6	2.000	6.4
0.400	5.6	1.200	5.0	2.200	6.7
0.500	5.6	1.400	5.4	2.400	7.0
		2.600	7.2	5.000	9.8
		3.000	7.7	5.500	10.3
		3.500	8.3	6.000	10.7
		4.000	8.8	6.500	11.1
		4.500	9.4	7.000	11.5
Orifice Manhole: R.SHW B2, DS/PN: R.S23.003, Volume (m³): 0.5					
Diameter (m)		0.021	Discharge Coefficient	0.600	Invert Level (m) 23.776
Orifice Manhole: R.S94, DS/PN: R.S25.003, Volume (m³): 0.0					
Diameter (m)		0.021	Discharge Coefficient	0.600	Invert Level (m) 24.156
©1982-2020 Innovyze					

9 Prussia Street

Dublin 7

Ireland

Date 27/09/2022 12:53

File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX

Designed by EH

Checked by MK

Network 2020.1.3

Orifice Manhole: R.SHW B3, DS/PN: R.S31.004, Volume (m³): 0.5

Diameter (m)	0.021	Discharge Coefficient	0.600	Invert Level (m)	23.584
--------------	-------	-----------------------	-------	------------------	--------

Hydro-Brake® Optimum Manhole: R.S72, DS/PN: R.S23.006, Volume (m³): 2.7

Unit Reference MD-SHE-0098-5000-1500-5000

Design Head (m)

Design Flow (l/s)

Flush-Flo™

Objective

Application

Sump Available

89

Invert Level (m) 23.357

150
Diameter (mm)

Diameter (mm) 1200

Control Points	Head (m)	Flow (l/s)	Control Points	Head (m)	Flow (l/s)
Design Point (Calculated)	1.500	5.0	Kisk-Flo®	0.878	3.9
Flush-Flow™	0.431	4.9	Mean Flow over Head Range	-	4.3

The hydrological calculations have been based on the Head/Discharge relationship for the Hydro-Brake® Optimum as specified. Should another type of control device other than a Hydro-Brake Optimum® be utilised then these storage routing calculations will be invalidated

Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)
0.100	3.2	0.600	4.8	1.600	5.1	2.600	6.5	5.000	8.8	7.500	10.7				
0.200	4.4	0.800	4.3	1.800	5.4	3.000	6.9	5.500	9.2	8.000	11.0				
0.300	4.8	1.000	4.1	2.000	5.7	3.500	7.4	6.000	9.6	8.500	11.3				
0.400	4.9	1.200	4.5	2.200	6.0	4.000	7.9	6.500	10.0	9.000	11.6				
0.500	4.9	1.400	4.8	2.400	6.2	4.500	8.4	7.000	10.3	9.500	11.9				

O'Connor Sutton Cronin

9 Prussia Street
Dublin 7
Ireland

Date 27/09/2022 12:53
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX

XP Solutions

EMMET ROAD

Designed by EH
Checked by MK
Network 2020.1.3



Hydro-Brake® Optimum Manhole: R.S17, DS/PN: R.S6.010, Volume (m³): 4.8

Unit Reference MD-SHE-0124-9000-2000-9000

Design Head (m) 2.000

Design Flow (l/s) 9.0

Flush-Flow™

Objective Minimise upstream storage

Application Surface

Sump Available Yes

Diameter (mm) 124

Invert Level (m) 22.288

Calculated Minimum Outlet Pipe Diameter (mm) 150

Suggested Manhole Diameter (mm) 1200

Control Points

Head (m)

Flow (l/s)

Control Points

Head (m)

Flow (l/s)

Design Point (Calculated)

2.000

9.0

Kick-Flo®

1.108

6.8

Flush-Flow™

0.543

8.6

Mean Flow over Head Range

-

7.7

The hydrological calculations have been based on the Head/Discharge relationship for the Hydro-Brake® Optimum as specified. Should another type of control device other than a Hydro-Brake Optimum® be utilised then these storage routing calculations will be invalidated

Depth (m)

Flow (l/s)

Depth (m)

Flow (l/s)

Depth (m)

Flow (l/s)

Depth (m)

Flow (l/s)

Depth (m)

Flow (l/s)

0.100

4.4

0.600

8.6

1.600

8.1

2.600

10.2

5.000

13.9

7.500

16.9

0.200

7.4

0.800

8.3

1.800

8.6

3.000

10.9

5.500

14.5

8.000

17.4

0.300

8.1

1.000

7.6

2.000

9.0

3.500

11.7

6.000

15.2

8.500

17.9

0.400

8.5

1.200

7.1

2.200

9.4

4.000

12.5

6.500

15.7

9.000

18.4

0.500

8.6

1.400

7.6

2.400

9.8

4.500

13.2

7.000

16.3

9.500

18.9

©1982-2020 Innovyze

O'Connor Sutton Cronin		Page 35	
9 Prussia Street Dublin 7 Ireland		EMMET ROAD	
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Designed by EH Checked by MK	
XP Solutions		Network 2020.1.3	
Offline Controls for SW R			
Pipe Manhole: R.SOF1, DS/PN: R.S2.001, Loop to PN: R.S1.001			
Diameter (m)	0.150	Length (m)	5.000
Section Type	Pipe/Conduit	Roughness k (mm)	0.600
Slope (1:X)	60.0	Entry Loss Coefficient	0.500
		Coefficient of Contraction	0.600
		Upstream Invert Level (m)	26.200
Pipe Manhole: R.S4, DS/PN: R.S5.000, Loop to PN: R.S1.001			
Diameter (m)	0.225	Length (m)	2.000
Section Type	Pipe/Conduit	Roughness k (mm)	0.600
Slope (1:X)	80.0	Entry Loss Coefficient	0.500
		Coefficient of Contraction	0.600
		Upstream Invert Level (m)	26.250
Pipe Manhole: R.SHW A2, DS/PN: R.S12.002, Loop to PN: R.S6.005			
Diameter (m)	0.150	Length (m)	2.000
Section Type	Pipe/Conduit	Roughness k (mm)	0.600
Slope (1:X)	50.0	Entry Loss Coefficient	0.500
		Coefficient of Contraction	0.600
		Upstream Invert Level (m)	25.200
Pipe Manhole: R.SHW A3, DS/PN: R.S12.004, Loop to PN: R.S6.005			
Diameter (m)	0.150	Length (m)	2.000
Section Type	Pipe/Conduit	Roughness k (mm)	0.600
Slope (1:X)	40.0	Entry Loss Coefficient	0.500
		Coefficient of Contraction	0.600
		Upstream Invert Level (m)	25.200
©1982-2020 Innovyze			

O'Connor Sutton Cronin			Page 36																																																																																												
9 Prussia Street Dublin 7 Ireland		EMMET ROAD																																																																																													
Date 27/09/2022 12:53		Designed by EH																																																																																													
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK																																																																																													
XP Solutions		Network 2020.1.3																																																																																													
<u>Pipe Manhole: R.SHW 3, DS/PN: R.S15.002, Loop to PN: R.S6.006</u> <table><tr><td>Diameter (m)</td><td>0.150</td><td>Length (m)</td><td>2.000</td><td>Coefficient of Contraction</td><td>0.600</td></tr><tr><td>Section Type</td><td>Pipe/Conduit</td><td>Roughness k (mm)</td><td>0.600</td><td>Upstream Invert Level (m)</td><td>25.000</td></tr><tr><td>Slope (1:X)</td><td>100.0</td><td>Entry Loss Coefficient</td><td>0.500</td><td></td><td></td></tr></table> <u>Pipe Manhole: R.SHW 3, DS/PN: R.S15.002, Loop to PN: R.S6.005</u> <table><tr><td>Diameter (m)</td><td>0.150</td><td>Length (m)</td><td>5.000</td><td>Coefficient of Contraction</td><td>0.600</td></tr><tr><td>Section Type</td><td>Pipe/Conduit</td><td>Roughness k (mm)</td><td>0.600</td><td>Upstream Invert Level (m)</td><td>25.000</td></tr><tr><td>Slope (1:X)</td><td>40.0</td><td>Entry Loss Coefficient</td><td>0.500</td><td></td><td></td></tr></table> <u>Pipe Manhole: R.SHW A5, DS/PN: R.S16.002, Loop to PN: R.S6.005</u> <table><tr><td>Diameter (m)</td><td>0.150</td><td>Length (m)</td><td>5.000</td><td>Coefficient of Contraction</td><td>0.600</td></tr><tr><td>Section Type</td><td>Pipe/Conduit</td><td>Roughness k (mm)</td><td>0.600</td><td>Upstream Invert Level (m)</td><td>25.000</td></tr><tr><td>Slope (1:X)</td><td>100.0</td><td>Entry Loss Coefficient</td><td>0.500</td><td></td><td></td></tr></table> <u>Pipe Manhole: R.SHW 4, DS/PN: R.S16.006, Loop to PN: R.S6.005</u> <table><tr><td>Diameter (m)</td><td>0.300</td><td>Length (m)</td><td>2.000</td><td>Coefficient of Contraction</td><td>0.600</td></tr><tr><td>Section Type</td><td>Pipe/Conduit</td><td>Roughness k (mm)</td><td>0.600</td><td>Upstream Invert Level (m)</td><td>25.000</td></tr><tr><td>Slope (1:X)</td><td>100.0</td><td>Entry Loss Coefficient</td><td>0.500</td><td></td><td></td></tr></table> <u>Pipe Manhole: R.SHW B2, DS/PN: R.S23.003, Loop to PN: R.S30.000</u> <table><tr><td>Diameter (m)</td><td>0.150</td><td>Length (m)</td><td>2.000</td><td>Coefficient of Contraction</td><td>0.600</td></tr><tr><td>Section Type</td><td>Pipe/Conduit</td><td>Roughness k (mm)</td><td>0.600</td><td>Upstream Invert Level (m)</td><td>23.800</td></tr><tr><td>Slope (1:X)</td><td>400.0</td><td>Entry Loss Coefficient</td><td>0.500</td><td></td><td></td></tr></table>						Diameter (m)	0.150	Length (m)	2.000	Coefficient of Contraction	0.600	Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	25.000	Slope (1:X)	100.0	Entry Loss Coefficient	0.500			Diameter (m)	0.150	Length (m)	5.000	Coefficient of Contraction	0.600	Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	25.000	Slope (1:X)	40.0	Entry Loss Coefficient	0.500			Diameter (m)	0.150	Length (m)	5.000	Coefficient of Contraction	0.600	Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	25.000	Slope (1:X)	100.0	Entry Loss Coefficient	0.500			Diameter (m)	0.300	Length (m)	2.000	Coefficient of Contraction	0.600	Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	25.000	Slope (1:X)	100.0	Entry Loss Coefficient	0.500			Diameter (m)	0.150	Length (m)	2.000	Coefficient of Contraction	0.600	Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	23.800	Slope (1:X)	400.0	Entry Loss Coefficient	0.500		
Diameter (m)	0.150	Length (m)	2.000	Coefficient of Contraction	0.600																																																																																										
Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	25.000																																																																																										
Slope (1:X)	100.0	Entry Loss Coefficient	0.500																																																																																												
Diameter (m)	0.150	Length (m)	5.000	Coefficient of Contraction	0.600																																																																																										
Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	25.000																																																																																										
Slope (1:X)	40.0	Entry Loss Coefficient	0.500																																																																																												
Diameter (m)	0.150	Length (m)	5.000	Coefficient of Contraction	0.600																																																																																										
Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	25.000																																																																																										
Slope (1:X)	100.0	Entry Loss Coefficient	0.500																																																																																												
Diameter (m)	0.300	Length (m)	2.000	Coefficient of Contraction	0.600																																																																																										
Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	25.000																																																																																										
Slope (1:X)	100.0	Entry Loss Coefficient	0.500																																																																																												
Diameter (m)	0.150	Length (m)	2.000	Coefficient of Contraction	0.600																																																																																										
Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	23.800																																																																																										
Slope (1:X)	400.0	Entry Loss Coefficient	0.500																																																																																												
©1982-2020 Innovyze																																																																																															

O'Connor Sutton Cronin		Page 37																																																																																											
9 Prussia Street Dublin 7 Ireland	EMMET ROAD																																																																																												
	Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX	Designed by EH Checked by MK																																																																																											
	XP Solutions Network 2020.1.3																																																																																												
<u>Pipe Manhole: R.S94, DS/PN: R.S25.003, Loop to PN: R.S30.000</u> <table><tr><td>Diameter (m)</td><td>0.150</td><td>Length (m)</td><td>5.000</td><td>Coefficient of Contraction</td><td>0.600</td></tr><tr><td>Section Type</td><td>Pipe/Conduit</td><td>Roughness k (mm)</td><td>0.600</td><td>Upstream Invert Level (m)</td><td>24.800</td></tr><tr><td>Slope (1:X)</td><td>40.0</td><td>Entry Loss Coefficient</td><td>0.500</td><td></td><td></td></tr></table> <u>Pipe Manhole: R.SHW B3, DS/PN: R.S31.004, Loop to PN: R.S30.000</u> <table><tr><td>Diameter (m)</td><td>0.150</td><td>Length (m)</td><td>2.000</td><td>Coefficient of Contraction</td><td>0.600</td></tr><tr><td>Section Type</td><td>Pipe/Conduit</td><td>Roughness k (mm)</td><td>0.600</td><td>Upstream Invert Level (m)</td><td>24.750</td></tr><tr><td>Slope (1:X)</td><td>40.0</td><td>Entry Loss Coefficient</td><td>0.500</td><td></td><td></td></tr></table> <u>Pipe Manhole: R.S72, DS/PN: R.S23.006, Loop to PN: R.S6.008</u> <table><tr><td>Diameter (m)</td><td>0.225</td><td>Length (m)</td><td>5.000</td><td>Coefficient of Contraction</td><td>0.600</td></tr><tr><td>Section Type</td><td>Pipe/Conduit</td><td>Roughness k (mm)</td><td>0.600</td><td>Upstream Invert Level (m)</td><td>24.750</td></tr><tr><td>Slope (1:X)</td><td>40.0</td><td>Entry Loss Coefficient</td><td>0.500</td><td></td><td></td></tr></table> <u>Pipe Manhole: R.SHW B5, DS/PN: R.S34.005, Loop to PN: R.S6.009</u> <table><tr><td>Diameter (m)</td><td>0.150</td><td>Length (m)</td><td>2.000</td><td>Coefficient of Contraction</td><td>0.600</td></tr><tr><td>Section Type</td><td>Pipe/Conduit</td><td>Roughness k (mm)</td><td>0.600</td><td>Upstream Invert Level (m)</td><td>24.100</td></tr><tr><td>Slope (1:X)</td><td>20.0</td><td>Entry Loss Coefficient</td><td>0.500</td><td></td><td></td></tr></table> <u>Pipe Manhole: R.S94, DS/PN: R.S35.005, Loop to PN: R.S6.010</u> <table><tr><td>Diameter (m)</td><td>0.150</td><td>Length (m)</td><td>2.000</td><td>Coefficient of Contraction</td><td>0.600</td></tr><tr><td>Section Type</td><td>Pipe/Conduit</td><td>Roughness k (mm)</td><td>0.600</td><td>Upstream Invert Level (m)</td><td>24.200</td></tr><tr><td>Slope (1:X)</td><td>40.0</td><td>Entry Loss Coefficient</td><td>0.500</td><td></td><td></td></tr></table>				Diameter (m)	0.150	Length (m)	5.000	Coefficient of Contraction	0.600	Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	24.800	Slope (1:X)	40.0	Entry Loss Coefficient	0.500			Diameter (m)	0.150	Length (m)	2.000	Coefficient of Contraction	0.600	Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	24.750	Slope (1:X)	40.0	Entry Loss Coefficient	0.500			Diameter (m)	0.225	Length (m)	5.000	Coefficient of Contraction	0.600	Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	24.750	Slope (1:X)	40.0	Entry Loss Coefficient	0.500			Diameter (m)	0.150	Length (m)	2.000	Coefficient of Contraction	0.600	Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	24.100	Slope (1:X)	20.0	Entry Loss Coefficient	0.500			Diameter (m)	0.150	Length (m)	2.000	Coefficient of Contraction	0.600	Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	24.200	Slope (1:X)	40.0	Entry Loss Coefficient	0.500		
Diameter (m)	0.150	Length (m)		5.000	Coefficient of Contraction	0.600																																																																																							
Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	24.800																																																																																								
Slope (1:X)	40.0	Entry Loss Coefficient	0.500																																																																																										
Diameter (m)	0.150	Length (m)	2.000	Coefficient of Contraction	0.600																																																																																								
Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	24.750																																																																																								
Slope (1:X)	40.0	Entry Loss Coefficient	0.500																																																																																										
Diameter (m)	0.225	Length (m)	5.000	Coefficient of Contraction	0.600																																																																																								
Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	24.750																																																																																								
Slope (1:X)	40.0	Entry Loss Coefficient	0.500																																																																																										
Diameter (m)	0.150	Length (m)	2.000	Coefficient of Contraction	0.600																																																																																								
Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	24.100																																																																																								
Slope (1:X)	20.0	Entry Loss Coefficient	0.500																																																																																										
Diameter (m)	0.150	Length (m)	2.000	Coefficient of Contraction	0.600																																																																																								
Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	24.200																																																																																								
Slope (1:X)	40.0	Entry Loss Coefficient	0.500																																																																																										
©1982-2020 Innovyze																																																																																													

O'Connor Sutton Cronin		Page 38													
9 Prussia Street Dublin 7 Ireland		EMMET ROAD													
Date 27/09/2022 12:53		Designed by EH													
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK													
XP Solutions Network 2020.1.3															
Storage Structures for SW R															
<u>Infiltration Basin Manhole: R.SOF1, DS/PN: R.S2.001</u>															
Invert Level (m) 25.790 Infiltration Coefficient Side (m/hr) 0.00000 Porosity 1.00 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0															
<table><thead><tr><th>Depth (m)</th><th>Area (m²)</th><th>Depth (m)</th><th>Area (m²)</th><th>Depth (m)</th><th>Area (m²)</th></tr></thead><tbody><tr><td>0.000</td><td>25.0</td><td>0.450</td><td>58.0</td><td>0.451</td><td>0.0</td></tr></tbody></table>				Depth (m)	Area (m²)	Depth (m)	Area (m²)	Depth (m)	Area (m²)	0.000	25.0	0.450	58.0	0.451	0.0
Depth (m)	Area (m²)	Depth (m)	Area (m²)	Depth (m)	Area (m²)										
0.000	25.0	0.450	58.0	0.451	0.0										
<u>Infiltration Basin Manhole: R.S9, DS/PN: R.S4.001</u>															
Invert Level (m) 25.877 Infiltration Coefficient Side (m/hr) 0.00000 Porosity 1.00 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0															
<table><thead><tr><th>Depth (m)</th><th>Area (m²)</th><th>Depth (m)</th><th>Area (m²)</th><th>Depth (m)</th><th>Area (m²)</th></tr></thead><tbody><tr><td>0.000</td><td>12.0</td><td>0.450</td><td>28.0</td><td>0.451</td><td>0.0</td></tr></tbody></table>				Depth (m)	Area (m²)	Depth (m)	Area (m²)	Depth (m)	Area (m²)	0.000	12.0	0.450	28.0	0.451	0.0
Depth (m)	Area (m²)	Depth (m)	Area (m²)	Depth (m)	Area (m²)										
0.000	12.0	0.450	28.0	0.451	0.0										
<u>Complex Manhole: R.S4, DS/PN: R.S5.000</u>															
<u>Infiltration Blanket</u>															
Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 25.700 Cap Volume Depth (m) 0.400 Safety Factor 1.0 Diameter/Width (m) 8.0 Porosity 0.30 Length (m) 10.0															
©1982-2020 Innovyze															

O'Connor Sutton Cronin		Page 39																																				
9 Prussia Street Dublin 7 Ireland		EMMET ROAD																																				
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Designed by EH Checked by MK																																				
XP Solutions		Network 2020.1.3																																				
Bio-Retention Area																																						
Invert Level (m) 26.100 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 1.0 Porosity 1.00 Infiltration Coefficient Side (m/hr) 0.00000																																						
<table><tr><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th></tr><tr><td>0.000</td><td>53.0</td><td>54.000</td><td>0.450</td><td>93.0</td><td>72.000</td></tr><tr><td></td><td></td><td></td><td></td><td>0.451</td><td>0.0</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td>72.000</td></tr></table>				Depth (m)	Area (m²)	Perimeter (m)	Depth (m)	Area (m²)	Perimeter (m)	0.000	53.0	54.000	0.450	93.0	72.000					0.451	0.0						72.000											
Depth (m)	Area (m²)	Perimeter (m)	Depth (m)	Area (m²)	Perimeter (m)																																	
0.000	53.0	54.000	0.450	93.0	72.000																																	
				0.451	0.0																																	
					72.000																																	
Filter Drain Pipe: R.S1.001																																						
<table><tr><td colspan="2">Manning's N</td><td>0.045</td><td>Invert Level (m)</td><td>25.074</td><td colspan="2">Number of Pipes</td></tr><tr><td>Infiltration Coefficient Base (m/hr)</td><td>0.00000</td><td></td><td>Trench Width (m)</td><td>5.0</td><td>Slope (1:X)</td><td>251.3</td></tr><tr><td>Infiltration Coefficient Side (m/hr)</td><td>0.00000</td><td></td><td>Trench Length (m)</td><td>17.3</td><td>Cap Volume</td><td>Depth (m) 1.500</td></tr><tr><td>Safety Factor</td><td>1.0</td><td></td><td>Pipe Diameter (m)</td><td>0.150</td><td>Cap Infiltration</td><td>Depth (m) 0.000</td></tr><tr><td>Porosity</td><td>0.30</td><td></td><td>Pipe Depth above Invert (m)</td><td>0.250</td><td></td><td></td></tr></table>				Manning's N		0.045	Invert Level (m)	25.074	Number of Pipes		Infiltration Coefficient Base (m/hr)	0.00000		Trench Width (m)	5.0	Slope (1:X)	251.3	Infiltration Coefficient Side (m/hr)	0.00000		Trench Length (m)	17.3	Cap Volume	Depth (m) 1.500	Safety Factor	1.0		Pipe Diameter (m)	0.150	Cap Infiltration	Depth (m) 0.000	Porosity	0.30		Pipe Depth above Invert (m)	0.250		
Manning's N		0.045	Invert Level (m)	25.074	Number of Pipes																																	
Infiltration Coefficient Base (m/hr)	0.00000		Trench Width (m)	5.0	Slope (1:X)	251.3																																
Infiltration Coefficient Side (m/hr)	0.00000		Trench Length (m)	17.3	Cap Volume	Depth (m) 1.500																																
Safety Factor	1.0		Pipe Diameter (m)	0.150	Cap Infiltration	Depth (m) 0.000																																
Porosity	0.30		Pipe Depth above Invert (m)	0.250																																		
Filter Drain Pipe: R.S1.002																																						
<table><tr><td colspan="2">Manning's N</td><td>0.045</td><td>Invert Level (m)</td><td>25.005</td><td colspan="2">Number of Pipes</td></tr><tr><td>Infiltration Coefficient Base (m/hr)</td><td>0.00000</td><td></td><td>Trench Width (m)</td><td>0.5</td><td>Slope (1:X)</td><td>249.2</td></tr><tr><td>Infiltration Coefficient Side (m/hr)</td><td>0.00000</td><td></td><td>Trench Length (m)</td><td>17.4</td><td>Cap Volume</td><td>Depth (m) 1.500</td></tr><tr><td>Safety Factor</td><td>1.0</td><td></td><td>Pipe Diameter (m)</td><td>0.150</td><td>Cap Infiltration</td><td>Depth (m) 0.000</td></tr><tr><td>Porosity</td><td>0.30</td><td></td><td>Pipe Depth above Invert (m)</td><td>0.250</td><td></td><td></td></tr></table>				Manning's N		0.045	Invert Level (m)	25.005	Number of Pipes		Infiltration Coefficient Base (m/hr)	0.00000		Trench Width (m)	0.5	Slope (1:X)	249.2	Infiltration Coefficient Side (m/hr)	0.00000		Trench Length (m)	17.4	Cap Volume	Depth (m) 1.500	Safety Factor	1.0		Pipe Diameter (m)	0.150	Cap Infiltration	Depth (m) 0.000	Porosity	0.30		Pipe Depth above Invert (m)	0.250		
Manning's N		0.045	Invert Level (m)	25.005	Number of Pipes																																	
Infiltration Coefficient Base (m/hr)	0.00000		Trench Width (m)	0.5	Slope (1:X)	249.2																																
Infiltration Coefficient Side (m/hr)	0.00000		Trench Length (m)	17.4	Cap Volume	Depth (m) 1.500																																
Safety Factor	1.0		Pipe Diameter (m)	0.150	Cap Infiltration	Depth (m) 0.000																																
Porosity	0.30		Pipe Depth above Invert (m)	0.250																																		
Filter Drain Pipe: R.S1.003																																						
<table><tr><td colspan="2">Manning's N</td><td>0.045</td><td>Infiltration Coefficient Side (m/hr)</td><td>0.00000</td><td>Porosity</td><td>0.30</td></tr><tr><td>Infiltration Coefficient Base (m/hr)</td><td>0.00000</td><td></td><td>Safety Factor</td><td>1.0</td><td>Invert Level (m)</td><td>24.935</td></tr></table>				Manning's N		0.045	Infiltration Coefficient Side (m/hr)	0.00000	Porosity	0.30	Infiltration Coefficient Base (m/hr)	0.00000		Safety Factor	1.0	Invert Level (m)	24.935																					
Manning's N		0.045	Infiltration Coefficient Side (m/hr)	0.00000	Porosity	0.30																																
Infiltration Coefficient Base (m/hr)	0.00000		Safety Factor	1.0	Invert Level (m)	24.935																																
©1982-2020 Innovyze																																						

O'Connor Sutton Cronin		Page 40	
9 Prussia Street Dublin 7 Ireland		EMMET ROAD	
Date 27/09/2022 12:53		Designed by EH	
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK	
XP Solutions		Network 2020.1.3	
<u>Filter Drain Pipe: R.S1.003</u> Trench Width (m) 0.5 Pipe Depth above Invert (m) 0.250 Cap Volume Depth (m) 1.500 Trench Length (m) 17.5 Number of Pipes 1 Cap Infiltration Depth (m) 0.000 Pipe Diameter (m) 0.150 Slope (1:X) 249.5 <u>Filter Drain Pipe: R.S1.004</u> Manning's N 0.045 Invert Level (m) 24.865 Number of Pipes 1 Infiltration Coefficient Base (m/hr) 0.00000 Trench Width (m) 0.5 Slope (1:X) 249.8 Infiltration Coefficient Side (m/hr) 0.00000 Trench Length (m) 17.2 Cap Volume Depth (m) 1.500 Safety Factor 1.0 Pipe Diameter (m) 0.150 Cap Infiltration Depth (m) 0.000 Porosity 0.30 Pipe Depth above Invert (m) 0.250 <u>Filter Drain Pipe: R.S1.005</u> Manning's N 0.045 Invert Level (m) 24.796 Number of Pipes 1 Infiltration Coefficient Base (m/hr) 0.00000 Trench Width (m) 0.5 Slope (1:X) 249.2 Infiltration Coefficient Side (m/hr) 0.00000 Trench Length (m) 19.9 Cap Volume Depth (m) 1.500 Safety Factor 1.0 Pipe Diameter (m) 0.150 Cap Infiltration Depth (m) 0.000 Porosity 0.30 Pipe Depth above Invert (m) 0.250 <u>Porous Car Park Manhole: R.S3, DS/PN: R.S1.006</u> Infiltration Coefficient Base (m/hr) 0.00000 Porosity 0.30 Slope (1:X) 300.0 Membrane Percolation (mm/hr) 1000 Invert Level (m) 24.716 Depression Storage (mm) 5 Max Percolation (l/s) 125.0 Width (m) 5.0 Evaporation (mm/day) 1 Safety Factor 2.0 Length (m) 90.0 Cap Volume Depth (m) 1.500			
©1982-2020 Innovyze			



O'Connor Sutton Cronin		Page 41																															
9 Prussia Street Dublin 7 Ireland		EMMET ROAD																															
Date 27/09/2022 12:53		Designed by EH																															
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK																															
XP Solutions		Network 2020.1.3																															
Infiltration Basin Manhole: R.S14, DS/PN: R.S10.002 Invert Level (m) 24.772 Infiltration Coefficient Side (m/hr) 0.00000 Porosity 1.00 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0 <table><thead><tr><th>Depth (m)</th><th>Area (m²)</th><th>Depth (m)</th><th>Area (m²)</th><th>Depth (m)</th><th>Area (m²)</th></tr></thead><tbody><tr><td>0.000</td><td>120.0</td><td>0.500</td><td>180.0</td><td>0.501</td><td>0.0</td></tr></tbody></table> Complex Manhole: R.SHW A2, DS/PN: R.S12.002 Infiltration Blanket Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 24.160 Cap Volume Depth (m) 0.750 Safety Factor 2.0 Diameter/Width (m) 4.0 Porosity 0.30 Length (m) 41.0 Bio-Retention Area Invert Level (m) 24.910 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0 Porosity 1.00 Infiltration Coefficient Side (m/hr) 0.00000 <table><thead><tr><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th></tr></thead><tbody><tr><td>0.000</td><td>124.0</td><td>80.000</td><td>0.450</td><td>165.0</td><td>90.000</td></tr><tr><td></td><td></td><td></td><td>0.451</td><td>0.0</td><td>90.000</td></tr></tbody></table>				Depth (m)	Area (m ²)	Depth (m)	Area (m ²)	Depth (m)	Area (m ²)	0.000	120.0	0.500	180.0	0.501	0.0	Depth (m)	Area (m ²)	Perimeter (m)	Depth (m)	Area (m ²)	Perimeter (m)	0.000	124.0	80.000	0.450	165.0	90.000				0.451	0.0	90.000
Depth (m)	Area (m ²)	Depth (m)	Area (m ²)	Depth (m)	Area (m ²)																												
0.000	120.0	0.500	180.0	0.501	0.0																												
Depth (m)	Area (m ²)	Perimeter (m)	Depth (m)	Area (m ²)	Perimeter (m)																												
0.000	124.0	80.000	0.450	165.0	90.000																												
			0.451	0.0	90.000																												
©1982-2020 Innovyze																																	



O'Connor Sutton Cronin

9 Prussia Street
Dublin 7
Ireland

Date 27/09/2022 12:53
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX

XP Solutions

EMMET ROAD

Designed by EH
Checked by MK
Network 2020.1.3



Complex Manhole: R.SHW A3, DS/PN: R.S12.004

Infiltration Blanket

Infiltration Coefficient Base (m/hr) 0.00000

Invert Level (m) 23.875

Cap Volume Depth (m) 0.750

Safety Factor 2.0

Diameter/Width (m) 4.0

Porosity 0.30

Length (m) 9.5

Bio-Retention Area

Invert Level (m) 24.625

Infiltration Coefficient Base (m/hr) 0.00000

Safety Factor 2.0

Porosity 1.00

Infiltration Coefficient Side (m/hr) 0.00000

Depth (m)	Area (m ²)	Perimeter (m)	Depth (m)	Area (m ²)	Perimeter (m)	Depth (m)	Area (m ²)	Perimeter (m)
0.000	28.0	26.000	0.500	37.0	24.000	0.501	0.0	24.000

Infiltration Basin Manhole: R.S14, DS/PN: R.S6.006

Invert Level (m) 22.465

Infiltration Coefficient Side (m/hr) 0.00000

Safety Factor 2.0

Porosity 0.30

Depth (m)	Area (m ²)	Depth (m)	Area (m ²)	Depth (m)	Area (m ²)
0.000	400.0	1.250	400.0	1.251	0.0

©1982-2020 Innovyze

Page 42

O'Connor Sutton Cronin		Page 43	
9 Prussia Street Dublin 7 Ireland	EMMET ROAD		
	Designed by EH		
	Checked by MK		
Date 27/09/2022 12:53			
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX			
XP Solutions			
Network 2020.1.3			
Complex Manhole: R.SHW 3, DS/PN: R.S15.002			
Infiltration Blanket			
Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 24.222 Cap Volume Depth (m) 0.500			
Safety Factor 2.0 Diameter/Width (m) 6.0			
Porosity 0.30 Length (m) 11.0			
Bio-Retention Area			
Invert Level (m) 24.722 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0			
Porosity 1.00 Infiltration Coefficient Side (m/hr) 0.00000			
Depth (m) Area (m²) Perimeter (m) Depth (m) Area (m²) Perimeter (m)			
0.000 40.0 22.000 0.500 68.0 30.000 0.501 0.0 30.000			
Complex Manhole: R.SHW A5, DS/PN: R.S16.002			
Infiltration Blanket			
Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 25.221 Cap Volume Depth (m) 0.750			
Safety Factor 2.0 Diameter/Width (m) 6.0			
Porosity 0.30 Length (m) 30.0			
©1982-2020 Innovyze			

O'Connor Sutton Cronin		Page 44																																					
9 Prussia Street Dublin 7 Ireland		EMMET ROAD																																					
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Designed by EH Checked by MK																																					
XP Solutions		Network 2020.1.3																																					
Bio-Retention Area Invert Level (m) 25.971 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0 Porosity 1.00 Infiltration Coefficient Side (m/hr) 0.00000 <table><thead><tr><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th></tr></thead><tbody><tr><td>0.000</td><td>138.0</td><td>54.000</td><td>0.500</td><td>180.0</td><td>78.000</td></tr><tr><td></td><td></td><td></td><td>0.501</td><td>0.0</td><td>78.000</td></tr></tbody></table> Complex Manhole: R.SHW 4, DS/PN: R.S16.006 Infiltration Blanket Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 24.000 Cap Volume Depth (m) 0.750 Safety Factor 2.0 Diameter/Width (m) 8.0 Porosity 0.30 Length (m) 51.0 Bio-Retention Area Invert Level (m) 24.750 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0 Porosity 1.00 Infiltration Coefficient Side (m/hr) 0.00000 <table><thead><tr><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th></tr></thead><tbody><tr><td>0.000</td><td>340.0</td><td>70.000</td><td>0.500</td><td>410.0</td><td>120.000</td></tr><tr><td></td><td></td><td></td><td>0.501</td><td>0.0</td><td>120.000</td></tr></tbody></table>				Depth (m)	Area (m ²)	Perimeter (m)	Depth (m)	Area (m ²)	Perimeter (m)	0.000	138.0	54.000	0.500	180.0	78.000				0.501	0.0	78.000	Depth (m)	Area (m ²)	Perimeter (m)	Depth (m)	Area (m ²)	Perimeter (m)	0.000	340.0	70.000	0.500	410.0	120.000				0.501	0.0	120.000
Depth (m)	Area (m ²)	Perimeter (m)	Depth (m)	Area (m ²)	Perimeter (m)																																		
0.000	138.0	54.000	0.500	180.0	78.000																																		
			0.501	0.0	78.000																																		
Depth (m)	Area (m ²)	Perimeter (m)	Depth (m)	Area (m ²)	Perimeter (m)																																		
0.000	340.0	70.000	0.500	410.0	120.000																																		
			0.501	0.0	120.000																																		
©1982-2020 Innovyze																																							



O'Connor Sutton Cronin		Page 45	
9 Prussia Street Dublin 7 Ireland		EMMET ROAD	
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX XP Solutions		Designed by EH Checked by MK Network 2020.1.3	
Filter Drain Pipe: R.S21.000			
Manning's N	0.040	Invert Level (m)	25.250
Infiltration Coefficient Base (m/hr)	0.00000	Trench Width (m)	0.5
Infiltration Coefficient Side (m/hr)	0.00000	Trench Length (m)	13.1
Safety Factor	2.0	Pipe Diameter (m)	0.150
Porosity	0.30	Pipe Depth above Invert (m)	0.100
		Number of Pipes	1
		Slope (1:X)	56.8
		Cap Volume Depth (m)	1.500
		Cap Infiltration Depth (m)	0.000
Filter Drain Pipe: R.S21.002			
Manning's N	0.040	Invert Level (m)	24.978
Infiltration Coefficient Base (m/hr)	0.00000	Trench Width (m)	0.5
Infiltration Coefficient Side (m/hr)	0.00000	Trench Length (m)	9.6
Safety Factor	2.0	Pipe Diameter (m)	0.150
Porosity	0.30	Pipe Depth above Invert (m)	0.100
		Number of Pipes	1
		Slope (1:X)	95.6
		Cap Volume Depth (m)	1.500
		Cap Infiltration Depth (m)	0.000
Filter Drain Pipe: R.S21.004			
Manning's N	0.040	Invert Level (m)	24.818
Infiltration Coefficient Base (m/hr)	0.00000	Trench Width (m)	0.5
Infiltration Coefficient Side (m/hr)	0.00000	Trench Length (m)	9.8
Safety Factor	2.0	Pipe Diameter (m)	0.150
Porosity	0.30	Pipe Depth above Invert (m)	0.100
		Number of Pipes	1
		Slope (1:X)	97.7
		Cap Volume Depth (m)	1.500
		Cap Infiltration Depth (m)	0.000
Filter Drain Pipe: R.S21.006			
Manning's N	0.040	Safety Factor	2.0
Infiltration Coefficient Base (m/hr)	0.00000	Porosity	0.30
Infiltration Coefficient Side (m/hr)	0.00000	Invert Level (m)	24.660
		Trench Width (m)	0.5
		Trench Length (m)	9.9
		Pipe Diameter (m)	0.150
©1982-2020 Innovyze			

O'Connor Sutton Cronin		Page 46	
9 Prussia Street Dublin 7 Ireland		EMMET ROAD	
Date 27/09/2022 12:53		Designed by EH	
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK	
XP Solutions		Network 2020.1.3	
Filter Drain Pipe: R.S21.006 Pipe Depth above Invert (m) 0.100 Slope (1:X) 39.8 Cap Infiltration Depth (m) 0.000 Number of Pipes 1 Cap Volume Depth (m) 1.500 Manning's N 0.040 Invert Level (m) 24.350 Number of Pipes 1 Infiltration Coefficient Base (m/hr) 0.00000 Trench Width (m) 0.5 Slope (1:X) 53.7 Infiltration Coefficient Side (m/hr) 0.00000 Trench Length (m) 7.0 Cap Volume Depth (m) 1.000 Safety Factor 2.0 Pipe Diameter (m) 0.150 Cap Infiltration Depth (m) 0.000 Porosity 0.30 Pipe Depth above Invert (m) 0.500 Filter Drain Pipe: R.S21.008 Infiltration Blanket Manhole: R.S58, DS/PN: R.S21.009 Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 24.280 Cap Volume Depth (m) 0.800 Safety Factor 2.0 Diameter/Width (m) 0.5 Porosity 0.30 Length (m) 50.0 Filter Drain Pipe: R.S22.000 Manning's N 0.040 Invert Level (m) 25.500 Number of Pipes 1 Infiltration Coefficient Base (m/hr) 0.00000 Trench Width (m) 0.5 Slope (1:X) 99.8 Infiltration Coefficient Side (m/hr) 0.00000 Trench Length (m) 9.1 Cap Volume Depth (m) 1.000 Safety Factor 2.0 Pipe Diameter (m) 0.150 Cap Infiltration Depth (m) 0.000 Porosity 0.30 Pipe Depth above Invert (m) 0.100			
©1982-2020 Innovyze			

O'Connor Sutton Cronin		Page 47			
9 Prussia Street Dublin 7 Ireland		EMMET ROAD			
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX XP Solutions		Designed by EH Checked by MK Network 2020.1.3			
Micro Drainage					
Filter Drain Pipe: R.S22.002					
Manning's N	0.040	Invert Level (m)	25.358	Number of Pipes	1
Infiltration Coefficient Base (m/hr)	0.00000	Trench Width (m)	0.5	Slope (1:X)	100.0
Infiltration Coefficient Side (m/hr)	0.00000	Trench Length (m)	9.7	Cap Volume Depth (m)	1.000
Safety Factor	2.0	Pipe Diameter (m)	0.150	Cap Infiltration Depth (m)	0.000
Porosity	0.30	Pipe Depth above Invert (m)	0.100		
Filter Drain Pipe: R.S22.004					
Manning's N	0.040	Invert Level (m)	25.216	Number of Pipes	1
Infiltration Coefficient Base (m/hr)	0.00000	Trench Width (m)	0.5	Slope (1:X)	100.0
Infiltration Coefficient Side (m/hr)	0.00000	Trench Length (m)	12.3	Cap Volume Depth (m)	1.000
Safety Factor	2.0	Pipe Diameter (m)	0.150	Cap Infiltration Depth (m)	0.000
Porosity	0.30	Pipe Depth above Invert (m)	0.100		
Filter Drain Pipe: R.S22.006					
Manning's N	0.040	Invert Level (m)	25.056	Number of Pipes	1
Infiltration Coefficient Base (m/hr)	0.00000	Trench Width (m)	0.5	Slope (1:X)	58.0
Infiltration Coefficient Side (m/hr)	0.00000	Trench Length (m)	9.9	Cap Volume Depth (m)	0.600
Safety Factor	2.0	Pipe Diameter (m)	0.150	Cap Infiltration Depth (m)	0.000
Porosity	0.30	Pipe Depth above Invert (m)	0.100		
Infiltration Blanket Manhole: R.S66, DS/PN: R.S22.007					
Infiltration Coefficient Base (m/hr)	0.00000	Invert Level (m)	24.886	Cap Volume Depth (m)	1.000
Safety Factor	2.0	Diameter/Width (m)	1.0		
Porosity	0.30	Length (m)	50.0		
©1982-2020 Innovyze					

O'Connor Sutton Cronin		Page 48	
9 Prussia Street Dublin 7 Ireland	EMMET ROAD		
	Designed by EH		
	Checked by MK		
Date 27/09/2022 12:53			
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX			
XP Solutions		Network 2020.1.3	
Complex Manhole: R.SHW B2, DS/PN: R.S23.003			
Infiltration Blanket			
Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 23.776 Cap Volume Depth (m) 0.500			
Safety Factor 2.0 Diameter/Width (m) 4.0			
Porosity 0.30 Length (m) 25.0			
Bio-Retention Area			
Invert Level (m) 24.276 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0			
Porosity 1.00 Infiltration Coefficient Side (m/hr) 0.00000			
Depth (m) Area (m²) Perimeter (m) Depth (m) Area (m²) Perimeter (m)			
0.000 78.0 45.000 0.500 98.0 60.000 0.501 0.0 60.000			
Complex Manhole: R.SHW B1, DS/PN: R.S25.002			
Infiltration Blanket			
Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 24.337 Cap Volume Depth (m) 0.700			
Safety Factor 2.0 Diameter/Width (m) 4.0			
Porosity 0.30 Length (m) 34.0			
©1982-2020 Innovyze			

O'Connor Sutton Cronin		Page 49																															
9 Prussia Street Dublin 7 Ireland		EMMET ROAD																															
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Designed by EH Checked by MK																															
XP Solutions		Network 2020.1.3																															
Bio-Retention Area Invert Level (m) 25.037 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0 Porosity 1.00 Infiltration Coefficient Side (m/hr) 0.00000 <table><thead><tr><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th></tr></thead><tbody><tr><td>0.000</td><td>112.0</td><td>68.000</td><td>0.500</td><td>135.0</td><td>80.000</td></tr><tr><td></td><td></td><td></td><td>0.501</td><td>0.0</td><td>80.000</td></tr></tbody></table> Infiltration Basin Manhole: R.S71, DS/PN: R.S23.005 Invert Level (m) 23.460 Infiltration Coefficient Side (m/hr) 0.00000 Porosity 0.40 Infiltration Coefficient Base (m/hr) 0.00000 <table><thead><tr><th>Depth (m)</th><th>Area (m²)</th><th>Depth (m)</th><th>Area (m²)</th></tr></thead><tbody><tr><td>0.000</td><td>165.0</td><td>1.200</td><td>165.0</td></tr><tr><td></td><td></td><td>1.210</td><td>0.0</td></tr></tbody></table> Complex Manhole: R.SHW B3, DS/PN: R.S31.004 Infiltration Blanket Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 23.584 Cap Volume Depth (m) 0.500 Safety Factor 2.0 Diameter/Width (m) 4.0 Porosity 0.30 Length (m) 25.0				Depth (m)	Area (m ²)	Perimeter (m)	Depth (m)	Area (m ²)	Perimeter (m)	0.000	112.0	68.000	0.500	135.0	80.000				0.501	0.0	80.000	Depth (m)	Area (m ²)	Depth (m)	Area (m ²)	0.000	165.0	1.200	165.0			1.210	0.0
Depth (m)	Area (m ²)	Perimeter (m)	Depth (m)	Area (m ²)	Perimeter (m)																												
0.000	112.0	68.000	0.500	135.0	80.000																												
			0.501	0.0	80.000																												
Depth (m)	Area (m ²)	Depth (m)	Area (m ²)																														
0.000	165.0	1.200	165.0																														
		1.210	0.0																														
©1982-2020 Innovyze																																	



O'Connor Sutton Cronin

9 Prussia Street
Dublin 7
Ireland

Date 27/09/2022 12:53
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX

XP Solutions

EMMET ROAD

Designed by EH
Checked by MK
Network 2020.1.3



Invert Level (m) 24.084
Porosity 1.00

Infiltration Coefficient Base (m/hr) 0.00000
Infiltration Coefficient Side (m/hr) 0.00000

Depth (m) Area (m²) Perimeter (m)

Depth (m) Area (m²) Perimeter (m)

Depth (m) Area (m²) Perimeter (m)

0.00075.045.000

0.50098.060.000

0.5010.060.000

Complex Manhole: R.S93, DS/PN: R.S34.004

Infiltration Blanket

Infiltration Coefficient Base (m/hr) 0.00000
Safety Factor 2.0
Porosity 0.30

Invert Level (m) 23.404
Diameter/Width (m) 3.0
Length (m) 30.0

Cap Volume Depth (m) 0.500

Bio-Retention Area

Invert Level (m) 23.904
Porosity 1.00

Infiltration Coefficient Base (m/hr) 0.00000
Infiltration Coefficient Side (m/hr) 0.00000

Depth (m) Area (m²) Perimeter (m)

Depth (m) Area (m²) Perimeter (m)

Depth (m) Area (m²) Perimeter (m)

0.00075.045.000

0.50090.066.000

0.5010.066.000

©1982-2020 Innovyze

O'Connor Sutton Cronin		Page 51	
9 Prussia Street Dublin 7 Ireland	EMMET ROAD		
	Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX	Designed by EH Checked by MK	
XP Solutions			
Network 2020.1.3			
Complex Manhole: R.SHW B4, DS/PN: R.S35.004			
Infiltration Blanket			
Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 23.003 Cap Volume Depth (m) 0.750 Safety Factor 2.0 Diameter/Width (m) 2.0 Porosity 0.30 Length (m) 30.0			
Bio-Retention Area			
Invert Level (m) 23.753 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0 Porosity 1.00 Infiltration Coefficient Side (m/hr) 0.00000			
Depth (m) Area (m²) Perimeter (m) Depth (m) Area (m²) Perimeter (m)			
0.000 50.0 25.000 0.500 68.0 42.000 0.501 0.0 42.000			
Cellular Storage Manhole: R.S17, DS/PN: R.S6.010			
Invert Level (m) 22.288 Infiltration Coefficient Side (m/hr) 0.00000 Porosity 0.95 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0			
Depth (m) Area (m²) Inf. Area (m²) Depth (m) Area (m²) Inf. Area (m²)			
0.000 420.0 0.0 1.200 420.0 0.0 1.201 0.0 0.0			
©1982-2020 Innovyze			

O'Connor Sutton Cronin		Page 52	
9 Prussia Street Dublin 7 Ireland		EMMET ROAD	
Date 27/09/2022 12:53		Designed by EH	
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK	
XP Solutions		Network 2020.1.3	
Summary of Critical Results by Maximum Level (Rank 1) for SW R			
Simulation Criteria			
Areal Reduction Factor 1.000		Manhole Headloss Coeff (Global) 0.500	
Hot Start (mins) 0		Foul Sewage per hectare (l/s) 0.000	
Hot Start Level (mm) 0		Additional Flow - % of Total Flow 0.000	
Number of Input Hydrographs 0		Number of Offline Controls 14	
Number of Online Controls 11		Number of Storage Structures 34	
Number of Time/Area Diagrams 19		Number of Real Time Controls 0	
Synthetic Rainfall Details			
Rainfall Model		FSR M5-60 (mm) 16.500	
Region Scotland and Ireland		Ratio R 0.277	
Cv (Summer) 1.000		Cv (Winter) 1.000	
Margin for Flood Risk Warning (mm)		300.0	
Analysis Timestep 2.5 Second		Increment (Extended) DVD Status OFF	
DTS Status		ON	
Profile(s)			
Duration(s) (mins)		15, 30, 60, 120, 180, 240, 360, 480, 600, 720, 960, 1440, 2160, 2880, 4320, 5760, 7200, 8640, 10080	
Return Period(s) (years)		100	
Climate Change (%)		20	
US/MH		US/CL	
Name		Level (m)	
Event		Depth (m)	
Water Surcharged		Flow / Flow	
PN		Cap. (l/s)	
Status		Status	
R.S1.000		R.S1	
15 minute		100 year	
Summer I+20%		27.400	
26.211		0.061	
1.17		19.4	
SURCHARGED			
©1982-2020 Innovyze			

O'Connor Sutton Cronin			Page 56				
9 Prussia Street Dublin 7 Ireland		EMMET ROAD					
Date 27/09/2022 12:53							
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX							
XP Solutions							
Designed by EH							
Checked by MK							
Network 2020.1.3							
Summary of Critical Results by Maximum Level (Rank 1) for SW R							
PN	US/MH Name	Event	US/CL (m)	Water Level (m)	Surcharged Depth (m)	Pipe Flow / Cap. (l/s)	Status
R.S22.005	R.S64	15 minute 100 year Summer	I+20% 25.770	25.369	0.126	1.46 17.6	SURCHARGED
R.S22.006	R.S65	15 minute 100 year Summer	I+20% 25.670	25.289	-0.367	0.44 19.0	OK
R.S22.007	R.S66	30 minute 100 year Summer	I+20% 25.490	25.269	0.308	2.53 6.5	FLOOD RISK
R.S23.000	R.SR C1	960 minute 100 year Summer	I+20% 25.150	24.858	0.158	0.08 1.9	FLOOD RISK
R.S23.001	R.S68	15 minute 100 year Summer	I+20% 25.000	24.550	0.500	0.99 17.2	SURCHARGED*
R.S24.000	R.SR C2	720 minute 100 year Summer	I+20% 25.000	24.856	0.306	0.12 2.1	FLOOD RISK
R.S23.002	R.S69	15 minute 100 year Summer	I+20% 25.000	24.473	0.500	2.33 31.6	SURCHARGED*
R.S23.003	R.SHW B2	960 minute 100 year Summer	I+20% 25.000	24.916	1.065	0.30 0.7	FLOOD RISK
R.S23.004	R.S86	2880 minute 100 year Winter	I+20% 25.000	23.817	0.000	0.02 0.7	SURCHARGED*
R.S25.000	R.SGR C4	60 minute 100 year Summer	I+20% 26.000	25.461	-0.089	0.35 5.4	OK
R.S25.001	R.S81	360 minute 100 year Summer	I+20% 26.000	25.143	0.493	0.33 4.2	SURCHARGED*
R.S26.000	R.SGR C6	360 minute 100 year Summer	I+20% 25.400	25.167	0.117	0.29 4.5	FLOOD RISK
R.S26.001	R.S82	600 minute 100 year Winter	I+20% 25.500	24.990	0.340	0.18 3.2	SURCHARGED*
R.S27.000	R.SGR C5	60 minute 100 year Summer	I+20% 25.900	25.375	-0.075	0.49 7.1	OK
R.S26.002	R.S83	360 minute 100 year Summer	I+20% 25.750	25.151	0.608	0.70 10.3	SURCHARGED*
R.S25.002	R.SHW B1	360 minute 100 year Summer	I+20% 26.000	25.140	0.728	2.97 7.8	SURCHARGED
R.S25.003	R.S94	15 minute 100 year Summer	I+20% 25.875	24.381	0.000	0.02 0.7	SURCHARGED*
R.S28.000	R.SGR C2	60 minute 100 year Summer	I+20% 25.750	25.106	-0.094	0.30 3.3	OK
R.S28.001	R.S109	30 minute 100 year Summer	I+20% 25.750	25.092	-0.079	0.41 6.6	OK
R.S25.004	R.S83	960 minute 100 year Summer	I+20% 25.750	24.823	0.543	0.08 2.6	SURCHARGED
R.S29.000	R.SGR C1	60 minute 100 year Summer	I+20% 25.500	24.956	-0.094	0.30 3.3	OK
R.S29.001	R.S80	30 minute 100 year Summer	I+20% 25.500	24.936	-0.085	0.35 5.5	OK
R.S25.005	R.S84	960 minute 100 year Summer	I+20% 25.750	24.823	0.593	0.05 4.2	SURCHARGED
R.S30.000	R.S78	720 minute 100 year Summer	I+20% 25.500	24.956	0.456	0.96 16.2	SURCHARGED
R.S23.005	R.S71	720 minute 100 year Summer	I+20% 25.000	24.822	1.137	0.26 11.4	FLOOD RISK
©1982-2020 Innovyze							

O'Connor Sutton Cronin			Page 58		
9 Prussia Street Dublin 7 Ireland		EMMET ROAD			
		Designed by EH Checked by MK			
Date 27/09/2022 12:53		Network 2020.1.3			
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX					
XP Solutions					
Summary of Critical Results by Maximum Level (Rank 1) for SW R					
PN	US/MH Name	Event	US/CL (m)	Water Surcharged Level (m)	Pipe Flow / Cap. (l/s) Status
R.S1.011	R.S8 600 minute	100 year Winter I+20%	24.250	22.098	0.19 9.9 OK
R.S1.012	R.S9 600 minute	100 year Winter I+20%	23.400	21.906	0.19 9.9 OK
©1982-2020 Innovyze					

O'Connor Sutton Cronin			Page 1									
9 Prussia Street Dublin 7 Ireland		EMMET ROAD										
		Designed by EH Checked by MK Network 2020.1.3										
Date 27/09/2022 12:53												
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX												
XP Solutions												
STORM SEWER DESIGN by the Modified Rational Method												
Design Criteria for SW C												
Pipe Sizes IW Manhole Sizes IW												
FSR Rainfall Model – Scotland and Ireland												
Return Period (years)		5	Foul Sewage (l/s/ha)		0.000							
M5-60 (mm)		16.500	Volumetric Runoff Coeff.		0.750							
Ratio R		0.277	PIMP (%)		100							
Maximum Rainfall (mm/hr)		50	Add Flow / Climate Change (%)		20							
Maximum Time of Concentration (mins)		30	Minimum Backdrop Height (m)		0.000							
			Maximum Backdrop Height (m)		1.500							
			Min Design Depth for Optimisation (m)		0.750							
			Min Vel for Auto Design only (m/s)		1.00							
			Min Slope for Optimisation (1:X)		500							
Designed with Level Soffits												
Network Design Table for SW C												
PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	n	HYD SECT	DIA (mm)	Section Type	Auto Design
SW C1.000	33.854	0.282	120.0	0.026	5.00	0.0	0.600	o	225	Pipe/Conduit		
Network Results Table												
PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	E I.Area (ha)	E Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)		
SW C1.000	50.00	5.47	23.100	0.026	0.0	0.0	0.0	0.7	1.19	47.4	4.2	
©1982-2020 Innovyze												

O'Connor Sutton Cronin			Page 5									
9 Prussia Street Dublin 7 Ireland			EMMET ROAD									
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX XP Solutions			Designed by EH Checked by MK Network 2020.1.3									
												
Network Design Table for SW C												
PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k	n	HYD SECT	DIA (mm)	Section Type	Auto Design
SW C7.000	2.046	0.020	102.3	0.011	5.00	0.0	0.600	o	150	Pipe/Conduit		
SW C7.001	2.046	0.020	100.1	0.000	0.00	0.0	0.600	o	150	Pipe/Conduit		
SW C1.005	9.366	0.056	166.6	0.000	0.00	0.0	0.600	o	225	Pipe/Conduit		
SW C8.000	27.878	0.278	100.1	0.037	5.00	0.0	0.600	o	150	Pipe/Conduit		
SW C1.006	33.387	0.200	166.6	0.000	0.00	0.0	0.600	o	225	Pipe/Conduit		
SW C9.000	1.640	0.016	100.0	0.016	5.00	0.0	0.600	o	150	Pipe/Conduit		
Network Results Table												
PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap Flow (l/s)	Flow (l/s)		
SW C7.000	50.00	5.03	23.000	0.011	0.0	0.0	0.3	0.99	17.6	1.8		
SW C7.001	50.00	5.07	22.980	0.011	0.0	0.0	0.3	1.00	17.7	1.8		
SW C1.005	46.49	9.93	22.507	0.178	0.0	0.0	4.5	1.01	40.2	27.0		
SW C8.000	50.00	5.46	23.100	0.037	0.0	0.0	1.0	1.00	17.7	6.0		
SW C1.006	45.31	10.48	22.451	0.216	0.0	0.0	5.3	1.01	40.2	31.8		
SW C9.000	50.00	5.03	22.650	0.016	0.0	0.0	0.4	1.00	17.8	2.7		
©1982-2020 Innovyze												

9 Prussia Street
Dublin 7
Ireland

EMMET ROAD



Date 27/09/2022 12:53

Designed by EH

File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX

Checked by MK

XP Solutions

Network 2020.1.3

Network Design Table for SW C

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	n	HYD SECT	DIA (mm)	Section Type	Auto Design
SW C1.008	7.604	0.527	14.4	0.000	0.00	0.0	0.600		o	225	Pipe/Conduit	👉
SW C1.009	10.573	0.044	240.0	0.011	0.00	0.0	0.600		o	300	Pipe/Conduit	👉
SW C1.010	9.023	0.038	240.0	0.000	0.00	0.0	0.600		o	300	Pipe/Conduit	👉
SW C1.011	21.839	0.118	184.5	0.000	0.00	0.0	0.600		o	300	Pipe/Conduit	👉
SW C1.012	7.981	0.033	240.0	0.000	0.00	0.0	0.600		o	300	Pipe/Conduit	👉

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
SW C1.008	44.88	10.69	21.419	0.395	0.0	0.0	9.6	3.46	137.7	57.6
SW C1.009	44.53	10.86	20.817	0.406	0.0	0.0	9.8	1.01	71.4	58.7
SW C1.010	44.24	11.01	20.773	0.406	0.0	0.0	9.8	1.01	71.4	58.7
SW C1.011	43.63	11.33	20.736	0.406	0.0	0.0	9.8	1.15	81.6	58.7
SW C1.012	43.39	11.46	20.617	0.406	0.0	0.0	9.8	1.01	71.4	58.7

O'Connor Sutton Cronin			Page 9			
9 Prussia Street Dublin 7 Ireland		EMMET ROAD				
Date 27/09/2022 12:53		Designed by EH				
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK				
XP Solutions		Network 2020.1.3				
Area Summary for SW C						
Pipe Number	PIMP Type	PIMP Name	PIMP (%)	Gross Area (ha)	Imp. Area (ha)	Pipe Total (ha)
1.000	As Zoned	Default	90	0.028	0.025	0.025
		Roof (Std)	95	0.000	0.000	0.025
		Bioretention / Planted	30	0.002	0.001	0.026
2.000	As Zoned	Default	90	0.031	0.028	0.028
		Bioretention / Planted	30	0.010	0.003	0.031
		Grass (Lawn)	15	0.000	0.000	0.031
1.001	-	-	100	0.000	0.000	0.000
3.000	As Zoned	Default	90	0.012	0.011	0.011
		Pervious Paving	70	0.009	0.006	0.017
		Bioretention / Planted	30	0.006	0.002	0.019
3.001	As Zoned	Default	90	0.009	0.008	0.008
		Pervious Paving	70	0.008	0.006	0.013
		Bioretention / Planted	30	0.003	0.001	0.014
3.002	As Zoned	Default	90	0.009	0.008	0.008
		Pervious Paving	70	0.000	0.000	0.008
		Bioretention / Planted	30	0.003	0.001	0.009
3.003	As Zoned	Default	90	0.013	0.012	0.012
		Pervious Paving	70	0.008	0.006	0.018
		Bioretention / Planted	30	0.001	0.000	0.018
4.000	As Zoned	Default	90	0.008	0.007	0.007
		Bioretention / Planted	30	0.009	0.003	0.010
4.001	As Zoned	Default	90	0.008	0.007	0.007
		Bioretention / Planted	30	0.000	0.000	0.007
4.002	As Zoned	Default	90	0.004	0.004	0.004
		Roof (Std)	95	0.000	0.000	0.004
		Bioretention / Planted	30	0.003	0.001	0.005
4.003	As Zoned	Default	90	0.006	0.005	0.005
©1982-2020 Innovyze						

O'Connor Sutton Cronin			Page 10			
9 Prussia Street Dublin 7 Ireland		EMMET ROAD				
Date 27/09/2022 12:53		Designed by EH				
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK				
XP Solutions		Network 2020.1.3				
Area Summary for SW C						
Pipe Number	PIMP Type	PIMP Name	PIMP (%)	Gross Area (ha)	Imp. Area (ha)	Pipe Total (ha)
4.004	-	-	100	0.000	0.000	0.000
3.004	-	-	100	0.000	0.000	0.000
1.002	-	-	100	0.000	0.000	0.000
5.000	As Zoned	Default	90	0.010	0.009	0.009
		Bioretention / Planted	30	0.003	0.001	0.010
5.001	-	-	100	0.000	0.000	0.000
1.003	-	-	100	0.000	0.000	0.000
6.000	As Zoned	Default	90	0.013	0.012	0.012
		Bioretention / Planted	30	0.003	0.001	0.013
6.001	-	-	100	0.000	0.000	0.000
1.004	-	-	100	0.000	0.000	0.000
7.000	As Zoned	Default	90	0.010	0.009	0.009
		Bioretention / Planted	30	0.005	0.002	0.011
7.001	-	-	100	0.000	0.000	0.000
1.005	-	-	100	0.000	0.000	0.000
8.000	As Zoned	Default	90	0.039	0.035	0.035
		Bioretention / Planted	30	0.007	0.002	0.037
1.006	-	-	100	0.000	0.000	0.000
9.000	As Zoned	Default	90	0.015	0.014	0.014
		Bioretention / Planted	30	0.008	0.003	0.016
9.001	-	-	100	0.000	0.000	0.000
1.007	As Zoned	Default	90	0.036	0.032	0.032
10.000	As Zoned	Default	90	0.004	0.003	0.003
		Roof (Std)	95	0.000	0.000	0.003
		Bioretention / Planted	30	0.002	0.001	0.004
10.001	-	-	100	0.000	0.000	0.000
11.000	As Zoned	Default	90	0.033	0.030	0.030
©1982-2020 Innovyze						

O'Connor Sutton Cronin			Page 11			
9 Prussia Street Dublin 7 Ireland		EMMET ROAD				
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Designed by EH Checked by MK				
XP Solutions		Network 2020.1.3				
Area Summary for SW C						
Pipe Number	PIMP Type	PIMP Name	PIMP (%)	Gross Area (ha)	Imp. Area (ha)	Pipe Total (ha)
Roof (Std)						
		Bioretention / Planted	95	0.000	0.000	0.030
11.001	-		30	0.004	0.001	0.031
10.002	-		100	0.000	0.000	0.000
12.000	As Zoned		100	0.000	0.000	0.000
		Default	90	0.051	0.046	0.046
Roof (Std)						
		Bioretention / Planted	95	0.000	0.000	0.046
			30	0.000	0.000	0.046
		Tree SuDS Pit	50	0.005	0.003	0.048
12.001	-		100	0.000	0.000	0.000
10.003	-		100	0.000	0.000	0.000
13.000	As Zoned		90	0.052	0.047	0.047
13.001	-		100	0.000	0.000	0.000
1.008	-		100	0.000	0.000	0.000
1.009	As Zoned		90	0.009	0.008	0.008
		Default	30	0.012	0.004	0.011
Bioretention / Planted						
1.010	-		100	0.000	0.000	0.000
1.011	-		100	0.000	0.000	0.000
1.012	-		100	0.000	0.000	0.000
		Total		0.514	0.406	0.406
						Total
						0.406

O'Connor Sutton Cronin		Page 12		
9 Prussia Street Dublin 7 Ireland Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX XP Solutions	EMMET ROAD			
	Designed by EH			
	Checked by MK			
Network 2020.1.3				
Free Flowing Outfall Details for SW C				
Outfall Pipe Number	Outfall C. Level (m)	I. Level (m)	D, L I. Level (mm) (m)	W (mm)
SW C1.012	SW C 22.300	20.584	0.000	0
©1982-2020 Innovyze				

O'Connor Sutton Cronin		Page 13	
9 Prussia Street Dublin 7 Ireland	EMMET ROAD		
	Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX XP Solutions	Designed by EH Checked by MK Network 2020.1.3	
Online Controls for SW C			
<u>Orifice Manhole: SW C11, DS/PN: SW C4.004, Volume (m³): 1.7</u>			
Diameter (m) 0.021 Discharge Coefficient 0.600 Invert Level (m) 23.661			
<u>Orifice Manhole: SW C7, DS/PN: SW C3.004, Volume (m³): 2.9</u>			
Diameter (m) 0.031 Discharge Coefficient 0.600 Invert Level (m) 23.274			
<u>Orifice Manhole: SW C16, DS/PN: SW C5.001, Volume (m³): 0.5</u>			
Diameter (m) 0.015 Discharge Coefficient 0.600 Invert Level (m) 23.136			
<u>Orifice Manhole: SW C18, DS/PN: SW C6.001, Volume (m³): 0.3</u>			
Diameter (m) 0.015 Discharge Coefficient 0.600 Invert Level (m) 23.383			
<u>Orifice Manhole: SW C22, DS/PN: SW C7.001, Volume (m³): 0.5</u>			
Diameter (m) 0.015 Discharge Coefficient 0.600 Invert Level (m) 22.980			
<u>Orifice Manhole: SW C27, DS/PN: SW C9.001, Volume (m³): 0.5</u>			
Diameter (m) 0.015 Discharge Coefficient 0.600 Invert Level (m) 22.634			
©1982-2020 Innovyze			

9 Prussia Street

Dublin 7

Ireland

Date 27/09/2022 12:53

File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX

XP Solutions

EMMET ROAD

Designed by EH

Checked by MK

Network 2020.1.3



Micro
Drainage

Hydro-Brake® Optimum Manhole: SW C9, DS/PN: SW C1.008, Volume (m³): 4.0

Unit Reference	MD-SHE-0092-5000-2000-5000	Sump Available	Yes
Design Head (m)	2.000	Diameter (mm)	92
Design Flow (l/s)	5.0	Invert Level (m)	21.419
Flush-Flow™	Calculated	Minimum Outlet Pipe Diameter (mm)	150
Objective	Minimise upstream storage	Suggested Manhole Diameter (mm)	1200
Application	Surface		

	Control Points	Head (m)	Flow (l/s)	Control Points	Head (m)	Flow (l/s)
Design Point	(Calculated)	2.000	5.0	Kick-Flow®	0.816	3.3
	Flush-Flow™	0.398	4.1	Mean Flow over Head Range	–	3.9

The hydrological calculations have been based on the Head/Discharge relationship for the Hydro-Brake® Optimum as specified. Should another type of control device other than a Hydro-Brake Optimum® be utilised then these storage routing calculations will be invalidated

Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)
0.100	2.9	0.600	4.0	1.600	4.5	2.600	5.6	5.000	7.7	7.500	9.3
0.200	3.8	0.800	3.4	1.800	4.8	3.000	6.0	5.500	8.0	8.000	9.6
0.300	4.1	1.000	3.6	2.000	5.0	3.500	6.5	6.000	8.4	8.500	9.9
0.400	4.1	1.200	3.9	2.200	5.2	4.000	6.9	6.500	8.7	9.000	10.2
0.500	4.1	1.400	4.2	2.400	5.4	4.500	7.3	7.000	9.0	9.500	10.4

O'Connor Sutton Cronin		Page 15	
9 Prussia Street Dublin 7 Ireland		EMMET ROAD	
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Designed by EH Checked by MK	
XP Solutions		Network 2020.1.3	
Offline Controls for SW C			
Pipe Manhole: SW C11, DS/PN: SW C4.004, Loop to PN: SW C3.003			
Diameter (m)	0.150	Length (m)	5.000
Section Type	Pipe/Conduit	Roughness k (mm)	0.600
Slope (1:X)	20.0	Entry Loss Coefficient	0.500
		Coefficient of Contraction	0.600
		Upstream Invert Level (m)	24.500
Pipe Manhole: SW C16, DS/PN: SW C5.001, Loop to PN: SW C1.003			
Diameter (m)	0.150	Length (m)	2.000
Section Type	Pipe/Conduit	Roughness k (mm)	0.600
Slope (1:X)	20.0	Entry Loss Coefficient	0.500
		Coefficient of Contraction	0.600
		Upstream Invert Level (m)	24.100
Pipe Manhole: SW C18, DS/PN: SW C6.001, Loop to PN: SW C1.004			
Diameter (m)	0.150	Length (m)	2.000
Section Type	Pipe/Conduit	Roughness k (mm)	0.600
Slope (1:X)	20.0	Entry Loss Coefficient	0.500
		Coefficient of Contraction	0.600
		Upstream Invert Level (m)	24.100
Pipe Manhole: SW C22, DS/PN: SW C7.001, Loop to PN: SW C1.005			
Diameter (m)	0.150	Length (m)	2.000
Section Type	Pipe/Conduit	Roughness k (mm)	0.600
Slope (1:X)	20.0	Entry Loss Coefficient	0.500
		Coefficient of Contraction	0.600
		Upstream Invert Level (m)	24.050
©1982-2020 Innovyze			

O'Connor Sutton Cronin		Page 16																			
9 Prussia Street Dublin 7 Ireland Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX XP Solutions	EMMET ROAD																				
	Designed by EH																				
	Checked by MK																				
Network 2020.1.3																					
Pipe Manhole: SW C27, DS/PN: SW C9.001, Loop to PN: SW C1.007 <table><tr><td>Diameter (m)</td><td>0.150</td><td>Length (m)</td><td>5.000</td><td>Coefficient of Contraction</td><td>0.600</td></tr><tr><td>Section Type</td><td>Pipe/Conduit</td><td>Roughness k (mm)</td><td>0.600</td><td>Upstream Invert Level (m)</td><td>23.750</td></tr><tr><td>Slope (1:X)</td><td>20.0</td><td>Entry Loss Coefficient</td><td>0.500</td><td></td><td></td></tr></table>				Diameter (m)	0.150	Length (m)	5.000	Coefficient of Contraction	0.600	Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	23.750	Slope (1:X)	20.0	Entry Loss Coefficient	0.500		
Diameter (m)	0.150	Length (m)	5.000	Coefficient of Contraction	0.600																
Section Type	Pipe/Conduit	Roughness k (mm)	0.600	Upstream Invert Level (m)	23.750																
Slope (1:X)	20.0	Entry Loss Coefficient	0.500																		
©1982-2020 Innovyze																					

O'Connor Sutton Cronin			Page 17		
9 Prussia Street Dublin 7 Ireland		EMMET ROAD			
Date 27/09/2022 12:53		Designed by EH			
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Checked by MK			
XP Solutions		Network 2020.1.3			
Storage Structures for SW C					
Filter Drain Pipe: SW C3.000					
Manning's N	0.040	Invert Level (m)	23.800	Number of Pipes	
Infiltration Coefficient Base (m/hr)	0.00000	Trench Width (m)	0.5	Slope (1:X)	
Infiltration Coefficient Side (m/hr)	0.00000	Trench Length (m)	18.4	Cap Volume	
Safety Factor	2.0	Pipe Diameter (m)	0.150	Infiltration Depth (m)	
Porosity	0.30	Pipe Depth above Invert (m)	0.150	Cap Infiltration Depth (m)	
				1	
				Slope (1:X)	
				Cap Volume	
				Infiltration Depth (m)	
				Cap Infiltration Depth (m)	
				199.6	
				1.000	
				0.000	
Filter Drain Pipe: SW C3.001					
Manning's N	0.040	Invert Level (m)	23.708	Number of Pipes	
Infiltration Coefficient Base (m/hr)	0.00000	Trench Width (m)	0.5	Slope (1:X)	
Infiltration Coefficient Side (m/hr)	0.00000	Trench Length (m)	16.7	Cap Volume	
Safety Factor	2.0	Pipe Diameter (m)	0.150	Infiltration Depth (m)	
Porosity	0.30	Pipe Depth above Invert (m)	0.150	Cap Infiltration Depth (m)	
				1	
				Slope (1:X)	
				Cap Volume	
				Infiltration Depth (m)	
				Cap Infiltration Depth (m)	
				199.4	
				1.000	
				0.000	
Filter Drain Pipe: SW C3.002					
Manning's N	0.040	Invert Level (m)	23.624	Number of Pipes	
Infiltration Coefficient Base (m/hr)	0.00000	Trench Width (m)	0.5	Slope (1:X)	
Infiltration Coefficient Side (m/hr)	0.00000	Trench Length (m)	10.2	Cap Volume	
Safety Factor	2.0	Pipe Diameter (m)	0.150	Infiltration Depth (m)	
Porosity	0.30	Pipe Depth above Invert (m)	0.150	Cap Infiltration Depth (m)	
				1	
				Slope (1:X)	
				Cap Volume	
				Infiltration Depth (m)	
				Cap Infiltration Depth (m)	
				200.1	
				1.000	
				0.000	
©1982-2020 Innovyze					

O'Connor Sutton Cronin		Page 18	
9 Prussia Street Dublin 7 Ireland		EMMET ROAD	
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX XP Solutions		Designed by EH Checked by MK Network 2020.1.3	
Filter Drain Pipe: SW C3.003			
Manning's N	0.040	Invert Level (m)	23.350
Infiltration Coefficient Base (m/hr)	0.00000	Trench Width (m)	0.5
Infiltration Coefficient Side (m/hr)	0.00000	Trench Length (m)	15.2
Safety Factor	2.0	Pipe Diameter (m)	0.150
Porosity	0.30	Pipe Depth above Invert (m)	0.150
		Number of Pipes	1
		Slope (1:X)	200.3
		Cap Volume (m)	1.000
		Cap Infiltration Depth (m)	0.000
Filter Drain Pipe: SW C4.000			
Manning's N	0.040	Invert Level (m)	23.950
Infiltration Coefficient Base (m/hr)	0.00000	Trench Width (m)	0.4
Infiltration Coefficient Side (m/hr)	0.00000	Trench Length (m)	24.0
Safety Factor	2.0	Pipe Diameter (m)	0.150
Porosity	0.30	Pipe Depth above Invert (m)	0.150
		Number of Pipes	1
		Slope (1:X)	200.0
		Cap Volume (m)	1.000
		Cap Infiltration Depth (m)	0.000
Filter Drain Pipe: SW C4.001			
Manning's N	0.040	Invert Level (m)	23.830
Infiltration Coefficient Base (m/hr)	0.00000	Trench Width (m)	0.5
Infiltration Coefficient Side (m/hr)	0.00000	Trench Length (m)	9.6
Safety Factor	2.0	Pipe Diameter (m)	0.150
Porosity	0.30	Pipe Depth above Invert (m)	0.150
		Number of Pipes	1
		Slope (1:X)	150.0
		Cap Volume (m)	1.000
		Cap Infiltration Depth (m)	0.000
Filter Drain Pipe: SW C4.002			
Manning's N	0.040	Safety Factor	2.0
Infiltration Coefficient Base (m/hr)	0.00000	Porosity	0.30
Infiltration Coefficient Side (m/hr)	0.00000	Invert Level (m)	23.700
		Pipe Diameter (m)	0.150
		Trench Width (m)	0.5
		Trench Length (m)	14.5
		Pipe Diameter (m)	0.150
©1982-2020 Innovyze			

O'Connor Sutton Cronin		Page 19	
9 Prussia Street Dublin 7 Ireland	EMMET ROAD		
Date 27/09/2022 12:53	Designed by EH		
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX	Checked by MK		
XP Solutions		Network 2020.1.3	
Filter Drain Pipe: SW C4.002 Pipe Depth above Invert (m) 0.150 Slope (1:X) 149.5 Cap Infiltration Depth (m) 0.000 Number of Pipes 1 Cap Volume Depth (m) 1.000 Filter Drain Pipe: SW C4.003 Manning's N 0.040 Invert Level (m) 23.710 Number of Pipes 1 Infiltration Coefficient Base (m/hr) 0.00000 Trench Width (m) 0.5 Slope (1:X) 199.5 Infiltration Coefficient Side (m/hr) 0.00000 Trench Length (m) 9.8 Cap Volume Depth (m) 1.000 Safety Factor 2.0 Pipe Diameter (m) 0.150 Cap Infiltration Depth (m) 0.000 Porosity 0.30 Pipe Depth above Invert (m) 0.150 Complex Manhole: SW C11, DS/PN: SW C4.004 Infiltration Blanket Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 23.586 Cap Volume Depth (m) 0.500 Safety Factor 2.0 Diameter/Width (m) 5.0 Porosity 0.30 Length (m) 25.0 Bio-Retention Area Invert Level (m) 24.086 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0 Porosity 1.00 Infiltration Coefficient Side (m/hr) 0.00000			
©1982-2020 Innovyze			

O'Connor Sutton Cronin		Page 20																																					
9 Prussia Street Dublin 7 Ireland	EMMET ROAD																																						
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX XP Solutions	Designed by EH Checked by MK Network 2020.1.3																																						
Bio-Retention Area <table><thead><tr><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th></tr></thead><tbody><tr><td>0.000</td><td>90.0</td><td>50.000</td><td>0.500</td><td>120.0</td><td>60.000</td></tr><tr><td></td><td></td><td></td><td>0.501</td><td>0.0</td><td>60.000</td></tr></tbody></table> Infiltration Blanket Manhole: SW C7, DS/PN: SW C3.004 Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 23.274 Cap Volume Depth (m) 0.500 Safety Factor 2.0 Diameter/Width (m) 5.0 Porosity 0.30 Length (m) 55.0 Complex Manhole: SW C16, DS/PN: SW C5.001 Infiltration Blanket Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 23.136 Cap Volume Depth (m) 0.500 Safety Factor 2.0 Diameter/Width (m) 3.0 Porosity 0.30 Length (m) 8.5 Bio-Retention Area Invert Level (m) 23.636 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0 Porosity 1.00 Infiltration Coefficient Side (m/hr) 0.00000 <table><thead><tr><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th></tr></thead><tbody><tr><td>0.000</td><td>15.0</td><td>16.000</td><td>0.400</td><td>25.0</td><td>22.000</td></tr><tr><td></td><td></td><td></td><td>0.401</td><td>0.0</td><td>22.000</td></tr></tbody></table> ©1982-2020 Innovyze				Depth (m)	Area (m²)	Perimeter (m)	Depth (m)	Area (m²)	Perimeter (m)	0.000	90.0	50.000	0.500	120.0	60.000				0.501	0.0	60.000	Depth (m)	Area (m²)	Perimeter (m)	Depth (m)	Area (m²)	Perimeter (m)	0.000	15.0	16.000	0.400	25.0	22.000				0.401	0.0	22.000
Depth (m)	Area (m²)	Perimeter (m)	Depth (m)	Area (m²)	Perimeter (m)																																		
0.000	90.0	50.000	0.500	120.0	60.000																																		
			0.501	0.0	60.000																																		
Depth (m)	Area (m²)	Perimeter (m)	Depth (m)	Area (m²)	Perimeter (m)																																		
0.000	15.0	16.000	0.400	25.0	22.000																																		
			0.401	0.0	22.000																																		

O'Connor Sutton Cronin		Page 21			
9 Prussia Street Dublin 7 Ireland	EMMET ROAD				
	Designed by EH				
	Checked by MK				
Date 27/09/2022 12:53	Network 2020.1.3				
File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX					
XP Solutions					
Complex Manhole: SW C18, DS/PN: SW C6.001					
Infiltration Blanket					
Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 23.383 Cap Volume Depth (m) 0.500					
Safety Factor 2.0 Diameter/Width (m) 3.0					
Porosity 0.30 Length (m) 11.0					
Bio-Retention Area					
Invert Level (m) 23.883 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0					
Porosity 1.00 Infiltration Coefficient Side (m/hr) 0.00000					
Depth (m)	Area (m²)	Perimeter (m)	Depth (m)	Area (m²)	Perimeter (m)
0.000	23.0	19.000	0.400	33.0	28.000
				0.401	0.0
					28.000
Complex Manhole: SW C22, DS/PN: SW C7.001					
Infiltration Blanket					
Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 22.980 Cap Volume Depth (m) 0.750					
Safety Factor 2.0 Diameter/Width (m) 8.0					
Porosity 0.30 Length (m) 7.0					
©1982-2020 Innovyze					

O'Connor Sutton Cronin		Page 22																																					
9 Prussia Street Dublin 7 Ireland	EMMET ROAD																																						
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX XP Solutions	Designed by EH Checked by MK Network 2020.1.3																																						
Bio-Retention Area Invert Level (m) 23.730 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0 Porosity 1.00 Infiltration Coefficient Side (m/hr) 0.00000 <table><thead><tr><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th></tr></thead><tbody><tr><td>0.000</td><td>42.0</td><td>28.000</td><td>0.500</td><td>55.0</td><td>33.000</td></tr><tr><td></td><td></td><td></td><td>0.501</td><td>0.0</td><td>33.000</td></tr></tbody></table> Complex Manhole: SW C27, DS/PN: SW C9.001 Infiltration Blanket Infiltration Coefficient Base (m/hr) 0.00000 Invert Level (m) 22.634 Cap Volume Depth (m) 0.750 Safety Factor 2.0 Diameter/Width (m) 3.0 Porosity 0.30 Length (m) 21.0 Bio-Retention Area Invert Level (m) 23.384 Infiltration Coefficient Base (m/hr) 0.00000 Safety Factor 2.0 Porosity 1.00 Infiltration Coefficient Side (m/hr) 0.00000 <table><thead><tr><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th><th>Depth (m)</th><th>Area (m²)</th><th>Perimeter (m)</th></tr></thead><tbody><tr><td>0.000</td><td>40.0</td><td>55.000</td><td>0.500</td><td>63.0</td><td>65.000</td></tr><tr><td></td><td></td><td></td><td>0.501</td><td>0.0</td><td>65.000</td></tr></tbody></table> ©1982-2020 Innovyze				Depth (m)	Area (m²)	Perimeter (m)	Depth (m)	Area (m²)	Perimeter (m)	0.000	42.0	28.000	0.500	55.0	33.000				0.501	0.0	33.000	Depth (m)	Area (m²)	Perimeter (m)	Depth (m)	Area (m²)	Perimeter (m)	0.000	40.0	55.000	0.500	63.0	65.000				0.501	0.0	65.000
Depth (m)	Area (m²)	Perimeter (m)	Depth (m)	Area (m²)	Perimeter (m)																																		
0.000	42.0	28.000	0.500	55.0	33.000																																		
			0.501	0.0	33.000																																		
Depth (m)	Area (m²)	Perimeter (m)	Depth (m)	Area (m²)	Perimeter (m)																																		
0.000	40.0	55.000	0.500	63.0	65.000																																		
			0.501	0.0	65.000																																		

O'Connor Sutton Cronin		Page 23													
9 Prussia Street Dublin 7 Ireland	EMMET ROAD														
	Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX	Designed by EH Checked by MK													
XP Solutions Network 2020.1.3															
Tank or Pond Manhole: SW C9, DS/PN: SW C1.008 Invert Level (m) 21.419 <table><thead><tr><th>Depth (m)</th><th>Area (m²)</th><th>Depth (m)</th><th>Area (m²)</th><th>Depth (m)</th><th>Area (m²)</th></tr></thead><tbody><tr><td>0.000</td><td>500.0</td><td>1.250</td><td>500.0</td><td>1.251</td><td>0.0</td></tr></tbody></table>				Depth (m)	Area (m ²)	Depth (m)	Area (m ²)	Depth (m)	Area (m ²)	0.000	500.0	1.250	500.0	1.251	0.0
Depth (m)	Area (m ²)	Depth (m)	Area (m ²)	Depth (m)	Area (m ²)										
0.000	500.0	1.250	500.0	1.251	0.0										
©1982-2020 Innovyze															

O'Connor Sutton Cronin		Page 24	
9 Prussia Street Dublin 7 Ireland		EMMET ROAD	
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Designed by EH Checked by MK	
XP Solutions		Network 2020.1.3	
Summary of Critical Results by Maximum Level (Rank 1) for SW C			
Simulation Criteria			
Areal Reduction Factor 1.000		Manhole Headloss Coeff (Global) 0.500	MADD Factor * 10m³/ha Storage 2.000
Hot Start (mins) 0		Foul Sewage per hectare (l/s) 0.000	Inlet Coefficient 0.800
Hot Start Level (mm) 0		Additional Flow - % of Total Flow 0.000	Flow per Person per Day (l/per/day) 0.000
Number of Input Hydrographs 0		Number of Offline Controls 5	Number of Time/Area Diagrams 0
Number of Online Controls 7		Number of Storage Structures 15	Number of Real Time Controls 0
Synthetic Rainfall Details			
Rainfall Model		FSR M5-60 (mm) 16.500	Cv (Summer) 1.000
Region Scotland and Ireland		Ratio R 0.277	Cv (Winter) 1.000
Margin for Flood Risk Warning (mm)		300.0	DVD Status OFF
Analysis Timestep 2.5 Second Increment (Extended)		Inertia Status OFF	
DTS Status		ON	
Profile(s)			
Duration(s) (mins)		15, 30, 60, 120, 180, 240, 360, 480, 600, 720, 960, 1440, 2160, 2880, 4320, 5760, 7200, 8640, 10080	Summer and Winter
Return Period(s) (years)		100	
Climate Change (%)		20	
PN	US/MH Name	Event	US/CL Level (m)
SW C1.000	SW C1	15 minute	100 year
			Summer I+20% 24.000
			23.183
			-0.142
			0.28
			12.7
			OK
©1982-2020 Innovyze			

9 Prussia Street
Dublin 7
Ireland

EMMET ROAD



Date 27/09/2022 12:53

Designed by EH

File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX

Checked by MK

XP Solutions

Network 2020.1.3

Summary of Critical Results by Maximum Level (Rank 1) for SW C

PN	US/MH Name	Event	US/CL (m)	Water Level (m)	Surcharged Depth (m)	Flow / Cap. (l/s)	Pipe Flow (l/s)	Status
SW C2.000	SW C2	15 minute 100 year Summer I+20%	24.750	24.147	0.197	1.39	14.9	SURCHARGED
SW C1.001	SW C2	15 minute 100 year Summer I+20%	24.400	22.987	-0.056	0.91	27.4	OK
SW C3.000	SW C3	15 minute 100 year Summer I+20%	25.180	24.063	-0.737	0.22	9.1	OK
SW C3.001	SW C4	15 minute 100 year Summer I+20%	24.950	24.032	-0.676	0.33	13.5	OK
SW C3.002	SW C5	30 minute 100 year Summer I+20%	24.750	23.984	-0.640	0.40	16.0	OK
SW C3.003	SW C6	30 minute 100 year Summer I+20%	24.800	23.827	-0.523	0.52	21.0	OK
SW C4.000	SW C7	15 minute 100 year Summer I+20%	24.850	24.145	-0.705	0.17	4.6	OK
SW C4.001	SW C8	15 minute 100 year Summer I+20%	24.850	24.020	-0.810	0.14	6.6	OK
SW C4.002	SW C9	30 minute 100 year Summer I+20%	24.780	23.971	-0.729	0.18	8.2	OK
SW C4.003	SW C10	30 minute 100 year Summer I+20%	24.610	23.956	-0.654	0.27	9.8	OK
SW C4.004	SW C11	720 minute 100 year Summer I+20%	24.700	23.932	0.121	0.03	0.5	SURCHARGED
SW C3.004	SW C7	960 minute 100 year Summer I+20%	24.500	23.655	0.231	0.11	1.2	SURCHARGED
SW C1.002	SW C3	15 minute 100 year Summer I+20%	24.400	22.921	-0.076	0.77	27.6	OK
SW C5.000	SW C15	240 minute 100 year Summer I+20%	24.400	23.567	0.267	0.14	1.5	SURCHARGED
SW C5.001	SW C16	240 minute 100 year Summer I+20%	24.350	23.566	0.280	0.03	0.3	SURCHARGED
SW C1.003	SW C4	15 minute 100 year Summer I+20%	24.300	22.821	-0.069	0.66	26.6	OK*
SW C6.000	SW C17	360 minute 100 year Summer I+20%	24.300	23.868	0.318	0.14	1.5	SURCHARGED
SW C6.001	SW C18	360 minute 100 year Summer I+20%	24.300	23.868	0.335	0.03	0.3	SURCHARGED
SW C1.004	SW C5	15 minute 100 year Summer I+20%	24.300	22.777	-0.016	0.80	27.9	OK*
SW C7.000	SW C19	360 minute 100 year Summer I+20%	24.200	23.244	0.094	0.12	1.3	SURCHARGED
SW C7.001	SW C22	360 minute 100 year Summer I+20%	24.250	23.244	0.114	0.02	0.2	SURCHARGED
SW C1.005	SW C6	15 minute 100 year Summer I+20%	24.300	22.748	0.017	0.88	29.5	SURCHARGED*
SW C8.000	SW C7	15 minute 100 year Summer I+20%	24.000	23.283	0.033	1.06	18.0	SURCHARGED
SW C1.006	SW C7	15 minute 100 year Summer I+20%	24.300	22.723	0.047	1.06	39.9	SURCHARGED
SW C9.000	SW C23	600 minute 100 year Summer I+20%	23.850	23.024	0.224	0.13	1.4	SURCHARGED

O'Connor Sutton Cronin			Page 26				
9 Prussia Street Dublin 7 Ireland		EMMET ROAD					
Date 27/09/2022 12:53 File B967-OCSC-XX-XX-MD-C-0001-S2-P08.MDX		Designed by EH Checked by MK					
XP Solutions		Network 2020.1.3					
Summary of Critical Results by Maximum Level (Rank 1) for SW C							
PN	US/MH Name	Event	US/CL (m)	Water Level (m)	Surcharged Depth (m)	Pipe Flow / Cap. (l/s)	Status
SW C9.001	SW C27	600 minute 100 year Summer	I+20% 24.075	23.024	0.240	0.02	0.3 SURCHARGED
SW C1.007	SW C8	30 minute 100 year Summer	I+20% 24.300	22.500	0.025	1.18	48.1 SURCHARGED*
SW C10.000	SW C20	15 minute 100 year Summer	I+20% 24.000	23.133	-0.117	0.11	2.0 OK
SW C10.001	SW C21	15 minute 100 year Summer	I+20% 23.800	22.359	0.209	0.13	4.1 SURCHARGED
SW C11.000	SW C27	15 minute 100 year Summer	I+20% 23.500	22.722	-0.028	0.66	15.0 OK
SW C11.001	SW C32	15 minute 100 year Summer	I+20% 23.500	22.662	0.045	1.18	15.0 SURCHARGED
SW C10.002	SW C27	15 minute 100 year Summer	I+20% 23.500	22.354	0.504	1.04	15.7 SURCHARGED
SW C12.000	SW C29	15 minute 100 year Summer	I+20% 23.500	22.987	0.237	2.17	23.5 SURCHARGED
SW C12.001	SW C35	15 minute 100 year Summer	I+20% 23.500	22.842	0.114	2.17	23.5 SURCHARGED
SW C10.003	SW C27	15 minute 100 year Summer	I+20% 23.500	22.287	0.506	2.16	35.1 SURCHARGED
SW C13.000	SW C22	15 minute 100 year Summer	I+20% 23.800	23.209	0.159	0.91	22.0 SURCHARGED
SW C13.001	SW C38	15 minute 100 year Summer	I+20% 23.650	23.084	0.184	1.49	21.8 SURCHARGED
SW C1.008	SW C9	960 minute 100 year Summer	I+20% 23.500	21.767	0.123	0.04	3.8 SURCHARGED
SW C1.009	SW C10	30 minute 100 year Summer	I+20% 22.500	20.884	-0.233	0.11	6.7 OK*
SW C1.010	SW C11	30 minute 100 year Summer	I+20% 22.500	20.839	-0.234	0.11	6.7 OK*
SW C1.011	SW C12	30 minute 100 year Summer	I+20% 22.500	20.797	-0.239	0.09	6.7 OK
SW C1.012	SW C13	30 minute 100 year Summer	I+20% 22.300	20.687	-0.230	0.13	6.7 OK
©1982-2020 Innovyze							

APPENDIX E. WASTEWATER DESIGN CALCULATIONS

- As per Irish Water Code of Practice for Wastewater Infrastructure, IW-CDS-5030-03

Appendix E

Wastewater Design Calculations

JOB NAME:

Emmet Road

JOB NO:

B967

DATE:

19.09.2022

TITLE:

Wastewater Design Calculations

CALCS BY:

MK

CHECK'D:

PR



Zone	Area (m ²)	No. of Units (nr)	Area/person (m ²)	Occupancy (nr/m ²)	Population Equivalent	Flow (l/unit/day)	Infiltration (% of flow)	Total Flow (m ³ /day)	DWF (l/s)	Peak Factor for Pipe Sizing	Peak Flow (l/s)
Domestic											
<i>Apartments</i>											
Block A		306		2.7	826	150	10%	136.32	1.6		
Block B		181		2.7	489	150	10%	80.64	0.9		
Block C		91		2.7	246	150	10%	40.54	0.5		
TOTAL Domestic		578			1,561			257.50	3.0	3.0	8.9
Non-Domestic											
<i>Retail</i>											
Large Unit	3,245										
Other Retail	2,476		80	0.013	31	90	10%	3.1	0.07		
	769		50	0.020	15	90	10%	1.5	0.04		
<i>Community Buildings</i>											
Library / Community Hub	2,810		200	0.005	50	15	10%	0.8	0.02		
<i>Childcare</i>											
Childcare	816		18	0.056	45	90	10%	4.5	0.10		
TOTAL Non-Domestic	6,871				142			9.9	0.23	4.5	1.03
DEVELOPMENT TOTAL					1,702			267	3.21		9.97

Occupancy Rates are assumed with flow rates adjusted to hourly rates

Residential Occupancy rates from Appendix C of IW Code of Practice for Wastewater Infrastructure, December 2017 (IW-CDS-5030-03)

Flow rates from Appendix D of IW Code of Practice for Wastewater Infrastructure, December 2017 (IW-CDS-5030-03)

Infiltration rates from Appendix C of IW Code of Practice for Wastewater Infrastructure, December 2017 (IW-CDS-5030-03)

Peaking Factor from Appendix C of IW Code of Practice for Wastewater Infrastructure, December 2017 (IW-CDS-5030-03)

APPENDIX F. IRISH WATER CONFIRMATION OF FEASIBILITY

Appendix F

Irish Water Confirmation of Feasibility

Mark Killian

OCSC
9 Prussia Street
Stoneybatter
Dublin 7
D07KT57

Uisce Éireann
Bosca OP 448
Oifig Sheachadta na
Cathrach Theas
Cathair Chorcaí

Irish Water
PO Box 448,
South City
Delivery Office
Cork City

www.water.ie


8 June 2022

Re: CDS22003279 pre-connection enquiry - Subject to contract | Contract denied

Connection for Multi/Mixed Use Development of 634 units at Emmet Road, Inchicore, Dublin

Dear Sir/Madam,

Irish Water has reviewed your pre-connection enquiry in relation to a Water & Wastewater connection at Emmet Road, Inchicore, Dublin (the **Premises**). Based upon the details you have provided with your pre-connection enquiry and on our desk top analysis of the capacity currently available in the Irish Water network(s) as assessed by Irish Water, we wish to advise you that your proposed connection to the Irish Water network(s) can be facilitated at this moment in time.


SERVICE	OUTCOME OF PRE-CONNECTION ENQUIRY <u>THIS IS NOT A CONNECTION OFFER. YOU MUST APPLY FOR A CONNECTION(S) TO THE IRISH WATER NETWORK(S) IF YOU WISH TO PROCEED.</u>
Water Connection	Feasible Subject to upgrades
Wastewater Connection	Feasible without infrastructure upgrade by Irish Water
SITE SPECIFIC COMMENTS	
Water Connection	In order to accommodate the proposed connection, upgrade of the existing 6" main to a 200mm ID pipe in Emmet Road for approximately 180mm (including bridge crossing) will be required. The water main section is highlighted in red below. 

Connection main should be also a 200 mm ID pipe connected to the new 200mm ID main. A DMA meter is to be installed on the connection main and linked to telemetry online.

The proposed Development indicates that Irish Water assets are present on the site. The Developer has to demonstrate that proposed structures and works will not inhibit access for maintenance or endanger structural or functional integrity of the assets during and after the works. Drawings (showing clearance distances, changing to ground levels) and Method Statements should be included in the Detailed Design of the Development. A wayleave in favour of Irish Water will be required over the assets that are not located within the Public Space. For design submissions and queries related to diversion/build near or over, please contact IW Diversion Team via email address diversions@water.ie

The design and construction of the Water & Wastewater pipes and related infrastructure to be installed in this development shall comply with the Irish Water Connections and Developer Services Standard Details and Codes of Practice that are available on the Irish Water website. Irish Water reserves the right to supplement these requirements with Codes of Practice and these will be issued with the connection agreement.

The map included below outlines the current Irish Water infrastructure adjacent to your site:



Reproduced from the Ordnance Survey of Ireland by Permission of the Government. License No. 3-3-34

Whilst every care has been taken in its compilation Irish Water gives this information as to the position of its underground network as a general guide only on the strict understanding that it is based on the best available information provided by each Local Authority in Ireland to Irish Water. Irish Water can assume no responsibility for and give no guarantees, undertakings or warranties concerning the accuracy, completeness or up to date nature of the information provided and does not accept any liability whatsoever arising from any errors or omissions. This information should not be relied upon in the event of excavations or any other works being carried out in the vicinity of the Irish Water underground network. The onus is on the parties carrying out excavations or any other works to ensure the exact location of the Irish Water underground network is identified prior to excavations or any other works being carried out. Service connection pipes are not generally shown but their presence should be anticipated.

General Notes:

- 1) The initial assessment referred to above is carried out taking into account water demand and wastewater discharge volumes and infrastructure details on the date of the assessment. **The availability of capacity may change at any date after this assessment.**
- 2) This feedback does not constitute a contract in whole or in part to provide a connection to any Irish Water infrastructure. All feasibility assessments are subject to the constraints of the Irish Water Capital Investment Plan.
- 3) The feedback provided is subject to a Connection Agreement/contract being signed at a later date.
- 4) A Connection Agreement will be required to commencing the connection works associated with the enquiry this can be applied for at <https://www.water.ie/connections/get-connected/>
- 5) A Connection Agreement cannot be issued until all statutory approvals are successfully in place.
- 6) Irish Water Connection Policy/ Charges can be found at <https://www.water.ie/connections/information/connection-charges/>
- 7) Please note the Confirmation of Feasibility does not extend to your fire flow requirements.
- 8) Irish Water is not responsible for the management or disposal of storm water or ground waters. You are advised to contact the relevant Local Authority to discuss the management or disposal of proposed storm water or ground water discharges
- 9) To access Irish Water Maps email datarequests@water.ie
- 10) All works to the Irish Water infrastructure, including works in the Public Space, shall have to be carried out by Irish Water.

If you have any further questions, please contact Marina Byrne from the design team via email mzbyrne@water.ie For further information, visit **www.water.ie/connections**.

Yours sincerely,



Yvonne Harris

Head of Customer Operations



OCSC

O'CONNOR | SUTTON | CRONIN

Multidisciplinary
Consulting Engineers

9 Prussia Street
Dublin 7
Ireland

T | +353 (0)1 8682000
F | +353 (0)1 8682100
W | www.ocsc.ie

Dublin | London | Abu Dhabi | Belfast | Cork | Galway | Glasgow | Libya | Poland | Romania | Russia