Intended for Vantage Data Centers DUB13 Limited

Date March 2023

Project Number 1620014883

VANTAGE DUBLIN DATA CENTER **VOLUME 3: TECHNICAL APPENDICIES**





Volume 3: Technical Appendices Table of Contents

- **Technical Appendix 1.1:** IEMA Quality Mark Checklist
- **Technical Appendix 7.1:** Traffic Flow and Distribution Diagrams
- Technical Appendix 7.2: Accident Data
- **Technical Appendix 7.3:** Cumulative Schemes Daily Traffic Flood Diagrams
- **Technical Appendix 7.4: Proposed Development Trip Generation**
- Technical Appendix 8.1: Air Quality Modelling Inputs
- Technical Appendix 8.2: Air Quality Detailed Results
- Technical Appendix 9.1: Acoustic Terminology
- **Technical Appendix 9.2: Preliminary Construction Noise Assessment**
- **Technical Appendix 10.1A: Engineering Planning Strategy**
- **Technical Appendix 10.2** Site-Specific Flood Risk Assessment
- **Technical Appendix 10.3A: Foul and Surface Water Drainage Layout**
- **Technical Appendix 10.4N: Engineering Planning Report Letter of Conformity**
- Technical Appendix 11.1A: Ecological Impact Assessment Report
- **Technical Appendix 11.2A: Appropriate Assessment Screening Report**
- **Technical Appendix 11.3A: Biodiversity Management Plan**
- **Technical Appendix 12.1:** Ground Investigation & Geotechnical Report
- **Technical Appendix 12.2: Contaminated Land Interpretative Report**

Technical Appendix 1.1: IEMA Quality Mark Checklist

Та	ble 1.1: IEMA Quality Mark Check	
EI	A Commitment and ES Review Criteria	d J J J J J J J J
El	A Commitment 1: Regulatory Compliance ¹	
a)	Does the ES, in the light of the project being assessed, identify, describe and assess effects on:	\checkmark
-	Human Beings	\checkmark
-	Fauna & Flora	\checkmark
-	Soil	\checkmark
-	Water	\checkmark
-	Air	\checkmark
-	Climate	\checkmark
-	Landscape	\checkmark
-	Cultural Heritage	\checkmark
-	Material Assets	\checkmark
b)	Does the ES attempt to set out the interaction between the factors set out under criteria 1.a)?	\checkmark
c)	Does the ES contain a clear section, or sections, providing a description of the project comprising information on the site, design and size of the project?	\checkmark
d)	Does the ES contain a section, or sections, that describe the likely significant effects of the proposed project on the environment?	\checkmark
e)	Does the ES contain a clear section, or sections, that provide a description of the measures envisaged in order to avoid, reduce and, if possible, remedy significant adverse effects?	\checkmark
f)	Does the ES contain a clear section, or sections, that provides the data required to identify and assess the main effects which the project is likely to have on the environment?	\checkmark
g)	Does the ES contain a section, or sections, that outline the main alternatives studied by the developer and an indication of the main reasons for his choice, taking into account the environmental effects?	\checkmark
h)	Has a Non-Technical Summary been produced containing an outline of the information mentioned in 1c) to 1h)?	\checkmark
El	A Commitment 4: EIA Context	
A)	Scoping	
i)	Has the ES clearly stated what effects will be addressed and how this decision was reached?	\checkmark
ii)	Are the main environmental concerns and their locations, where relevant, clearly identified with an explanation of the risks posed from the project? Including relevant environmental issues beyond the boundary of the proposal?	\checkmark
iii)	Does the ES identify the environmental issues that will not be assessed and explain why they are not being considered further?	\checkmark

¹ A number of the criteria under this Commitment cover similar issues to criteria set out in the other three Commitments, below. Where this occurs IEMA recognise that there will inevitably be some overlap between the criteria. However, the assessment of the criteria under this Commitment is focussed on the presence or absence of the issue, whereas the assessment of similar criteria, within the other three Commitments, will focus on the quality of the consideration of the issue in question.

Та	ble 1.1: IEMA Quality Mark Check	
El/	A Commitment and ES Review Criteria	
iv)	Is the sub-topic scope undertaken in relation to each of the topics included in the EIA appropriate and focussed	V
B)	Alternatives, including iterative design	
i)	Does the ES set out the main alternatives that were considered at different points during the development of the proposal?	\checkmark
ii)	Are the main reasons for the selection of the proposal over distinct alternatives and design iterations easily identifiable?	\checkmark
iii)	Does the ES clearly indicate how the EIA process, environmental issues and consultee responses influenced the iterative design process that led to the proposed project?	\checkmark
El/	A Commitment 5: EIA Content	
A)	Baseline	
i)	Does the ES describe the current condition of those aspects of the environment that are likely to be significantly affected by the development?	\checkmark
ii)	Is the sensitivity / importance of the baseline environment clearly evaluated?	\checkmark
iii)	Are limitations in the baseline information identified and clearly set out?	\checkmark
B)	Assessment	
i)	Are the methods for establishing the magnitude of impacts on the receiving environment clearly defined?	\checkmark
ii)	Does the ES set out a generic methodology for the assessment and evaluation of significance OR clearly explain and justify a specific method for each environmental issue?	\checkmark
iii)	Does the assessment of significance consider the impact's deviation from the established baseline condition? (e.g. the sensitivity of the environment, the extent to which the impact is reversible, etc.).	\checkmark
iv)	Does the ES identify the significance of impacts that would be anticipated to remain following the successful implementation of any mitigation set out in the ES?	V
vii)	Does the ES give appropriate prominence to both positive and negative effects relative to their significance?	\checkmark
C)	Environmental Management	
i)	Does the ES describe the measures proposed to be implemented to avoid, reduce, and if possible, remedy significant adverse impacts of the proposed development?	\checkmark
ii)	Is an indication of the effectiveness of the stated mitigation measures provided?	\checkmark
iii)	Are details provided related to any management plans that the ES indicates should be implemented to deliver the mitigation measures and/or monitor the environmental impact of the project?	
iv)	Does the ES identify the general groups who will be responsible for the follow- up programme?	

Та	ble 1.1: IEMA Quality Mark Check	
EL	A Commitment and ES Review Criteria	
EI	A Commitment 6: EIA Communication	
A)	Consultation	
i)	Does the description of any consultation include details of those who were contacted, including statutory and non-statutory consultees, and the public?	\checkmark
ii)	Does the main text of the ES provide a summary of the main issues raised by consultees?	V
iii)	Does the ES set out if any of the issues raised by consultees will not be dealt with in the ES?	V
lf s	so is clear justification set out as to why the issue has been scoped out?	\checkmark
B)	ES Quality	
i)	Does the ES provide appropriate illustrations through the use of maps and/or diagrams? In particular this should cover:	
	- the location of the site, site layout and boundary,	\checkmark
	- operational appearance,	√
	- main environmental receptors and	√
	 impacts displayed in a visual format where appropriate. 	\checkmark
ii)	Is the area of proposed land clearly described and indicated on an appropriate map or diagram?	\checkmark
iii)	Are the anticipated timescales of construction, operation and (where appropriate) decommissioning of the proposal clearly set out in the main text?	V
iv)	Is the information in the ES presented in a manner in which a non-specialist would be able to logically identify information they were seeking?	\checkmark
v)	Are technical terms kept to a minimum, with a glossary provided?	\checkmark
C)	Non-Technical Summary (NTS)	
i)	Does the NTS provide sufficient information for the non-specialist reader to understand the main environmental impacts of the proposal without reference to the main ES?	\checkmark
ii)	Are maps and diagrams included in the NTS that, at a minimum, illustrate the location of the application site, the footprint of the proposed development, and the location of relevant key features?	\checkmark
iii)	Is it clear that the NTS was made available as a separate, stand-alone document to facilitate a wider readership?	V



Commitments.

excellence in the following areas:

EIA Team Capabilities EIA Regulatory Compliance EIA Context & Influence EIA Content **EIA Presentation**

www.iema.net/qmark

Technical Appendix 7.1: Traffic Flow and Distribution Diagrams





Vantage Data Centers DUB11 Limited Vantage Data Center DUB-13

Technical Appendix 7.2: Accident Data



Trip Distribution:

Development traffic is distributed onto the network according to the directional

splits recorded by the 2019 traffic survey. Traffic continues straight along Nangor Road (R134).





splits recorded by the 2019 traffic survey. Traffic continues straight along Nangor Road (R134).





Trip Distribut

Development traffic is distributed onto the network according to the directional splits recorded by the 2019 traffic survey. Traffic continues straight along Nangor Road (R134).









Total Vehicles

Trip Distribution

Light construction vehicles have been distributed across the surrounding network in the same manner as the 2019 traffic surveys.

All heavy construction traffic travels to the site from the N7 National Road and from the M50 artirial motoriway via the R34 and R136 and departs along the same routes.





Trip Distribution

Development traffic is distributed onto the network according to the directional splits recorded by the 2019 traffic survey. Traffic continues straight along Nangor Road (R134).





Trip Distributio

Light construction vehicles have been distributed across the surrounding network in the same manner as the 2019 traffic surveys.

All heavy construction traffic travels to the site from the N7 National Road and from the M50 artirial motoriway via the R34 and R136 and departs along the same routes.







All Fuel HGVs travel to the site from the N7 National Road and from the M50 artirial motoriway via the R34 and R136 and departs along the same routes.





Technical Appendix 7.3: Cumulative Schemes Daily Traffic Flow Diagrams



0	Legend	
51,	Red Line Boundary	
	Accident Severity	
\sim	Sea Fatal	
Ro 7/	O Severe	
80	O Slight	
	Sight	
15		
-F		
2		
\geq		
L		
91		
15 0		
Fer \		
115		
-		
1		
-		
R136		
	Client	
	Vantage Data Centers	Dub11
	Vantage Data Centers	Dub11
	Vantage Data Centers Limited Project Title	Dub11
	Vantage Data Centers Limited Project Title VDC DUB 13	Dub11
	Vantage Data Centers Limited Project Title VDC DUB 13 Project Number 1620014883	Dub11
	Vantage Data Centers Limited Project Title VDC DUB 13 Project Number 1620014883 Figure Title	Dub11
	Vantage Data Centers Limited Project Title VDC DUB 13 Project Number 1620014883 Figure Title Accident Data (2021	Dub11
	Vantage Data Centers Limited Project Title VDC DUB 13 Project Number 1620014883 Figure Title Accident Data (2021	Dub11 1-2016)
	Vantage Data Centers Limited Project Title VDC DUB 13 Project Number 1620014883 Figure Title Accident Data (2021 RAMBCI Date 30/09/2022	Dub11 1-2016) Prepared By NS
	Vantage Data Centers Limited Project Title VDC DUB 13 Project Number 1620014883 Figure Title Accident Data (2021 RAMB Date 30/09/2022 Figure No.	Dub11 I-2016) L Prepared By NS Revision

Coordinate System: TM65 Irish Grid. Projection: Transverse Mercator. Datum: TM65.

Technical Appendix 7.4: Proposed Development Trip Generation











Technical Appendix 8.1: Air ality etaile Metho ology Mo elling Approach an ata

Volume 3: Technical Appendices Technical Appendix 8.1: Air Quality Detailed Methodology, Modelling Approach and Data

1. DUST RISK ASSESSMENT METHODOLOGY

Large	Medium	Small
Demolition		
 total building volume >50,000 m³ potentially dusty construction material (e.g. concrete) on-site crushing and screening demolition activities >20 m above ground level 	 total building volume 20,000m³ – 50,000 m³ potentially dusty construction demolition activities 10-20 m above ground level 	 total building volume 20,000 m³ construction material with low potential for dust release (e.g. metal cladding or timber) demolition activities <10 m above ground during wetter months
Earthworks		
 total site area >10,000 m² potentially dusty soil type (e.g. clay, which will be prone to suspension when dry due to small particle size) >10 heavy earth moving vehicles active at any one time formation of bunds >8 m in height total material moved >100,000 tonnes 	 total site area 2,500 m² - 10,000 m² moderately dusty soil type (e.g. silt) 5-10 heavy earth moving vehicles active at any one time formation of bunds 4 m - 8 m in height total material moved 20,000 - 100,000 tonnes 	 total site area <2,500 m² soil type with large grain size (e.g. sand) <5 heavy earth moving vehicles active at any one time formation of bunds <4 m in height total material moved <20,000 tonnes earthworks during wetter months
Construction		
 total building volume >100,000 m³ piling on-site concrete batching sandblasting 	 total building volume 25,000 m³ - 100,000 m³ potentially dusty construction material (e.g. concrete) piling on-site concrete batching 	 total building volume 25,000 m³ construction material with low potential for dust release (e.g. metal cladding or timber)
Trackout	1	1
 >50 HGV (>3.5t) movements in any one day potentially dusty surface material (e.g. high clay content) unpaved road length >100 m 	 10-50 HGV (>3.5t) movements in any one day moderately dusty surface material (e.g. high clay content) unpaved road length 50 m - 100 m 	 <10 HGV (>3.5t) movements in any one day surface material with low potential for dust release unpaved road length <50 m

High	Medium	Low
Sensitivities of People to Dust	Soiling Effects	
 users can reasonably expect enjoyment of a high level of amenity; or the appearance, aesthetics or value of their property would be diminished by soiling; and the people or property would reasonably be expected to be present continuously, or at least regularly for extended periods, as part of the normal pattern of use of the land. indicative examples include dwellings, museums and other culturally important collections, medium and long term car parks and car showrooms. 	 users would expect to enjoy a reasonable level of amenity, but would not reasonably expect to enjoy the same level of amenity as in their home; or the appearance, aesthetics or value of their property could be diminished by soiling; or the people or property would not reasonably be expected to be present continuously or regularly for extended periods as part of the normal pattern of use of the land. indicative examples include parks and places of work. 	 the enjoyment of amenity would not reasonably be expected; or property would not reasonably be expected to be diminished in appearance, aesthetics or value by soiling; or there is transient exposure, where the people or property would reasonably be expected to be present only for limited periods of time as part of the normal pattern of use of the land. indicative examples include playing fields, farmland (unless commercially-sensitive horticultural), footpaths, short term car parks and roads.
Sensitivities of People to the H	lealth Effects of PM ₁₀	
• locations where members of the public are exposed over a time period relevant to the air quality objective for PM_{10} (in the case of the 24-hour objectives, a relevant location would be one where individuals may be exposed for eight hours or more in a day).	• locations where the people exposed are workers, and exposure is over a time period relevant to the air quality objective for PM ₁₀ (in the case of the 24-hour objectives, a relevant location would be one where individuals may be exposed for eight hours or more in a day).	 Locations where human exposure is transient. indicative examples include public footpaths, playing fields parks and shopping streets.
• indicative examples include residential properties, hospitals, schools and residential care homes should also be considered as having equal sensitivity to residential areas for the purposes of this assessment.	• indicative examples include office and shop workers but will generally not include workers occupationally exposed to PM ₁₀ , as protection is covered by Health and Safety at Work legislation.	

Sensitivities of Receptors to Ecological Effects

period relevant to the pjective for PM ₁₀ (in the 24-hour objectives, a ation would be one duals may be exposed rs or more in a day).	 indicative examples include public footpaths, playing fields, parks and shopping streets.
examples include office rkers but will generally workers occupationally PM10, as protection is Health and Safety at tion.	
ects	

Table 1.2: Determining Recepto	r Sensitivity	
• locations with an international or national designation <i>and</i> the designated features may be affected by dust soiling; or	• locations where there is a particularly important plant species, where its dust sensitivity is uncertain or unknown; or	 locations with a local designation where the features may be affected by dust deposition.
 locations where there is a community of a particularly dust sensitive species such as vascular species included in the Red Data List For Great Britain. indicative examples include a Special Area of Conservation (SAC) designated for acid heathlands or a local site designated for lichens adjacent to the demolition of a large site containing concrete (alkali) buildings. 	 locations with a national designation where the features may be affected by dust deposition. indicative example is a Site of Special Scientific Interest (SSSI) with dust sensitive features. 	• indicative example is a local Nature Reserve with dust sensitive features.

Table 1.3: Determining Sensitivity of the Area - Dust Soiling Effects on People and Property					
Receptor	Number of	Distance from the Source (m)			
Sensitivity	Receptors	<20	<50	<100	<350
	>100	High	High	Medium	Low
High	10-100	High	Medium	Low	Low
	1-10	Medium	Low	Low	Low
Medium	>1	Medium	Low	Low	Low
Low	>1	Low	Low	Low	Low

	Annual Mean Num PM ₁₀ Rec concentration	Number of Receptors	Distance	from the	Source (n	1)	
			<20	<50	<100	<200	<350
High	>32 µg/m ³	>100	High	High	High	Medium	Low
		10-100	High	High	Medium	Low	Low
		1-10	High	Medium	Low	Low	Low
	>28-32 µg/m ³	>100	High	High	Medium	Low	Low
		10-100	High	Medium	Low	Low	Low
		1-10	High	Medium	Low	Low	Low
	>24-28 µg/m ³	>100	High	Medium	Low	Low	Low
		10-100	High	Medium	Low	Low	Low
		1-10	Medium	Low	Low	Low	Low
	<24 µg/m ³	>100	Medium	Low	Low	Low	Low
		10-100	Low	Low	Low	Low	Low
		1-10	Low	Low	Low	Low	Low
Medium		>1	High	Medium	Low	Low	Low
Low		>1	Medium	Low	Low	Low	Low

Table 1.5: Determining Risk of Dust Impacts				
Sensitivity of Area Dust Emission				
	Large			
High	High Risk			
Medium	High Risk			
Low	Medium Risk			

Table 1.6: Determining Risk of Dust Impacts - Earthworks

Sensitivity of Area	Dust Emission Magnitude				
	Large	Medium	Small		
High	High Risk	Medium Risk	Low Risk		
Medium	Medium Risk	Medium Risk	Low Risk		
Low	Low Risk	Low Risk	Negligible		

Table 1.7: Determining Risk of Dust Impacts – Construction

Sensitivity of Area	Dust Emission Magnitude						
	Large	Medium	Small				
High	High Risk	Medium Risk	Low Risk				
Medium	Medium Risk	Medium Risk	Low Risk				
Low	Low Risk	Low Risk	Negligible				

Table 1.8: Determining Risk of Dust Impacts –Trackout						
Sensitivity of Area Dust Emission Magnitude						
	Large	Medium	Small			
High	High Risk	Medium Risk	Low Risk			
Medium	Medium Risk	Low Risk	Negligible			
Low	Low Risk	Low Risk	Negligible			

Volume 3: Technical Appendices Technical Appendix 8.1: Air Quality Technical Appendix

- Demolition nitude Medium Small Medium Risk Medium Risk Medium Risk Low Risk Low Risk Negligible

2. MODEL INPUTS AND RESULTS PROCESSING TOOLS

2.1 ADMS 5

- 2.1.1 The predicted impacts on local air quality associated with point source emissions associated with the operation of the scheme was assessed using Cambridge Environmental Research Consultants (CERC) atmospheric dispersion modelling system for industrial installations (ADMS-5)¹. ADMS 5 is used by several consultancies in the UK and across the world for air quality management and assessment studies of complex situations in large industrial areas.
- 2.1.2 The ADMS suite of models have been developed and validated by CERC. CERC was established in 1985 and has a leading position in environmental software development by encapsulating advanced scientific research into a number of computer models, providing user-friendly front-ends on PC based Windows platforms.
- 2.1.3 ADMS 5 model is an advanced dispersion model used to model the air quality impact of existing and proposed industrial installations. It was originally developed for regulatory authorities in the UK. Its many features include allowance for the impacts of buildings, complex terrain, coastlines and variations in surface roughness; dry and wet deposition; NOx chemistry schemes; short term releases (puffs); calculation of fluctuations of concentration on short timescales, odours and condensed plume visibility; and allowance for radioactive decay including y-ray dose. It can predict long-term and short-term concentrations, as well as calculations of percentile concentrations. The science of ADMS 5 is significantly more advanced than that of most other air dispersion models in that it incorporates the latest understanding of the boundary layer structure and goes beyond the simplistic Pasquill-Gifford stability categories method with explicit calculation of important parameters.
- 2.1.4 The ADMS 5 model validation process includes comparisons against available measured data obtained from real world situations, field campaigns and wind tunnel experiments, with the results being published on CERC's model validation page². Validation of the ADMS dispersion models has been performed using many experimental datasets that test different aspects of the models, for instance: ground/high level sources, passive and buoyant releases, buildings, complex terrain, chemistry, deposition and plume visibility. CERC is also involved in European programmes on model harmonisation, and their models were compared favourably against other EU and U.S. EPA systems. Further information in relation to this is available from the CERC web site at http://www.cerc.co.uk/environmentalsoftware/modelvalidation.html.

2.2 Point Sources

- 2.2.1 The operation of the emergency generators has been assessed according to the methodology published by the UK Environmental Agency guidance^{3,4}. The UK guidance is a conservative probabilistic approach which uses the emergency generators maximum hourly emissions to determine the number of hours that all the generators could operate simultaneously in any one year with a 1% chance of exceeding the 1-hour mean objective based on the worst modelled meteorological year.
- 2.2.2 Following the UK Environmental Agency methodology, the hourly emissions and the allowable operating hours for emergency operation were estimated from a statistical analysis of the likelihood of breaching the 1-hour objective for NO_2 concentrations by using the hypergeometric distribution function. The allowable operating hours were calculated for a 1% probability of exceeding the one-hour mean objective at the most impacted receptor location. In accordance with the emissions from specified

generators guidance, in an emergency when the operating period is greater than one hour, the calculated probability has been multiplied by 2.5. For compliance with the annual mean objectives, the predicted concentrations were scaled to the total annual operating hours that the generators were determined to run for the 1% probability of exceeding the one-hour mean objective.

- 2.2.3 The likelihood of exceeding the 1-hour mean objective also considers the baseline pollutant objective, the exceedance concentration in the model was set as follows:
 - Model exceedance concentration = (200 twice annual mean background)/0.35.
- 2.2.4 For this assessment, the conversion of NOx to NO_2 has been estimated using the worst-case assumptions set out in the UK Environment Agency guidance:
 - NO_2 ; and
 - NO₂.
- 2.2.5 For the annual average the PC is added to the baseline concentrations (process environmental twice the annual mean determined from the roads modelling assessment.
- 2.2.6 The dispersion modelling has been undertaken with five years of hourly sequenced meteorology data south of the site. The Casement Aerodrome windroses are presented in Table 2.1.
- EIAR Volume 3.
- 2.2.

concentrations in the vicinity of the site. For the short-term assessment, the background concentration is assumed to be twice the annual mean background concentration. As the dispersion modelling was undertaken for NOx emissions, for estimating the number of exceedances of the hourly mean NO₂

• For the assessment of long term (annual mean) impacts at receptors 70% of NOx is converted to

• For the assessment of short term (hourly mean) impacts at receptors 35% of NOx is converted to

contribution- PEC) and for the short-term assessment, the baseline concentrations are assumed to be

for the years 2015 to 2019 inclusive, from Casement Aerodrome which is approximately 1 km to the

2.2.7 To undertake the assessment the emergency generators were allocated their own flues which were combined in ADMS in triples or quadruples when adjacent, according to the plans configuration. The location and flues parameters used in the model are shown are shown in Technical Appendix 8.1 in the

2.2.8 Further information on the model set up is provided in Table 2.1 and shown in Figure 2.1 and Figure

¹ http://www.cerc.co.uk/environmental-software/ADMS-model.html

² http://www.cerc.co.uk/environmental-software/model-validation.html

³ Guidance Specified generators: dispersion modelling assessment. Available at: https://www.gov.uk/guidance/specified-generatorsdispersion-modelling-assessment [Accessed on 04/08/2021]

⁴ UK Environmental Agency. Guidance Specified generators: dispersion modelling assessment. Available at: https://consult.environmentagency.gov.uk/psc/mcp-and-sg-

regulations/supporting_documents/Specified%20Generators%20Modelling%20GuidanceINTERIM%20FINAL.pdf [Accessed on 04/08/2021]

Table 2.1: Roads Emissions Model Inputs						
Meteorological Data	2015-2019 Hourly meteorological data from Casement Aerodrome Station has been used in the model. The 2015-2019 combined wind rose is shown below.					
ADMS	ADMS5 version 5.2					
Latitude	53.3					
Surface Roughness	Topographic features, buildings or vegetation increase the ground's surface roughness which impact son the vertical mixing of a plume and changes the wind-speed profile at elevated heights due to mechanical turbulence generated as the air moves over the ground. Given the rural setting of the study area, a value of 0.3 m for Agricultural areas was used to represent the modelled area and the meteorological station site.					
Minimum Monin- Obukhov length	The Minimum Monin-Obukhov provides a measure of the stability of the atmosphere and allows for the effect of heat production in cities, which is not represented by the meteorological data. The minimum standard value of 10 for small towns was used to represent the modelled area and the meteorological station site.					

2.3 Terrain

2.3.1 The terrain in the vicinity of the site is flat with no slopes more than 10% and no large changes in surface roughness are expected. Following ADMS 5 manual recommendation, the terrain effects have not been included within the modelling.

2.4 Buildings

2.4.1 Tall buildings can have a substantial impact on the dispersion of pollutants from stacks, as a result shown in Figure 2.1 and Figures 2.2 have been included within the ADMS 5 model.

Table 2.2: Scenario 1 and 2 Buildings Dimensions								
Name	X (m)	Y (m)	Height (m)	Length (m) / Diameter (m)	Width (m)	Angle (Degrees)		
DUB 11.1 & 11.2	703658	703658	14.2	85.4	127	67.0		
DUB 12 A	703671	730668	14.2	83	62.0	78.0		
DUB11 B	703653	730832	14.2	63.7	43.7	67.0		
DUB12 B	703683	730632	14.2	74.1	13.0	258.0		
DUB11.1 ChillerA	703642	730822	18.5	53.0	21.2	67		
DUB11.1 ChillerB	703643	730797	18.5	22.7	36.4	157.0		
DUB11 Elc Stor	703631	730766	19.1	9.3	123.1	67		
Power Plant DUB 11	703582	730712	14	22.1	63.0	83.5		
DUB11.2 ChillerA	703667	730761	18.5	53.0	21.2	67.0		
DUB11.2 ChillerB	703668	730736	18.5	22.7	36.4	157.0		
DUB12 Elc Stor	703645	730662	19.1	8.69	63.1	78.0		
Kilcarbery Park	703773	730990	19	291.7	84.6	280.6		
Kilcarbery BP A	703985	730951	12	26.5	87.0	93.1		
Kilcarbery BP B	704023	730948	12	19.4	76.0	93.1		
Google DC	703206	730497	12	138.5	123.6	115.1		
AWS	702910	730677	12	258.3	68.2	104.5		
Power Plant DUB 12	703578	730610	14	23.1	50.1	103.9		
Dub 11.1 Lift Shaft	703622	730834	21.6	13.8	9.3	67.4		

of building downwash i.e., pollutants being drawn down in the wake of a building, giving rise to high concentrations close to the base of the buildings. Buildings within five times the stacks height have been considered in the assessment. The nearby buildings may also have an impact on the dispersion, and therefore these have also been included. The buildings set out in Table 2.2 and

Volume 3: Technical Appendices Technical Appendix 8.1: Air Quality Technical Appendix

Table 2.2: Scenario 1 and 2 Buildings Dimensions								
DUB13	703815	730819	14.2	81.2	64.1	30.2		
DUB13 Elc Stor	703800	730796	19.1	8.7	63.1	30.1		
DU13 B	703850	730804	14.2	73.1	12.7	209.6		
DUB13 Chiller 703820 730821 18.5 53.0 45.6 30.1								









Figure 2-2: Scenario 2 Modelled Buildings and Point Source Locations

Grid 2.5

results are shown in Appendix 8.2 in Volume 3.

Table 2.3: Modelled Grids							
Outer Grid 5x5 km							
Ref	Start	Finish	No. points	Spacing (m)			
Х	708610	698610	21	500			
У	735726	725726	21	500			
Z	4.5	4.5	1				
Middle Grid 3x3 km							
Х	706610	700610	61	100			
У	700610	727726	61	100			
Z	4.5	4.5	1				
Inner Grid 500x500m							
Х	703110	704110	50	20			
у	730226	731226	50	20			

Vantage Data Centers DUB11 Limited Vantage Dublin Data Center DUB-13

2.5.1 Concentrations were predicted at three grids. These consist of numerous receptors modelled at a height of 4.5m. The contour plots are centred at the coordinates 703610, 730726 with the spacing as defined in Table 2.3. Contours were modelled at 4.5m height. This was the height which modelled receptors experiences the highest concentration, and represent the second or top floor of a building. full receptor

Table 2.3: Modelled Grid	ds			
Z	4.5	4.5	1	

2.6 Hypergeometric Distribution Function

2.6.1 A worked hypothetical example as provided in Environment Agency guidance⁴ is presented below.

The applicant applies for an environmental permit to operate:

- an aggregated diesel specified generator site with a capacity of 40 MWth
- any time of the year for up to a maximum of 400 hours per year

Operations are expected to last up to 4 hours when needed.

Therefore, the operating envelope is all 8760 hours in the year. There are 400 operational hours within the operating envelope.

Dispersion modelling over the full year shows that the Predicted Environmental Concentration (PEC) exceeds the hourly mean limit value of 200mg/m³ for 300 hours at a sensitive receptor over the worst modelled meteorological year.

This gives:

- 400 operational hours the sample size denoted by 'N'
- an 8760 hour operating envelope the population size denoted by 'M'
- 300 exceedance hours or the number of failures in the population denoted by 'e'
- 8460 non-exceedance hours the number of successes in the population denoted by 'K', where K = M e = 8760 300 = 8460

The probability of randomly selecting 19 or more exceedance hours (failures) in 400 sample trials, is the same as selecting at most 'N' minus 19 non-exceedance hours (successes) in 400 sample trials (N - 19 = 400 - 19 = 381). So you can calculate the probability of an exceedance, 'P' by using the cumulative hypergeometric distribution.

$$P = \sum_{i=0}^{N-19} \frac{\binom{K}{i}\binom{M-K}{N-i}}{\binom{M}{N}}$$

Based on these data the cumulative hypergeometric distribution is 9.3%. As the continuous operations can be up to 4 hours, you multiply this probability by 2.5, giving a probability of exceedance of 23.25%. This indicates there is potential for an exceedance of the hourly standard.

The cumulative hypergeometric distribution calculates the probability to be less than 1.8% when there are 330 operational hours. Again multiplying this by the 2.5 factor gives a probability of 4.6%, indicating short term exceedances are unlikely.

Therefore we would propose to permit the generator and restrict the operational hours to 330 hours per year.

Volume 3: Technical Appendices Technical Appendix 8.1: Air Quality Technical Appendix Vantage Data Centers DUB11 Limited Vantage Dublin Data Center DUB-13

Technical Appendix 8.2: Air Quality Results

1. SCENARIO 1 DUB-13 EMERGENCY GENERATORS MODEL RESULTS

1.1 Scenario 1 DUB-13 Emergency Generators

Table 8.2.1: Scenario 1 DUB-13 Emergency Generators Maximum Annual Mean Concentrations									
Receptor	Height (m)	NO ₂ PC (µg/m ³)	PC % AQS	NO ₂ Average Background (µg/m ³)	Annual Mean PEC (µg/m ³)	PEC % AQS	Number Exceeding Hours*	Probability Exceedance for 62h operation	
R1 GF	1.5	0.36	0.89	17.4	17.8	44.4	85.4	0.0%	
R1 TF	18	0.79	1.99	17.4	18.2	45.5	1446.0	1.0%	
R2 GF	1.5	0.43	1.07	17.4	17.8	44.6	459.7	0.0%	
R2 TF	12	0.59	1.49	17.4	18.0	45.0	785.8	0.0%	
R3 GF	1.5	0.45	1.12	17.4	17.8	44.6	456.8	0.0%	
R3 TF	4.5	0.45	1.14	17.4	17.9	44.6	470.9	0.0%	
R4 GF	1.5	0.05	0.12	17.4	17.4	43.6	11.1	0.0%	
R4 TF	4.5	0.05	0.12	17.4	17.4	43.6	12.1	0.0%	
R5 GF	1.5	0.12	0.31	17.4	17.5	43.8	135.4	0.0%	
R5 TF	12	0.21	0.53	17.4	17.6	44.0	236.2	0.0%	
R6	1.5	0.10	0.24	17.4	17.5	43.7	0.0	0.0%	
R7	1.5	0.11	0.28	17.4	17.5	43.8	0.0	0.0%	
R8	1.5	0.11	0.28	17.4	17.5	43.8	0.0	0.0%	
R9	1.5	0.01	0.02	17.4	17.4	43.5	0.0	0.0%	
R10	1.5	0.01	0.02	17.4	17.4	43.5	0.0	0.0%	
R11	1.5	0.01	0.02	17.4	17.4	43.5	0.0	0.0%	
R12	1.5	0.01	0.03	17.4	17.4	43.5	0.0	0.0%	
R13	1.5	0.01	0.03	17.4	17.4	43.5	0.0	0.0%	
R14	1.5	0.01	0.03	17.4	17.4	43.5	0.0	0.0%	
R15	1.5	0.02	0.04	17.4	17.4	43.5	0.0	0.0%	
R16	1.5	0.02	0.05	17.4	17.4	43.6	0.0	0.0%	
R17	1.5	0.02	0.06	17.4	17.4	43.6	0.0	0.0%	
R18	1.5	0.03	0.07	17.4	17.4	43.6	0.0	0.0%	
R19	1.5	0.04	0.10	17.4	17.4	43.6	0.0	0.0%	
R20	1.5	0.04	0.11	17.4	17.4	43.6	0.0	0.0%	
R21	1.5	0.04	0.11	17.4	17.4	43.6	0.0	0.0%	
R22	1.5	0.04	0.11	17.4	17.4	43.6	0.0	0.0%	
R23	1.5	0.04	0.10	17.4	17.4	43.6	0.0	0.0%	
AQS 40							-		
PC: process contribution PEC: predicted environmental concentration (i.e. including background)									

2.1 Scenario 2 DUB11 and DUB12 Emergency Generators

Table 8.2.1: Scenario 2 DUB-13 and DUB-1 Campus Emergency Generators Maximum Annual									
Mean Concentrations for 29 hours Operation									
Receptor	Height (m)	NO2 PC (µg/m³)	PC % AQS	NO ₂ Average Background (µg/m ³)	Annual Mean PEC (µg/m ³)	PEC % AQS	Number Exceeding Hours*	Probability Exceedance for 62h operation	
R1 GF	1.5	0.58	1.45	17.4	18.0	45.0	2727.3	0.0%	
R1 TF	18	0.89	2.22	17.4	18.3	45.7	3426.7	0.9%	
R2 GF	1.5	0.56	1.39	17.4	18.0	44.9	1957.1	0.0%	
R2 TF	12	0.66	1.64	17.4	18.1	45.1	2286.1	0.0%	
R3 GF	1.5	0.51	1.28	17.4	17.9	44.8	1824.3	0.0%	
R3 TF	4.5	0.52	1.29	17.4	17.9	44.8	1842.4	0.0%	
R4 GF	1.5	0.08	0.21	17.4	17.5	43.7	241.3	0.0%	
R4 TF	4.5	0.09	0.22	17.4	17.5	43.7	257.6	0.0%	
R5 GF	1.5	0.44	1.10	17.4	17.8	44.6	732.2	0.0%	
R5 TF	12	0.53	1.33	17.4	17.9	44.8	1214.6	0.0%	
R6	1.5	0.14	0.34	17.4	17.5	43.8	0.0	0.0%	
R7	1.5	0.15	0.38	17.4	17.6	43.9	0.0	0.0%	
R8	1.5	0.15	0.38	17.4	17.6	43.9	0.0	0.0%	
R9	1.5	0.02	0.05	17.4	17.4	43.5	47.3	0.0%	
R10	1.5	0.02	0.04	17.4	17.4	43.5	37.2	0.0%	
R11	1.5	0.01	0.03	17.4	17.4	43.5	35.2	0.0%	
R12	1.5	0.02	0.04	17.4	17.4	43.5	36.2	0.0%	
R13	1.5	0.02	0.04	17.4	17.4	43.5	42.2	0.0%	
R14	1.5	0.02	0.05	17.4	17.4	43.6	40.2	0.0%	
R15	1.5	0.03	0.06	17.4	17.4	43.6	39.7	0.0%	
R16	1.5	0.04	0.10	17.4	17.4	43.6	76.3	0.0%	
R17	1.5	0.05	0.12	17.4	17.4	43.6	96.6	0.0%	
R18	1.5	0.06	0.14	17.4	17.5	43.6	112.9	0.0%	
R19	1.5	0.08	0.20	17.4	17.5	43.7	228.0	0.0%	
R20	1.5	0.09	0.22	17.4	17.5	43.7	249.4	0.0%	
R21	1.5	0.09	0.22	17.4	17.5	43.7	242.3	0.0%	
R22	1.5	0.09	0.21	17.4	17.5	43.7	228.0	0.0%	
R23	1.5	0.08	0.20	17.4	17.5	43.7	187.3	0.0%	
AQS		40					-		
PC: process	s contribu	tion							

PEC: predicted environmental concentration (i.e. including background)
Technical Appendix 9.1: Glossary of Noise and Vibration Terminology

1. TERMINOLOGY RELATING TO NOISE

Term	Definition
Sound Pressure	Sound, or sound pressure, is a fluctuation in air pressure over the static
	ambient pressure
Sound Pressure Level	The sound level is the sound pressure relative to a standard reference
(Sound Level)	pressure of 20μ Pa (20×10^{-6} Pascals) on a decibel scale
Decibel (dB)	A scale for comparing the ratios of two quantities including sound
	pressure and sound power. The difference in level between two sounds s
	and s2 is given by 20 log10 ($_{c1/c2}$). The decidel can also be used to
	measure absolute quantities by specifying a reference value that fixes
	one point on the scale. For sound pressure, the reference value is 20µPa.
A-weighting, dB(A)	The unit of sound level, weighted according to the A-scale, which takes
it weighting, ab(it)	into account the increased sensitivity of the human ear at some
	frequencies.
Noise Level Indices	Noise levels usually fluctuate over time, so it is often necessary to
	consider an average or statistical noise level. This can be done in several
	ways, so a number of different noise indices have been defined.
	according to how the averaging or statistics are carried out.
	A noise level index called the equivalent continuous noise level over the
-Acq, 1	time period T. This is the level of a notional steady sound that would
	contain the same amount of sound energy as the actual, possibly
	fluctuating, sound that was recorded.
	A noise level index defined as the maximum noise level during the time
	period T. L _{max} is sometimes used for the assessment of occasional loud
	noises, which may have little effect on the overall Leg noise level but will
	still affect the noise environment. Unless described otherwise, it is
	measured using the 'fast' sound level meter response.
Lan T or Background	A noise level index defined as the noise level exceeded for 90% of the
Noise Level	time over the time period T. L_{90} can be considered to be the "average
	minimum" noise level and is often used to describe the background noise
L _{10 T}	A noise level index. The noise level exceeded for 10% of the time over
10,1	the period T. L_{10} can be considered to be the "average maximum" noise
	level. Generally used to describe road traffic noise.
Free-Field	Far from the presence of sound reflecting objects (except the ground),
	usually taken to mean at least 3.5 metres
Fast Time Weighting	An averaging time used in sound level meters. Defined in BS5969.
Rating Level $(L_{Ar Tr})$	To BS 4142:2014+A1:2019, the rating level is defined as the equivalent
J (//////	continuous A-weighted sound pressure level produced by the specific
	sound source over a given reference time interval. Tr plus any
	adjustment for the characteristic features of the sound (tonality.
	impulsivity, etc).
NSR	A Noise Sensitive Receiver is any receiver that is classed as being
	sensitive to noise sources, (residential properties, churches, music
	studios etc).
R _w + C _{tr}	Weighted Sound Reduction index (R _w) with low frequency sound
	correction factor (C_{tr}). $R_w + C_{tr}$ is used when increased control of low
	frequency sound sources is required such as amplified music, and traffic

2. TERMINOLOGY RELATING TO VIBRATION

Table 2.1: Vibration Terminology			
Term	Definition		
VDV	Vibration Dose Value		
Displacement,	Vibration is an oscillat		
Acceleration and	defined in terms of di		
Velocity	that something move		
Root Mean Square	acceleration (the rate		
(r.m.s.) and Peak	one must specify whe		
Values	displacement or maxi		
Peak Particle Velocity	an average value) are		
(PPV)	damage are usually g		
	Peak Particle Velocity		
	often described in ter		

atory motion. The magnitude of vibration can be lisplacement (how far from the equilibrium position es), velocity (how fast something moves), or e of change of velocity). When describing vibration, ether peak values are used (i.e. the maximum simum velocity) or r.m.s. / r.m.q. values (effectively re used. Standards for the assessment of building given in terms of peak velocity (usually referred to as y, or PPV), whilst human response to vibration is rms of r.m.s. or r.m.q. acceleration.

Technical Appendix 9.2: Preliminary Construction Noise Assessment

Volume 3: Technical Appendices Technical Appendix 9.2: Noise and Vibration Technical Appendix

RAMBOLL

1. PLANT ITEMS AND NOISE LEVELS USED IN THE ASSESSMENT

Table 1.1: Demolition and Construction Noise Plant and Sound Power Levels Used in Assessment						
Activity	Plant	Sound Power Level L _{wA} dB	No. of plant	Overall L _{wA} dB	On-time (% of hour)	Reference
	Wheeled excavator	94	2	97	50	BS 5228 Table C4.no.10
	Dumper	111	2	114	20	BS 5228 Table C.2 ave no.s 30-31
	Loading lorries	106	2	109	10	BS 5228 Table C1. no.7
	Scaffold erection	108	1	108	20	BS 5228 Table C.2 ave no.s 26-28
Site enabling works	Generator	102	1	102	100	BS 5228 Table D.7 no.1
	Electric drills	104	2	107	10	BS 5228 Table C.4 no. 32
	Metal cutter	107	2	110	5	BS 5228 Table D.6 no.54
	Electric bolter	104	2	107	10	BS 5228 Table C.1 no.18
	Road sweeper	104	1	104	10	BS 5228 Table D.6 no.54
	Telescopic handler	102	1	102	20	BS 5228 Table C.4 no.45
	Dozer	106	1	106	20	BS 5228 Table C.8 no. 6
	Pneumatic breaker	116	2	119	50	BS 5228 Table D.2 ave 7-10
Demolition	Excavator (tracked)	110	2	113	50	BS 5228 Table D.3 ave no.s 34-40
	Dumper	101	2	104	33	BS 5228 Table D.7 ave no.s 81-92
	Generator	102	1	102	10	BS 5228 Table C.4 no. 32
	Excavator (tracked)	110	2	113	50	BS 5228 Table D.3 ave no.s 34-40
Substructure	Lorry mounted concrete pump	107	2	110	80	BS 5228 Table D.6 ave no.s 34 & 36
	Dumper	101	2	104	50	BS 5228 Table D.7 ave no.s 81-92

Table 1.1: Demolition and Construction Noise Plant and Sound Power Levels Used in Assessment						
Activity	Plant	Sound Power Level L _{wA} dB	No. of plant	Overall L _{wA} dB	On-time (% of hour)	Reference
	Road sweeper	104	2	107	30	BS 5228 Table C.4 no.90
	Generator	102	1	102	10	BS 5228 Table C.4 no. 32
	Crane	97	1	97	100	BS 5228 Table C.3 ave no.s 28-30
	Lorry mounted concrete pump	107	2	110	50	BS 5228 Table D.6 ave no.s 34 & 36
	Crane	106	1	106	50	BS 5228 Table C.4 no. 38
	Generator	102	1	102	100	BS 5228 Table C.4 no. 32
Superstructure	Electric drills	104	2	107	30	BS 5228 Table D.6 no.54
	Metal cutter	107	2	110	20	BS 5228 Table C.1 no.18
	Electric bolter	104	2	107	20	BS 5228 Table D.6 no.54
	Hydraulic access platforms	95	2	98	70	BS 5228 Table C.4 no. 57
	Road sweeper	104	2	107	10	BS 5228 Table C.4 no.90
	Generator	102	1	102	100	BS 5228 Table C.4 no. 32
Internal works / Fit-out	Welding plant	102	2	105	30	BS 5228 Table C.3 no. 31
	Electric drills	104	3	109	10	BS 5228 Table D.6 no. 54
	Generator	102	1	102	100	BS 5228 Table C.4 no. 32
External works	Excavator (tracked)	110	2	113	50	BS 5228 Table D.3 ave no.s 34-40
	Road sweeper	104	2	107	10	BS 5228 Table C.4 no.90
	Dumper	101	2	104	33	BS 5228 Table D.7 ave no.s 81-92
	Cement mixer truck	105	2	108	10	BS 5228 Table C.4 ave no.s 18 & 20

Technical Appendix 10.1A: Engineering Planning Strategy

Technical Appendix 10.2: Site-Specific Flood Risk Assessment



Vantage Data Centres Ltd.

Proposed Industrial Development, DUB13, Profile Park, Grangecastle, Co. Dublin

Report on Site-Specific Flood Risk Assessment

Vantage Data Centres Ltd.	Document Ref. No.	Kilgallen & Partners
	22050-R-SSFRA Issue PL1	Consulting Engineers Well Road, Portlaoise Co. Laois

REVISION HISTORY

Client	Vantage Data Centres Ltd.
Project	Proposed Industrial Development, DUB13, Profile Park, Grangecastle, Co. Dublin
Title	Report on Site-Specific Flood Risk Assessment

Date	Detail of Issue	Issue No.	Origin	Checked	Approved
27/10/2022	Initial issue	PL1	СР	РВ	РВ

TABLE OF CONTENTS

1.	Intro	oduction	1
2.	Proc	ess for Site-Specific Flood Risk Assessment	2
	2.1	Potential Sources of Flood Risk	2
	2.2	Flood Risk Indicators	2
	2.3	Identification of the Presence and Extent of Fluvial Flood Risk	3
	2.4	Identification of the Presence and Extent of Pluvial Flood Risk	3
	2.5	Identification of the Presence and Extent of Groundwater Flood Risk	3
	2.6	Assessment of Proposed Development	3
3.	Site	Description	5
4.	Prop	osed Development	8
	4.1	Description	8
	4.2	Vulnerability	9
5.	Fluvi	al Flood Risk – Initial Assessment	11
	5.1	Flood Risk Indicators - Desktop	11
	5.2	Flood Risk Indicators - Site Walkover	13
	5.3	Initial Assessment	18
6.	Fluvi	al Flood Risk – Detailed Assessment	19
	6.1	Estimating Peak Flood Flows	19
	6.2	Pre-development Hydrological Model	21
	6.3	Development Proposals - Surface Water Drainage	22
	6.4	Development Proposals - Road crossing of Baldonnell Stream	22
	6.5	Conclusion of Detailed Assessment of Fluvial Flood Risk	23
7.	Floo	l Risk from Groundwater	24
	7.1	Flood Risk Indicators - Desktop	24
	7.2	Flood Risk Indicators – Site Walkover	25
	7.3	Initial Assessment	25
8.	Pluvi	al Flood Risk	26
	8.1	Flood Risk Indicators - Desktop	26
	8.2	Flood Risk Indicators – Site Walkover	26
	8.3	Surface water drainage system for the proposed development	26
	8.4	Initial Assessment	26
9.	Resi	dual Flood Risk	27
	9.1	Flood Risk Management Plan	27
	9.2	Blockage in culvert immediately downstream of the Site	27
10). N	1inimum Finished Levels	28
1:	L. C	Development Management Justification Test	29

30

Proposed Industrial Development, DUB13, Profile Park, Grangecastle, Co. Dublin

12.1	Summary	30
12.2	Conclusion	31

Appendix A Schedule of Documents

Appendix B Estimation of run-off from stream catchment

1. INTRODUCTION

Vantage Data Centres Ltd. ['the Applicant'] intends to apply to South Dublin County Council for planning permission for an industrial development ['the proposed development'] on lands to the south of the New Nangor Road (R134), Dublin 22; and on land within the townlands of Ballybane and Kilbride within Profile Park, Clondalkin, Dublin 22 on an overall site of 3.79hectares ['the Site].

The Applicant appointed Kilgallen and Partners Consulting Engineers to :

- carry out a Site-Specific Flood Risk Assessment ['SSFRA'] for the proposed development in accordance with the 'Planning System and Flood Risk Management – Guidelines for Planning Authorities' ['the Guidelines'];
- prepare a report presenting the findings of the SSFRA to support the application for planning permission;

This is the report referred to above.

2. PROCESS FOR SITE-SPECIFIC FLOOD RISK ASSESSMENT

The initial stage of the SSFRA comprises an assessment of available flood risk data to identify flood risk indicators in the Study Area. If the Site is identified to be at risk of flooding, the SSFRA will proceed to a detailed assessment.

2.1 Potential Sources of Flood Risk

Potential flood risk mechanisms are summarised in Table 2-1.

Source	Mechanism
Fluvial:	Overtopping of Rivers and Streams
Pluvial:	The intensity of rainfall events is such that the ground cannot absorb rainfall run-off effectively or urban drainage systems cannot carry the run-off generated.
Groundwater:	Rising water table
Coastal:	Tidal levels and / or wave action
Infrastructure	Failure of flood protection or drainage infrastructure

Table 2-1 Flood Risk Mechanisms

As an inland site upstream of tidal influences and possible wave action, the Site is not subject to coastal flood risk and so this mechanism does not need to be considered further in this assessment.

The assessment will therefore consider the following mechanisms:

- Fluvial;
- Pluvial;
- Groundwater;
- Drainage Infrastructure (considered under Section 9 Residual Flood Risk)

2.2 Flood Risk Indicators

Indicators of flood risk are identified using available data, most of which is historically derived. Typically, this data is not prescriptive in relation to flood return periods and neither predictive nor inclusive of climate change analysis.

Flood risk indicators include:

• Records available on the OPW's National Flood Risk Website. As part of the National Flood Risk Management Policy, the OPW developed the <u>www.floodinfo.ie</u> web-based data set, which contains

information concerning historical flood data and displays related mapped information and provides tools to search for and display information about selected flood events;

- PFRA & CFRAM mapping produced under the CFRAM programme;
- The Strategic Flood Risk Assessment carried out to inform the making of the Local Area Plan;
- Geological Survey of Ireland (GSI) mapping Hydrogeological mapping maintained by the GSI and made available through its website <u>www.gsi.ie</u>;
- Ordnance Survey mapping Ordnance Survey maps include areas which are marked as being "Liable to Floods". Generally, these areas are only shown identified indicatively and suggest historical flooding, usually recurrent. In addition, the maps indicate areas of wet or hummocky ground, bog, marsh, springs, rises and wells as well as surface water features including rivers, streams, bridges, weirs and dams;
- Topographical survey information;
- Records of previous floods from other sources;
- Flood Studies, Reports and Flood Relief Schemes carried out in the vicinity of the Study Area;
- Site Walkover.

2.3 Identification of the Presence and Extent of Fluvial Flood Risk

Where the initial process of examining flood risk indicators demonstrates the existence of a risk of fluvial flooding, the study progresses to the next stage, which is a detailed flood risk assessment. This is based on field measurements and hydrological modelling and enables mapping of the zones of Flood Risk within the Site to be established.

In accordance with the Guidelines, flood risk zones are categorized as follows:

- Flood Zone A where the probability of flooding in any year is greater than 1% (i.e. Flood Zone in respect of a flood with a return period of 100years);
- Flood Zone B where the probability of flooding in any year is between 0.1% and 1% (i.e. Flood Zone in respect of a flood with a return period of between 100years and 1,000years);
- Flood Zone C where the probability of flooding in any year is less than 0.1% (i.e. Flood Zone in respect of a flood with a return period of greater than 1,000years).

2.4 Identification of the Presence and Extent of Pluvial Flood Risk

Where the initial process of examining flood risk indicators demonstrates the existence of a risk of pluvial flooding, the study progresses to the next stage, which is a detailed assessment to establish the extent of pluvial flood risk at the Site.

2.5 Identification of the Presence and Extent of Groundwater Flood Risk

Where the initial process of examining flood risk indicators demonstrates the existence of a risk of flooding from groundwater, the assessment progresses to the next stage, which is a detailed assessment to establish the extent of groundwater flood risk at the Site.

2.6 Assessment of Proposed Development

As described in the previous paragraphs, the first stages of the assessment process are concerned with identifying whether the Site is at risk of pluvial, fluvial or groundwater flooding and establishing the extent of any such flood risks.

The next steps in the assessment process are:

- Determination of the impact that any of the identified flood risks will have on the proposed Development;
- Determination of any impact that the Development itself might have in terms of increasing the level of flood risk elsewhere outside the Site;
- Identification of mitigation measures in respect of any such impacts and identification of any residual risks after those mitigation measures are put in place;
- Applying the Development Management Justification Test if appropriate;
- Providing a conclusion as to the appropriateness of the proposed development in terms of flood risk.

3. SITE DESCRIPTION

Figure 3-1 shows the Site in the context of its immediate surroundings and Figure 3-2 shows the main drainage features and site topography indicatively.

The Site is located in Profile Park Business Park. It is bounded:

- to the north by the R134 New Nangor Road;
- to the east by a distributor road ['the Park Road'] through Profile Park;
- to the west and south by unused agricultural lands which are the site for a recently approved industrial development (PI Reg. Ref. No. SD21A/0241).

The Site is undeveloped and does not appear to be used for any purpose.

Main Drainage Features

The Baldonnell Stream ['the Stream'] crosses under the Park Road and enters the Site close to its southern boundary. The Baldonnell Stream flows through the Site for approximately 45m and then exits the Site at its west boundary. 190m downstream of the Site the Stream flows through a short 600mm dia. culvert. 300m downstream of the Site, the Stream discharges to a long twin-pipe culvert.

There is no evidence of pluvial drainage entering the Site.

The vegetation is suggestive of poorly draining upper soils but there is no evidence of standing groundwater.

Topography

The Site can be described as relatively flat, with a general shallow fall from northeast to southwest.





Figure 3-1 Site Context



Figure 3-2 Site Topography / Main Drainage Features

4. **PROPOSED DEVELOPMENT**

4.1 Description

The proposed development comprises industrial buildings, parking areas, circulation roads, ancillary landscaping, drainage (including SUDS measures), services and ancillary Site works.

The development will consist of the demolition of the two storey dwelling (207.35sqm) and associated outbuildings and farm structures (348.36sqm); and the construction of 1 no. two storey data center with plant at roof level and associated ancillary development that will have a gross floor area of 12,893sqm that will consist of the following:

- 1 no. two storey data center (Building 13) with a gross floor area of 12,893sqm. It will include 13 no. emergency back-up generators of which 12 will be double stacked and one will be single stacked within a compound to the south-western side of the data center with associated flues that each will be 22.316m in height and 7 no. hot-air exhaust cooling vents that each will be 20.016m in height;
- the data center will include data storage rooms, associated electrical and mechanical plant rooms, loading bays, maintenance and storage spaces, office administration areas, and plant including PV panels at roof level as well as a separate house generator that will provide emergency power to the admin and ancillary spaces. Each generator will include a diesel tank and there will be a refuelling area to serve the proposed emergency generators;
- The data center will have a primary parapet height of 14.246m above ground level, with plant and screen around plus a plant room above at roof level. The plant room has an overall height of 21.571m;
- Construction of an internal road network and circulation areas, with a staff entrance off Falcon Avenue to the east, as well as a secondary vehicular access for service and delivery vehicles only across a new bridge over the Baldonnel Stream from the permitted entrance as granted under SDCC Planning Ref. SD21A/0241 from the south-west, both from within Profile Park that contains an access from the New Nangor Road (R134);
- Provision of 60 no. car parking spaces (to include 12 EV spaces and 3 disabled spaces), and 34 no. cycle parking spaces;
- Signage (5.7sqm) at first floor level at the northern end of the eastern elevation of the data center building; and
- Ancillary site development works, will include footpaths, attenuation ponds that will include an amendment to the permitted attenuation pond as granted to the north of the Baldonnel Stream under SDCC Planning Ref. SD21A/0241, as well as green walls and green roof. The installation and connection to the underground foul and storm water drainage network, and installation of utility ducts and cables, that will include the drilling and laying of ducts and cables under the internal road network within Profile Park. Other ancillary site development works will include hard and soft landscaping that will include an amendment to the permitted landscaping as granted under SDCC Planning Ref. SD21A/0241, lighting, fencing, signage, services road, entrance gates, and sprinkler tanks.

A schematic layout for the proposed development is shown in Figure 4-1. Relevant proposals for the development are shown on the schedule of documents contained in Appendix A.



Figure 4-1 Schematic Layout of Proposed Development

4.2 Vulnerability

Table 3.1 of the Guidelines classifies different types of development in terms of their vulnerability to flooding. Figure 4-2 contains an extract from this table which shows industrial development classified as Less Vulnerable. The proposed development is an industrial development and so falls under this classification.

Less vulnerable development	Buildings used for: retail, leisure, warehousing, commercial, industrial and non-residential institutions; Land and buildings used for holiday or short-let caravans and camping, subject to specific warning and evacuation plans;
	Land and buildings used for agriculture and forestry;
Waste treatment (except landfill and hazardous waste);	
	Mineral working and processing; and
	Local transport infrastructure.

Figure 4-2 Classification of development type by vulnerability to flooding

Table 3.2 of the Guidelines provides a matrix of development vulnerability versus Flood Zone which illustrates the appropriateness of a development type for each Flood Zone. This table is reproduced in Figure 4-3 and shows the Guidelines regards Less Vulnerable development as being appropriate for Sites in Flood Zone B and requiring the Justification Test for Sites in Flood Zone A

	Flood Zone A	Flood Zone B	Flood Zone C	
Highly vulnerable development (including essential infrastructure)	Justification Test	Justification Test	Appropriate	
Less vulnerable development	Justification Test	Appropriate	Appropriate	
Water-compatible development	Appropriate	Appropriate	Appropriate	
Table 3.2: Matrix of vulnerability versus flood zone to illustrate appropriate development and that required to meet the Justification Test.				

Figure 4-3 Matrix of vulnerability versus Flood Zone

5. FLUVIAL FLOOD RISK – INITIAL ASSESSMENT

5.1 Flood Risk Indicators - Desktop

A number of datasets were interrogated for indicators of fluvial flood risk:

(i) SFRA

Mapping prepared as part of the Strategic Flood Risk Assessment for the South Dublin County Development Plan indicates the Site is not affected by either the 0.1% AEP and 1.0% AEP flood events. The only exception is at the southern corner where the existing Park Road is shown to be subject to flood risk. An extract from this mapping is shown in Figure 5-1.



Figure 5-1 Extract from SFRA showing fluvial flood risk at the Site

Report on Site-Specific Flood Risk Assessment

(ii) OPW National Flood Hazard Mapping Website

The OPW maintains the National Flood Hazard Mapping website (floodinfo.ie) which contains information about locations that may be at risk from flooding. The source of this information includes Local Authorities and other historic records such as newspaper articles and other documentation about reported floods.

The website does not have any records of flooding at this location.

(iii) CFRAM

Mapping prepared as part of the CFRAM programme indicates the Site is not affected by the 0.1% AEP flood event but not the 1.0% AEP event. As with SSFRA mapping, the only exception is at the southern corner where the existing Park Road is shown to be subject to flood risk. An extract from this mapping is shown in Figure 5-2.



Figure 5-2 Extract from CFRAM mapping showing fluvial flood risk at the Site

(iv) Ordnance Survey Mapping

Figure 5-3 shows the historic 25" OS mapping for the Site and its immediate surroundings. There is no indication of flood risk at the Site.



Figure 5-3 Historic OS Map

5.2 Flood Risk Indicators - Site Walkover

The Baldonnell Stream ['the Stream'] crosses under the Park Road through a twin-pipe culvert, each pipe 1400mm diameter, and enters the Site close to its southern boundary.

The Baldonnell Stream flows through the Site for approximately 45m and then exits the Site at its west boundary.

190m downstream of the Site the Stream flows through a short 600mm dia. culvert.

300m downstream of the Site, the Stream discharges to a long twin-pipe culvert. The inlet to this culvert is poorly constructed and hydraulically inefficient; it was observed that in addition to the pipes, the gaps between the pipes also provides a flow path for the stream to discharge to.

A visual assessment of the channel of the stream suggests the twin-pipe culvert will have a significantly lower hydraulic capacity than the channel.



Figure 5-4 View of Site at East Boundary from North



Figure 5-5 View of Site at West Boundary from North



Figure 5-6 View of Site at West Boundary from South



Figure 5-7 Upstream View of Culvert under Park Road

Report on Site-Specific Flood Risk Assessment



Figure 5-8 Typical View of Stream Channel through Site



Figure 5-7 Typical Section of Stream Channel downstream of Site



Figure 5-8 Inlet to twin-pipe culvert

Report on Site-Specific Flood Risk Assessment

5.3 Initial Assessment

The indicators described in Section 5.1 suggest the Site is not at significant risk from fluvial flooding. However, the Site Walkover suggests the Site may be at risk of flooding caused by inadequate hydraulic culvert capacity downstream of the Site.

Accordingly, it is the conclusion of this SSFRA that detailed assessment of fluvial flood risk is appropriate.

6. FLUVIAL FLOOD RISK – DETAILED ASSESSMENT

6.1 Estimating Peak Flood Flows

The catchment area for the stream, shown outlined blue on Figure 6-1, measures 1.0 km².



Figure 6-1 Catchment Area for Stream

The OPW provides a Web Portal for estimating peak flood flows in natural catchments (Flood Studies Update (FSU) Web Portal). While the use of this portal is generally considered best practice for the estimation of flood flows, the portal advises particular caution where peak flows are being estimated for catchments of less than 25km². Accordingly, peak flood flows were estimated using statistical methods for ungauged small catchments.

Table 6-1 shows a number of Physical Catchment Descriptors taken from the FSU portal that were used to estimate peak flood flows.

PCD	Value	
BFISOIL	0.5199	
SAAR	714.82	mm
FARL	1	
DRAIND	0.721	km/km ²
S1085	0.1	m/km
ARTDRAIN2	0	
ARTDRAIN2	0	
URBEXT	0.3589	

Table 6-1 Physical Catchment Descriptors from FSU Web Portal

Initially, various alternative statistical methods were used and the results of these are reproduced in Table 6-2 (details of these calculations are included in Appendix B). All flow estimates include a climate change factor of 20%.

Typically, peak flow estimates for the 1% AEP flood event are below 1.0m³/s. The only exception is the flow estimate given by IH124 which is over three times the next greatest estimate and not consistent with the size of the catchment and the drainage infrastructure in the area. IH124 it generally considered to over-estimate peak flood flows *{WP4.2 Flood Estimation in Small and Urbanised Catchments – OPW 2012}*. Therefore, the IH124 flow estimate will not be used and instead the flow estimates used will be the next greatest; i.e. those given by the FEH-Statistical method.

Method	1% AEP	0.1% AEP
	m³/s	m³/s
IH124	2.79	3.69
FSU Update	0.47	0.64
FSU-3V	0.14	0.18
FSU_7V	0.37	0.51
FEH-Statistical	0.89	1.20

Table 6-2Estimates for Peak Flood Flows

6.2 Pre-development Hydrological Model

A hydrological model was prepared to simulate flow patterns during the 1% and 0.1% AEP rainfall events. This model was developed using the River and Flood Analysis module of the industry standard package Infrastructure Ultimate Design Suite produced by Autodesk. The hydrological modelling within this module is itself based on the HEC-RAS modelling software produced by the US Army Corps of Engineers.

The module calculates flood risk zones for the catchment based on the peak flood flows and the following:

- a terrain model created using topographical survey data;
- dimensions of culverts and other drainage structures;
- appropriate values for the roughness coefficient 'Manning's n' as determined from visual inspection of the Site.

Culvert downstream of Site

As described above, the stream is culverted downstream of the Site. This culvert comprises two 600mm diameter pipes at its inlet. A CCTV survey of the culvert revealed that one of the pipes changes to 450mm diameter approximately 20m from the inlet. Furthermore, both pipes show significant blockages that greatly reduce the capacity of the culvert; the extent of these blockages was such that the survey could not be completed for the full length of the culvert.

In regard to this culvert, the hydraulic models assumes:

- the culvert comprises a 600mm dia. pipe and 450mm dia. pipe for its entire length;
- the culvert will be cleared of all obstructions and maintained free of debris / deposition throughout the operational life of the proposed development;
- the maximum depth of deposition in the culvert will be 100mm.

Pre-Development Fluvial Flood Risk Zones at the Development Site

The map in Figure 6-2 shows the existing fluvial flood risk zones determined using the hydrological model described above. Peak water levels are as follows:

- 1.0% AEP Flood Event 72.15 m;
- 0.1% AEP Flood Event 72.53 m.

The Site was found to be <u>not</u> affected by either 1% or 0.1% AEP flood risk zones.



Figure 6-2 Fluvial flood risk zones - Pre-Development

6.3 Development Proposals - Surface Water Drainage

The surface water drainage system for the proposed development has been designed by Pinnacle Consulting Engineers who have provided design calculations demonstrating compliance with the Greater Dublin Strategic Drainage Study in the schedule of documents listed in Appendix A.

Full compliance with GDSDS ensures the drainage system ensures the flood regime in the receiving stream will not be affected, thus not giving rise to flood risk elsewhere.

6.4 Development Proposals - Road crossing of Baldonnell Stream

As described in Section 5.2, the Stream crosses under the Park Road through a twin-pipe culvert, each pipe 1400mm diameter. The proposed road crossing is 20m downstream from the Park Road culvert.

Figure 6-3 shows a box culvert to convey the Stream under the proposed crossing.

The internal dimensions of the box culvert are 1.4m in height and 3.5m in width and it thus has a significantly greater hydraulic capacity than that of the Park Road culvert.

To meet the requirements of the Office of Public Works (OPW) for granting Section 50 approval under the Arterial Drainage Act, culverts are typically required to have a minimum 300mm clearance between the 1% AEP water level and the soffit of the culvert. Figure 6-3 shows the box culvert will have 650mm clearance between the 1% AEP water level and the soffit level, thus comfortably exceeding OPW requirements.



Figure 6-3 Fluvial flood risk zones - Pre-Development

6.5 Conclusion of Detailed Assessment of Fluvial Flood Risk

The proposed development will not be at risk of flooding from fluvial sources and will not give rise to fluvial flood risk elsewhere.

7. FLOOD RISK FROM GROUNDWATER

7.1 Flood Risk Indicators - Desktop

Various datasets were interrogated for indicators of flood risk from Ground Water. These comprise:

(i) OPW National Flood Hazard Mapping

Records from the National Flood Hazard Mapping website maintained by the OPW do not contain any evidence of flood events at the Site associated with fluctuations in groundwater level;

(ii) Geological Survey of Ireland (GSI)
 The GSI maintains a web portal that provides data for Groundwater (<u>https://www.gsi.ie</u>), including groundwater flooding data.
 The portal does not show any groundwater flooding at or in the vicinity of the Site.

The portal indicates the Site to be in an area of high groundwater vulnerability with subsoils of low permeability.

(iii) Historical Ordnance Survey Mapping

Historical OS maps shows a well immediately northwest of the Site. No other information is available for this well. There is no indication of springs at the Site.



Figure 7-1 Historic OS Mapping

(iv) Ground Investigation

A ground investigation at the Site encountered groundwater generally between 1.0m and 2.0m blow existing ground level.

(v) Topography

The topography of the Site does not include localised low-lying areas that would give rise to groundwater ponding to a significant depth.

7.2 Flood Risk Indicators – Site Walkover

No evidence of flood risk from groundwater was observed during a Site walkover.

7.3 Initial Assessment

The ground investigation did encounter water-bearing strata relatively close to the surface however all indicators suggest the Site is not at risk from groundwater flooding. Detailed assessment of flood risk from this mechanism is not required.

8. PLUVIAL FLOOD RISK

8.1 Flood Risk Indicators - Desktop

A number of datasets were interrogated for indicators of pluvial flood risk:

(i) SFRA

The Strategic Flood Risk Assessment for the South Dublin County Council does not contain any information regarding pluvial flood risk at the Site.

(ii) OPW National Flood Hazard Mapping Website

The OPW maintains the National Flood Hazard Mapping website (floodinfo.ie) which contains information about locations that may be at risk from flooding. The source of this information includes Local Authorities and other historic records such as newspaper articles and other documentation about reported floods. This source does not register any previous flood events associated with pluvial flood risk at the Site.

- *(iii) CFRAM study programme undertaken by the OPW* Maps prepared for the CFRAM study programme do not show any pluvial flood risk at the Site.
- *(iv)* Urban Drainage Systems The Site is not affected by urban drainage systems that would give rise to overland flow across the Site.

8.2 Flood Risk Indicators – Site Walkover

No indicators of pluvial flood risk were observed during a site walkover

8.3 Surface water drainage system for the proposed development

The surface water drainage system for the proposed development has been designed by Pinnacle Consulting Engineers to comply with the Greater Dublin Strategic Drainage Study.

Full compliance with GDSDS ensures the drainage system will have sufficient capacity to accommodate rainfall events up to 1% AEP (including climate change) without causing pluvial flood risk within the development and without leading to an increase in pluvial flood risk elsewhere

8.4 Initial Assessment

Based on the indicators described in Section 8.1, on the site walkover described in Section 8.2 and the design of the surface water drainage system as described in Section 8.3, the initial assessment indicates the Site is not at risk from pluvial flooding and further assessment is not required.
9. RESIDUAL FLOOD RISK

Residual risk is the risk that remains after all mitigation measures to reduce the frequency of flooding have been taken.

9.1 Flood Risk Management Plan

The assessment to this point has found the proposed development is not at risk of flooding. However, all developments include some element of residual flood risk that must be addressed during their operational lives; for example the failure of building drainage due to lack of maintenance.

To address this residual risk, it is recommended that a Site-Specific Flood Risk Mitigation Plan prepared in accordance with the Guidelines is implemented throughout the operational life of the proposed development.

9.2 Blockage in culvert immediately downstream of the Site

As described already, the stream is culverted downstream of the Site. This culvert comprises two 600mm diameter pipes at its inlet. A CCTV survey of the culvert revealed that one of these pipes changes to 450mm diameter approximately 20m from the inlet. Furthermore, the CCTV survey found both pipes to have significant blockages that greatly reduce the overall capacity of the culvert; the extent of these blockages was such that the survey could not be completed for the full length of the culvert.

Therefore, the condition and size of the culvert downstream of the blockages is unknown and there is potential, for example in the event of culvert collapse, of the stream surcharging within the Site to a level exceeding that predicted by the hydrological models. To mitigate this risk, it is recommended that an overflow be constructed from the Site which would allow such excess to discharge to the stream immediately downstream of the Nangor Road. Subject to the capacity being available, this overflow could possibly discharge to existing surface water drainage in the Nangor Road but a dedicated surface water pipe might be required from the Site to a new outfall downstream of the Nangor Road.

The Flood Risk Mitigation Plan described in Section 9.1 must include should include a maintenance regime for all drainage features within the Site and for regular inspection of drainage features immediately upstream and downstream of the Site.

10. MINIMUM FINISHED LEVELS

In order to ensure that elements of development of the Site not compatible with water (i.e. roads, buildings etc.) are not at risk of flooding, the Guidelines recommend that floor levels and road levels be kept above the 1% AEP flood level with an appropriate allowance for freeboard.

A freeboard of 500mm is appropriate for floor levels and a freeboard of 250mm is appropriate for road levels.

The maximum water level during the 1% AEP flood event is 72.15m. The minimum floor level is 74.00m and the minimum parking level is 73.45m and so both meet the recommendations of the Guidelines.

11. DEVELOPMENT MANAGEMENT JUSTIFICATION TEST

A Development Management Justification Test was carried out in respect of the proposed development in accordance with Section 5.15 of the Flood Risk Management Guidelines and incorporating the findings of the subject FRA. Table 11.1 presents the results of this test which conclude that the proposed development satisfies the criteria of the Justification test.

1.1	The s an op	ubject lands have been zoned or otherwise designated for the particular use or form of development in erative development plan, which has been adopted or varied taking account of these Guidelines.				
	Ye	5				
1.2	The p	proposal has been subject to an appropriate flood risk assessment which demonstrates that :				
	(i)	the proposed development will not increase flood risk elsewhere and, if practicable, will reduce overall flood risk;				
		Yes				
	(ii)	the proposed development includes measures to minimise flood risk to people, property, the econom and the environment as far as reasonably possible;				
		The proposed development includes proposals for treating and controlling surface water discharge which, will minimise flood risk to people, property, the economy and the environment as far as reasonably possible.				
	(iii)	the proposed development includes measures to ensure that residual risks to the area and/or development can be managed to an acceptable level as regards the adequacy of existing flood protection measures or the design, implementation and funding of any future flood risk management measures and provisions for emergency services access;				
		The proposed development does not impact on any existing flood protection measures and will not prevent possible future flood risk management measures.				
	(iv)	the proposed development addresses the above in a manner that is also compatible with the achievement of wider planning objectives in relation to development of good urban design and vibrant and active streetscapes.				
		Yes.				

Table 11.1 Justification Test

12. SUMMARY AND CONCLUSION

12.1 Summary

This report presents the findings of a Site-specific flood risk assessment (SSFRA) carried out by Kilgallen and Partners in regard to proposed development on lands to the south of the New Nangor Road (R134), Dublin 22 and on land within the townlands of Ballybane and Kilbride within Profile Park, Clondalkin, Dublin 22 on an overall site of 3.79hectares ['the Site].

The SSFRA was carried out in accordance with the document '*Planning System and Flood Risk Management – Guidelines for Planning Authorities*' ['the Guidelines'].

Initial assessment

For an inland Site of this nature and for which there are no existing flood defence mechanisms that could affect flood risk at the Site, the potential flood risk mechanisms are Fluvial, Pluvial, Groundwater and failure of drainage infrastructure (assessed as a residual risk).

Initial assessment of existing flood risk indicators indicate the Site is not at risk from either Pluvial or Groundwater flooding. The designers of the surface water drainage system have confirmed the surface water drainage system for the proposed development is designed in accordance with the Greater Dublin Strategic Drainage Study and so will be sufficient to ensure surface water run-off from the proposed development will cause flood risk within the proposed development and will not give rise to flood risk elsewhere.

Initial assessment of flood risk indicators suggest the Site could be at risk from Fluvial Flooding during the 1.0% AEP and 0.1% AEP events. Accordingly, a detailed assessment of fluvial flood risk was carried out.

Detailed assessment of fluvial flood risk

The detailed assessment of fluvial flood risk confirmed the Site is not affected by Flood Risk Zone A (the 1% AEP flood event) and to a greater extent by Flood Risk Zone B (the 0.1% AEP flood event).

The surface water drainage system for the proposed development has been designed by Pinnacle Consulting Engineers in compliance with the Greater Dublin Strategic Drainage Study. Full compliance with GDSDS ensures the drainage system ensures the flood regime in the receiving stream will not be affected, thus not giving rise to flood risk elsewhere.

The proposed development includes a road crossing of the Park Road culvert. A box culvert with internal dimensions of 1.4m in height and 3.5m can installed at this crossing and would provide a significantly greater hydraulic capacity than that of the Park Road culvert and comfortably exceed OPW requirements for clearance between the soffit level of the culvert and the 1% AEP water level.

Finished levels for buildings and roads in the proposed development provide an appropriate freeboard above the 1% AEP water level in accordance with the Guidelines.

The detailed assessment of fluvial flood risk concluded the proposed development will not be at risk of flooding from fluvial sources and will not give rise to fluvial flood risk elsewhere.

Recommendations arising from assessment of residual flood risk

All developments include some element of residual flood risk that must be addressed during their operational life. To address this residual risk, it is recommended that a Site-Specific Flood Risk Mitigation Plan prepared in accordance with the Guidelines is implemented throughout the operational life of the proposed development. This plan should include a maintenance regime for all drainage features within the Site and for regular inspection of drainage features immediately upstream and downstream of the Site.

A CCTV survey of a culvert downstream of the Site revealed significant blockages that greatly reduce its capacity. The detailed fluvial flood risk assessment carried out for this report assumed the culvert is cleared of all obstructions and maintained free of debris / deposition throughout the operational life of the proposed development. However, the condition and size of the culvert downstream of the blockages is unknown and there is potential, for example in the event of culvert collapse, of the stream surcharging to the Site to a level exceeding that predicted by the hydraulic model. To mitigate this risk, it is recommended that an overflow be constructed from the Site which would allow such excess to discharge to the stream immediately downstream of the Nangor Road. Subject to the capacity being available, this overflow could possibly discharge to existing surface water drainage in the Nangor Road but a dedicated surface water pipe might be required from the Site to a new outfall downstream of the Nangor Road.

Justification Test

The proposed development was subject to and passed the Development Management Justification Test.

12.2 Conclusion

Assuming the implementation of the recommendations arising from this assessment, the proposed development is not at risk of flooding and will not increase flood risk elsewhere. The proposed development is therefore appropriate from a flood risk perspective.

Appendix A

Schedule of Relevant Planning Documents

PINNACLE CONSULTING ENGINEERS DUB13-DR-SP-C124-V2-WS3-PIN-PROPOSED LEVELS & WATERMAIN LAYOUT DUB13-DR-UG-C127-V2-WS3-PINPROPOSED DRAINAGE LAYOUT DUB13-DR-SP-C130-V2-WS3-PIN-EXTERNAL WORKS LAYOUT DUB13-RP-00-C001-V1-WS3-PIN Appendix B

Estimation of Run-off from Stream Catchment

IH124 Estimation of Q $_{100}$ and Q $_{1000}$					
$Q_{BAR RURAL} = 0.00108 \times AREA^{0.89} \times SAAR^{1.17} \times SOIL^{2.17}$					
Characteristic	Value	Unit	Source		
Area (A)	1.0	km ²	FSU		
Average Annual Rainfall (SAAR)	715	mm	FSU		
G1 % =	0	%	Fig I 4.18		
G2 % =	0	%	Fig I 4.18		
G3 % =	0	%	Fig I 4.18		
G4 % =	0	%	Fig I 4.18		
G5 % =	100	%	Fig I 4.18		
Soil index (G) =	0.50	%			
Q _{BAR RURAL} =	0.52	m3/sec			
CWI =	106.3		Fig I 6.62		
CIND =	45.96		Eqn 7.2		
NC =	0.75		Eqn 7.3		
urban =	0.4		FSU		
Q bar urban / Q bar rural =	1.367		Eqn 7.4		
Q _{BAR} =	0.717	m3/sec			
Q $_{100}$ / Q $_{BAR}$ (Ireland)	1.96		FSR - Ireland		
$Q_{1,000}$ / Q_{BAR} (Ireland)	2.6		FSR - Ireland		
Q ₁₀₀ =	1.406	m3/sec			
Q _{1,000} =	1.865	m3/sec			
Factorial Error Factor =	1.651		Page 37 IOH124		
Climate Change Factor =	1.2		FRMG		
Q ₁₀₀ =	2.79	m3/sec			
Q 1,000 =	3.69	m3/sec			

FSU Update estimation of Q ₁₀₀ & Q ₁₀₀₀				
Characteristic	Value	Unit	Source	
Area	1.0	km ²	FSU Portal	
SAAR	715	mm	FSU Portal	
BFI _{soil}	0.520		FSU Portal	
FARL	1.0		FSU Portal	
S1085	0.10	m/km	FSU Portal	
QMED _{rural}	0.09	m3/s		
URBEXT	0.36		FSU Portal	
QMED _{urban}	0.14			
Climate Change Factor	1.2		OPW	
Q ₁₀₀ / QMED _{rural}	2.77		FSU Portal	
Q ₁₀₀₀ / QMED _{rural}	3.74		FSU Portal	
Q 100	0.473	m3/sec		
Q 1,000	0.639	m3/sec		

FSU-3V estimation of Q ₁₀₀ & Q ₁₀₀₀							
Characteristic Value Unit Source							
Area	1.0	km ²	FSU Portal				
BFI _{soil}	0.520		FSU Portal				
SAAR	715	mm	FSU Portal				
QMED	0.041	m3/s					
Climate Change Factor	1.2		OPW				
Q ₁₀₀ / QMED	2.77						
Q ₁₀₀₀ / QMED	3.74						
Q 100	0.136	m3/sec					
Q 1,000	0.183	m3/sec					

FSU-7V estimation of Q ₁₀₀ & Q ₁₀₀₀				
Characteristic	Value	Unit	Source	
Area	1.0	km ²	FSU Portal	
BFI _{soil}	0.520		FSU Portal	
SAAR	715	mm	FSU Portal	
FARL	1.0		FSU Portal	
DRAIND	0.72	km/km ²		
S1085	0.10	m/km	FSU Portal	
ARTDRAIN	0.00			
QMED _{rural}	0.072	m3/s		
URBEXT	0.36		FSU Portal	
QMED _{urban}	0.11			
Climate Change Factor	1.2		OPW	
Q ₁₀₀ / QMED _{rural}	2.77		FSU Portal	
Q ₁₀₀₀ / QMED _{rural}	3.74		FSU Portal	
Q 100	0.375	m3/sec		
Q 1,000	0.506	m3/sec		

FEH-Statistical estimation of Q ₁₀₀ & Q ₁₀₀₀				
Characteristic	Value	Unit	Source	
Area	1.0	km ²	FSU Portal	
SAAR	715	mm	FSU Portal	
FARL	1.0		FSU Portal	
BFI _{soil}	0.520		FSU Portal	
QMED	0.27	m3/s		
Climate Change Factor	1.2		OPW	
Q ₁₀₀ / QMED	2.77		FSU Portal	
Q ₁₀₀₀ / QMED	3.74		FSU Portal	
Q 100	0.885	m3/sec		
Q 1,000	1.195	m3/sec		

Technical Appendix 10.3A: Foul and Surface Water Drainage Layout





G

C

Technical Appendix 10.4N: Engineering Planning Report Letter of Conformity



Grosvenor Court 67a Patrick Street Dun Laoghaire Dublin **Phone** +353 1 231 1041

Email

dublin@iepinnacle.com

Website

www.pinnacleconsultingengineers.com

Wednesday 01 March 23

Planning Department

South Dublin County Council

County Hall, Tallaght

Dublin 24

D24 A3XC

Ref: P2207053

RE: Vantage Data Centres Dub 11 Ltd., Construction of 1No. Two Storey Data Centre, Townlands of Ballybane & Kilbride within Profile Park, Clondalkin, Dublin 22

Planning Reg. Ref. No. SD22A/0420

Further to the Additional Information request pertaining to Items 4, 10, 13 & 14(a) in respect of the above development, as received from the Local Authority, dated 12th January 2023, we would respond as follows:-

Item 4: The applicant is requested to submit a revised layout not less than 1:500 scale showing a footpath and cycle lane along the northern boundary to match the existing further west along the R134. The footpath and cycle lane shall be constructed to SDCC standards for public roads. The works on the public road will be undertaken by the applicant as part of the overall planning permission. The applicant is requested to secure the relevant letter of consent from SDCC.

Response:

Refer to Pinnacle Consulting Engineers Drawing No. DUB13-DR-XX-C104-V1-WS3-PIN-C104 for details of the layout showing a footpath and cycle lane along the northern boundary to match the existing further west along the R134. The footpath and cycle lane will be constructed to SDCC standards for public roads.



Item 10: The applicant is requested to demonstrate compliance with the SDCC SUDS Design Guide 2022, and Policies GI3, GI4, GI5, IE3, SM2, SM7, and sections 4.3.1, 12.7.6, 12.11.1, and 12.11.3. of the South Dublin County Development Plan 2022 - 2028 in relation to sustainable drainage systems.

(B) In relation to SUDs, the applicant is requested to submit plans showing how surface water shall be attenuated to greenfield run off rates and showing what SuDS (Sustainable Drainage Systems) are proposed.

(C) SUDs Management - The applicant is requested to submit a comprehensive SUDS Management Plan to demonstrate that the proposed SUDS features have reduced the rate of runoff into the existing surface water drainage network. A maintenance plan should also be included as a demonstration of how the system will function following implementation.

(D) Natural SUDS features should be incorporated into the proposed drainage system for the development such as bio-retention/constructed tree pits, permeable paving, green roofs, filtration planting, filter strip etc. In addition, the applicant should demonstrate how the proposed natural SUDS features will be incorporated and work within the drainage design for the proposed development. The applicant is requested to refer to the recently published 'SDCC Sustainable Drainage Explanatory, Design and Evaluation Guide 2022' for acceptable SUDS tree pit details.

(E) The applicant is requested to submit a report to show surface water attenuation calculations for proposed development. Show on a report and drawing what surface water attenuation capacity each SuDS (Sustainable Drainage System) system has in m3. Show in report what surface water attenuation capacity is required for proposed development. Show what different surface types, areas in m2 are proposed such as, green roofs, permeable paving, buildings, roads and their respective run off coefficients. Submit a drawing

Response:

- (a) Compliance has been met as contained within the SDCC SUDS Design Guide 2022 and all relevant policies of the SDCC County Development Plan 2022 – 2028 pertaining to Sustainable Drainage, have been addressed as far as is practical and as demonstrated within this submission – refer below:-
 - Policy G13 Sustainable Water Management This policy has been met and is covered off in the documentation as submitted by Ramboll / Neo Environmental and deals with the protection, enhancement, amenity & biodiversity value of existing watercourses, including for flood risk management & water quality etc. The integrity of riparian corridors along the edge of watercourses also forms part of this policy.

Further to the above, SuDS elements have been addressed in the form of restricting the rate of discharge off the site via the introduction of flow control mechanisms, i.e. Hydrobrake manholes. Water quality has also been improved via the use of permeable paving and petrol / oil interceptors.

 Policy G14 – Sustainable Drainage Systems – Elements of this policy have been met in the form of restricting the overall run-off from the site to Green field run-off rates.



The surface water has been managed in the form of small sub-catchments, incorporating a treatment train discharge via an open channel which discharges into the existing watercourse.

 Policy G15 – Climate Resilience – This calls for the enhancement of the biodiversity and ecosystems. Another objective is for the provision of green roofs.

Documentation as submitted by Ramboll / Neo Environmental provide information pertaining to this policy. Green roofs have not been considered in this instance, as it is an element that isn't normally associated with data centre developments.

• Policy IE3 – Surface Water & Groundwater – This calls for the management of surface water and enhancement of ground and surface water quality.

Elements of this policy have been addressed by introducing detention basins, permeable paving, interceptors & flow restrictors. Responses to groundwater have also been addressed by submissions from Ramboll / Neo Environmental.

 Policy SM2 – Walking & Cycling – This deals with sustainable modes of travel, prioritizing walking and cycling facilities.

Elements of the above have been dealt with under Item 4, as contained within this response.

- Policy SM7 Car Parking & EV Charging Elements of Objective 9 within this policy, have been complied by the introduction of permeable paving areas into the scheme, together with structural tree pits.
- 4.3.1 Components of the GI Network Responses to the majority of queries pertaining to the GI Network have been addressed in submissions by Kevin Fitzpatrick Landscape Architecture (KFLA) & Ramboll / Neo Environmental.
- 12.7.6 Car Parking Design & Layout This was addressed in the response under Policy SM7 above.
- 12.11.1 Water Management:– (i) Flood Risk Assessment an independent flood risk assessment has been carried out by Kilgallen & Partners in respect of this development; (ii) Surface Water the surface water outflow has been calculated in accordance with greenfield run-off rates using the Qbar calculation (refer Appendix A); (iii) Sustainable Urban Drainage Systems (SuDS) (a) in meeting SuDS requirements, the following have been installed detention basins, permeable paving & tree pits, (b) the existing stream has been bridged over as opposed to being culverted and the outflow from Detention Basin 1 has been conveyed in an open channel prior to discharging into the existing stream; (iv) Groundwater this has been addressed by Ramboll / Neo Environmental; (v) Rain Water Harvesting this has not been proposed in this scheme.
- 12.11.3 Waste Management this item has been fully addressed in submissions by Ramboll / Neo Environmental.



(b) The proposed Drainage Layout, Dwg. No. DUB13-DR-UG-C127-V2-WS4 Rev. V2, issued as part of the planning pack, clearly identified the Hydrobrake manholes, i.e. SWMH5.1 & SWMH 4.2, with associated restricted outflow rates of 0.3l/s & 2.5l/s respectively. The total green field run-off rate was calculated and issued as part of the surface water calculations, as contained within Appendix B of the Engineering Planning Report. The total allowable outflow from the development, based on the Qbar calculation is 2.9l/s and we have restricted the total outflow from the development to 2.8l/s.

Further to the above, the Drainage Layout, Dwg. No. DUB13-DR-UG-C127-V2-WS4 Rev. V3, as submitted as part of this response, has been slightly modified to accommodate revisions to the overall site masterplan. This drawing clearly illustrates the 2 No. Hydrobrake manholes, i.e. SWMH15.1 & SWMH 4.2, with associated restricted outflow rates of 0.3I/s & 2.5I/s respectively. As mentioned in (a) above, the total outflow has been restricted in accordance with the calculated Greenfield run-off formula – this calculation has been included in Appendix A.

This drawing also indicates all SuDS elements as indicated below:-

Attenuation Storage Element	Total Storage Volume
3 No. Detention Basins	1,640m ³
Permeable Paving	114m ³
3 No. Structural Tree Pits	60m ³
All Elements Combined	1,814m ³

- (c) Filtration through the permeable paving into the stone sub-base below provides for reduced peak flows to watercourses thereby reducing the risk of flooding downstream. In addition, the aggregate sub-base provides for enhanced water quality, prior to discharge. Other benefits include the following:-
 - Permeable Paving is a 'source control' method. Water is managed and dealt with on-site without piping off to storage tanks or surface water treatment systems.
 - The Water Framework Directive (Directive2000/60/EC) requires that surface water discharge is managed to ensure that risk of contamination or pollution are mitigated. Permeable Paving systems filter contaminants by microbial action. There is no requirement for additional filtering/polishing with Permeable Paving in normal use
 - Separate attenuation tank systems are not required
 - No need for gullies or channels or conventional drainage
 - Recharges ground water
 - Roofs, roads, and other non-permeable areas can be discharged into permeable paving (no gullies required)
 - No ponding or surface water
 - Collected water can potentially be re-used for non-potable purposes
 - Improves water quality

Various manufacturers of permeable paving products have specific maintenance guidelines and a full maintenance regime is presented on supply of the product.



The hydrobrake mechanisms are provided within manholes in order to restrict the outflow to the rates specified. Most manufacturers of these products provide cleaning, maintenance and repair service teams and partners, providing specialist operations and maintenance (O&M) cover, keeping water management equipment and systems operating at peak performance, effectiveness and efficiency.

The maintenance of the detention basins and flood compensatory storage area will be in line with recommendations from the Landscape Architect (KFLA) on the scheme and / or recommendations by Parks Department.

(d) The SUDS elements which form part of this application are as follows:-

- 3 No. Surface water detention basins the original application contained 2 No. Surface water detention basins
- Permeable paving no change from the original application
- 3 No. Tree pits new feature, these were not proposed under the original application
- Open swale / natural open channel (treatment train) linking Detention Basin 1 to the stream outfall the original application contained a piped outfall from Detention Basin 1 into the stream
- Hydrobrake manholes restricting the outflow no change from the original application
- Petrol / Oil Interceptors no change from the original application

The proposed tree pits, as mentioned above, are detailed on Kevin Fitzpatrick Landscape Architecture Dwg. No. 0462 – 203 and these have been derived from the 'SDCC Sustainable Drainage Explanatory, Design and Evaluation Guide 2022'.

An extract of same is included below:-



(e) Refer to the External Works Layout, Dwg. No. DUB13-DR-SP-C130-V2-WS3 Rev. V3, as previously issued and since revised, in order to accommodate layout modifications, clearly details the various surface types in m² and their respective run-off co-efficients pertaining to this development.



The surface water attenuation capacities and respective storage elements are clearly notated on our Dwg. No. DUB13-DR-UG-C127-V2-WS4 Rev. V3, i.e. 3 No. Detention Basins, Permeable Paving & SuDS Tree Pits.

The overall attenuation volume for this development is ultimately derived from the green field Qbar run-off rate of 2.9l/s. In fact, attenuation on the site has now been over provided for, as the original submission catered for $970m^3$ of storage in 2 No. detention basins + $114m^3$ of storage within the permeable paving sub-base.

This has now been increased to 1,640m³ of storage in 3 No. Detention Basins, the original 114m³ of storage within the permeable paving sub-base and an additional circa 60m³ of storage within the structural tree pit elements (3 No.). This has provided the overall site with an additional storage volume of attenuation of circa 730m³.

Item 13: (a) The sub catchment areas in the site do not add up to the total site area in surface water attenuation calculations submitted. Based on limited information submitted in terms of surface types and areas of same the surface water attenuation proposed of 970m3 or 1, 084m3 is undersized by approximately 2% to 11%. The applicant is requested to submit a report to show the areas in m2 of each surface type and their respective run off coefficients. Include the areas grasslands and explain why this has 0% runoff if that is the case. Note that the areas of all surface types should equal the total site area.

(b) The applicant is requested to examine if any surface water pipes can be replaced with swales or filter drains at any location of the site. Submit a drawing showing what if any additional SuDS (Sustainable Drainage Systems) can be provided on site.

Response:-

(a) The area stated in the Qbar calculation of 1.43Ha, is the hard standing area of the site. This area is cross referenced to the areas of the various surface types as indicated in the extract below, as taken off the External Works Layout drawing - Dwg. No. DUB13-DR-SP-C130-V2-WS3 Rev. V3, as included in the submission.

DESCRIPTION	AREA (m ²)	CO-EFFICIENT
PERMEABLE PAVING	759	0.6
ROOF	6,384	1.0
CONCRETE ROADS, GENERATOR YARDS, EXTERNALS CONCRETE SLABS	4,502	0.8
ASPHALT ROAD	2,395	0.8
WALKWAYS (CONCRETE)	394	0.8

KEY

The above area does not include for the existing road and walkways which fall under the redline boundary and it also excludes the landscaping areas as indicated on the layout.



Further to the above, the existing road (Falcon Avenue / Nangor Road) and walkways would never be considered as having to be attenuated under this development as they are entirely external, hence the area of same was not included. The landscaping berms and meadows contain tree and woodland planting and seeding elements, which cater for any rain water run-off falling on the berm elements themselves, due to their topography and shape and do not contribute run-off into any catchment areas feeding into the proposed surface water attenuation elements, hence the 0% co-efficient value.

Details of these landscaping elements are clearly detailed on Kevin Fitzpatrick Landscape Architecture Dwg. No. 0462 - 203. It should further be noted that the wet meadow area could not drain into the attenuation elements, as it is a depressed open area of the site, which is to be utilized as a flood compensatory storage area, as advised in the FRA produced by Kilgallen & Partners.

As stated in Item 10(e) above, even taking the worst case scenario of the attenuation being undersized by 11%, this would bring the total site attenuation requirement up to circa 1,203m³. As we are now providing an overall volume of 1,814m³, we would contend that we are in fact providing an over provision of attenuation in the amount of circa 611m³.

As advised above, please refer to the External Works Layout, Dwg. No. DUB13-DR-SP-C130-V2-WS3 Rev. V3, for details pertaining to surface type areas and associated co-efficient percentages.

We have provided a detail explanation above, as to why all surface area types do not contribute to the total site area, particularly for the calculation of attenuation storage volumes.

(b) All of the proposed Suds features have been detailed in this response. As an additional element, the previously piped outfall from Detention Basin 1 into the stream, has been replaced by a natural open channel / open swale. This is further detailed under the response to Item 14.

Item 14: (a) where possible, the applicant is requested to replace proposed overflow pipe with an open swale or natural open channel.

Response:-

The previously piped outfall from Detention Basin 1 into the stream, has been replaced by a natural open channel / open swale – refer Dwg. No. DUB13-DR-UG-C127-V2-WS4 Rev. V3.

Typical Bio Swale detail below.





We trust that this adequately addresses the conditions as listed above.

Your sincerely

Phil

Shaun O'Reilly Pinnacle shaun.oreilly@iepinnacle.com +353 (1) 231 1044 Encl. (18)



APPENDIX A

Surface Water Calculations

Qbar Calculation Using IOH Report 124 for Sites < 25 km ²					
Catchment Name DUB 13					
¹ Q _{bar} = 0.00108 * (AREA) ^{0.89} (SAAR) ^{1.17} (SOIL) ^{2.17}	Estimation of less than 25 I	QBAR from IOH Re cm ² using the 3 vari	eport 124 for cat	chments
SITE AREA = 1.43 Ha	Overall Redline Area				
CATCHMENT Ha (excl. Public AREA = Open Space)	Overall Catchment Area (Heo interpolated for smaller areas	ctares) For catchm	ents < 50 hectares in a	area, flow rates are	linearly
AREA = 0.014 km ²	Area of the Catchment (km ²)				
SAAR = 754 mm	Standard Annual Average Ra	iinfall (mm)			
SOIL = 0.30	Soil Type Expressed as a	Soil 1	Soil 2 Soil	3 Soil 4	Soil 5
	SOIL Value	0.15	0.30 0.40	0 0.45	0.50
Soil index value (SPR) calculated from Flood Studies Report Vol V Fig I 4.18(1) - The Classification of Soils from Winter Rainfall Acceptance Rate . $ \frac{I = (MS_{60}/MS_{2d}) 0.27} $ Flood Return Event ⁶ Growth Factor Permitted Flow (I/s) 1 0.85 2.4 QBAR 1 2.9 1 0 1.67 4.8 3 0 2.1 6.0 5 0 2.33 6.6 1 0 0 2.6 7.4 2 0 0 2.85 8.1 1 0 0 0 3.5 1 0.0 Pro-rata based on 50 Ha Site area to calculate Qbar Qbar = 0.00004 currecs/Ha Qbar = 2.0 I/s/Ha					
Q _{bar[rural]} = 2.9	l/s				
	Catchment Characteristic	S			
DUB 13	Area (m ²)	Runoff Coeff.	Effective Area (m ²)		
Roofs & Balconies - Type 1 (Draining to gullie	s) -	1.00	0.0		
Green Roofs	-	0.85	0.0		
Roads and Footpaths - Type 1 (Draining to gu	llies) -	0.80	0.0		
Roads and Pootpaths - Type 2 (Draining to Su Paved Areas	as reatures) -	0.70	0.0		
Permeable Paving	-	0.70	0.0		
Grass over Basement Parks (contributing)	-	0.70	0.0		
Public Open Space (non-contributing) - 0.00 0.0					
Include Public Open Space in Effective Catchment Area? NO Assumed open space area does not drain to surface water network					
Effective Catchment Area 0.0 m ²					
Effective Catchment Runoff Coefficient 0.00					

Technical Appendix 11.1A: Ecological Impact Assessment Report



Appendix 11.1A: Ecological Impact Assessment

27/02/2023



Disclaimer

Neo Environmental Limited shall have no liability for any loss, damage, injury, claim, expense, cost or other consequence arising as a result of use or reliance upon any information contained in or omitted from this document.

Copyright © 2023

The material presented in this report is confidential. This report has been prepared for the exclusive use of Ramboll. The report shall not be distributed or made available to any other company or person without the knowledge and written consent of Ramboll or Neo Environmental Ltd.

Neo Environmental Ltd			
Head Offic	ce - Glasgow:		
Wright Bus	siness Centre,		
1 Lonn	nay Road,		
Gla	sgow.		
G3	3 4EL		
T 0141	773 6262		
E: <u>info@neo-en</u>	vironmental.co.uk		
Warrington Office:	Rugby Office:		
Cinnamon House,	Valiant Suites,		
Crab Lane,	Lumonics House, Valley Drive,		
Warrington,	Swift Valley, Rugby,		
WA2 OXP.	Warwickshire, CV21 1TQ.		
T: 01925 661 716	T: 01788 297012		
E: info@neo-environmental.co.uk	E: info@neo-environmental.co.uk		
Ireland Office:	Northern Ireland Office:		
Johnstown Business Centre,	83-85 Bridge Street,		
Johnstown House,	Ballymena,		
Naas,	Co. Antrim		
Co. Kildare.	BT43 5EN		
T: 00 353 (0)45 844250	T : 0282 565 04 13		
E: info@neo-environmental.ie	E: info@neo-environmental.co.uk		



Appendix 11.1A: Ecological Impact Assessment

Prepared For:

Ramboll

Prepared By:

Approved By

Dara Dunlop BSc (Hons)



Name

Paul Neary



ENVIRONMENTAL

Signature

Part ton





Contents

Executive Summary	5
Introduction	6
Legislation and Planning Policy Context	9
Methodology	18
Baseline Conditions	23
Impact Assessment	40
Cumulative Effects	48
Conclusion	57
Appendices	59



EXECUTIVE SUMMARY

- 1.1 An Ecological Impact Assessment (EcIA) has been undertaken on lands within Profile Park, Clondalkin, Dublin to assess the potential impacts from the Proposed Development on local ecology. Baseline information within the ecological assessment comprises of an initial deskbased assessment and a Fossitt habitat survey, which was extended to identify the presence or likely absence of protected species. These have been outlined within the relevant sections of this report.
- 1.2 The desk-based assessment identified six Special Areas of Conservation (SACs) and three Special Protection Areas (SPA) within the Zone of Influence of the Application Site boundary. These designated sites have been outlined and fully assessed within the supporting Appropriate Assessment (AA) report. Considering the limited hydrological connectivity, it was concluded that no potential significant effects will be incurred on any Natura 2000 site as a result of the Proposed Development.
- 1.3 Within 5km of the site boundary there are two Proposed Natural Heritage Areas (pNHAs).
- A total of seven habitat types were noted during the Fossitt habitat survey undertaken in July
 2022. The main habitat types recorded within the Application Site is Amenity Grassland (GA2).
 The lands directly under and adjacent to the Proposed Development are of **low** ecological value.
- 1.5 From the current survey findings and impact assessment conducted it is considered that the Proposed Development is **unlikely to have significant impacts** on local wildlife.



INTRODUCTION

Background

1.6 Neo Environmental Ltd has been appointed by Ramboll on behalf of Vantage Data Centres Dub 11 Limited (the "Applicant") to undertake an Ecological Impact Assessment for a data centre building and associated development (the "Proposed Development") on lands within Profile Park, Clondalkin, Dublin (the "Application Site").

Development Description

1.7 The development consists of the construction of one no. two storey data centres with a gross floor area of c. 12,893 sqm that will include office at first floor. The proposed data centre comprises of a two-storey data centre that will include 13 no. standby emergency generators with associate flues (each 25m in height) to be located to the west of the building. The data centre will be c. 14.23m to parapet height with the roof plant increasing the height to 18.5m overall. The data centre will be accessed from a new emergency and service vehicular access off Falcon Avenue as well as from the site of the already permitted data centres to the west. The data centre will be served by 60 car parking spaces that will be located generally to the east of the data centre, of which 3 no. spaces will be disabled spaces and 6 of these spaces will be provided for electrical charging vehicles. Covered bicycle parking provision will be provided within the site. The data centre will be enclosed by landscape berms and planting to the north and north-east.

Site Description

- 1.8 The site is located at Irish grid reference O 03911 30784, within Profile Park. Profile Park is located approximately 10 kilometres (km) to the south-west of Dublin city centre, within South Dublin County.
- 1.9 The site boundaries are defined by:
 - New Nangor Road (R134) to the north;
 - Falcon Avenue, Equinix and Grange Castle Golf Club to the east;
 - Falcon Avenue to the south; and
 - The consented Vantage data centre development (Planning Reference: SD21A/0241) to the west, currently agricultural fields.
- 1.10 The site is a triangular parcel of agricultural land, with a residential dwelling located in the north-west corner of the site, and an area of hardstanding within the south-west of the site.



The site covers a total area of 3.31 ha and lies at an elevation between approximately 74 and 75 m Above Ordnance Datum (m AOD).

- 1.11 The existing Baldonnell steam runs adjacent to the sites southern boundary and enters the southern section of the site, orientated in a north-west to south-east direction, flowing towards the east.
- 1.12 The site can currently be accessed from three access points, two from the north off New Nangor Road (R134), and one from Falcon Avenue on the eastern border, which leads to a roundabout on the R134 New Nangor Road.
- 1.13N1 It is noted that a 5m section of existing hedge located in the north-west of the site (no.H7-C2) was removed by a Contractor on an adjacent site, this has since been reinstated through remedial works on the site.

Scope of the Assessment

- 1.14 An Ecological Impact Assessment was completed at the Application Site. The aims of this report are to:
 - Determine the main habitat types within and immediately adjacent to the Application Site in relation to the Proposed Development footprint;
 - Identify any actual or potential habitat or species constraints pertinent to the development of the Application Site and to identify how the Proposed Development can avoid, mitigate and, if necessary, compensate for impacts on these actual or potential constraints;
 - Assess the potential impacts of the Proposed Development during the construction, operation and decommissioning phases;
 - Provide mitigation to reduce the impacts of the activities undertaken during the various phases of the Proposed Development; and
 - Identify potential opportunities for the Proposed Development to enhance and add to the biodiversity resource within the site.
- 1.15 This allows for the identification of potential ecological impacts and the compilation of appropriate mitigation measures where applicable.

Statement of Authority

1.16 The assessment has been conducted by ecologists registered with the Chartered Institute of Ecology and Environmental Management ("CIEEM"). All work has been carried out in line with



the relevant professional guidance; CIEEM's Guidelines for Preliminary Ecological Appraisal¹ and the Environment, Heritage and Local Government's Guidance on Appropriate Assessments².

- 1.17 Dara Dunlop is a Qualifying Member of CIEEM with circa 4 years' experience in the ecology sector, including working for an ecological consultancy, undertaking a range of protected species surveys and extended phase 1 habitat surveys for industrial schemes, and land management of designated sites. Dara has authored a number of reports including Ecological Impact Assessments and Protected Species Reports for various developments.
- 1.18 Dylan Donoghue is an Ecologist in the process of receiving membership with the Chartered Institute of Ecology and Environmental management (CIEEM). Dylan has 2 years' experience in the Ecology Sector, including working for an ecological consultancy, undertaking bird and bat surveys.
- 1.19 Eiméar Rose Cunningham is an Ecologist and is a Qualifying Member of the Chartered Institute of Ecology and Environmental Management (CIEEM), with over 3 years' experience in the environmental/planning sector. She has experience of conducting habitat surveys as well as protected species surveys, including bats. In previous roles Eiméar Rose has experience of GIS map interpretation for large scale infrastructure projects. Furthermore, Eiméar Rose has experience in the completion of ecological report writing having co-authored a number of reports including Ecological Impact Assessments and Natura Impact Statements

² Environment, Heritage and Local Government, 2009. Appropriate Assessment of Plans and Projects in Ireland, Guidance for Planning Authorities. Available at www.npws.ie



¹ CIEEM, 2017. Guidelines for Preliminary Ecological Appraisal. Available at www.cieem.net

LEGISLATION AND PLANNING POLICY CONTEXT

European Legislation

1.20 European legislation relevant to the proposed development is outlined within **Table 1-1** below.

Table 1-1: Relevant European Legislation

Directive	Main Provisions			
	The EU Habitats Directive sets out the framework for the designation and protection of sites for nature conservation for species and habitats listed in Annex II, IV and V. The directive was adopted in 1992 as a response to the Bern Convention.			
EU Habitats Directive 92/43/EEC	"The main aim of the Habitats Directive is to promote the maintenance of biodiversity by requiring Member States to take measures to maintain or restore natural habitats and wild species listed on the Annexes to the Directive at a favourable conservation status, introducing robust protection for those habitats and species of European importance"			
	The protection of species outlined in the Habitats Directive is transposed into national legislation principally by 'EC (Natural Habitats) Regulations 1997 (amended)' ³ .			
	European Union members meet their obligations for bird species under the Bern Convention and Bonn Convention, and more generally by the means of the EU Birds Directive.			
The Birds Directive 2009/147/EC	The Birds Directive sets out the criteria for Special Protection Areas including; a list of species requiring protection in Annex 1 of the Directive and mechanisms for protecting wild birds naturally occurring in Europe. This Directive is transposed into national legislation principally by the 'EC (Birds and Natural Habitats) Regulations 2011' ⁴ .			
	The Directive provides a framework for the conservation and management of, and human interactions with, wild birds in Europe. It sets broad objectives for a wide range of activities, although the precise legal mechanisms for their achievement are at the discretion of each Member State.			

³ Office of the Attorney General (1997), European Communities (Natural Habitats) Regulations 1997 (amended 1998, 2005), available at www.irishstatutebook.ie

⁴ Office of the Attorney General (2011), European Communities (Birds and Natural Habitats) Regulations 2011, available at www.irishstatutebook.ie



Environmental Liability Directive 2004/35/EC	The Environmental Liability Directive aims to make those causing damage to the environment (water, land and nature) legally and financially responsible for that damage.
	The directive covers environmental damage caused by or resulting from occupational activities to species and natural habitats protected under the 1992 Habitats Directive and the 1979 Wild Birds Directive. Damage to protected species and natural habitats is "any damage that has significant adverse effects on reaching or maintaining the favourable conservation status of such habitats or species".
Bern Convention	The Bern Convention came into force in 1982, with the principal aims to ensure conservation and protection of wild plant and animal species and their natural habitats (listed in Appendices I and II of the Convention), to increase cooperation between contracting parties, and to regulate the exploitation of those species (including migratory species) listed in Appendix III.
Bonn Convention	The Bonn convention came into force in 1985. Contracting Parties work together to conserve migratory species and their habitats by providing strict protection for endangered migratory species (listed in Appendix I of the Convention), concluding multilateral Agreements for the conservation and management of migratory species which require or would benefit from international cooperation (listed in Appendix II), and by undertaking cooperative research activities.

National Legislation

- 1.21 The principal national legislation governing the protection of wildlife and natural resources in Ireland is:
 - The Wildlife Act 1976 (amended 2000)⁵ this is the principal legislation for the protection of wildlife in Ireland and outlines strict protection for species that have significant conservation value. The Act also provides a mechanism to give statutory protection to Natural Heritage Areas ("NHAs"). The amendment in 2000 broadens the scope of the Wildlife Acts to include most species, including the majority of fish and aquatic invertebrate species which were excluded from the 1976 Act.

⁵ Office of the Attorney General (1976) Wildlife Act 1976 (amended 2000), available at www.irishstatutebook.ie



- EC (Birds and Natural Habitats) Regulations 2011 (amended 2015)⁶ transposes the EU directives into law. It protects species and priority habitats considered to be of European interest.
- Flora Protection Order 2015⁷ this Order makes it illegal to cut, uproot or damage a listed species in any way. It is illegal to alter, damage or interfere in any way with their habitats. This protection applies wherever the plants are found.
- The EC (Water Policy) Regulations 2003⁸ transposes the Water Framework Directive into national law.
- 1.22 The regulations contained within the above referenced legislation have all been taken into account during the production of this ecological report.

Planning and Development Act, 2000 (as amended)⁹

1.23 Relevant sections regarding ecology within the Planning and Development Act 2000 (amended 2006) are as follows:

First Schedule, Part IV Environment and Amenities

"5. (a) Preserving and protecting flora, fauna and ecological diversity.

(b) Preserving and protecting trees, shrubs, plants and flowers.

6. Protecting and preserving (either in situ or by record) places, caves, sites, features and other objects of archaeological, geological, historical, scientific or ecological interest."

Fifth Schedule

"19. Any condition relating to the protection of features of the landscape which are of major importance for wild fauna and flora.

20. Any condition relating to the preservation and protection of trees, shrubs, plants and flowers.

⁹ Office of the Attorney General (2000) Planning and Development Act 2000, available at www.irishstatutebook.ie



⁶ Office of the Attorney General (2011) European Communities (Birds and Natural Habitats Regulations 2011 (amended 2015), available at www.irishstatutebook.ie

⁷ Office of the Attorney General (2015) Flora Protection Order 2015, available at www.irishstatutebook.ie

⁸ Office of the Attorney General (2003) European Communities (Water Policy) Regulations 2003, available at www.irishstatute book.ie
21. Any condition relating to the preservation (either in situ or by record) of places, caves, sites, features or other objects of archaeological, geological, historical, scientific or ecological interest.

22. Any condition relating to the conservation and preservation of -

(a) one or more specific—

(i) (I) natural habitat types in Annex I of the Habitats Directive, or

(II) species in Annex II of the Habitats Directive which the site hosts,

contained in a European site selected by the Minister for Arts, Heritage, Gaeltacht and the Islands in accordance with Annex III (Stage 1) of that Directive,

(ii) species of bird or their habitat or other habitat contained in a European site specified in Article 4 of the Birds Directive, which formed the basis of the classification of that site,

or

(b) any other area prescribed for the purpose of section 10(2)(c)."

Part XIV

"212. -(1) A planning authority may develop or secure or facilitate the development of land and, in particular and without prejudice to the generality of the foregoing, may do one or more of the following:

(f) secure the preservation of any view or prospect, any protected structure or other structure, any architectural conservation area or natural physical feature, any trees or woodlands or any site of archaeological, geological, historical;

(g) secure the creation, management, restoration or preservation of any site of scientific or ecological interest, including any Nature Conservation Site."

Planning Policy Statement 2015¹⁰

1.24 The aim of Planning Policy Statement 2015 is as follows:

"Planning legislation in Ireland seeks to ensure, in the interests of the common good, the proper planning and sustainable development of urban and rural areas."

1.25 The Government outlined 10 key principles as a strategic guide in implementing the aim above. Relevant ecological principals outlined within this document include:

¹⁰Environment, Community and Local Government (2015), Planning Policy Statement 2015, available at www.environ.ie



"4. Planning must support the transition to a low carbon future and adapt to a changing climate taking full account of flood risk and facilitating, as appropriate, the use of renewable resources, particularly the development of alternative indigenous energy resources.

8. Planning will conserve and enhance the rich qualities of natural and cultural heritage of Ireland in a manner appropriate to their significance, from statutorily designated sites to sites of local importance, and including the conservation and management of landscape quality to the maximum extent possible, so that these intrinsic qualities of our country can be enjoyed for their collective contribution to the quality of life of this and future generations.

9. Planning will support the protection and enhancement of environmental quality in a manner consistent with the requirements of relevant national and European standards by guiding development towards optimal locations from the perspective of ensuring high standards of water and air quality, biodiversity and the minimisation of pollution risk."

South Dublin Development Plan 2022–2028¹¹

- 1.26 The Plan sets out an overall strategy for the proper planning and sustainable development of the County and consists of a written statement and accompanying plans and maps
- 1.27 Chapter 3 of the Plan refers to the county's natural heritage and contains a number of key policies (outlined below), which aim to protect and enhance biodiversity and designated sites within the county:

NCBH1: Objective 1: To protect, conserve and enhance natural, built and cultural heritage features, seeking opportunities to identify, retain, protect, and incorporate heritage assets into plans and development.

NCBH1 Objective 2: To support the objectives and actions of the County Heritage Plan and the County Biodiversity Action Plan in the promotion and protection of natural, built and cultural heritage, and to take full cognisance of the County's Landscape Character Assessment and the County Geological Audit in the sustainable management of development.

NCBH1 Objective 3: To carry out an audit and assessment, based on an initial pilot study of the County's natural and built heritage assets including Council owned protected structures and archaeological features; to identify and safeguard these assets from the potential impacts of climate change; and to explore possible uses as part of climate change mitigation.

NCBH2 Objective 1: To support the implementation of the National Biodiversity Action Plan (2017-2021) and the All-Ireland Pollinator Plan (2021-2025) and to support the adoption and implementation of the South Dublin County Biodiversity Action Plan (2020-2026) and Pollinator Action Plan (2021-2025) and any superseding plans.



¹¹ Available from : https://www.sdcc.ie/en/devplan2022/adopted-plan/

NCBH2 Objective 2: To ensure the protection of designated sites in compliance with relevant EU Directives and applicable national legislation.

NCBH2 Objective 3: To protect and conserve the natural heritage of the County, and to conserve and manage EU and nationally designated sites and non-designated locally important areas which act as 'stepping stones' for the purposes of green infrastructure and Article 10 of the Habitats Directive.

NCBH2 Objective 4: To protect our rivers and in particular to avoid overdevelopment which could have an adverse effect on the biodiversity and ecosystems of the river.

NCBH3 Objective 1: To prevent development and activities that would adversely affect the integrity of any Natura 2000 site located within or adjacent to the County and promote the favourable conservation status of the habitats and species integral to these sites.

NCBH3 Objective 2: To ensure that plans, including land use plans, will only be adopted, if they either individually or in combination with existing and / or proposed plans or projects, will not have a significant adverse effect on a European Site, or where such a plan is likely or might have such a significant adverse effect (either alone or in combination), South Dublin County Council will, as required by law, carry out an appropriate assessment as per requirements of Article 6(3) of the Habitats Directive 92 / 43 / EEC of the 21 May 1992 on the conservation of natural habitats and of wild fauna and flora, as transposed into Irish legislation. Only after having ascertained that the plan will not adversely affect the integrity of any European site, will South Dublin County Council adopt the plan, incorporating any necessary mitigation measures. A plan which could adversely affect the integrity of a European site may only be adopted in exceptional circumstances, as provided for in Article 6(4) of the Habitats Directive as transposed into Irish legislation.

NCBH3 Objective 3: To ensure that planning permission will only be granted for a development proposal that, either individually or in combination with existing and / or proposed plans or projects, will not have a significant adverse effect on a European Site, or where such a development proposal is likely or might have such a significant adverse effect (either alone or in combination), the planning authority will, as required by law, carry out an appropriate assessment as per requirements of Article 6(3) of the Habitats Directive 92 / 43 / EEC of the 21 May 1992 on the conservation of natural habitats and of wild fauna and flora, as transposed into Irish legislation. Only after having ascertained that the development proposal will not adversely affect the integrity of any European site, will the planning authority agree to the development and impose appropriate mitigation measures in the form of planning conditions. A development proposal which could adversely affect the integrity of a European site may only be permitted in exceptional circumstances, as provided for in Article 6(4) of the Habitats Directive as transposed into Irish legislation.

NCBH4: Protect the ecological, visual, recreational, environmental and amenity value of the County's proposed Natural Heritage Areas and associated habitats and species.



NCBH5: Protect and promote the conservation of biodiversity outside of designated areas and ensure that species and habitats that are protected under the Wildlife Acts 1976 to 2018, the Birds Directive 1979 and the Habitats Directive 1992, the Flora (Protection) Order 2015, and wildlife corridors are adequately protected.

NCBH10: Protect against and prevent the introduction and spread of invasive species within the County and require landowners and developers to adhere to best practice guidance in relation to the control of invasive species.

NCB11: Review Tree Preservation Orders (TPO) within the County and maintain the conservation value of trees and groups of trees that are the subject of a Tree Preservation Order while also recognising the value of and protecting trees and hedgerows which are not subject to a TPO.

South Dublin County Council Draft Biodiversity Action Plan 2020-202612

- 1.28 The preparation of this Biodiversity Action Plan is an objective of the South Dublin County Heritage Plan and the South Dublin County Council Development Plan 2022-2028. The South Dublin County Biodiversity Plan was prepared in the context of a range of national and international plans for biodiversity protection and enhancement
- 1.29 The National Biodiversity Plan lists a range of actions for biodiversity that aim to achieve this vision, arranged under a series of 7 Strategic Objectives. These objectives are:
 - the mainstreaming of biodiversity issues across the decision-making in all sectors;
 - the strengthening of the knowledge base for conservation, management and sustainable use of biodiversity;
 - increasing public awareness and appreciation of biodiversity and ecosystem services;
 - the conservation and restoration of biodiversity and ecosystem services in the wider countryside;
 - the conservation and restoration of biodiversity and ecosystem services in the marine environment;
 - the expansion and improved management of protected areas and species; and
 - the strengthening of international governance for biodiversity and ecosystem services.

¹²https://consult.sdublincoco.ie/en/consultation/draft-biodiversity-action-plan-south-dublin-county-connecting-nature-2020-2026



Guidance Documents

BS 42020:2013 Biodiversity¹³

- 1.30 The British Standards Institute has published BS 42020:2013 Biodiversity. Code of practice for planning and development which offers a coherent methodology for biodiversity management. This document seeks to promote transparency and consistency in the quality and appropriateness of ecological information submitted with planning applications and applications for other regulatory approvals.
- 1.31 BS 42020:2013 cites CIEEM EcIA Guidelines as the acknowledged reference on ecological impact assessment. These guidelines provide recommendations on topics such as professional practice, proportionality, pre-application discussions, ecological surveys, adequacy of ecological information, reporting and monitoring.

CIEEM Guidelines

- 1.32 The Chartered Institute of Ecology and Environmental Management (CIEEM) have produced guidance on Ecological Impact Assessment¹⁴ (EcIA) and Ecological Report Writing¹⁵.
- 1.33 EcIA is a process of identifying, quantifying and evaluating potential effects from activities such as those related to development on habitats, species and ecosystems. This EcIA process follows the tasks set out in **Table 1-2**.

	Task	Description
-	Scoping	Determining the matters to be addressed in the EcIA, including consultation to ensure the most effective input to defining the scope. Scoping is an ongoing process – the scope of the EcIA may be modified following further ecological survey/research and during impact assessment.
	Establishing the baseline	Collecting information and describing the ecological conditions in the absence of the proposed project, to inform the assessment of impacts.
	Important ecological features	Identifying important ecological features (habitats, species and ecosystems, including ecosystem function and processes) that may be affected, with reference to a geographical context in which they are considered important.

Table 1-2: EcIA Process



 $^{^{\}rm 13}$ BS 42020:2013 Biodiversity. Code of practice for planning and development

¹⁴ CIEEM (2018) Guidelines for Ecological Impact Assessment in the UK and Ireland. Terrestrial, Freshwater, Coastal and Marine.

¹⁵ CIEEM (2017) Guidelines for Ecological Report Writing

Impact assessment	An assessment of whether important ecological features will be subject to impacts and characterisation of these impacts and their effects3. Assessment of the significance of the residual ecological effects of the project (those remaining after mitigation), including cumulative effects.		
Avoidance, mitigation, compensation and enhancement	Incorporating measures to avoid, reduce and compensate negative ecological impacts and their effects, and the provision of ecological enhancements. Monitoring impacts and their effects. Evaluation of the success of proposed mitigation, compensation and enhancement measures.		

1.34 The aims of their EcIA guidelines are to:

- promote good practice;
- promote a scientifically rigorous and transparent approach to EcIA;
- provide a common framework to EcIA in order to promote better communication and closer cooperation between ecologists involved in EcIA; and
- provide decision-makers with relevant information about the likely ecological effects of a project.



METHODOLOGY

Zone of Influence

1.35 The Zone of Influence (ZOI) is the area encompassing all predicted negative ecological effects from a proposed scheme and is informed by the habitats present within the site and the nature of the proposals. Due to the scale and nature of the proposal, it is considered that the ZOI will fall within the distances from the proposed solar farm outlined in **Table 1-3** below. These were therefore considered appropriate for gathering information for the desk study.

ECOLOGICAL FEATURE	STUDY AREA
International/European statutory designations	15km, or wherever hydrological influence extends
National statutory designations	5km
Protected and Priority Species	2km
Fossitt habitat survey	50m

Table 1-3: Study areas for ecological features

Desk Study

- 1.36 A desk-based assessment was undertaken to collate available ecological information for the Application Site and the surrounding area. This included a search of statutory designated sites within a 5km radius of the Proposed Development, including: Special Protection Areas (SPAs), Special Areas of Conservation (SACs), Ramsar Sites, Nature Reserves (NRs), Wildfowl Sanctuaries, Natural Heritage Areas (NHAs) and Proposed Natural Heritage Areas (pNHAs). The descriptions of each of these sites was obtained utilising the National Parks and Wildlife Service (NPWS) website¹⁶.
- 1.37 A data search was conducted though the National Biodiversity Data Centre (NBDC) to obtain information regarding protected/notable species within 2km of the Application Site boundary. The Application Site is located at Irish Grid Reference (IGR) O 03911 30784.
- 1.38 Additional information on the suitability of habitat in the surrounding area for bats was also obtained from the NBDC in the form of a habitat suitability map. The map provided enhanced information on the recorded distribution of bats and broad-scale geographic patterns of occurrence and local roosting habitat requirements for Irish bat species.



¹⁶ NPWS website; available at: http://www.npws.ie/protected-sites.

Field Survey

Fossitt Habitat Survey

- 1.39 A Fossitt habitat survey was undertaken on the 20th of July 2022 by Eiméar Rose Cunningham. The Ecological Survey Area (ESA) covered all land within the Application Site and a 50m buffer around the entire site (where accessible).
- 1.40 Survey work was carried out in accordance with Fossitt habitat survey guidance¹⁷; habitats were mapped electronically in the field in order to produce a habitat map.

Species Scoping Survey

- 1.41 A species scoping survey was carried out to identify the presence of protected species, or the potential of the Application Site to support protected species. The aim of the survey was to provide an overview of the Application Site and to determine whether any further survey work was required.
- 1.42 No additional protected species surveys were undertaken at this time.
- 1.43 **Table 1-4** below outlines the relevant habitat and field signs that indicate the potential presence of protected or notable species within the ESA.

TAXON	INDICATIVE HABITAT(S)	Field Signs (In Addition to Sightings)
Bats	Roosts – trees, buildings, bridges, caves, etc. Foraging areas – e.g. parkland, water bodies, streams, wetlands, woodland edges and hedgerow. Commuting routes – linear features (e.g.) hedgerows, water courses, tree lines). See Appendix C for preferred foraging and commuting habitat for individual species.	In or on potential roost sites: droppings stuck to walls, urine spotting in roof spaces, oil from fur staining round roost entrances, feeding remains (e.g. moth wings under a feeding perch).
Badger Meles meles	Found in most rural and many urban habitats.	Excavations and tracks: sett entrances, latrines, hairs, well-worn paths, prints, scratch marks on trees.

Table 1-4: Indicative Habitats and Field Signs of Protected Species



¹⁷ Fossitt (2000) A Guide to Habitats in Ireland

TAXON	INDICATIVE HABITAT(S)	Field Signs (In Addition to Sightings)	
Otter <i>Lutra lutra</i>	Watercourses.	Holts (or dens), prints, spraints (droppings), slide marks into watercourses, feeding signs (e.g. fish bones).	
Birds	Trees, scrub, hedgerow, field margins, grassland, buildings.	Nests, droppings below nest sites (especially in buildings of trees), tree holes.	
Common lizard Zootoca vivipara	Rough grassland, log and rubble piles.	Sloughed skins.	

Additional Surveys

- 1.44 Bat activity surveys were completed in August 2022 to determine the use of buildings on site by roosting bats. Two dusk emergence surveys; one of the shed in the southwest and one of the house in the northwest of the site were undertaken by Eiméar Rose Cunningham, Dylan Donoghue and Dara Dunlop on the 3rd August and the 30th August 2022. The results of 2022 bat survey is outlined in **Appendix B**.
- 1.45 No bats were observed emerging from either building within the Application Site, surveys indicate that the site is used by very low numbers of commuting bats.

Weather Conditions

1.46 **Table 1-5** describes the weather conditions at the time of survey giving air temperature (°C), wind speed (Beaufort force), cloud cover (percentage) and precipitation.

Survey Date	Temperature (°C)	Wind Speed (Beaufort Scale)	Cloud- cover (oktas)	Precipitation
20/07/2022	17-19°c	3	7	None

Table 1-5: Weather conditions at time of survey

Limitations

1.47 Results of the assessment undertaken by Neo Environmental are representative of the time that surveying was undertaken.



- 1.48 The absence of specific species records returned during the data search does not necessarily indicate absence of a species or habitat from an area, but rather that these have not been recorded or are perhaps under-recorded within the search area.
- 1.49 A Fossitt habitat survey does not aim to produce a full botanical or faunal species list or provide a full protected species survey, but enables competent ecologists to ascertain an understanding of the ecology of the site in order to:
 - Identify broadly the nature conservation value of a site and preliminary assess the significance of any potential impacts on habitat/species recorded, and/or
 - Confirm the need and extent of any additional specific ecological surveys that are required to identify the true nature conservation value of a site.
- 1.50 At the time of the initial survey, access was only permitted within the landownership boundary. The areas of land which formed the ESA which were not within the landownership boundary were viewed from field boundaries, with the use of binoculars, where needed. It is considered that the limited access to areas of land directly adjacent to the Proposed Development boundary has not unduly impacted upon the findings of the habitat or species scoping surveys.

Evaluation Methods

1.51 The evaluation of ecological receptors is based upon the CIEEM guidelines¹⁸ (2018) which suggests that the value or potential value of an ecological resource or feature (for example a habitat type, species or ecosystems) should be determined within a geographical context (e.g. rare at a local level). Attributing a value to a receptor, which is also a designated site, is generally precise, as the designations themselves provide an indication of value.

Impact Assessment

- 1.52 The impact assessment process involves:
 - identifying and characterising impacts and their effects
 - incorporating measures to avoid and mitigate negative impacts and effects
 - assessing the significance of any residual effects after mitigation
 - identifying appropriate compensation measures to offset significant residual effects; and
 - identifying opportunities for ecological enhancement.



¹⁸ CIEEM (2018) Guidelines for the Ecological Impact Assessment in the UK and Ireland

- 1.53 The terms 'impact' and 'effect' are used commonly throughout ecological reports. Impact is defined as a change experienced by an ecological feature, while effect is defined as the outcome to an ecological feature from an impact. Impacts and effects can be positive, negative or neutral.
- 1.54 Assessment of potential impacts and effects needs to consider on-site, adjacent and more distant ecological features, including habitats, species and statutory and ecological designated sites.
- 1.55 This ecological impact assessment has been concluded by an experienced ecologist following CIEEM guidance¹⁹.

¹⁹ CIEEM (2018) Guidelines for Ecological Impact Assessment in the UK and Ireland. Terrestrial, Freshwater, Coastal and Marine.



BASELINE CONDITIONS

Designated Sites

- 1.56 The Proposed Development does not lie within or directly adjacent to any statutory or nonstatutory designated environmental sites.
- 1.57 Within the ZOI there are six Special Areas of Conservation (SACs) and three Special Protection Areas (SPA). Within 5km of the Application Site boundary there are two Proposed Natural Heritage Areas (pNHAs).
- 1.58 Each of these sites are outlined in **Table 1-6** below, and detailed within **Figure 1 of Appendix A**.
- 1.59 The site descriptions are derived from the original site citations available from NPWS²⁰.

Table 1-6: Designated Sites.

Site Code	Site Name	Qualifying/Notable Features	Distance (km) and Direction	Potential Connectivity with the Proposed Development Site
SAC				
001398	Rye Water Valley/Carton SAC	Petrifying springs with tufa formation (<i>Cratoneurion</i>) [7220] <i>Vertigo angustior</i> (Narrow-mouthed Whorl Snail) [1014] <i>Vertigo moulinsiana</i> (Desmoulin's Whorl Snail) [1016]	5.88km northwest	None
001209	Glenasmole Valley SAC	Semi-natural dry grasslands and scrubland facies on calcareous substrates (<i>Festuco-Brometalia</i>) (*	8.05km southeast	None



²⁰ http://www.npws.ie/protected-sites

		[6210] Molinia meadows on calcareous, peaty or clayey-silt-laden soils (<i>Molinion caeruleae</i>) [6410] Petrifying springs with tufa formation (<i>Cratoneurion</i>) [7220]		
002122	Wicklow Mountains SAC	Oligotrophic waters containing very few minerals of sandy plains (<i>Littorelletalia uniflorae</i>) [3110] Natural dystrophic lakes and ponds [3160] Northern Atlantic wet heaths with <i>Erica</i> <i>tetralix</i> [4010] European dry heaths [4030] Alpine and Boreal heaths [4060] Calaminarian grasslands of the <i>Violetalia</i> <i>calaminariae</i> [6130] Species-rich Nardus grasslands, on siliceous substrates in mountain areas (and submountain areas, in Continental Europe) [6230] Blanket bogs (* if active bog) [7130] Siliceous scree of the montane to snow levels (<i>Androsacetalia alpinae</i> and <i>Galeopsietalia</i> <i>ladani</i>) [8110]	9.76km southeast	None



		Calcareous rocky slopes with chasmophytic vegetation [8210] Siliceous rocky slopes with chasmophytic vegetation [8220] Old sessile oak woods with Ilex and Blechnum in the British Isles [91A0] <i>Lutra lutra</i> (Otter) [1355]		
000397	Red Bog, Kildare SAC	Transition mires and quaking bogs [7140]	14.44km southwest	None
000210	South Dublin Bay SAC	Mudflats and sandflats not covered by seawater at low tide [1140] Annual vegetation of drift lines [1210] Salicornia and other annuals colonising mud and sand [1310] Embryonic shifting dunes [2110]	15.21km east	Hydrological connectivity via the Baldonnell stream and the River Liffey
000206	North Dublin Bay SAC	Mudflats and sandflats not covered by seawater at low tide [1140] Annual vegetation of drift lines [1210] Salicornia and other annuals colonising mud and sand [1310] Atlantic salt meadows (<i>Glauco-Puccinellietalia</i> <i>maritimae</i>) [1330]	17.90km northeast	Hydrological connection via the Baldonnell stream and the River Liffey



		Mediterranean salt meadows (Juncetalia maritimi) [1410] Embryonic shifting dunes [2110] Shifting dunes along the shoreline with Ammophila arenaria (white dunes) [2120] Fixed coastal dunes with herbaceous vegetation (grey dunes) [2130] Humid dune slacks [2190] Petalophyllum ralfsii (Petalwort) [1395]		
SPA				
004040	Wicklow Mountains SPA	Merlin (<i>Falco</i> <i>columbarius</i>) [A098] Peregrine (<i>Falco</i> <i>peregrinus</i>) [A103]	12.88km southeast	None
004024	South Dublin Bay and River Tolka Estuary SPA	Light-bellied Brent Goose (<i>Branta bernicla</i> <i>hrota</i>) [A046] Oystercatcher (<i>Haematopus</i> <i>ostralegus</i>) [A130] Ringed Plover (<i>Charadrius hiaticula</i>) [A137] Grey Plover (<i>Pluvialis</i> <i>squatarola</i>) [A141] Knot (<i>Calidris canutus</i>) [A143] Sanderling (<i>Calidris</i> <i>alba</i>) [A144]	14.81km east	Hydrological connectivity via the Baldonnell stream and the River Liffey (28km downstream)



		Dunlin (<i>Calidris alpina</i>) [A149]		
		Bar-tailed Godwit (<i>Limosa lapponica</i>) [A157]		
		Redshank (<i>Tringa</i> <i>totanus</i>) [A162]		
		Black-headed Gull (<i>Chroicocephalus</i> <i>ridibundus</i>) [A179]		
		Roseate Tern (<i>Sterna</i> <i>dougallii</i>) [A192]		
		Common Tern (<i>Sterna</i> <i>hirundo</i>) [A193]		
		Arctic Tern (<i>Sterna</i> paradisaea) [A194]		
		Wetland and Waterbirds [A999]		
		Light-bellied Brent Goose (<i>Branta bernicla</i> <i>hrota</i>) [A046]		
		Shelduck (<i>Tadorna</i> <i>tadorna</i>) [A048]		
		Teal (<i>Anas crecca</i>) [A052]		
		Pintail (<i>Anas acuta</i>) [A054]	19.71km east	Hydrological connectivity via the Baldonnell
004006	North Bull Island SPA	Shoveler (<i>Anas</i> <i>clypeata</i>) [A056]		
		Oystercatcher (<i>Haematopus</i> ostralegus) [A130]		River Liffey
		Golden Plover (<i>Pluvialis</i> <i>apricaria</i>) [A140]		
		Grey Plover (<i>Pluvialis</i> squatarola) [A141]		
		Knot (<i>Calidris canutus</i>) [A143]		



		Sanderling (<i>Calidris</i> <i>alba</i>) [A144] Dunlin (Calidris alpina) [A149] Black-tailed Godwit (<i>Limosa limosa</i>) [A156] Bar-tailed Godwit (<i>Limosa lapponica</i>) [A157] Curlew (<i>Numenius</i> <i>arquata</i>) [A160] Redshank (<i>Tringa</i> <i>totanus</i>) [A160] Redshank (<i>Tringa</i> <i>totanus</i>) [A162] Turnstone (<i>Arenaria</i> <i>interpres</i>) [A169] Black-headed Gull (<i>Chroicocephalus</i> <i>ridibundus</i>) [A179] Wetland and Waterbirds [A999]		
pNHA				
002104	Grand Canal pNHA	Canal system banked by hedgerow, tall herbs, calcareous grassland, reed fringe, open water, scrub and woodland.	1.39km north	Hydrological connectivity via the Baldonnell stream
000128	Liffey Valley pNHA	River system	4.57km north	Hydrological connectivity via the Baldonnell stream

Habitats

1.60 A Fossitt habitat survey was undertaken in July 2022 which identified seven habitat types within the survey boundary; each of these is outlined in **Table 1-7** below. In addition, the habitat map is shown in **Figure 2 of Appendix A**.



Table 1-7: Habitat types on site

НАВІТАТ ТҮРЕ	SPECIES PRESENT	OTHER OBSERVATIONS/ POTENTIAL FOR SPECIES
Building and Artificial Surfaces (BL3)	N/A	Two buildings were determined to have low bat roost potential.
Amenity Grassland (GA2)	Perennial ryegrass (<i>Lolium perenne</i>), creeping buttercup (<i>Ranunculus</i> <i>repens</i>), common nettle (<i>Urtica</i> <i>dioica</i>), daisy (<i>Bellis perennis</i>), ribwort plantain (<i>Plantago</i> <i>lanceolata</i>), white clover (<i>Trifolium</i> <i>repens</i>).	The majority of the site is comprised of amenity grassland. This habitat is generally considered to be of low ecological value.
Recolonising Bare Ground (ED3)	Rosebay Willowherb (<i>Chamerion</i> <i>angustifolium</i>), great willowherb (<i>Epilobium hirsutum</i>) and spear thistle (<i>Cirsium vulgare</i>).	This habitat is generally considered to be of low ecological value.
Scrub (WS1)	Bramble (<i>Rubus fruticosus</i>), spear thistle (<i>Cirsium vulgare</i>), cow parsley (<i>Anthriscus sylvestris</i>), perennial ryegrass (<i>Lolium perenne</i>).	A patch of scrub surrounds the building in the southwest of the application site. Provides some limited nesting opportunities for birds and
Depositing/Lowland rivers (FW2)	Brambles (<i>Rubus fruticosus</i>).	Watercourses are considered to be an important water source for local ecology at the site level.
Hedgerows (WL1)	Brambles (Rubus fruticosus), hawthorn (Crataegus monogyna), elder (Sambucus nigra), common nettle (Urtica dioica), European beech (Fagus sylvatica).	Providing bird nesting opportunities as well as foraging opportunities for many species.
Treelines (WL2)	European beech (<i>Fagus sylvatica</i>) Cypress (<i>Cupressus spp.</i>) and poplar (Populus spp.), hawthorn (<i>Crataegus monogyna</i>), bramble (<i>Rubus fruticosus</i>), horse chestnut (<i>Aesculus hippocastanum</i>), goat willow (<i>Salix caprea</i>), small leaved linden (<i>Tilia cordata</i>).	Providing bird nesting opportunities as well as foraging opportunities for many species.



Protected and Notable Species

Desk Study

- 1.61 The potential presence of protected species within the study area was assessed though a data search conducted through the NBDC. This identified records of invasive, rare, scarce and protected species within 2km of the Proposed Development location. The Application Site is located within the 2km grid squares: O03F. A database search was also carried out for adjacent grid squares to ensure a full assessment of the 2km radius, from Irish Grid Reference (IGR) O 03894 30791. These include 2km grid squares O03G, O03L, O03K, O02P and O02J.
- 1.62 Additional information on the suitability of habitat in the surrounding area for bats was also obtained from the NBDC in the form of a habitat suitability map. The map provided enhanced information on the recorded distribution of bats, and broad-scale geographic patterns of occurrence and local roosting habitat requirements for Irish bat species.
- 1.63 In addition, the Fossitt habitat survey included a species scoping survey in order to assess the potential of the site to support protected species.
- 1.64 **Table 1-8** summarises the protected/notable species recorded within the search area, and their potential to be present within the Application Site.

Species	Grids with Recordings of Species	Suitable Habitat or Field Signs Observed within Survey Area	Potential for species within Application Site
MAMMALS			
Eurasian Badger (<i>Meles meles</i>)	O02P	Yes, treelines, hedgerows and grassland habitats available	Yes
Western European hedgehog (<i>Erinaceus</i> <i>europaeus</i>)	003K, 003F, 003G, 003L	Grassland and hedgerows offer some potential for commuting/foraging/ breeding	Yes
Brown long-eared bat (<i>Plecotus auritus</i>)	003F, 003G, 003L	Yes, buildings on site offer low bat roosting	Yes

Table 1-8: Summary of Biological Records



		potential, foraging potential along treeline	
Daubenton's bat (<i>Myotis daubentonii</i>)	003F, 003G, 003L	Yes, buildings on site offer low bat roosting potential, foraging potential along treeline and stream	Yes
Leisler's bat (<i>Nyctalus</i> <i>leisleri</i>)	003K, 003F, 003G, 003L, 002P	Yes, buildings on site offer low bat roosting potential, foraging potential along treeline and stream identified in flight	Yes
Pipistrelle (Pipistrellus pipistrellus sensu lato)	003K, 003F, 003G, 003L, 002P	Trees unsuitable for roosting, however buildings on site offer low bat roosting potential, foraging potential along treeline and stream	Yes
Soprano pipistrelle (<i>Pipistrellus</i> <i>pygmaeus</i>)	003K, 003F, 003G, 003L, 002P	Yes, buildings on site offer low bat roosting potential, foraging potential along treeline and stream	Yes
Pine Marten (<i>Martes martes</i>)	O03F	Yes, multiple habitats on site are suitable for species	Yes
European otter (<i>Lutra</i> <i>lutra</i>)	003G, 002P	Yes, stream habitat available for foraging and commuting	Yes
American mink* (<i>Mustela vison</i>)	O03K, O02P	Yes, suitable habitat available in the form of a stream and treelines	Yes
Eurasian Pygmy Shrew	003G	Yes, grassland and hedgerow habitats are	Yes



(Sorex minutus)		available	
Greater White- toothed Shrew (<i>Crocidura russula</i>)*	O02P	Yes, grassland habitat available	Yes
European Rabbit (<i>Oryctolagus</i> <i>cuniculus</i>)*	003G, 002P	Yes, grassland and hedgerow habitats are available	Yes
Eastern grey squirrel* (<i>Sciurus carolinensis</i>)	003K, 003G, 002P	Yes, potential habitat available in treelines present on site	Yes
Birds			
House martin (<i>Delichon urbicum</i>)	002J, 003G	Yes, some nesting potential in buildings and structures, limited foraging potential	Yes
House sparrow (Passer domesticus)	003K, 003G, 003L	Yes, some nesting potential in buildings and structures, limited foraging potential	Yes
Barn Swallow (Hirundo rustica)	002J, 003K, 003G, 002P	Yes, some nesting potential in buildings and structures, limited foraging potential	Yes
Black-headed Gull (<i>Larus ridibundus</i>)	003K, 003F	No, lacks suitable nesting and foraging potential such as wetland areas, such as bogs and marshes and will also use manmade lakes and arable fields	No
Great Black-backed Gull (<i>Larus marinus</i>)	O03F	No, lacks suitable habitat (coastal), well- vegetated rocky coastline with stacks and cliffs, flat-roofed buildings	No



Herring Gull (<i>Larus</i> argentatus)	003F, 003L	No, lacks suitable habitat (coastal), well- vegetated rocky coastline with stacks and cliffs, flat-roofed buildings	No
Lesser Black-backed Gull (Larus fuscus)	O03F	No. lacks suitable habitat such as farmland, wetlands coastal areas, scavenges in rubbish tips and in urban areas	No
Common Coot (Fulica atra)	003K, 003G, 003L, 002P	Yes, stream within the survey area offers suitable habitat	Yes
Common Pochard (Aythya ferina)	O03L	No, marsh and lake habitats are not available	No
Common Linnet (<i>Carduelis cannabina</i>)	O03L	Yes, dense hedgerow, scrub, and hawthorn bushes available	Yes
Great Cormorant (Phalacrocorax carbo)	O03K, O03F, O03L	No, prefer coastal habitats or inland lakes or estuaries	No
Common Kingfisher (<i>Alcedo atthis</i>)	O03F	Yes, stream within the survey area offers suitable habitat	Yes
Common Redshank (Tringa totanus)	O03F	No, prefer coastal habitats, marshy grassland, or inland lakes, estuaries or large rivers	No
Eurasian Tree Sparrow (<i>Passer montanus</i>)	003K	Yes, can nest in cavities in buildings, especially under eaves or holes	Yes
Common Starling (Sturnus vulgaris)	002J, 003K, 003G, 003L	Yes, some nesting potential in buildings	Yes



		and structures, limited foraging potential	
Northern Wheatear (<i>Oenanthe oenanthe</i>)	O02J	No, lacks suitable habitat such as rocky coasts, pasture with stone walls and bogs in uplands.	No
Yellowhammer (Emberiza citrinella)	002J	Yes, but limited nesting and foraging potential	Yes
Little Grebe (<i>Tachybaptus</i> <i>ruficollis</i>)	O03K, O03F, O03L	Yes, breeding habitat available in the freshwater stream	Yes
Mallard (Anas platyrhynchos)	003K, 003F, 003G, 003L	Yes, breeding habitat available in the freshwater stream	Yes
Mute swan (<i>Cygnus</i> olor)	003K, 003F	No, the small stream in the survey area is not considered suitable habitat for the species	No
Peregrine Falcon (<i>Falco peregrinus</i>)	003G	No, breed and winter on coastal and inland cliff areas and estuaries	No
Northern lapwing (Vanellus vanellus)	003K, 003F, 003L	No, lacks suitable habitat such as agricultural cereal crop fields, meadows or wet grasslands	No
Sand Martin (<i>Riparia</i> <i>riparia</i>)	O03K, O02P	Yes, suitable habitat available in the freshwater stream	Yes
Tufted Duck (Aythya fuligula)	O03K, O03F, O03L	Yes, suitable habitat available in the freshwater stream	Yes
Common Swift (<i>Apus</i> apus)	002P	Yes, can nest in cavities in buildings,	Yes



		especially under eaves or holes	
INVERTEBRATES			
Large red tailed bumblebee (<i>Bombus</i> (<i>Melanobombus)</i> <i>lapidarius</i>)	002J, 002P	Grassland offers some limited potential	Yes
Trimmer's Mining Bee (Andrena (Hoplandrena) trimmerana)	O03G	No, habitats preferred are coastal landslips and cliffs and, inland, from heaths, open woodland, chalk grassland,	No
Iridescent pea mussel (Pisidium pulchellum)	003G	Yes, stream habitat is suitable	Yes
Freshwater white- clawed crayfish (Austropotamobius pallipes)	002P	Yes, stream habitat within the survey area	Yes
Flora			
Butterfly-bush (<i>Buddleja davidii</i>)*	002P	Yes, suitable habitat available	Yes
Indian Balsam (<i>Impatiens</i> glandulifera)*	003К	Yes, suitable habitat available	Yes
Giant Hogweed (Heracleum mantegazzianum)	O02P	Yes, suitable habitat available	Yes
Japanese Knotweed (<i>Fallopia japonica</i>)*	003К	Yes, suitable habitat available	Yes
Spanish Bluebell (Hyacinthoides hispanica)*	003К	Yes, suitable habitat available	Yes
Three-cornered Garlic (<i>Allium triquetrum</i>)	003К	Yes, suitable habitat available	Yes
НЕРДТИЕС			



Common frog (Rana temporaria)	002J	Yes, watercourses within survey area	Yes
----------------------------------	------	--------------------------------------	-----

*indicates an invasive species

1.65 **Table 1-9** below details the results of the NBDC Bat Suitability Index search undertaken for the Proposed Development. The index ranges from 0 to 100, with 0 being least favourable and 100 most favourable for bats.

Table 1-9: Bat Suitability Index

SPECIES	INDEX SCORE
Brown long-eared bat (Plecotus auritus)	35
Common pipistrelle (Pipistrellus pipistrellus)	40
Daubenton's bat (<i>Myotis daubentonii</i>)	41
Leisler's bat (Nyctalus leisleri)	0
Lesser horseshoe bat (<i>Rhinolophus hipposideros</i>)	41
Nathusius's pipistrelle (Pipistrellus nathusii)	19
Natterer's bat (<i>Myotis nattereri</i>)	19
Soprano pipistrelle (<i>Pipistrellus pygmaeus</i>)	19
Whiskered bat (Myotis mystacinus)	26

Baseline Results

Bats

- 1.66 The bat suitability index is presented in **Table 1-9**. With the area scoring an overall suitability index score of 26.67, suggesting the area is relatively low suitability for bats. From the 2km grid square results, records of Brown Long-eared Bat (*Plecotus auritus*), Daubenton's bat (*Myotis daubentonii*), Lesser Noctule (*Nyctalus leisleri*) Pipistrelle (*Pipistrellus pipistrellus sensu lato*) and Soprano Pipistrelle (*Pipistrellus pygmaeus*) were found within 2km of the Application Site.
- 1.67 Two structures within the Application Site boundary were identified as being of low bat roosting suitability during the species scoping survey and as such further bat surveys were carried out due to their potential for use by roosting bats. The surveys covered a shed to the southwest of the site (see Target Note 1 in Figure 2, Appendix A) and a house to the northwest of the site (Target Note 2). The trees identified within the site, including horse chestnut and ash, among others, were considered unsuitable for bat roosting.



1.68 A bat emergence of the shed was carried out on the 2nd and a survey of the house was carried out on the 30th August 2022. No bats were seen emerging from either building, overall bat activity at the site was **very low**.

Badger

- 1.69 Records of badger were returned from one of the six grid squares assessed in the 2km desk study.
- 1.70 Habitats within the Application Site, such as hedgerows and the scrub areas, would provide suitable foraging habitat for badger. There were however no field signs or evidence of badgers within the Application Site during the Fossitt habitat survey.

Otter

- 1.71 Records of otter were returned for two of the grid squares checked within 2km of the Application Site (not covering the Application Site itself). The Baldonnell stream which flows along the southern boundary of the site is too narrow to support breeding and foraging otter, and the surrounding habitats (business parks, a golf course and a significant amount of residential housing and shopping centres) are not suitable to support commuting otter.
- 1.72 No sightings or field signs of otter were observed within the survey area.

Hedgehog

- 1.73 Records of hedgehog were returned from four of the 2km grid squares assessed, including the grid square that covers the Application Site.
- 1.74 No sightings or signs of hedgehog were observed within the study area although habitats within the ESA are expected to be suitable foraging areas for hedgehog. These habitats include scrub, hedgerow and amenity grassland.

Other Mammals

- 1.75 Records of eastern grey squirrel, American mink, brown rat, greater white-toothed shrew, and European rabbit, were returned from the 2km desk study, all of which are invasive species in Ireland. Suitable habitat is available for all species within the Application Site in the form of hedgerows, scrub, a treelines and amenity grassland.
- 1.76 There were no field signs or sightings of any of these species during the Fossitt habitat survey.
- 1.77 Recordings of pine marten were returned from one of the 2km grid squares assessed in the desk study and this was the 2km grid square that covered the Application Site.



- 1.78 There was no evidence or sightings of Pine Marten during the site visit, whilst the scrub within the application site offers suitable habitat for the species, it was present in a very small amount and was patchy and not continuous habitat.
- 1.79 Evidence of Eurasian pygmy shrew was returned from one of the 2km grid squares assessed in the desk study, not the grid square covering the Application Site. Habitats such as hedgerows and grassland offer suitable foraging habitat for the species.
- 1.80 There was no evidence or sightings of Eurasian pygmy shrew found during the survey of the site.
- 1.81 No other evidence of any additional mammal species was observed during the site visit.

Birds

- 1.82 Whilst no formal bird surveys were undertaken within the proposed ESA, the species scoping survey was completed to identify the presence of protected species, or the potential of the Application Site to support protected species. Any incidental observations of bird species during the walk over survey were recorded to provide information for the assessment of potential bird activity within the Application Site.
- 1.83 Sightings of swallow, swift, buzzard and magpie were recorded during the Fossitt habitat survey within the Application Site. Of which, swallow and swift are the only species of significant note as they have amber and red Birds of Conservation Concern in Ireland (BoCCI) status' respectively²¹. The site does offer suitable nesting and foraging habitat for bird species in the form of hedgerows, buildings treelines and scrub. Swallows were observed flying in and out of potential nesting sites within the residential home to the northwest of the site and the shed at the southwest of the Application Site .

Herptiles

1.84 Records of common frog were found within 2km of the Application Site boundary. The species is known to utilise stream freshwater habitats, such as the Baldonnell stream located south of the redline boundary of the site. However, no signs of this species were recorded during the survey.

Invertebrates

1.85 Of the notable species identified within the 2km grid square study, the Large Red Tailed Bumble Bee, Iridescent pea mussel and the Freshwater white-clawed crayfish were identified as being able to utilise habitat available within the Application Site.

²¹ Birds of Conservation Concern in Ireland 4: 2020–2026: Gillian Gilbert, Andrew Stanbury & Lesley Lewis



Flora

1.86 None of the flora species recorded in the 2km data search were observed within the boundaries of the Application Site during the Fossitt habitat survey. Whilst there are recordings of invasive Japanese Knotweed, giant hogweed, butterfly bush and Indian balsam within the 2km study, these were not observed on site during the survey.



IMPACT ASSESSMENT

Best Practice Pollution Prevention Measures

- 1.87 Standard best practice pollution prevention measures will be adhered to, which will reduce the potential for impacts on ecology during the construction stage. As these are standard requirements, they are separate to mitigation measures (which are outlined later in this report). This is of particular importance with the proposed stream re-alignment.
- 1.88 Relevant measures include, but are not limited to:

Pollution Prevention

- Hydrocarbons, greases and hydraulic fluids will be stored in a secure compound area;
- All plant machinery will be properly serviced and maintained, thereby reducing risk of spillage or leakage;
- All waste produced from construction will be collected in skips, with the construction site kept tidy at all times;
- Excavated soil will be stored on site or removed by a licensed waste disposal unit;
- All materials and substances used for construction will be stored in a secure compound and all chemicals will be stored in secure containers to avoid potential contamination;
- Location of spill kit to be known by all construction workers and used in the event of spillage or leakage.

Waste Management

- Skips are to be used for site waste/debris at all times, and collected regularly or when full;
- All hydrocarbons and fluids are to be collected in leak-proof containers and removed from site for disposal or recycling;
- All waste from construction is to be stored within the site confines and then removed to a permitted waste facility.

Environmental Monitoring



• Contractor is to nominate member of staff as the environmental officer with the responsibility to ensure best practice measures are implemented and adhered to, with any incidents or non-compliance issues being reported to project team.

Designated Sites

- 1.89 Within 15km of the Application Site there are six Special Areas of Conservation (SACs) and three Special Protection Areas (SPAs). Within 5km of the Application Site boundary there are two potential Natural Heritage Areas (pNHAs).
- 1.90 There is hydrological connectivity between the Application Site and the South Dublin Bay SAC, the North Dublin Bay SAC, the South Dublin Bay and River Tolka Estuary SPA and the North Bull Island SPA. All of this connectivity is roughly 28km downstream via the Baldonnell stream which flows along the southern boundary of the Application Site and feeds into the River Liffey.
- 1.91 Given the distance between the sites and dilution that any potential contaminants would undergo from the proposed development site before they reach these designated sites, it is unlikely the development would have a significant negative impact on any of the species or habitats for which the above sites are designated.
- 1.92 Hydrological connectivity also exists between the proposed development site and both the Grand Canal pNHA and the Liffey Valley pNHA.
- 1.93 The majority of the qualifying bird species of the SPAs listed above prefer coastal or wetland habitats for foraging and/or breeding. Despite some habitats available on site being suitable for some of the species of the SPAs, the habitats within the site are in a less than ideal location, adjacent to a business park, main roads and multiple housing estates and retail centres. The bird species outlined within the SPAs above can obtain more favourable habitat closer to the SPAs in a more suitable location than the site in question, given the distance between the Application Site and the SPAs listed above.
- 1.94 It is considered that the survey area is unlikely to support any of the Annex II species or assemblages listed above. Narrow-mouthed whorl snail and Desmoulin's whorl snail are restricted to the marsh vegetation of the Rye Water Valley/Carton SAC. The Application site is not considered to offer suitable habitat for otter. The Baldonnell Stream is too narrow to support breeding and foraging otter, and the surrounding habitats (business parks, a golf course and a significant amount of residential housing and shopping centres) are not suitable to support otters commuting from the Wicklow Mountains SAC.



In the Absence of Mitigation

Natura 2000 Sites (SPAs and SACs)

- 1.95 The Dublin Bay is located approximately 15km from the Application Site. Hydrological connectivity exists between these the Application Site and four sites within the Dublin Bay; South Dublin Bay and River Tolka SPA, North Bull Island SPA, South Dublin Bay SAC and North Dublin Bay SAC.
- 1.96 The South Dublin Bay and River Tolka SPA and North Bull Island SPA are designated due to supporting assemblages of wetland and waterbirds. Due to a lack of suitable habitat within the site, it is considered highly unlikely that these species would be present on site.
- 1.97 The only opportunity for pollution arising from the Proposed Development to impact upon the designated site is through the contamination of the Baldonell stream. Given the drainage measures in place at the site, and the large distance between the Application Site and the Dublin Bay, the dilution factor will result in a **negligible** impact upon the qualifying features of the SPAs and SACs.
- 1.98 Therefore, **no significant effects** are predicted in the absence of mitigation.

Proposed Natural Heritage Areas (pNHAs)

- 2.1. The Grand Canal pNHA is located approximately 1.4km north of the Application Site. The Liffey Valley is located approximately 4.6km north. Both sites are hydrological connected via the Baldonnell stream.
- 1.99 As outlined above, there are no watercourses within the Application Site, and so the only pathway for contaminants would be through the contamination of surface waters. Chapter 5: Demolition and Construction Environmental Management outlines the procedures that will be implemented to prevent any spillages to the Balonnell stream.
- 1.100 With the implementation of these best practice procedures, **no significant effects** are predicted in the absence of mitigation.

Recommended Mitigation Measures

- 1.101 There will be no significant contamination of water in the absence of mitigation. Notwithstanding this, during the construction phase, standard best practice measures will be adhered to.
- 1.102 In order to prevent any spillages of fuels to the Baldonnel Stream, or groundwater, the following measures are proposed:
 - Designation of a bunded refuelling areas on the site;
 - Provision of spill kit facilities across the site;



- Where mobile fuel bowsers are used the following measures would be taken:
- Any flexible pipe, tap or valve would be fitted with a lock and would be secured when not in use;
- Pumps or valves would be fitted with a lock and would be secured when not in use;
- All bowsers to carry a spill kit;
- Operatives must have spill response training; and
- Drip trays used on any required mobile fuel units.
- In the case of drummed fuel or other potentially polluting substances which may be used during the demolition and construction stage the following procedures will be adopted:
- Secure storage of all containers that contain potential polluting substances in a dedicated internally bunded chemical storage cabinet unit or inside a concrete bunded area;
- Clear labelling of containers so that appropriate remedial measures can be taken in the event of a spillage;
- All drums to be quality approved and manufactured to a recognised standard;
- If drums are to be moved around the site, they would be secured and on spill pallets; and
- Drums to be loaded and unloaded by competent and trained personnel using appropriate equipment.
- 1.103 Potential pathways for contamination could be minimised as follows:
 - Groundwater would be prevented from entering excavations by dewatering, if required;
 - Surface water would be prevented from entering excavations by using cut-off ditches, covering the excavation, or captured within the groundwater pumping system;
 - Potentially contaminating activities such as concrete preparation, vehicle washing and fuelling etc. are constrained to dedicated protected areas where contaminated water can be collected; and
 - Contaminated water from excavations would be collected within a settlement tank or lagoon to enable treatment prior to release.
- 1.104 Any soil excavated should be retained on site and reused as fill material or landscaping. Excavation works will be carefully monitored by a suitably qualified person to ensure any potentially contaminated soil is identified and segregated from clean/inert soil.
- 1.105 Any stockpiles will be formed within the boundary of the site and there will be no direct link or pathway from this area to any surface water body.



Residual Effects

1.106 With best practice measures implemented during the construction of the Proposed Development there will be **no significant negative residual effects**.

Habitats

In the Absence of Mitigation

- 1.107 The construction of the Proposed Development will occur over land which has been identified as amenity grassland, buildings and artificial surfaces and recolonising bare ground. These habitats are considered to be of **low ecological value** and currently offer limited potential to support wildlife.
- 1.108 Other potential impacts during the construction phase include indirect loss or damage of habitats as a result of dust and other air- or water-borne pollution. As the construction phase will adhere to all relevant legislation and best practice construction and pollution prevention methods, this is expected to cause only **negligible** loss in a local context where these habitats are frequent. Overall habitat loss is **not considered to be significant** in terms of the Application Site's intrinsic habitat interest.
- 1.109 It is therefore considered that the loss of habitat under the Proposed Development footprint will not be significant.

Recommended Mitigation Measures

1.110 It is considered that no significant impacts will occur in the absence of mitigation, and therefore no mitigation measures are proposed.

Residual Effects

1.111 With best practice measures implemented during the construction of the Proposed Development there will be **no significant negative residual effects**.

Protected and Notable Species

In the Absence of Mitigation

1.112 Each section below details the potential impacts in the absence of mitigation for protected and notable species during the construction phase and the operational phase (expected to be >20 years) of the Proposed Development.



Bats

- 1.113 The Proposed Development will involve the removal of the house and outbuilding, classified as having low bat roost potential. Emergence surveys undertaken in 2022 found that there are no bats roosting within these dwellings. Therefore, in the absence of mitigation the loss in this habitat will not damage or destroy an existing roost, therefore the loss of this habitat will have a **negligible effect** on local bat populations.
- 1.114 The majority of the Application Site is comprised of amenity grassland; this habitat offers suboptimal foraging habitat for bat species due to the limited number of prey species present. The loss of these habitats under the Proposed Development footprint **will not lead to a significant reduction in foraging habitat** for local bats.
- 1.111A Hedgerows and treelines provide suitable habitat for foraging and commuting bats. The removal of <u>79</u>74 trees located in the treeline adjacent to the residential property is proposed. The loss of this amount of treeline will not lead to a significant reduction in foraging habitat for local bats, given the abundance of similar habitat in the surrounding landscape, and the poor quality of this habitat.
 - 1.115 The site is currently subjected to high amounts of artificial light from neighbouring similar developments and streetlighting. The increased amount of artificial light has the potential to reduce the suitability of this habitat to commuting and foraging bats.

Badger

- 1.116 Habitats on site are suitable to support badger, however no badger setts, or evidence of badger was identified on site during the site surveys.
- 1.117 Given that badgers are a highly mobile species and new setts may be built prior to construction, there is the potential for the disturbance of badger during the construction phase of the Proposed Development. During the construction phase, the Proposed Development can cause undue stress in a number of ways. Installation of security fencing or hoarding can disrupt badger paths and cut off foraging areas within a clan's territory. Excavations can destroy badger setts, and any excavations lefts overnight can trap badgers.
- 1.118 The construction phase may have a minor temporary impact on commuting badger. This would result in an effect of **low** spatial and **short-term** temporal magnitude. Given the scale of the project it is considered likely that the Proposed Development will have a **negligible effect on the local badger population.**

Birds

- 1.119 Main impacts on bird species from developments include:
 - Direct loss or deterioration of habitats.



- Indirect habitat loss as a result of displacement by disturbance.
- 1.120 The Proposed Development will occur on land that is currently of low ecological value and is subject to a level of disturbance from surrounding industrial developments. However, in the absence of mitigation there is **potential for significant effects** on breeding birds if construction works are undertaken between the months of March and August inclusive.
- 1.121 Swallows were observed flying in and out of potential nesting sites within the garage of the residential home and in the shed at the southwest of the site.
- 1.122 The construction phase may have a temporary adverse impact on breeding birds within and adjacent to the Application Site. This would result in an effect of **low** spatial and **medium-term** temporal magnitude. The effect may continue beyond a single bird generation but is expected to be sufficiently small for the local population to recover relatively soon. This effect would be **not significant** for the commoner species but could be **significant** for priority species and birds of conservation concern.

Mitigation Measures and Further Survey

Badger

- 1.122A All excavations are to be securely covered or closed off at the end of each working day to prevent the accidental trapping of badgers. Where this is not possible, a means of escape (for example a ramp) must be included to allow safe exit from the excavation. Checks of any open excavations should be performed by site staff prior to each day's works. The proposed security fencing will have mammal gates or a gap of at least 10cm at the bottom to allow free movement of badgers through the site.
- 1.124 With the implementation of these measures, **no significant effects** upon badger are predicted as a result of the Proposed Development.

Birds

- 1.125 As swallows were observed using the residential dwelling to the northwest of the site and the shed at the southwest of the site as nesting habitat, it is advised that no demolition of these buildings occur within their summer breeding season of April October, after which they will fledge their nesting sites as the species are summer visitors. Checks of the building should be completed prior to demolition to ensure all swallows have migrated for the season. It is also recommended that appropriate replacement habitat be provided for these species following demolition.
- 1.126 If any trees or hedgerow are to be removed during the breeding season (March to August inclusive), potential significant impacts may occur on breeding birds in the absence of mitigation. This could include the loss of nests, eggs and/or young. It is therefore recommended



that pre-commencement breeding bird surveys should be carried out on any trees and hedgerows which may be removed.

Residual Effects

1.127 With the implementation of mitigation measures and further survey prior to and during the construction phase of the Proposed Development, it is considered that there will be **a negligible effect** upon protected or notable species.


CUMULATIVE EFFECTS

- 1.128 As well as singular effects, cumulative effects also need to be considered. Article 6 of the EU Habitats Directive and Regulation 15 of the European Communities (Natural Habitats) Regulations state that any plan or project that may, either alone or in combination with other plans or projects, significantly affect a designated site, should be the subject of an Appropriate Assessment.
- 1.129 Cumulative impacts can be an issue when multiple proposals each have a small impact on designated sites. If several proposals also have a small impact, the combined result can have a significant impact on a Natura site.
- 1.130 A search of the South Dublin County Council online planning portal was undertaken to identify any Projects or developments within 3km which could impact any ecological features, either alone or in combination with the Proposed Development. These developments are outlined in **Table 1-10** below.

Name	Planning Reference	Project Type	Approx. distance from the site
Microsoft - Grange Castle Business Park, Nangor Road, Clondalkin, Dublin 22	SD20A/0283	Demolition of existing single storey vacant house, garage and outhouse (total gross floor area (GFA) c.291.2sq.m) and removal of existing temporary construction car park; Construction of a single 1-4 storey Central Administration Building and 2 2-storey (with mezzanine) data centres (DUB14 & DUB15) all to be located west of data centres DUB9, DUB10, DUB12 & DUB13 within the MS campus. <i>Grant Permission –</i> 29/03/2021 <i>Enabling works in progress</i>	400 m NW

Table 1-10: Key Developments within 3km of the Proposed Development



UBC Properties - Townlands within Grange Castle South Business Park, Baldonnell, Dublin 22	SD20A/0121	The development will consist of the demolition of the existing two storey dwelling of Ballybane and associated farm buildings (565sq.m) and the construction of 3 two storey data centres with mezzanine floors at each level of each facility and associated ancillary development that will have a gross floor area of 80,269sq.m on an overall site of 16.5hectares. <i>Grant Permission</i> – 09/09/2020 <i>Construction in progress</i>	850 m W
UBC Properties - Grange Castle South Business Park, Dublin 22	VA06S.308585	Clutterland 110kV GIS Substation building and 2 underground single circuit transmission lines. Approved 07/05/21	400 m W
Digital Reality Trust - Profile Park, Baldonnell, Dublin 22, D22 TY06	SD17A/0377	Revisions and alterations of the permitted development of a data processing facility under planning Ref: SD12A/0002 on a 3.85 hectare site. The revised application consists of alterations to the DUB14 (previously DUB12) data centre/warehouse structure, granted in the previous application. The alterations to the DUB14 (Previously DUB12) include: (i) 2 data halls 2137 sq.m (increase of 180sq.m), (ii) offices/reception 478sq.m (decrease of 190 sq.m), (iii)	400 m S



		support space/staff facilities and internal plant with a floor area of 953sq.m (increase of 84sq.m), (iv) external plant of 1,777sq.m (footprint increase of 35sq.m). Grant Permission – 15/12/2017 Constructed – site appears to be fully built out based on aerial imagery.	
Cyrus One - Grange Castle Business Park, Clondalkin, Dublin 22	SD18A/0134	Demolition of the existing single storey house of 'Erganagh' and the construction of a two storey data centre and delivery bays with associated three storey office block and services that will have a gross floor area of 35,426sq.m on an overall site of 9.2 hectares. <i>Grant Permission –</i> 24/09/2018 <i>Site appears to be partially</i> <i>but not fully built out based</i> <i>on aerial imagery</i>	1000 m SW
Cyrus One Townlands within Grange Castle South Business Park, Baldonnel, Dublin 22	SD20A/0295 (amendment to SD18A/0134)	Amendments and modifications to the permitted data centre development granted under Reg. Ref. SD18A/0134 - ABP Ref. ABP-302813-18 and the temporary substation permission granted under SD19A/0300	1000 m SW
Cyrus One - Grange Castle South Business	VA06S.309146	2 no. 110kV transmission lines and a 110kV Gas	900 m SW



Park, Baldonnel, Dublin 22.		Insulated Switchgear (GIS) substation Grant Permission with Conditions - 19/07/2021	
Centrica Business Solutions – Profile Park, Baldonnel, Dublin 22	SD21A/0167	Construction of a gas fired power plant with an electrical output of up to 125MW with associated balance of plant, equipment and buildings. <i>Grant Permission –</i> 19/07/2022	50 m S
quinix (Ireland) Ltd – Plot 100, Profile Park, Nangor Road, Clondalkin, Dublin 22	SD21A/0186	Construction of a three- storey (part four-storey) data centre known as 'DB8' to include data halls, electrical/plant rooms including internal generators, offices, lobbies, ancillary staff areas including break rooms and toilets, stores, stair/lift cores throughout and photovoltaic panels at roof level. <i>Grant Permission –</i> 05/05/2022	< 50 m E
Equinix (Ireland) Ltd	SD22A/0156	10 year permission on a site is bounded to the east and south by Grange Castle Golf Club, to the north by Nangor Road (R134) and to the west by an estate road known as Falcon Avenue) for modifications to the permitted data centre granted under SDCC Reg. Ref. SD21A/0186 comprising the following, reconfiguration and alterations to the data< 50 m	



centre building to include	
removal of front of house	
offices at third floor level,	
alterations to floor levels at	
second floor to provide	
consistency between front	
of house and data halls,	
parapet height increase of	
front of house to c.16.8m,	
provision of storage at	
second floor level in lieu of	
relocated internal	
generators to the external	
generator yard and	
associated elevational	
alterations; extension of	
loading dock at ground floor	
level by c.6osqm in area	
with minor height increase	
to c.5.3m; removal of 3 air	
plenums to the front (north)	
elevation and provision of	
screening to generator flues	
in lieu of omitted plenums;	
alterations at roof level to	
include removal of 2m high	
gantry screening; alterations	
to the permitted generator	
plant yard to the north of	
the data centre to include	
the removal of fuel tanks,	
reconfiguration of plant and	
generators, provision of 2	
additional external	
generators (increase from 5	
to 9 external generators),	
provision of 4 additional	
external plant rooms,	
provision of diesel pump	
tank cabinets and stepover,	
relocation of generator yard	
doors and enlarged	
generator yard to	



· · · · · · · · · · · · · · · · · · ·		
	accommodate the proposed	
	modifications; increase in	
	plant areas by c.77sq.m;	
	reconfiguration of plant	
	within the permitted chiller	
	plant yard to the south of	
	the data centre; removal of	
	1 sprinkler/water tank and	
	removal of stairs and door	
	to the side of the waste	
	compound; reconfiguration	
	of car parking and	
	motorcycle spaces and	
	removal of 1 accessible	
	space. 64 total number of	
	car parking spaces; the	
	proposal also includes	
	provision of on-site gas	
	power generation	
	compound (c.2,604sq.m in	
	area) in the area previously	
	reserved for a future data	
	centre; the compound	
	comprises 7 modular plant	
	rooms (totalling c.180sq.m	
	in area) in the area	
	previously reserved for a	
	future data centre; the	
	compound comprises 7	
	modular plant rooms	
	(totalling c.180sq.m in area),	
	10 gas fired generators and	
	associated flues c.14.7m	
	high, gas skid, associated	
	modular plant, boundary	
	treatment surrounding the	
	compound c.6.5m high and	
	2 vehicular access points	
	including general and	
	emergency access; all	
	associated site development	
	works, services provision,	
	drainage works, access,	



		landscaping and boundary	
		treatment works; no	
		buildings are proposed	
		above the existing ESB and	
		SDCC wayleaves to the west	
		and north of the site; the	
		overall Gross Floor Area of	
		the development is reduced	
		by c.44sq.m to c.9,795sq.m	
		from previously permitted	
		under SDCC Reg. Ref.	
		SD21A/0186; the application	
		is accompanied by a Natura	
		Impact Statement.	
		Request Additional	
		Information 25/07/2022	
		mjormation – 25/07/2022	
		10 year permission for	
		development consisting of	
		removal of an existing	
		unused waste water	
		treatment facility on site	
		and the erection of two data	
		centre buildings, gas	
		powered energy generation	
		compound, and all other	
		associated ancillary	
		buildings and works: the	
Digital		two data centre buildings.	
Netherlands VIII	SD21A/0217	DUB 15 and DUB 16 will	100 m S
B.V		comprise a total floor area	
		of c 33 577sq m over two	
		storevs: the first 2 storev	
		data centre building	
		(DUB15) located to the	
		southwest of the site will	
		comprise 16 865sa m data	
		storage use ancillary office	
		use and associated electrical	
		and mochanical plant	
		rooms, loading bays,	
		maintenance and storage	



	space; a second 2 storey	
	data centre building	
	(DUB16), located to the	
	southeast of the site, will	
	comprise 16,712sq.m data	
	storage areas, ancillary	
	office use and associated	
	electrical and mechanical	
	plant rooms, loading bays,	
	maintenance and storage	
	space; both data centre	
	buildings will reach a height	
	of 20m; emergency	
	generators and associated	
	emission flues and plant are	
	proposed in compounds	
	adjacent to each data centre	
	building; gas powered	
	energy generation is	
	proposed to the north east	
	corner of the site to provide	
	electricity for the proposed	
	development; the	
	application proposes to re-	
	route and widen an existing	
	watercourse constructed	
	following an earlier planning	
	permission; it is proposed to	
	reroute this watercourse	
	along the eastern and	
	southern boundary of the	
	site; landscaping is	
	proposed to the south of	
	the site to screen the	
	buildings; fencing and	
	security gates are proposed	
	around the site; new access	
	roads within the site are	
	proposed along with 71 car	
	parking spaces and 26 cycle	
	spaces, bin stores, site	
	lighting, and all associated	
	works including	



		underground foul and storm water drainage attenuation and utility cables and all other ancillary works; a Natura Impact Statement will be submitted to the planning authority with the application. <i>Grant Permission</i> – 02/08/2022	
Vantage Data Centers Dub 11 Limited Profile Park Business Park and partly within Grange Castle Business Park, Dublin 22.	ABP Ref: VA06S.312793	110kV Gas Insulated Switchgear (GIS) Substation compound and 110kV transmission lines along with associated and ancillary works Due to be decided – 18/10/2022	< 100 m SW

- 1.131 As the Proposed Development is situated within an industrial area, the majority of planning applications are for similar developments. Beyond 1km of the Application site, many sites to the north and east are residential in nature, with industrial and military areas also noted to the south.
- 1.132 It is considered that with the implementation of mitigation measures there will be no impact of the development upon any ecological feature. In conclusion, there is no potential for significant effects as a result of the Proposed Development upon any Natura 2000 site within the ZOI.
- 1.133 It is considered that the Proposed Development is comprised of land which is of low ecological significance. Therefore, the small cumulative loss in habitat will not be significant.
- 1.134 It has been concluded, that with measures included in Proposed Development and the implementation of best practice measures, that it is likely that there will **be no significant cumulative effects** to designated sites or any other ecological feature in combination with any other development.



CONCLUSION

- 1.135 To minimise potential impacts on local wildlife, ecological measures have been incorporated into the Proposed Development as part of the iterative design process (see Table 1-11 below). Standard best practice pollution prevention measures for the construction stage have also been outlined and considered as part of the impact assessment stage, prior to mitigation. These measures are also outlined within Table 1-11.
- 1.136 A total of seven habitat types were noted during the habitat survey undertaken in July 2022. The main impacts during the construction phase include the direct loss of habitat under the Proposed Development footprint and indirect loss of habitat due to disturbance and pollution.
- 1.137 The desk-based assessment identified six Special Areas of Conservation (SACs) and three Special Protection Area (SPA) within the study zone. These designated sites have been outlined and fully assessed within the supporting Appropriate Assessment (AA) report. There is a hydrological connection between the Application Site and designated sites within the Dublin Bay (South Dublin Bay and River Tolka SPA, North Bull Island SPA, South Dublin Bay SAC and North Dublin Bay SAC). There are two Proposed Natural Heritage Areas (pNHAs) located within 5km of the Application Site.
- 1.138 There will be **no significant effect** on any designated sites as a result of the Proposed Development.
- 1.139 It is considered that the short-term disturbance from the Proposed Development will not be significant on all ecological features if the recommended mitigation is implemented. With the implementation of the Biodiversity Management Plan, the potential of the site to support local wildlife will increase, resulting in **long-term positive effects**.



Table 1-11A: Integral design measures and standard best practice

SITE/ Species	POTENTIAL DEVELOPMENT IMPACTS	PHASE OF DEVELOPMENT	MEASURES IMPLEMENTED
INTEGRAL DESIG	N MEASURES		
Badger	Exclusion from foraging habitat	Operational	Security fencing to have <u>mammal</u> <u>gates</u> 10cm gap at base to allow free movement of badger through the site.
STANDARD BEST	PRACTICE MEASURES		
Aquatic environment	Pollution	Construction	Best practice pollution prevention measures implemented prior to and throughout the construction phase to prevent contaminants entering the aquatic environment.
Badger	Accidental trapping within excavations	Construction	All excavations should be securely covered, or a suitable means of escape provided at the end of each working day.
Mitigation Me	asures		
Badger	Disturbance / destruction of setts	Construction	Pre-construction badger survey
Breeding birds	Disturbance / destruction of nest (Only if works are undertaken between March and August)	Construction	Pre-construction breeding bird survey (Only if works are undertaken between March and August) No demolition of buildings within the swallow summer breeding season April – October. Pre- demolition check of building for nesting birds.



APPENDICES

Appendix A – Figures

- Figure 1 Environmental Designations Map
- Figure 2 Habitat Map

Appendix B – Bat Report



Technical Appendix 11.2A: Appropriate Assessment Screening Report



27/02/2023



Disclaimer

Neo Environmental Limited shall have no liability for any loss, damage, injury, claim, expense, cost or other consequence arising as a result of use or reliance upon any information contained in or omitted from this document.

Copyright © 2023

The material presented in this report is confidential. This report has been prepared for the exclusive use of Ramboll. The report shall not be distributed or made available to any other company or person without the knowledge and written consent of Ramboll or Neo Environmental Ltd.

Neo Environmental Ltd			
Head Offic	ce - Glasgow:		
Wright Bu	siness Centre,		
1 Lonr	nay Road,		
Gla	isgow.		
G3	3 4EL		
T 0141	773 6262		
E: info@neo-er	wironmental.co.uk		
Warrington Office:	Rugby Office:		
Cinnamon House,	Valiant Suites,		
Crab Lane,	Lumonics House, Valley Drive,		
Warrington,	Swift Valley, Rugby,		
WA2 OXP.	Warwickshire, CV21 1TQ.		
T: 01925 661 716	T: 01788 297012		
E: info@neo-environmental.co.uk	E: info@neo-environmental.co.uk		
Ireland Office:	Northern Ireland Office:		
Johnstown Business Centre,	83-85 Bridge Street,		
Johnstown House,	Ballymena,		
Naas,	Co. Antrim		
Co. Kildare.	BT43 5EN		
T: 00 353 (0)45 844250	T: 0282 565 04 13		
E: info@neo-environmental.ie	E: info@neo-environmental.co.uk		



Prepared For:

Ramboll

Prepared By:

Dara Dunlop BSc (Hons)



	Name	Date
Edited By:	Dara Dunlop	27/02/2023
Checked By:	Daniel Flenley	27/02/2023
	Name	Signature
Approved By	Paul Neary	Parl tom
Approved By	Paul Neary	Pul An



Contents

1.	Executive Summary	.5
2.	Introduction	.6
3.	Legislation & Guideance	.8
R	equirement for Appropriate Assessment	.8
4.	Assessment Methodology1	LO
5.	Baseline1	L3
E	cological Site Visit1	L3
lo	lentification of Natura 2000 Sites1	14
6.	Assessment Of Likely Effects1	19
7.	Cumulative Impacts2	24
8.	Conclusion2	25
9.	Appendices2	26



Appendix 11.2A: Appropriate Assessment Screening Page 5 of 26 **1. EXECUTIVE SUMMARY**

1.1. A Stage 1 Appropriate Assessment has been undertaken for a proposed for a data centre building and associated development, located within Profile Park, Clondalkin, Dublin. The aim of the Appropriate Assessment Screening is to assess the potential for connectivity between the Proposed Development and any Natura 2000 site within a 15km radius of the Application Site.

- 1.2. To provide a current baseline for the Application Site, an ecological site visit was undertaken in July 2022 by Eiméar Rose Cunningham. During this site visit habitats were assessed for their potential to support protected/notable species. No evidence of any qualifying species was observed within or adjacent to the Application Site during the site visit and habitats on site are considered to be sub-optimal.
- 1.3. Within the 15km Zone of Influence ("ZOI") surrounding the Site, there are nine Natura 2000 designated sites, comprising six Special Areas of Conservation ("SACs") and three Special Protection Areas ("SPAs").
- 1.4. Connectivity (potential pathways for impact) exists between the Application Site and four designated sites; the North Dublin Bay SAC, the South Dublin Bay and River Tolka Estuary SPA and the North Bull Island SPA. This connectivity is roughly 28km downstream via the Baldonnel stream.
- 1.5. The Proposed Development will not impact the Baldonnell stream. Given the distance (approximately 30km downstream) and dilution factors, it is not anticipated that the Proposed Development will cause any impact to the designated site or its qualifying features.
- 1.6. It is therefore considered that the next stage of the Appropriate Assessment is not required, and that the development will not result in any significant effects for any Natura 2000 site.



2. INTRODUCTION

Background

- 2.1. Neo Environmental Ltd has been appointed by Ramboll on behalf of Vantage Data Centers Dub 11 Limited (the "Applicant") to undertake an Appropriate Assessment (AA) Screening for a data centre building and associated development (the "Proposed Development") located on lands within Profile Park, Clondalkin, Dublin (the "Application Site").
- 2.2. The aim of this screening document is to determine whether a Natura Impact Statement (NIS) is required for the Proposed Development.

Site Description

- 2.3. The site is located at Irish grid reference O 03911 30784, within Profile Park. Profile Park is located approximately 10 kilometres (km) to the south-west of Dublin city centre, within South Dublin County.
- 2.4. The site boundaries are defined by:
 - New Nangor Road (R134) to the north;
 - Falcon Avenue, Equinix and Grange Castle Golf Club to the east;
 - Falcon Avenue to the south; and
 - The consented Vantage data centre development (planning reference SD21A/0241) to the west, currently agricultural fields.
- 2.5. The site is a triangular parcel of agricultural land, with a residential dwelling located in the north-west corner of the site, and an area of hardstanding within the south-west of the site. The site covers a total area of 3.31 ha and lies at an elevation between approximately 74 and 75 m Above Ordnance Datum (m AOD).
- 2.6. The existing Baldonnel steam runs adjacent to the sites southern boundary and enters the southern section of the site, orientated in a north-west to south-east direction, flowing towards the east.
- 2.7. The site can currently be accessed from three access points, two from the north off New Nangor Road (R134), and one from Falcon Avenue on the eastern border, which leads to a roundabout on the R134 New Nangor Road.



Page **7** of **26**

Development Description

2.8. The development consists of the construction of one no. two storey data centres with a gross floor area of c. 12,893 sqm that will include office at first floor. The proposed data centre comprises of a two-storey data centre that will include 13 no. standby emergency generators with associate flues (each 25m in height) to be located to the west of the building. The data centre will be c. 14.23m to parapet height with the roof plant increasing the height to 18.5m overall. The data centre will be accessed from a new emergency and service vehicular access off Falcon Avenue as well as from the site of the already permitted data centres to the west. The data centre will be served by 60 car parking spaces that will be located generally to the east of the data centre, of which 3 no. spaces will be disabled spaces and 6 of these spaces will be provided for electrical charging vehicles. Covered bicycle parking provision will be provided within the site. The data centre will be enclosed by landscape berms and planting to the north and north-east.

Statement of Authority

- 2.9. The assessment has been conducted by an ecologist registered with the Chartered Institute of Ecology and Environmental Management (CIEEM). All work has been carried out in line with the relevant professional guidance, namely CIEEM's Guidelines for Report Writing¹ and the Environment, Heritage and Local Government Guidance on Appropriate Assessments².
- 2.10. Dara Dunlop is a Qualifying Member of the Chartered Institute of Ecology and Environmental Management (CIEEM) with circa 3 years' experience in the ecology sector. This includes working for an ecological consultancy, undertaking a range of protected species surveys and extended phase 1 habitat surveys for residential schemes and land management of designated sites. Dara has co-authored a number of reports for various developments including Ecological Impact Assessments and Protected Species Reports.
- 2.11. Eiméar Rose Cunningham is an Ecologist and is a Qualifying Member of the Chartered Institute of Ecology and Environmental Management (CIEEM), with over 3 years' experience in the environmental/planning sector. She has experience of conducting habitat surveys as well as protected species surveys, including bats. In previous roles Eiméar Rose has experience of GIS map interpretation for large scale infrastructure projects. Furthermore, Eiméar Rose has experience in the completion of ecological report writing having co-authored a number of reports including Ecological Impact Assessments and Natura Impact Statements.

² Environment, Heritage and Local Government (2009) Appropriate Assessment of Plans and Projects in Ireland, Guidance for Planning Authorities. Available at www.npws.ie



¹ CIEEM (2017) Guidelines for Ecological Report Writing. Available at <u>www.cieem.net</u>

REQUIREMENT FOR APPROPRIATE ASSESSMENT

- The requirement for Appropriate Assessment of plans or projects originates from Article 6 (3) and (4) of European Union (EU) Habitats Directive. This is implemented in Ireland through the European Communities (Natural Habitats) Regulations of 1997, and the European Communities (Birds and Natural Habitats) Regulations 2011 2015 (as amended).
- The wording of Article 6 (3) of the Directive is as follows:

"Any plan or project not directly connected with or necessary to the management of the site but likely to have a significant effect thereon, either individually or in combination with other plans or projects, shall be subject to appropriate assessment of its implications for the site in view of the site's conservation objectives. In the light of the conclusions of the assessment of the implications for the site and subject to the provisions of paragraph 4, the competent national authorities shall agree to the plan or project only after having ascertained that it will not adversely affect the integrity of the site concerned and, if appropriate, after having obtained the opinion of the general public."

- The aim of Stage 1, 'Screening' is to determine whether or not Stage 2 of the Appropriate Assessment is required, therefore to determine whether the Proposed Development is likely to have a significant, negative impact upon any Natura 2000 site. This is done by considering the type of development and the conservation objectives of any Natura 2000 sites which may be impacted.
- As outlined in the European Commission document 'Assessment of plans and projects significantly affecting Natura 2000 sites'³, any project that is not directly connected with or necessary to the management of a Natura 2000 site, but likely to have a significant effect upon it, either individually or cumulatively will be subject to Appropriate Assessment.
- Where significant effects are uncertain or unknown at the screening stage an AA will be required, due to the need to apply the precautionary principle. Conversely, if a project will have impacts on a site, but these impacts will clearly not affect or undermine those conservation objectives, it is not considered that it will have a significant effect on the site concerned.
- As part of the assessment consideration is afforded to 'in combination' effects with other plans or projects on the integrity of Natura 2000 sites. Where adverse impacts are identified,



 $^{^3}$ European Commission. 2021. Assessment of plans and projects in relation to Natura 2000 sites - Methodological guidance on Article 6(3) and (4) of the Habitats Directive 92/43/EEC.

Page **9** of **26**

mitigation measures can be proposed that would avoid reduce or remedy any such negative impacts and the plan or project should then be amended accordingly, thereby avoiding the need to proceed to Stage 3 'Alternative Solutions'.

- If the assessment cannot exclude significant impacts either alone or in combination with other plans or projects, then the process must proceed to Stage 2.
- The following legislation were used to inform the Article 6 assessments within this report:
 - Council Directive 92/43/EEC on the conservation of natural habitats and of wild fauna and flora, 1992⁴;
 - Council Directive 2009/147/EC on the conservation of wild birds, 2009⁵;
 - The Planning and Development Acts 2000 (as amended)⁶;and
 - National Parks & Wildlife Service (NPWS), The Status of EU Protected Habitats and Species in Ireland. Habitat Assessments, Unpublished Report, 2013⁷.

Guidance

- The following guidance has been collated and reviewed to inform the Article 6 assessments within this report:
 - Appropriate Assessment of Plans and Projects in Ireland Guidance for Planning Authorities, 2009 (as amended)⁸;
 - Appropriate Assessment under Article 6 of the Habitats Directive: Guidance for Planning Authorities. Circular NPWS 1/10⁹ & PSSP 2/10, 2008¹⁰;
 - European Commission. 2021. Assessment of plans and projects in relation to Natura 2000 sites Methodological guidance on Article 6(3) and (4) of the Habitats Directive 92/43/EEC¹¹
 - CIEEM, Guidelines for Ecological Report Writing, 2017¹².



⁴ Available at: <u>https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX:31992L0043</u>

⁵ Available at: <u>https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX:32009L0147</u>

⁶ Available at: <u>http://www.irishstatutebook.ie/eli/2017/act/20/enacted/en/html</u>

⁷ Available at: <u>https://www.npws.ie/sites/default/files/publications/pdf/Article_17_Print_Vol_3_report_species_v1_1_0.pdf</u>

⁸ Available at: <u>https://www.npws.ie/sites/default/files/publications/pdf/NPWS_2009_AA_Guidance.pdf</u>

⁹ Available at: <u>https://www.npws.ie/sites/default/files/general/Circular%20NPW1-10%20%26%20PSSP2-10%20Final.pdf</u>

¹⁰ Available at: <u>https://www.npws.ie/sites/default/files/general/circular-npws-02-08.pdf</u>

¹¹Available at: <u>https://ec.europa.eu/environment/nature/natura2000/management/pdf/methodological-guidance_2021-</u> <u>10/EN.pdf</u>

¹² CIEEM (2017) Guidelines for Ecological Report Writing

Stages of Appropriate Assessment

- The Appropriate Assessment process comprises of four stages in order to identify whether proposals have the potential to significantly impact upon Natura 2000 designations. The stages are as follows:
 - Stage 1 Screening: To determine the likelihood of significant impacts;
 - Stage 2 Natura Impact Statement: To assess the impact of proposals on the integrity of the Natura 2000 site, considering the conservation objectives of the site and its ecological structure and function;
 - Stage 3 Assessment of alternatives: Where significant impacts are anticipated despite mitigation measures, the proposal should progress to Stage 3 or no longer proceed;
 - Stage 4 Assessment where no alternative exists and where adverse impacts remain: The final stage involves examining whether there are imperative reasons of overriding public interest for allowing the proposal to adversely impact upon a Natura 2000 site.

Study Zone Identification

- The 'Appropriate Assessment of Plans and Projects in Ireland, Guidance for Planning Authorities'¹³ states that the AA Screening should include the following:
 - *"Any Natura 2000 sites within or adjacent to the plan or project area;*
 - Any Natura 2000 sites within the likely zone of impact of the plan or project;
 - A distance of 15km [...] currently recommended in the case of plans, [which] derives from UK guidance (Scott Wilson et. al., 2006). For projects, the distance could be much less than 15km, and in some cases less than 100m, but this must be evaluated on a case-by-case basis with reference to the nature, size and location of the project, and the sensitivities of the ecological receptors, and the potential for in combination effects; and
 - Natura 2000 sites that are more than 15km from the plan or project area depending on the likely impacts of the plan or project, and the sensitivities of the ecological receptors,

¹³ Department for Environment, Heritage and Local Government (2009) Appropriate Assessment of Plans and Projects in Ireland Guidance for Planning Authorities. Available at: http://www.npws.ie/sites/default/files/publications/pdf/NPWS_2009_AA_Guidance.pdf



Page **11** of **26**

bearing in mind the precautionary principle. In the case of sites with water dependent habitats or species, and a plan or project that could affect water quality or quantity, for example, it may be necessary to consider the full extent of the upstream and/or downstream catchment."

• It is considered that the Zone of Influence ('ZOI') for the Natura 2000 designated sites and their qualifying features will fall within a 15km radius of developments.

Desk Study

- Sources of material that were consulted as part of the desk study for the purposes of the assessment are as follows:
 - NPWS natural heritage database for Natura 2000 sites within the ZOI of the Application Site¹⁴,
 - NPWS site synopses, Natura 2000 Data Form and conservation objectives relating to each site and aerial images, and
 - Environmental Protection Agency ('EPA') maps of river catchments, sub-catchments and flow directions.

Impact Assessment Process

- The assessment process involves:
 - Identifying and characterising Natura 2000 sites identified within the 15km zone of influence surrounding the Application Site and their qualifying features and addressing whether any of these designated sites have any connectivity with the Proposed Development. If any site is found to have no connectivity, then the designated site will be 'scoped out' (not considered further);
 - Assessing whether there will be any significant impacts to any of the Natura 2000 site, in regard to changes that result from the construction, operation and decommissioning phases of a project. Qualifying features of a Natura 2000 site that lie outside of the ZOI and not subject to any impacts from the Proposed Development will be 'scoped out' (not considered further);

Environmental Protection Agency (EPA) maps available at: <u>https://gis.epa.ie/EPAMaps/</u>



¹⁴ Environment, Heritage and Local Government (2009) Appropriate Assessment of Plan and Projects in Ireland. Available at: <u>https://www.npws.ie/sites/default/files/publications/pdf/NPWS_2009_AA_Guidance.pdf</u>

Page **12** of **26**

- Identifying any significant impacts on the integrity of the Natura 2000 site from the development and 'in combination' with any other development within 5km; and
- Identifying the need for the Appropriate Assessment process to move to Stage 2: 'Natura Impact Statement'. If there are no impacts from the development, then the development may proceed.



5. BASELINE

- 5.1. In accordance with National Parks & Wildlife Service (NPWS) guidance, this stage of the AA has identified all Natura 2000 sites located within 15km of the development boundary. The potential effects associated with the Proposed Development have been identified. Those Natura 2000 sites which will not be significantly affected will be ruled out of any further assessment.
- 5.2. Effects can depend more on the nature of impacts, sensitivity of receptors and causal linkage, rather than actual distances. The assessment below considers connectivity, either ecological, ornithological or hydrological, that may exist between the Proposed Development and the designated sites.

ECOLOGICAL SITE VISIT

- 5.1. A habitat survey was undertaken which identified the following habitats
 - Building and Artificial Surfaces (BL3);
 - Amenity Grassland (GA2);
 - Recolonising Bare Ground (ED3);
 - Scrub (WS1);
 - Depositing/Lowland rivers (FW2);
 - Hedgerows (WL1), and
 - Treelines (WL2).
- 5.2. The construction of the Proposed Development will occur primarily over land which has been identified as amenity grassland and recolonising bare ground. These habitats are considered to be of low ecological value and currently offer limited potential to support wildlife.
- 5.3. Habitats on site are suitable for supporting low numbers of common widespread species.

- 5.4. There are nine Natura 2000 designated sites located within 15km of the Application Site, comprising six Special Areas of Conservation (SACs), and three Special Protection Areas (SPAs). The qualifying features of each have been outlined within Table 5-1 below.
- 5.5. Figure 1, Appendix A of this report details the location of these sites in relation to the Application Site.

Site Code	Site Name	Qualifying Features	Distance (km), Direction	Potential Connectivity with the Proposed Developmen t Site
SAC				
001398	Rye Water Valley/Carton SAC	Petrifying springs with tufa formation (<i>Cratoneurion</i>) [7220] <i>Vertigo angustior</i> (Narrow- mouthed Whorl Snail) [1014] <i>Vertigo moulinsiana</i> (Desmoulin's Whorl Snail) [1016]	5.88km northwest	None
001209	Glenasmole Valley SAC	Semi-natural dry grasslands and scrubland facies on calcareous substrates (<i>Festuco-Brometalia</i>) (* important orchid sites) [6210] Molinia meadows on calcareous, peaty or clayey-silt-laden soils (<i>Molinion caeruleae</i>) [6410] Petrifying springs with tufa formation (<i>Cratoneurion</i>) [7220]	8.05km southeast	None
002122	Wicklow Mountains SAC	Oligotrophic waters containing very few minerals of sandy plains (<i>Littorelletalia uniflorae</i>) [3110] Natural dystrophic lakes and ponds [3160]	9.76km southeast	None

Table 5-1: Natura 2000 sites within 15km



Appendix 11.2A: Appropriate Assessment Screening Page **15** of **26**

	1	Page 15 01 20	1	,
		Northern Atlantic wet heaths with <i>Erica tetralix</i> [4010]		
		European dry heaths [4030]		
		Alpine and Boreal heaths [4060]		
		Calaminarian grasslands of the <i>Violetalia calaminariae</i> [6130]		
		Species-rich Nardus grasslands, on siliceous substrates in mountain areas (and submountain areas, in Continental Europe) [6230]		
		Blanket bogs (* if active bog) [7130]		
		Siliceous scree of the montane to snow levels (<i>Androsacetalia alpinae</i> and <i>Galeopsietalia ladani</i>) [8110]		
		Calcareous rocky slopes with chasmophytic vegetation [8210]		
		Siliceous rocky slopes with chasmophytic vegetation [8220]		
		Old sessile oak woods with Ilex and Blechnum in the British Isles [91A0]		
		<i>Lutra lutra</i> (Otter) [1355]		
000397	Red Bog, Kildare SAC	Transition mires and quaking bogs [7140]	14.44km southwest	None
		Mudflats and sandflats not covered by seawater at low tide [1140]		Hydrological
000210	South Dublin Bay SAC	Annual vegetation of drift lines [1210]	15.21km east	via the Baldonnell
		Salicornia and other annuals colonising mud and sand [1310]		stream and the River
		Embryonic shifting dunes [2110]		Liffey
		Mudflats and sandflats not covered by seawater at low tide [1140]		Hydrological connection via
000206	North Dublin Bay SAC	Annual vegetation of drift lines [1210]	17.90km northeast	the Baldonnell stream and
		Salicornia and other annuals colonising mud and sand [1310]		the River Liffey



Appendix 11.2A: Appropriate Assessment Screening

		Atlantic salt meadows (<i>Glauco-Puccinellietalia maritimae</i>) [1330] Mediterranean salt meadows (<i>Juncetalia maritimi</i>) [1410] Embryonic shifting dunes [2110] Shifting dunes along the shoreline		
		with <i>Ammophila arenaria</i> (white dunes) [2120] Fixed coastal dunes with herbaceous vegetation (grey dunes) [2130]		
		Humid dune slacks [2190] <i>Petalophyllum ralfsii</i> (Petalwort) [1395]		
SPA				
004040	Wicklow Mountains SPA	Merlin (<i>Falco columbarius</i>) [A098] Peregrine (<i>Falco peregrinus</i>) [A103]	12.88km southeast	None
004024	South Dublin Bay and River Tolka Estuary SPA	Light-bellied Brent Goose (Branta bernicla hrota) [A046] Oystercatcher (Haematopus ostralegus) [A130] Ringed Plover (Charadrius hiaticula) [A137] Grey Plover (Pluvialis squatarola) [A141] Knot (Calidris canutus) [A143] Sanderling (Calidris alba) [A144] Dunlin (Calidris alpina) [A149] Bar-tailed Godwit (Limosa lapponica) [A157] Redshank (Tringa totanus) [A162] Black-headed Gull (Chroicocephalus ridibundus) [A179] Roseate Tern (Sterna dougallii)	14.81km east	Hydrological connectivity via the Baldonnell stream and the River Liffey



Appendix 11.2A: Appropriate Assessment Screening

Page 17 of 26					
		Common Tern (<i>Sterna hirundo</i>) [A193]			
		Arctic Tern (<i>Sterna paradisaea</i>) [A194]			
		Wetland and Waterbirds [A999]			
		Light-bellied Brent Goose (<i>Branta bernicla hrota</i>) [A046]			
		Shelduck (<i>Tadorna tadorna</i>) [A048]			
		Teal (Anas crecca) [A052]			
		Pintail (Anas acuta) [A054]			
		Shoveler (<i>Anas clypeata</i>) [A056]			
		Oystercatcher (<i>Haematopus</i> ostralegus) [A130]	19.71km east	Hydrological connectivity via the Baldonnell stream and the River Liffey	
		Golden Plover (<i>Pluvialis apricaria</i>) [A140]			
		Grey Plover (<i>Pluvialis squatarola</i>) [A141]			
	North Bull	Knot (<i>Calidris canutus</i>) [A143]			
004006	Island SPA	Sanderling (<i>Calidris alba</i>) [A144]			
		Dunlin (<i>Calidris alpina</i>) [A149]			
		Black-tailed Godwit (<i>Limosa</i> <i>limosa</i>) [A156]			
		Bar-tailed Godwit (<i>Limosa</i> <i>lapponica</i>) [A157]			
		Curlew (<i>Numenius arquata</i>) [A160]			
		Redshank (<i>Tringa totanus</i>) [A162]			
		Turnstone (<i>Arenaria interpres</i>) [A169]			
		Black-headed Gull (<i>Chroicocephalus ridibundus</i>) [A179]			
		Wetland and Waterbirds [A999]			

5.6. As shown in **Table 5-1**, the Application Site has a potential hydrological connection with four internationally designated sites.



Page **18** of **26**

- 5.7. The Baldonnell stream discharges into the River Liffey, approximately 7km from the Application Site. The River Liffey stretches approximately 28km before entering into the Dublin Bay. Therefore, it is considered that there is a hydrological connection between the Application Site and the designated sites within the Dublin Bay (South Dublin Bay and River Tolka SPA, North Bull Island SPA, South Dublin Bay SAC and North Dublin Bay SAC).
- 5.8. It is considered that the survey area is unlikely to support any of the Annex II species or assemblages listed above. Narrow-mouthed Whorl Snail and Desmoulin's whorl snail are restricted to the marsh vegetation of the Rye Water Valley/Carton SAC. The Application site is not considered to offer suitable habitat for otter, the Baldonnell Stream is too narrow to support breeding and foraging otter, and the surrounding habitats (business parks, a golf course and a significant amount of residential housing and shopping centres) are not suitable to support otters commuting from the Wicklow Mountains SAC.
- 5.9. The habitats are not suitable for supporting the qualifying bird species of the SPAs listed above. Merlin and Peregrine are associated with the upland habitats of the Wicklow Mountains SPA. Black-headed gulls (associated with Poulaphouca Reservoir SPA) nest in wetland habitats, but are not confined to wetlands, and will forage in domestic waste and fields of crop. As there is there is no food waste or crop associated within the Application Site it is considered there is no potential for gull species to scavenge within the site boundary. Greylag goose prefer coastal habitats or wetland habitats for foraging and/or breeding.
- 5.10. Given that no connectivity (potential pathway for impact) exists between the Application Site and the Natura 2000 designated sites, these sites have been scoped out of the impact assessment. No impacts upon these sites will result from the Proposed Development.



- 6.1. This section discusses and evaluates the likely impacts of the Proposed Development affecting the Natura 2000 sites within the Zone of Influence (ZOI) of the Application Site (i.e. where there is some ecological, ornithological or hydrological connection between the Application Site and the Natura 2000 site).
- 6.2. As outlined within **Table 5-1** above, the Application Site has hydrological connectivity with the South Dublin Bay and River Tolka Estuary SPA, offering a pathway for impacts through the movement of contaminated waters.
- 6.3. Aquatic systems and the species/habitats which are dependent on these systems are sensitive to pollution and contamination of surface waters. Pollution can result from any of the following entering a body of surface or groundwater:
 - Poisonous, noxious or polluting matter;
 - Waste matter (including silt, cement, concrete, oil, petroleum spirit, chemicals, solvents, sewage and other polluting matter);
 - Other harmful activities detrimentally affecting the status of a waterbody.
- 6.4. **Table 6-1** below details common water pollutants and their effect on the aquatic environment and standard Best Practice Pollution Measures. (This table has been extracted from Ciria guidance¹⁵).

Table 6-1: Common water pollutants and their effects on the aquatic environment and standard prevention measures



¹⁵ Ciria (2015) Environmental Good Practice on Site guide, fourth edition

Common Water Pollutants	Adverse Effect on Aquatic Environment	Standard Best Practice Pollution Prevention Measures	
Silt	Reduces water quality, clogs fish gills, covers aquatic plants, impacts aquatic invertebrates, leads to a reduction in prey for species and leads to degradation of habitat	Pollution Prevention Hydrocarbons, greases and hydraulic fluids will be stored in a secure compound area; All plant machinery will be properly serviced and maintained thereby reducing risk of spillage or leakage; All waste produced from construction will be collected in skips with the construction site kept tidy at all times;	
Bentonite (very fine silt)	Reduces water quality, clogs fish gills, covers aquatic plants, impacts aquatic invertebrates, leads to a reduction in prey for species and leads to degradation of habitat	Excavated soil will be stored on site or removed by a licensed waste disposal unit; All materials and substances used for construction will be stored in a secure compound and all chemicals to be stored in secure containers to avoid potential contamination; Location of spill kit to be known by all construction workers and implemented in the event of spillage or leakage. <u>Waste Management</u>	
Cement or concrete wash water (highly alkaline)	Changes the chemical balance, is toxic to fish and other wildlife. This can lead to direct impacts for aquatic species (including otter), or indirect through loss of prey resources		
Detergent	Removes dissolved oxygen, can be toxic to fish and other wildlife present within the aquatic environment	at all times and collected regularly of when full; All hydrocarbons and fluids are to b collected in leak-proof containers an removed from site for disposal of recycling;	



Page	21	of	26
------	----	----	----

		All waste from construction is to be
		stored within the site confines and
		removed to a permitted waste facility.
	Suffocates aquatic life,	
Hydrocarbons	damaging to the wildlife	Environmental Monitoring
(e.g. oil,	(e.g. birds), and to water	g
diesel)	supplies including industrial	Contractor to nominate member of staff
	abstractions	as the environmental officer with the
		responsibility to ensure best practice
		measures are implemented and adhered
		to, with any incidents or non-compliance
	Reduces water quality, is	issues being reported to project team.
Course and	toxic to aquatic wildlife,	
Sewage	and damages water	
	supplies	

Assessment of Likely Impacts Affecting Natura 2000 Designated sites in Dublin Bay

South Dublin Bay SAC

- 6.5. The South Dublin Bay SAC is located approximately 15km east, but connectivity is approximately 29km downstream of the Application Site. The site has been designated for a number of important Annex I habitats of the E.U. Habitats Directive, as detailed within Table 5-1 above. The Application Site and the designated sites do not share any of the same habitats.
- 6.6. The only opportunity for pollution arising from the Proposed Development to impact upon the designated site is through the contamination of the Baldonell stream. Given the drainage measures in place at the site, and the large distance between the Application Site and the Dublin Bay, the dilution factor will result in a **negligible impact** upon the SAC and its qualifying species.
- 6.7. Notwithstanding this, during the construction phase, standard best practice measures will be adhered to.
- 6.8. **Chapter 5: Demolition and Construction Environmental Management** outlines the procedures that will be implemented to prevent any spillages to the Balonnell stream. In order to prevent any spillages of fuels to the Baldonnel Stream, or groundwater, the following measures are proposed:
 - Designation of a bunded refuelling areas on the site;
 - Provision of spill kit facilities across the site;
 - Where mobile fuel bowsers are used the following measures would be taken:



Page 22 of 26

- Any flexible pipe, tap or valve would be fitted with a lock and would be secured when not in use;
- Pumps or valves would be fitted with a lock and would be secured when not in use;
- All bowsers to carry a spill kit;
- Operatives must have spill response training; and
- Drip trays used on any required mobile fuel units.
- In the case of drummed fuel or other potentially polluting substances which may be used during the demolition and construction stage the following procedures will be adopted:
- Secure storage of all containers that contain potential polluting substances in a dedicated internally bunded chemical storage cabinet unit or inside a concrete bunded area;
- Clear labelling of containers so that appropriate remedial measures can be taken in the event of a spillage;
- All drums to be quality approved and manufactured to a recognised standard;
- If drums are to be moved around the site, they would be secured and on spill pallets; and
- Drums to be loaded and unloaded by competent and trained personnel using appropriate equipment.
- 6.9. Additional measures are outlined in Chapter 5. With the implementation of best practice measures, and considering the distance and dilution factors, **no significant effects** are predicted on qualifying habitats and species of South Dublin Bay SAC.

North Dublin Bay SAC

- 6.1. The North Dublin Bay SAC is located approximately 17.9km northeast but connectivity is over 30km downstream of the Application Site.
- 6.2. As outlined above in the assessment of the South Dublin Bay SAC, there is limited hydrological connectivity between the Proposed Development and Natura 2000 Sites within the Dublin Bay. Due to the drainage measures in place, and likely dispersion it is considered that potential effects are **negligible**. With best practice pollution measures in place, it is considered that there is no potential for significant effects.



Page **23** of **26**

- 6.3. Potential impacts from the Proposed Development will not be significant or have a detrimental effect on the qualifying features of any Natura 2000 designated sites with a hydrological connection.
- 6.4. Therefore, **no significant effects** are predicted on qualifying species of North Dublin Bay SAC.

South Dublin Bay and River Tolka Estuary SPA

- 6.5. Given the large distance between the Application Site and the SPA, the dilution factor will result in a **negligible** impact upon the SPA and its qualifying species.
- 6.6. Therefore, **no significant effects** are predicted on qualifying species of South Dublin Bay and River Tolka Estuary SPA.

North Bull Island SPA

- 6.1. Given the large distance between the Application Site and the SPA, the dilution factor will result in a **negligible** impact upon the SPA and its qualifying species.
- 6.2. Therefore, **no significant effects** are predicted on qualifying species of North Bull Island SPA.


- 7.1. As well as singular effects, cumulative effects also need to be considered. Article 6 of the EU Habitats Directive and Regulation 15 of the European Communities (Natural Habitats) Regulations state that an AA should be performed for any plan or project that, either alone or in combination with other plans or projects, may significantly affect a Natura 2000 site.
- 7.2. Cumulative effects can be an issue when multiple proposals each have a low level of impact on Natura 2000 sites. If several proposals all have a small impact, the combined result can lead to a significant effect on the qualifying features of a Natura 2000 site.
- 7.3. However, the Proposed Development will have negligible impacts upon any Natura 2000 site. For the purposes of this assessment, it is therefore confirmed that no likely significant cumulative effects will occur upon any Natura 2000 sites as a result of the Proposed Development due to the
- 7.4. A search of the National Planning Application Database and the Dublin City Council online planning portal identified a large number of permitted plans or projects within 5km of the Proposed Development. However, as the Proposed Development will have no significant effects upon any Natura 2000 site, for the purposes of this this assessment it is therefore confirmed that **no likely cumulative effects will occur upon any Natura 2000 site as a result of the Proposed Development.**



8. CONCLUSION

- 8.1. According to NPWS (2009), the Appropriate Assessment Stage 1: Screening exercise can result in one of three conditions:
 - An Appropriate Assessment is not required i.e., where the plan/proposal is associated with the management of the site;
 - There is no potential for significant effects i.e., Appropriate Assessment is not required;
 - Significant effects are certain, likely or uncertain i.e., the project must either proceed to Stage 2: Appropriate Assessment or be rejected.
- 8.2. The Proposed Development was screened for likely significant adverse effects upon any designated sites within its Zone of Influence. Within 15km of the Application Site there are nine designated sites, comprising six Special Areas of Conservation (SACs) and three Special Protection Areas (SPAs).
- 8.3. Potential connectivity (potential pathways for impact) exists between the Application Site and four designated sites; the North Dublin Bay SAC, the South Dublin Bay and River Tolka Estuary SPA and the North Bull Island SPA. This connectivity is roughly 28km downstream via the Baldonnel stream.
- 8.4. Given that the Proposed Development does not involve any instream works, and considering the distance and dilution factors, it has been concluded that the Proposed Development will not lead to significant adverse impacts upon any Natura 2000 sites. No likely significant effect is foreseen upon these Natura 2000 sites as a result of the proposals, either alone or in combination with any other development.
- 8.5. This screening report, based on the best available scientific information, finds that there is no reasonable scientific doubt that the development does not pose any risk of significant adverse effects on Natura 2000 sites, and that the development does not require progression to a Stage 2 AA. It is considered that the next stage of the AA is not required.



9. APPENDICES

Appendix A

• Figure 1: Natura 2000 Designated Sites



Technical Appendix 11.3A: Biodiversity Management Plan



Appendix11.3A:BiodiversityManagement Plan

27/02/2023



Disclaimer

Neo Environmental Limited shall have no liability for any loss, damage, injury, claim, expense, cost or other consequence arising as a result of use or reliance upon any information contained in or omitted from this document.

Copyright © 2023

The material presented in this report is confidential. This report has been prepared for the exclusive use of Ramboll. The report shall not be distributed or made available to any other company or person without the knowledge and written consent of Ramboll or Neo Environmental Ltd.

Neo Environmental Ltd		
Head Offic	e - Glasgow:	
Wright Bus	iness Centre,	
1 Lonm	nay Road,	
Glas	sgow.	
G33	3 4EL	
T 0141	773 6262	
E: info@neo-environmental.co.uk		
Warrington Office:	Rugby Office:	
Cinnamon House,	Valiant Suites,	
Crab Lane,	Lumonics House, Valley Drive,	
Warrington,	Swift Valley, Rugby,	
WA2 OXP.	Warwickshire, CV21 1TQ.	
T: 01925 661 716	T: 01788 297012	
E: info@neo-environmental.co.uk	E: info@neo-environmental.co.uk	
Ireland Office:	Northern Ireland Office:	
Johnstown Business Centre,	83-85 Bridge Street,	
Johnstown House,	Ballymena, Co. Antrim	
INdas,	BT43 5EN	
	T: 0282 565 04 13	
1:00 353 (0)45 844250	E: info@neo-environmental.co.uk	
E: Into@neo-environmental.le		



Appendix 11.3A: Biodiversity Management Plan

Prepared For:

Ramboll

Prepared By:

Louis Maloney BSc (Hons) MSc

Dara Dunlop BSc (Hons) MSc



	Name	Date
Edited By:	Louis Maloney	27/02/2023
Checked By:	Dara Dunlop	27/02/2023
	Name	Signature
Approved By	Paul Neary	0 lat



Contents

EXECUTIVE SUMMARY	5
INTRODUCTION	6
CURRENT CONSERVATION & BIODIVERSITY	8
HABITATS & SPECIES PRESENT	14
POTENTIAL IMPACTS	15
MANAGEMENT & RECOMMENDATIONS	17
Management Objectives and Action Plan	19
HABITAT CREATION	23
APPENDICES	32



EXECUTIVE SUMMARY

- 1.1. Objectives have been established to enhance and maintain the biodiversity of the land at a proposed data centre building and associated development on lands within Profile Park, Clondalkin, Dublin.
- 1.2. Measures include: native riparian planting along the Baldonnel stream and wetland wildflower (meadow) planting, the planting of species-rich hedgerows to provide a plentiful source of food and shelter for a range of fauna species. Other enhancement measures include development of a wildflower meadow mix, native woodland, medium to large deciduous trees and native conifer trees on site. This would be in addition to creating a herptile hibernaculum and adding bird and bat boxes to the site.
- 1.3. A Fossitt habitat survey of the site was conducted on the 20th of July 2022 by Eiméar Rose Cunningham to assess the current baseline of the Application Site. An Ecological Impact Assessment (EcIA) was then conducted to assess the local area and its ability to support a range of wildlife, as part of the full planning application.
- 1.4. The enhancements and management measures set out in this document have been developed in accordance with the findings of the above habitat survey. This will enable the Proposed Development to deliver biodiversity gain.



INTRODUCTION

Background

1.6. Neo Environmental Ltd has been appointed by Ramboll on behalf of Vantage Data Centres Dub 11 Limited (the "Applicant") to undertake a Biodiversity Management Plan for a data centre building and associated development (the "Proposed Development") on lands within Profile Park, Clondalkin, Dublin (the "Application Site").

Development Description

- 1.7. The development applied for consists of the construction of one no. two storey data centres with a gross floor area of c. 12,893 sqm that will include office at first floor.
- 1.8. The proposed data centre comprises of a two-storey data centre that will include 13 no. standby emergency generators with associate flues (each 25m in height) to be located to the west of the building.
- 1.9. The data centre will be c. 14.23m to parapet height with the roof plant increasing the height to 18.5m overall.
- 1.10. The data centre will be accessed from a new emergency and service vehicular access off Falcon Avenue as well as from the site of the already permitted data centres to the west.
- 1.11. The data centre will be served by 60 car parking spaces that will be located generally to the east of the data centre, of which 3 no. spaces will be disabled spaces and 6 of these spaces will be provided for electrical charging vehicles. Covered bicycle parking provision will be provided within the site.
- 1.12. The data centre will be enclosed by landscape berms and planting to the north and northeast.

Site Description

- 1.13. The Application Site is centred at Irish Grid Reference (IGR) O 03894 30791.
- 1.14. The Application Site is located **Profile Park Business Park**, Nangor Road, Clondalkin, County Dublin, Ireland. The surrounding area is mostly commercial in nature with retail/business parks, data centres and other commercial businesses in the vicinity of the proposed site. There is one residential property within the red line boundary of the proposed development site.
- 1.15. The site's immediate boundaries are defined by the following:
 - The land is adjacent to Nangor Road which is situated north of the Application Site boundary.



- To the east of the site is the entrance to the business park as well as the Grange Castle Golf Club.
- To the south of the site are further green fields and commercial businesses within the business park, including Digital Reality Profile Park.
- Immediately to the south of the red line boundary of the site is the Baldonnel stream which flows west.
- To the west of the site is further green field and the continuation of the Baldonnel stream as well as Grange Castle Business Park and Bennet Construction.
- 1.16. Currently the site comprises mostly of amenity grassland with small areas of scrub, recolonising bare ground and buildings and other artificial surfaces. The site is bound by horse chestnut treeline to the south and bound by a combination of treeline and hedgerow elsewhere.
- 1.17. The wider context of the site is characterised by a mix of industrial and agricultural development with a fragmented mixture of commercial, industrial and residential uses.



OBJECTIVE OF THE BIODIVERSITY MANAGEMENT PLAN

- 1.18. The objective of this BMP is to minimise any potential negative impacts, arising from the Proposed Development, while increasing the habitat diversity. The enhancement of the land within the Application Site boundary will increase the sites capability of supporting wildlife.
- 1.19. This will be achieved by
 - Creating and maintaining native riparian vegetation along Baldonnel stream;
 - Creating and maintaining a wetland specific species-rich diverse grassland with a varied sward structure;
 - Creating and maintaining a wildflower meadow;
 - Creating and maintaining species-rich hedgerows;
 - Planting and maintaining medium to large deciduous trees;
 - Planting and maintaining coniferous trees;
 - Creating and maintaining wildlife shelters for priority and locally important species; and
 - Maximise the floral and faunal biodiversity of the created and retained habitats.

CURRENT CONSERVATION & BIODIVERSITY

National Conservation

Ireland's National Biodiversity Action Plan 2017 - 2021¹

- 1.20. Ireland's 4th National Biodiversity Action Plan for the period 2023-2027 has been in development since October 2021. Is it currently in the public consultation phase. For the purpose of this report, the objectivise of the 2017-2021 plan has been considered.
- 1.21. The National Biodiversity Action Plan² sets out a vision and seven strategic objectives to halt the decline of biodiversity across Ireland.

"Objective 1 - Mainstream biodiversity into decision-making across all sectors.

² Department of Arts, Heritage and the Gaeltacht (2011) Actions for Biodiversity 2011 – 2016 Ireland's National Biodiversity Action Plan. Available at: http://www.npws.ie/sites/default/files/general/national-biodiversity-plan-english.pdf



¹ Department of Culture, Heritage, and the Gaeltach (2017) National Biodiversity Action Plan 2017-2021

Objective 2 - Strengthen the knowledge base for conservation, management, and sustainable use of biodiversity.

Objective 3 - Increase awareness and appreciation of biodiversity and ecosystem services.

Objective 4 - conserve and restore biodiversity and ecosystem services in the wider countryside.

Objective 5 - conserve and restore biodiversity and ecosystem services in the marine environment.

Objective 6 - Expand and improve management of protected areas and species.

Objective 7 - Strengthen international governance for biodiversity and ecosystem services."

- 1.22. This document outlines that special protection to sites of highest nature value and species most at risk, including designated sites should be afforded. However, effective conservation and sustainable use of biodiversity should also occur within the wider countryside, as this is where much of the biodiversity lies.
- 1.23. The primary threat to biodiversity both within and outside protected areas is from habitat degradation, fragmentation and loss due to changes in agricultural practices (such as intensification), commercial forestry, fisheries over exploitation, peat extraction, air and water pollution, invasive alien species, land clearance and development, tourism and recreational activities and climate change.

National Biodiversity Action Strategy 2022-2026³

- 1.24. The National Biodiversity Action Strategy was created by the Office of Public Works to identify strategic actions to help government delivery of the National Biodiversity Action Plan. The Plan outlines 48 strategic actions, each with an expected outcome and key performance indicators defined. These actions are divided into five strategic themes;
 - 1. Strategic Theme 1 Planning for Nature
 - 2. Strategic Theme 2 Natural Leaders
 - 3. Strategic Theme 3 Working with Water and Wildlife
 - 4. Strategic Theme 4 Diversity by Design
 - 5. Strategic Theme 5 Natural Knowledge



³ OPW (2022) Biodiversity Action Strategy 2022-2027

South Dublin Development Plan 2022–2028 4

- 1.25. The Plan sets out an overall strategy for the proper planning and sustainable development of the County and consists of a written statement and accompanying plans and maps
- 1.26. Chapter 3 of the Plan refers to the county's natural heritage and contains a number of key policies (outlined below), which aim to protect and enhance biodiversity and designated sites within the county:

NCBH1: Objective 1: To protect, conserve and enhance natural, built and cultural heritage features, seeking opportunities to identify, retain, protect, and incorporate heritage assets into plans and development.

NCBH1 Objective 2: To support the objectives and actions of the County Heritage Plan and the County Biodiversity Action Plan in the promotion and protection of natural, built and cultural heritage, and to take full cognisance of the County's Landscape Character Assessment and the County Geological Audit in the sustainable management of development.

NCBH1 Objective 3: To carry out an audit and assessment, based on an initial pilot study of the County's natural and built heritage assets including Council owned protected structures and archaeological features; to identify and safeguard these assets from the potential impacts of climate change; and to explore possible uses as part of climate change mitigation.

NCBH2 Objective 1: To support the implementation of the National Biodiversity Action Plan (2017-2021) and the All-Ireland Pollinator Plan (2021-2025) and to support the adoption and implementation of the South Dublin County Biodiversity Action Plan (2020-2026) and Pollinator Action Plan (2021-2025) and any superseding plans.

NCBH2 Objective 2: To ensure the protection of designated sites in compliance with relevant EU Directives and applicable national legislation.

NCBH2 Objective 3: To protect and conserve the natural heritage of the County, and to conserve and manage EU and nationally designated sites and non-designated locally important areas which act as 'stepping stones' for the purposes of green infrastructure and Article 10 of the Habitats Directive.

NCBH2 Objective 4: To protect our rivers and in particular to avoid overdevelopment which could have an adverse effect on the biodiversity and ecosystems of the river.

NCBH3 Objective 1: To prevent development and activities that would adversely affect the integrity of any Natura 2000 site located within or adjacent to the County and promote the favourable conservation status of the habitats and species integral to these sites.

NCBH3 Objective 2: To ensure that plans, including land use plans, will only be adopted, if they either individually or in combination with existing and / or proposed plans or projects, will not



⁴ Available from : https://www.sdcc.ie/en/devplan2022/adopted-plan/

have a significant adverse effect on a European Site, or where such a plan is likely or might have such a significant adverse effect (either alone or in combination), South Dublin County Council will, as required by law, carry out an appropriate assessment as per requirements of Article 6(3) of the Habitats Directive 92 / 43 / EEC of the 21 May 1992 on the conservation of natural habitats and of wild fauna and flora, as transposed into Irish legislation. Only after having ascertained that the plan will not adversely affect the integrity of any European site, will South Dublin County Council adopt the plan, incorporating any necessary mitigation measures. A plan which could adversely affect the integrity of a European site may only be adopted in exceptional circumstances, as provided for in Article 6(4) of the Habitats Directive as transposed into Irish legislation.

NCBH3 Objective 3: To ensure that planning permission will only be granted for a development proposal that, either individually or in combination with existing and / or proposed plans or projects, will not have a significant adverse effect on a European Site, or where such a development proposal is likely or might have such a significant adverse effect (either alone or in combination), the planning authority will, as required by law, carry out an appropriate assessment as per requirements of Article 6(3) of the Habitats Directive 92 / 43 / EEC of the 21 May 1992 on the conservation of natural habitats and of wild fauna and flora, as transposed into Irish legislation. Only after having ascertained that the development proposal will not adversely affect the integrity of any European site, will the planning authority agree to the development and impose appropriate mitigation measures in the form of planning conditions. A development proposal which could adversely affect the integrity of a European site may only be permitted in exceptional circumstances, as provided for in Article 6(4) of the Habitats Directive as transposed into Irish legislation.

NCBH4: Protect the ecological, visual, recreational, environmental and amenity value of the County's proposed Natural Heritage Areas and associated habitats and species.

NCBH5: Protect and promote the conservation of biodiversity outside of designated areas and ensure that species and habitats that are protected under the Wildlife Acts 1976 to 2018, the Birds Directive 1979 and the Habitats Directive 1992, the Flora (Protection) Order 2015, and wildlife corridors are adequately protected.

NCBH10: Protect against and prevent the introduction and spread of invasive species within the County and require landowners and developers to adhere to best practice guidance in relation to the control of invasive species.

NCB11: Review Tree Preservation Orders (TPO) within the County and maintain the conservation value of trees and groups of trees that are the subject of a Tree Preservation Order while also recognising the value of and protecting trees and hedgerows which are not subject to a TPO.



South Dublin County Council Draft Biodiversity Action Plan 2020-2026⁵

- 1.27. The preparation of this Biodiversity Action Plan is an objective of the South Dublin County Heritage Plan and the South Dublin County Council Development Plan 2022-2028. The South Dublin County Biodiversity Plan was prepared in the context of a range of national and international plans for biodiversity protection and enhancement
- 1.28. The National Biodiversity Plan lists a range of actions for biodiversity that aim to achieve this vision, arranged under a series of 7 Strategic Objectives. These objectives are:
 - the mainstreaming of biodiversity issues across the decision-making in all sectors;
 - the strengthening of the knowledge base for conservation, management and sustainable use of biodiversity;
 - increasing public awareness and appreciation of biodiversity and ecosystem services;
 - the conservation and restoration of biodiversity and ecosystem services in the wider countryside;
 - the conservation and restoration of biodiversity and ecosystem services in the marine environment;
 - the expansion and improved management of protected areas and species; and
 - the strengthening of international governance for biodiversity and ecosystem services.

All Ireland Pollinator Plan 2021-20256

- 1.29. On the 17th of September 2015, Ireland joined a small number of countries in Europe who have developed a strategy to address pollinator decline and protect pollination services. In March 2021, a new Plan was released.
- 1.30. This new Plan has six objectives and has identified 186 actions in order to achieve its objectives. The six objectives are as follows:
 - Making farmland pollinator friendly. Working together with the farming community, increase awareness of pollinators and the resources they need in order to survive on farmland.

⁶ National Biodiversity Data Centre (2015) All Ireland Pollinator Plan 2021-2025. Available at: https://pollinators.ie/wp-content/uploads/2021/03/All-Ireland-Pollinator-Plan-2021-2025-WEB.pdf



⁵https://consult.sdublincoco.ie/en/consultation/draft-biodiversity-action-plan-south-dublin-county-connecting-nature-2020-2026

- Making public land pollinator friendly. Working with Councils, Transport Authorities,
 Local Communities and others, to strengthen links between this plan and other
 initiatives and to increase shelter and food resources for pollinators.
- Making private plan pollinator friendly. Work together with the public and community groups to create networks of biodiversity-friendly habitat across the landscape.
- All-Ireland honeybee strategy. Working with beekeepers, achieve healthy, sustainable populations, and for honeybees to be part of a cohesive pollinator message that balances managed and wild pollinator populations.
- Conserving rare pollinators. Improving our knowledge on rare pollinators, and raising awareness through dedicated initiatives, achieve a Plan that protects as much wild pollinator diversity as possible.
- Strategic coordination of the Plan. Continually raising awareness; addressing gaps in knowledge through research, tracking where pollinators occur and how populations are changing, work from an evidence base that enables us to coordinate a dynamic plan that is targeted and effective.
- 1.31. The enhancements set out within this BMP will create areas of flower-rich habitat that will support Ireland's pollinator species, including bees and flies.

Local Conservation

- 1.32. The Proposed Development does not lie within or directly adjacent to any statutory or nonstatutory designated environmental sites. Within 15km of the Application Site boundary there are nine Natura 2000 designated sites, six Special Areas of Conservation (SACs) and three Special Protection Areas (SPA)
- 1.33. Please refer to the supporting Appropriate Assessment (AA) Screening report (**Appendix 8.2**) for details of all Natura 2000 sites within 15km of the Application Boundary.
- 1.34. From the findings of the EcIA and AA it is considered that with the implementation of design, best practice and mitigation measures the Proposed Development will not significantly impact upon any of the designated and non-designated sites located within 15km of the Proposed Development.



HABITATS & SPECIES PRESENT

- 1.35. An extended habitat survey of the Proposed Development was undertaken in July 2022. The following habitat types were identified:
 - Building and Artificial Surfaces (BL3)
 - Amenity Grassland (GA2)
 - Recolonising Bare Ground (ED3)
 - Scrub (WS1)
 - Depositing/Lowland rivers (FW2)
 - Hedgerows (WL1)
 - Treelines (WL2)

(Note: Fossitt classification within brackets).

Fauna

- 1.36. The potential presence of protected species within the study area was assessed though a data search conducted through the NBDC. This identified records of invasive, rare, scarce and protected species within 2km of the Proposed Development location.
- 1.37. The Application Site is located within the 1km grid squares O03F. A database search was also carried out for adjacent grid squares to ensure a full assessment of the 2km radius.
- 1.38. Additional information on the suitability of habitat in the surrounding area for bats was also obtained from the NBDC in the form of a habitat suitability map. The map provided enhanced information on the recorded distribution of bats and broad-scale geographic patterns of occurrence and local roosting habitat requirements for Irish bat species.
- 1.39. In addition, the extended habitat survey included a species scoping survey in order to assess the potential of the site to support protected species.
- 1.40. The Application Site and adjacent areas offer suitable habitat for badger, hedgehog, otter, shrew, squirrel, bat, bird and herptile species which are known to be present in the local area.



POTENTIAL IMPACTS

- 1.41. Potential impacts which could arise from a Development include:
 - Potential habitat loss and fragmentation;
 - Disturbance during construction and decommissioning; and
 - Potential contamination of surface waters.
- 1.42. Each of these potential impacts have been considered below in relation to the Proposed Development.

Potential Habitat Loss and Fragmentation

- 1.43. The overall ground-level Proposed Development footprint take up 12,893m².
- 1.44. Currently the habitat present under the Proposed Development footprint is primarily amenity grassland, considered to be of low ecological value. As the surrounding landscape is of a similar nature, the loss of these small areas will not be significant and the alteration of this habitat will not result in fragmentation.
- 1.45. Post-construction, with the implementation of this BMP, existing habitats are to be enhanced, with new habitats created. This document sets out how the habitats including hedgerows, trees, wildflower meadow and wetland meadow within the Application Site will be sensitively managed to ensure the maximum potential of these habitats are maintained throughout the lifetime of the development.
- 1.46. It is therefore demonstrated that the Proposed Development will have a positive significant impact on local habitats and will indeed deliver biodiversity enhancements to the benefit of the site and wider area.

Disturbance During Construction and Operation

- 1.47. The construction and decommissioning phases of the Proposed Development have the greatest potential to impact upon local wildlife.
- 1.48A Measures will be implemented prior to construction and decommission work taking place to minimise any potential disturbance to wildlife. Mitigation measures recommended within the Ecological Impact Assessment (**Appendix 8.1**) include:
 - Pre-construction bird surveys, if works commence between March and August inclusive;
 - Pre-construction badger survey;
 - Pre-construction otter survey;



- Securely covering all excavations at the end of each working day to prevent accidental trapping of badger, otter or other small mammals;
- <u>Mammal gates will be installed at the base of security fence (every 10m, where possible)</u> to allow the free movement of badger and other small mammals through the site.
- 1.49. With the creation of the wildflower meadow, wetland meadow, native hedgerow and native woodland/trees along with the introduction of hibernacula, bat and bird boxes and the enhancement of existing hedgerows and riparian habitat combined with sensitive management, the sites potential for supporting local wildlife could be greatly increased post-construction.

Potential Disturbance and Contamination of Surface Waters

- 1.50. The construction phase of a development has the potential for contamination of surface waters, if appropriate measures are not implemented.
- 1.51. A Demolition and Construction Environmental Management Plan (DCEMP) Chapter 5 of the accompanying Environmental Impact Assessment Report (EIAR) has been produced by Pinnacle Consulting Engineers. This DCEMP report outlines measures to be implemented during demolition and construction works to prevent contamination of the stream through contaminated surface waters.
- The Baldonnel stream was assessed in the adjacent lands (in support of planning reference: SD20A/0283). Low species diversity of freshwater invertebrates were recorded, samples were dominated by freshwater shrimp and stone clingers.
- 1.53. Through following measures outlined in the DCEMP it is envisaged that no contaminants will enter the Baldonnel stream as a result of construction and demolition involved for the proposed development.
- 1.54A A bridge will be created to cross a small section of the Baldonnell stream. is proposed to be culverted, via two pipes, under the road in the south of the site. With the implementation of riparian planting and enhancements along the banks of the Baldonnel stream the Proposed Development will have a positive significant impact on local habitats (i.e. providing structure for invertebrate species, and thus, enhancing feeding for aquatic species such as frog) and will indeed deliver biodiversity enhancements to the benefit of the site and wider area.



MANAGEMENT & RECOMMENDATIONS

- 1.55. The following management recommendations have been made:
 - to maintain and improve the biodiversity of species within the site;
 - to enhance the quality of habitats present;
 - increase the sites potential for supporting wildlife; and
 - to avoid any potential negative impacts arising from the Proposed Development of the site.
- 1.56. It is proposed that the implementation of biodiversity and landscaping enhancements, will be undertaken early within the construction programme. This will enable habitats to establish before the operational phase of the development.

Recommended Management

1.57. Currently the amenity grassland of which the majority of the Application Site comprises offers limited benefit to wildlife. The potential of the site to support wildlife will be significantly increased by the habitat creation measures set out below.

Habitat Enhancement

- 1.58. Various options exist to enhance the biodiversity value of a site, including the creation of different habitats, such as: hedgerows, woodland, riparian zones, wildflower meadows and individual conifer and deciduous tree planting.
- 1.59. Habitats that will be created at the development site will include:
 - Native woodland;
 - Native hedgerow;
 - Riparian zones;
 - Wetland wildflower meadow;
 - Standard wildflower meadow;
 - Hibernaculum;
 - Bird and bat boxes;
 - Bee and beetle banks.



1.60. These habitats individually offer shelter and a food source for supporting a variety of wildlife. The mosaic of these new habitats combined with the existing hedgerows and existing trees, will support the existing wildlife within the site. They also have excellent potential to allow the biodiversity of the site to increase, by offering a wider range of habitats that benefit local wildlife.

General Considerations

Obligations

- 1.61. During each of the Proposed Development phases there are a number of legal obligations that should be considered by all those involved in site work:
 - Ensure obligations of the European Communities (Birds and Natural Habitats) Regulations 2011 are met by all involved with the site.
 - Ensure obligations of the Wildlife Act 1976 and Wildlife (Amendment) Act 2000 are met by all involved with the site.
 - Ensure all relevant Health & Safety at Work Act obligations.

Good Ecological Practice

1.62. Whilst management practices should only be altered if there is a good ecological reason for doing so, they should not be rigidly adhered to if they are obviously detrimental.

Invasive Non-Native Species

1.63. During the extended habitat survey no field signs or evidence of invasive non-native species were observed.



MANAGEMENT OBJECTIVES AND ACTION PLAN

Table 1-1A: Recommended Management

Objective	Action Plan Task	Timescale	Notes
Creating a diversity of habitats within the site	Wetland wildflower mix to contain:Devils Bit (Scabious Succisa pratensis), Common Sorrel (Rumex acetosa), Cuckoo Flower (Cardamine pratensis), Cowslip (Primula veris), Fleabane* (Erigeron), Greater Trefoil* (Lotus pedunculatus), Hemp Agrimony (Eupatorium cannabinum), Lesser Knapweed 	Year 1 (early within the construction phase)	Wetland Wildflower mix and Standard Wildflower Meadow will also provide habitat for small mammals and larvae of pollinating insects, including butterflies and moths.



	Meadow Buttercup (Ranunculus Acris), Meadow Vetchling (Lathyrus pratensis), Musk Mallow (Malva Moschata), Ox Eye Daisy (Leucanthemum Vulgare), Ragged Robin (Lychnis Flos Cuculi), Red Campion (Silene Dioica), Ribwort Plantain (Planatago Lanceolata), Rough Hawkbit (Leontodon hispidus), Salad Burnet (Sanguisorba Minor), Self Heal (Prunella Vulgaris), Small Scabious (Scabiosa columbaria), Common Sorrel (Rumex Acetosa), White Campion (Silene Alba), Wild Carrot (Daucus carota), Upright Hedge Parsley (Torilis Japonica), Yarrow (Achillea millefolium), Yellow Rattle (Rhinanathus Minor) and Wild Clary (Salvia Verbenaca). Grass Species 85% - Browntop Bent (<i>Agrostis capillaris</i>), Crested Dogstail (<i>Cynosurus cristatus</i>), Sheeps Fescue (<i>Festuca ovina</i>), Chewings Fescue (<i>Festuca rubra subsp.</i> <i>Commutate</i>), Slender Creeping Red Fescue (<i>Festuca Rubra</i> <i>Litoralis</i>), Yellow Oat Grass (<i>Trisetum flavescens</i>), Sweet		
	(Trisetum flavescens), Sweet Vernal Grass (Anthoxanthum odoratum).		
Creating a diversity of habitats within the site	Riparian mixto contain:Fool'swatercress(Apium nodiflorum),nodiflorum),Marsh-marigold(Caltha paulaustris),Yellow iris(Iris pseudacorus),Water forget- me-notme-not(Myosotis scorioides),Watermilfoil(Myriophyllum spicatum),Bur-reed	Year 1 (early within the construction phase)	Riparian mix will also provide an important source of food and shelter for aquatic species and support many terrestrial organisms, including bats and a wide range of bird species.



	(Sparganium spp.), Snow rush (Luzula nivea), Soft shield fern (Polystichum setiferum), Common fern (Dryopteris filix- mas) Riparian mix can be supplemented with species from Wetland Wildflower mix.		
Creating a diversity of habitats within the site	Tree planting mix to contain: Alder (Alnus glutinosa), Silver birch (Betula pendula), Scots pine (Pinus sylvestris) and Sessile Oak (Quercus petraea). Native woodland mix to contain: Alder (Alnus glutinosa), Silver birch (Betula pendula), Hazel (Corylus avellana), Hawthorn (Crataegus monogyna), Holly (Ilex aquifolium), Larch (Larix decidua), Scots pine (Pinus sylvestris), Bird Cherry (Prunus padus), Wild cherry (Prunus avium) and Sessile Oak (Quercus petraea).	Year 1 (early within the construction phase)	A patch of woodland/trees provides shelter and a source of food for a variety of species including birds, small mammals, amphibians, reptiles and butterflies. If the correct species are planted and maintained correctly, a woodland's potential can be maximised, providing food and shelter throughout the year.
To enhance the quality of habitats present & Creating a diversity of habitats within the site	Enhance existing hedgerow boundary Gap existing hedgerows and create new hedgerows with species such as blackthorn (<i>Prunus spinosa</i>), hawthorn (<i>Crataegus monogyna</i>) and holly (<i>Ilex aquifolium</i>) as listed in Table 1-4 . These corridors will allow the movement of small mammals and herptile species. To ensure a diverse hedgerow with a good structure it is important to plant and maintain	Year 1 (early within the construction phase)	A hedgerow provides shelter and a source of food for a variety of species including birds, small mammals, amphibians, reptiles and butterflies. If the correct species are planted and maintained correctly, a hedgerow's potential can be maximised, providing food and shelter throughout the year.



	ground flora along the hedgerow.		
Ensure fencing does not inhibit the movement of wildlife	To allow movement of badgers, small mammals and herptiles across the Proposed Development area the fence will <u>have mammal gates (130mm</u> <u>high, 10mm wide) at basebe</u> above ground level, with at least a 10cm gap at the base, allowing access for these species where required.	Year 1 (during construction phase)	Although badgers will not pass through a 13cm gap, they will dig a depression into the ground at the required areas.
Creating a diversity of habitats within the site	<u>Creation of hibernaculum, stone</u> piles and log piles	Year 1	See Appendix A The hibernaculum comprise log, rock and stone piles, which are aimed at providing shelter for herptile species to hibernate. However, the hibernaculum and log pile may also be used by a variety of insects and small mammals.
Creating a diversity of habitats within the site	<u>Creation of bat roosting habitat</u> Bat boxes will be placed on a few of the mature trees within the site.	Year 1	The creation of roosting habitat, along with the creation of species-rich habitat that will encourage an abundance of invertebrate life (a potential food source) will be beneficial to local bats.
Creating a diversity of habitats within the site	<u>Creation of bird nesting habitat</u> Bird boxes will be placed on a few of the mature trees within the site.	Year 1	The creation of nesting habitat, along with the creation of species rich habitat that will encourage an abundance of invertebrate life (a potential food source) and the wild bird seed mix areas



			will be beneficial to local birds. Boxes installed should include a mixture of single hole, and open fronted bird boxes.
Creating a diversity of habitats within the site	<u>Creation of invertebrate banks</u> <u>and insect hotels</u> Several earth banks shall be created across the site to support invertebrates.	Year 1	See Appendix B Some banks should be left bare, and south facing for insects such as solitary bees, while others should be sown with grass for beetles etc.
Maintaining the hedgerows	Section of hedgerow to be cut	Each year between January and February	Cutting on a rotational basis, following standard advice ⁷ , to ensure the optimal availability of berry and blossom for wildlife throughout the year, as a potential food source. Management will also ensure a good base is maintained within the hedgerow, to provide suitable habitat for a range of wildlife.

HABITAT CREATION

1.64. The existing groundcover (currently primarily amenity grassland) will be replaced by a mix of wetland meadow mix, wildflower meadow mix, native woodland and native hedgerow. Existing hedgerows will be enhanced, with new hedgerow created within the Proposed Development boundary. Native coniferous trees and medium or large deciduous trees have been proposed to give visual screening. A riparian planting mix has been proposed to be planted along the banks of the Baldonnel stream, southwest of the Application Site.

⁷ Hedgelink UK, The Complete Hedge Good Management Guide, Available at www.hedgelink.org.uk



1.65. These habitats will be in place and managed for the duration of the Proposed Development.

Riparian Planting

- 1.66. A riparian planting mix (**Table 1-2**) has been proposed to be planted along the banks of the Baldonnel stream, southwest of the Application Site.
- 1.67. They are an important source of food and shelter for aquatic species and support many terrestrial organisms, including bats and a wide range of bird species.

SCIENTIFIC NAME	English name
Apium nodiflorum	Fool's watercress
Caltha paulaustris	Marsh-marigold
Iris pseudacorus	Yellow iris
Myosotis scorioides	Water forget-me-not
Myriophyllum spicatum	Watermilfoil
Sparganium spp.	Bur-reed
Luzula nivea	Snow rush
Polystichum setiferum	Soft shield fern
Dryopteris filix-mas	Common fern

Table 1-2: Native Riparian Planting Mix

Management

- 1.68. Within the first year the main aim is to control weeds and to reduce competition from grasses.Where appropriate, this may include hand pulling of weeds.
- 1.69. After the wildflower mix has established, no specific management is required for the riparian strip

Wetland Wildflower Meadow

- 1.70. A wetland wildflower meadow has been proposed to be planted west of the proposed development footprint near the banks of a proposed attenuation area. These species will attract a wider range of species and create a diverse habitat which benefits invertebrates, bats, amphibians, and birds.
- 1.71. The species mixture is set out in **Table 1-2** below.



Table 2-2: Wetland wildflower meadow mix

SCIENTIFIC NAME	English name
Succisa pratensis	Devils Bit Scabious
Rumex acetosa	Common Sorrel
Cardamine pratensis	Cuckoo Flower
Primula veris	Cowslip
Erigeron	Fleabane*
Lotus pedunculatus	Greater Trefoil*
Eupatorium cannabinum	Hemp Agrimony
Centaurea nigra	Lesser Knapweed
Comarum palustre	Marsh Cinquefoil
Caltha palustris	Marsh Marigold
Ranunculus acris	Meadow Buttercup
Filipendula ulmaria	Meadowsweet
Thalictrum	Meadow Rue
Leucanthemum vulgare	Oxeye Daisy
Lythrum salicaria	Purple Loosestrife
Lychnis flos-cuculi	Ragged Robin
Trifolium pratense	Red Clover

Wildflower Meadow

- 1.72. The wildflower meadow, as shown within the landscape masterplan (by KFLA Architects) accompanying the application, is a species-rich grassland comprised of 85% grass species and 15% perennial species. This will create an insect-rich habitat and support a range of birds, mammals and invertebrates.
- 1.73. The species mixture is set out in **Table 1-3** below.

Table 1-3: Wildflower meadow mix

SCIENTIFIC NAME	English name
Lotus Corniculatus	Birdsfoot Trefoil
Hypochaeris Radicata	Common Cat's Ear
Primula Veris	Cowslip
Knautia Arvensis	Field Scabious
Galium Verum	Lady's Bedstraw
Centaurea Nigra	Lesser knapweed
Ranunculus Acris	Meadow Buttercup
Lathyrus pratensis	Meadow Vetchling
Malva Moschata	Musk Mallow
Leucanthemum Vulgare	Ox Eye Daisy
Lychnis Flos Cuculi	Ragged Robin



Silene Dioica	Red Campion
Planatago Lanceolata	Ribwort Plantain
Leontodon hispidus	Rough Hawkbit
Leontodon hispidus	Rough Hawkbit
Sanguisorba Minor	Salad Burnet
Prunella Vulgaris	Self Heal
Scabiosa columbaria	Small Scabious
Rumex Acetosa	Common Sorrel
Silene Alba	White Campion
Daucus carota	Wild Carrot
Torilis Japonica	Upright Hedge Parsley
Achillea millefolium	Yarrow
Rhinanathus Minor	Yellow Rattle
Salvia Verbenaca	Wild Clary
Agrostis capillaris	Browntop Bent
Cynosurus cristatus	Crested Dogstail
Festuca ovina	Sheeps Fescue
Festuca rubra subsp. Commutate	Chewings Fescue
Festuca Rubra Litoralis	Slender Creeping Red Fescue
Trisetum flavescens	Yellow Oat Grass
Anthoxanthum odoratum	Sweet Vernal Grass

Management

- 1.74. The wildflower mix will be sown in September or March/April, after the completion of the construction phase.
- 1.75. Within the first year the main aim is to control weeds and to reduce competition from grasses. The sward will be kept short in the first year until the end of June to reduce competition and then allowed to grow in July and August to permit any wildflowers to seed. All cuttings should be removed from site several days after cutting to avoid smothering the sward, but allowing any seeds to disperse.
- 1.76. After the wildflower mix has established, this area should only require one cutting in late summer (August September), allowing flowering species to seed with an additional cut in October. Cuttings should be left on site for several days to disperse any seeds, then removed from site.

Hedgerow

1.77. Existing hedgerow boundaries will be enhanced in line with the arborist report. Native species hedgerow will also be created.



1.78. Enhancement and creation of native hedgerows will benefit a range of local species including BAP Priority Species such as badgers, herptiles, invertebrates and birds. If the correct species are planted and maintained correctly, a hedgerow's potential can be maximised, providing food and shelter throughout the year, as well as connecting corridors.

Table 1-4: Hedgerow Species Mix

SCIENTIFIC NAME	ENGLISH NAME	
Crataegus monogyna	Common hawthorn	
Corylus avellana	Hazel	
Euonymus europaeus	European Spindleberry	
llex aquifolium	Holly	
Loinicera perclymenum	Common Honeysuckle	
Prunus spinosa	Blackthorn	
Rosa canina	Dog rose	
Viburnum opulus	Guelder rose	

1.79. It is also important to plant and maintain ground flora along the hedgerow to provide suitable commuting corridors for small mammals and herptiles.

Management

- 1.80. New hedgerows will be planted within the first available planting season (November March).
- 1.81. Any pruning or cutting should be done outside of the breeding bird season (March to August inclusive) to minimise disturbance to nesting birds.

Native woodland/tree planting

- 1.82. Triple staggered rows of native trees have been proposed to screen the Proposed Development from the surrounding area, the mix of trees proposed can be seen in Table 1-5. A woodland planting mix (Table 1-6) has been proposed to enhance habitats around the perimeter and throughout the site. A tree planting mix
- 1.83. Planting trees will provide potential new habitat for roosting bats and birds, providing food and shelter for other BAP Priority Species.

SCIENTIFIC NAME	ENGLISH NAME
Alnus glutinosa	Alder
Betula pendula	Silver birch
Corylus avellana	Hazel

Table 1-5: Tree planting mix



Pinus sylvestris	Scots pine
Quercus petraea	Sessile Oak

1.84. Native woodland planting is proposed around the perimeter and throughout the site to create a biodiverse native habitat as shown within the landscape masterplan (by KFLA Architects).

Table 1-6: Woodland planting mix

SCIENTIFIC NAME	ENGLISH NAME
Alnus glutinosa	Alder
Betula pendula	Silver birch
Corylus avellana	Hazel
Crataegus monogyna	Hawthorn
llex aquifolium	Holly
Larix decidua	Larch
Pinus sylvestris	Scots pine
Prunus padus	Bird Cherry
Prunus avium	Wild cherry
Quercus petraea	Sessile Oak

Wildlife Shelters

1.85. The creation of wildlife shelters strategically placed throughout the Application Site, will provide shelter to a wide range of species.

Bat boxes

- 1.86. Providing bat boxes will increase opportunities for roosting bats within the local area. Bat boxes should be erected in suitable locations throughout the site. It can however take bats a long time to make use of artificial roosts, therefore a number of factors must be considered when installing a new bat box.
- 1.87. Microclimate within a new roost is a very important factor in terms of increasing the chance of successful uptake by bats. In line with Bat Conservation Trust guidelines⁸ bat boxes should be draught-proof and made from a thermally stable material. They should be located where

⁸ Bat Conservation Trust – Bat Box Information Pack – Available at: http://www.bats.org.uk/data/files/publications/Bat_Box_Information_Pack_FINAL.pdf



they will receive full/partial sunlight (southerly orientation). The boxes should also be positioned a minimum of 2m above the ground. Access points should also be clear of any obstructions.

- 1.88. To allow a choice of roosting, bat boxes should be installed in more than one aspect. Bat boxes located on a shady side will be cooler and may be suitable as a hibernation roost or used by male bats throughout the entire year.
- 1.89. There is a wide range of bat boxes currently available, some which are more suitable for certain species. A variety of bat boxes are recommended in **Table 1-7**. It is recommended that three of each box detailed below be installed on site.



Table 1-7: Details of Bat Boxes

ВАТ ВОХ	DETAILS	IMAGE
Schwegler 1FF ⁹	Can be used as a summer roost or nursery site. Is open at the bottom and does not require cleaning.	
Schwegler 2F ¹⁰	Standard box and most popular. Simple entrance role. Used as summer roosting space.	
Schwegler 1FD ¹¹	Specific for smaller bats such as common pipistrelle, nathusius pipistrlle, daubenton's bat and brown long-eared.	

Bird boxes

- 1.90. In order to enhance the site for nesting birds, a number of bird boxes shall be placed throughout the site. Several types of nest boxes will be installed at suitable locations to favour a variety of bird species.
- 1.91. Open-fronted boxes will provide enhanced nesting opportunities for species such as robins, pied wagtails and spotted flycatchers. Boxes with entrance holes are suitable for tits, wren and tree sparrows.
- 1.92. Bird boxes should be mounted so that they face between the south-east and north to avoid direct sunlight. They should be tilted forwards so that rain is directed away from the entrance.
- 1.93. A variety of bird boxes are recommended in the table below.

⁹ Full specification available at: <u>http://www.nhbs.com/title/158636/1ff-schwegler-bat-box-with-built-in-wooden-rear-panel</u>

¹⁰ Full specification available at: <u>http://www.nhbs.com/title/158629</u>

¹¹ Full specification available at: http://www.nhbs.com/title/177076/1fd-schwegler-bat-box

Table 1-8: Details of Bird Boxes

BIRD BOX	DETAILS	IMAGE
1B Schwegler Nest Box ¹²	This nest box will attract a wide range of species and is available with different entrance hole sizes to prevent birds from competing with each other for the boxes. The 32mm entrance hole will attract Great, Blue, Marsh, Coal and Crested Tit, Redstart, Nuthatch, Collared and Pied Flycatcher, Wryneck, Tree and House Sparrow and bats. The 26mm entrance hole suits Blue, Marsh, Coal and Crested Tit and possibly Wren. All other species are prevented from using the nest box due to the smaller entrance hole.	
2H Schwegler Robin Box ¹³	This traditional design has proved to be highly effective in attracting robins, as well as other small species such as black redstart, spotted flycatcher and wren.	5

1.94. It is recommended that 1B Schwegler nest boxes (three 32mm and three 26mm holes) and 2H Schwegler robin boxes are installed.

Hibernacula

1.95. The hibernacula comprise of log, rock and stone piles and is aimed at providing shelter for reptile and amphibians to hibernate. It may also be used by a variety of insects and small mammals. The hibernacula will follow the instructions laid out within Appendix B below.

Management

1.96. Final location and number of bird nest boxes and bat boxes to be determined on site by an ecologist.

¹³ Full specification available at: http://www.nhbs.com/title/161277/2h-schwegler-robin-box



¹² Full specification available at: http://www.nhbs.com/title/158587/1b-schwegler-nest-box

APPENDICES

Appendix A - Hibernaculum Construction

1.97. The hibernaculum will follow the basic construction set out below, with the log and stone piles situated to the north of the hibernaculum.



- A 5m long east-west running ditch 1m deep and 1m wide will be dug.
- The base will be lined with sand and gravel.
- This will be followed with layers of stones, rocks and logs.
- Smaller branches will then be placed on top, and covered soil from the excavation will be placed over the pile, leaving gaps for access.
- The soil will be shaped into a mound.
- North facing side of the mound will be seeded / planted with species that will attract insects and will also provide extra shelter.
- South facing side will be maintained with a sparse vegetation cover to provide an area to bask.
• A log pile of approximately 2m by 1m will be placed to the north of the hibernaculum.

Appendix B – Invertebrate Bank Creation

Beetle Bank

- September is the best month to establish the grass sward that forms a beetle bank.
- Create a raised bank of about 0.4 metres.
- The grass mix should include up to 60% of tussock-forming species such as cocksfoot or Scots timothy grass. For the rest of the mix choose native species and include fescues.
- Up to three cuts may be needed in the first summer (when the sward reaches 10 cm in height) to encourage the grasses to tiller and to help control invasive annual weeds.
- Once established, the grass strips should be cut typically no more than once every three years.

Bee Bank

- Material (such as aggregate and sand) will be shaped into a mound with various slopes, hollows and angles that may be utilised and favoured by different species.
- Vertical banks created on bee banks take much longer to vegetate and this makes them attractive to many species. Over time a bee bank will be vegetated over through succession.
- Planting vegetation in an open structure in front of a bee bank will provide extra habitat for invertebrates that are attracted to the bee bank.
- These banks should be created close to flower-rich areas which will provide important foraging areas for pollinators.



Technical Appendix 12.1: Ground Investigation & Geotechnical Report

Volume 3: Technical Appendices Technical Appendix 12.1: Ground Investigation & Geotechnical Report Intended for Vantage Dublin Data Centers DUB11 Limited

Document type Report Date October 2022

VANTAGE DUBLIN DATA CENTERS DUB-13 TECHNICAL APPENDIX 12.1: GEOTECHNICAL ASSESSMENT REPORT



VANTAGE DUBLIN DATA CENTERS DUB-13 TECHNICAL APPENDIX 12.1: GEOTECHNICAL ASSESSMENT REPORT

Prepared by:Reviewed by:Approved by:Akash Guptar Graduate EngineerSteve WhiteJames FlackOraduate EngineerPrincipal EngineerDirectorRevisionDatePrepared byChecked byApproved by0.320/10/2022AGSWJFIssue to Client	Project name Project no. Recipient Document type Document no. Version Date Prepared by Checked by Approved by Description	Vantage DUB 1620014883 Vantage Data Report 0.3 2022/10/11 	8-13 a Centers DU	IB11 Limited				Ramboll Carlton Hous Ringwood Ro Woodlands Southampton SO40 7HT United Kingdo T +44 238 08 https://uk.ra
repared by:Reviewed by:Approved by:kash GuptaSteve WhiteJames Fackraduate EngineerPrincipal EngineerDirectorvisionDatePreparet byChecked by $Approved by$ 20/10/2022AGSWJFIssue to Client	ription	-						
Akash Guptar Steve Write James Fack Graduate Engineer Principi Engineer Director Revision Date Preparet by Checked by App-ved by Description 0.3 20/10/2022 AG SW JF Issue to Client	Prepared by:		Review	wed by:		Approve	ed by:	
Akash Gupta Steve White James Flack Graduate Engineer Principal Engineer Director Revision Date Preparet by Checked by Apprved by Description 0.3 20/10/2022 AG SW JF Issue to Client								
Graduate Engineer Principal Engineer Director Revision Date Prepared by Checked by Apprved by Description 0.3 20/10/2022 AG SW JF Issue to Client	Akash Gupta		Steve	White		James F	lack	
Revision Date Prepared by Checked by Approved by Description 0.3 20/10/2022 AG SW JF Issue to Client	Graduate Engine	Per						
Revision Date Prepared by Checked by Approved by Description 0.3 20/10/2022 AG SW JF Issue to Client			Princip	al Engineer		Director		
0.3 20/10/2022 AG SW JF Issue to Client			Princip	al Engineer		Director		
	Revision Dat	e Pre	Princip epared by	al Engineer Checked by	Appro	Director	Description	

This report is produced by Ramboll at the request of the client for the purposes detailed herein. This report and accompanying documents are intended solely for the use and benefit of the client for this purpose only and may not be used by or disclosed to, in whole or in part, any other person without the express written consent of Ramboll. Ramboll neither owes nor accepts any duty to any third party and shall not be liable for any loss, damage or expense of whatsoever nature which is caused by their reliance on the information contained in this report.

Ramboll UK Limited Registered in England & Wales Company No: 03659970 Registered office: 240 Blackfriars Road London SE1 8NW

CONTENTS

1.	INTRODUCTION	1
1.1	Site	1
1.2	Proposed Development	1
1.3	Limitations and Constraints	2
2.	GEOLOGY AND GROUND CONDITIONS	3
2.1	Historical Ground Investigation Data	3
2.2	Mining and Quarrying	3
3.	GROUND INVESTIGATION	3
4.	GEOTECHNICAL FINDINGS	4
4.1	Topsoil	5
4.2	Made Ground	5
4.3	Probable Till Deposits	5
Results of	the Atterberg Limit tests characterise the cohesive soils as being of intermediate plasticity, whilst modified plasticity index derived from	
	the tests classifying the soils as typically being of low volume	
	change potential, locally non-shrinkable.	7
4.4	Weathered Rock Deposits	7
4.5	Limestone Bedrock	8
5.	GROUNDWATER	9
6.	DERIVATION OF GEOTECHNICAL PARAMETERS	10
6.1	Geotechnical Parameters	12
7.	RECOMMENDATIONS	13
7.1	Foundations	13
7.2	Floor Slabs	14
7.3	Pavement Design	14
7.4	Buried Concrete	14
7.5	Earthworks / Material Re-use	14
7.6	Stability of Excavations	15
8.	GEOTECHNICAL RISK REGISTER	16
9.	REFERENCES	19

i

TABLE OF TABLES

Table 4-1: Summary of ground conditions encountered	4
Table 4-2: Summary of geotechnical test results - Possible Superficial	
Deposits	7
Table 4-3: Summary of geotechnical test results – Weathered Rock	
Deposits	7
Table 5-1: Groundwater monitoring results	9
Table 6-1: Recommended characteristic values for the geotechnical soil	
parameters	12

TABLE OF FIGURES

Figure 1: Relationship between plasticity index and undrained shear	
strength of fine grained soils, reproduced from Tomlinson, 2001	11

APPENDICES

Appendix A IGSL Factual Report

1. INTRODUCTION

On behalf of Vantage Data Centers (The Client), Ramboll UK Ltd (Ramboll) have completed a Phase II Site Investigation and Environmental Surveys to support the proposed development of a data centre located at the Profile Park Site, Kilcarbery (the 'site'), situated within the jurisdiction of South Dublin County Council (SDCC).

As part of the remit, Ramboll has been commissioned to undertake a high level geotechnical assessment of the site based on the findings of the 2022 IGSL Ltd ground investigation. This assessment summarises the findings and provides geotechnical recommendations with respect to design ground models, characteristic material parameters and where applicable outline recommendations in relation to the proposed development.

This assessment does not cover interpretation or recommendation with respect to potential ground and groundwater contamination at the site for which the reader should refer to the Ramboll Contaminated Land Interpretative Report (ref: 1620012232-CLIR-01).

1.1 Site

The site is located in Profile Park, approximately 10 kilometres (km) to the south-west of Dublin city centre, within South Dublin County, at Irish grid reference O 03911 30784 (Figure 1 in Appendix 1).

The site is a roughly rectangular parcel of agricultural land, with a residential dwelling located in the north-west corner of the site. The site covers a total area of 3.31 ha and at an elevation of between circa 74m and 75m Above Ordnance Datum (m AOD).

The site boundaries are defined by:

- New Nangor Road (R134) to the north;
- Falcon Avenue, Equinix and Grange Castle Golf Club to the east;
- Falcon Avenue to the south; and
- The consented Vantage data centre development (planning reference SD21A/0241) to the west which currently comprises agricultural fields.

The site consists predominantly of flat agricultural land, with a residential property present towards the north-west of the site and outbuildings in the south-east. A track is present providing entrance to the field from the northern site boundary and towards the outbuildings.

The site's surrounding context predominantly comprises Profile Park with an industrial development to the north, Grange Castle Golf Club to the east beyond which are residential properties. To the south comprises agricultural land and industrial development with the consented Vantage data centre development to the west, beyond which is Bolands Car Garage and further data centres. The existing Baldonnel stream runs adjacent to the southern boundary of the site and enters the southern section of the site, orientated in a north-west to south-east direction, flowing towards the east.

1.2 Proposed Development

At the time of writing the proposed development is understood to comprise the following:

- Demolition of the existing double-story dwelling and three outbuildings;
- Erection of DUB-13 along with associated emergency generators and flues with a gross floor area of approximately 12,893 m2; and
- Provision of 60 car parking spaces and 26 bicycle parking spaces provision.

1.3 Limitations and Constraints

This report has been prepared solely for Vantage Data Centers and shall not be relied upon by any third party unless that party has been granted a contractual right to rely on this report for the purpose for which it was prepared.

Ramboll has endeavoured to assess all information provided to them but makes no guarantees or warranties for the completeness or accuracy of information relied upon derived from third party sources.

It should be noted that as the ground conditions encountered during the ground investigation are only a known detail at each exploratory hole location, the ground conditions detailed on sections between holes have been interpolated and therefore the actual nature of the ground may differ from the interpretation provided by Ramboll. In addition, groundwater levels will vary seasonally and with changes in weather and climate or possibly due to leakage from faulty water infrastructure.

2. GEOLOGY AND GROUND CONDITIONS

The online British Geological Survey Maps Portal shows the Geological Survey of Ireland 1:63,630 historical geological map Sheet 111, Maynooth (1901) to present the geology of the area. The historical sheet indicates that the site and surrounding area is underlain by solid geology of the Carboniferous Middle Limestone. The sheet records typical bedrock dip angles of between 20 and 30 degrees to the south.

Data from the current online Geological Survey of Ireland Interactive Map, indicates that the site is underlain by The Lucan Formation of the Carboniferous. The dominant lithology comprising dark grey to black, fine-grained, occasionally cherty, micritic limestones that weather to pale grey. The drift deposits at the site are envisaged to consist of Till derived from the limestone.

The Geological Survey of Ireland Interactive Map indicates that the site area is host to a 'locally important aquifer' where the bedrock is moderately productive only in local zones.

2.1 Historical Ground Investigation Data

No historical ground investigation data for the site is available.

2.2 Mining and Quarrying

According to the Geological Survey of Ireland there are no active quarries located in the immediate vicinity of the site.

3. GROUND INVESTIGATION

A ground investigation was undertaken by IGSL Ltd for the purpose of investigating and reporting on the ground and groundwater conditions at the site to assist with identifying geotechnical and geoenvironmental risks and hazards. All works completed are detailed in the below referenced factual report (presented in Appendix A) which should be read in conjunction with this interpretative report:

• IGSL Ltd, 2022. Data Center Project 3 Profile Park. Ground Investigation Report – Factual. Project No 24188 (September 2022).

The ground investigation works were undertaken in accordance with:

- EN 1997-2 Eurocode 7: 2007 Geotechnical Design Part 2: Ground Investigation & Testing;
- EN ISO 22475-1:2006 Geotechnical Investigation and Sampling Sampling Methods & Groundwater Measurements;
- EN ISO 14688-1:2002 Geotechnical Investigation and Testing Identification and Classification of Soil, Part 1: Identification and Description;
- EN ISO 14688-2:2204 Geotechnical Investigation and Testing Identification and Classification of Soil, Part 2: Classification Principles;
- EN ISO 14689-1:2004 Geotechnical Investigation and Testing Identification & Classification of Rock, Part 1: Identification & Description;
- Engineers Ireland Specification for Ground Investigation, 2nd Edition, 2016;
- BS 5930:2015 Code of Practice for Ground Investigation; and
- BS 1377:1990, Parts 1 to 9.

The geotechnical element of the investigation was designed to provide site-specific information on:

- The presence, thickness, and composition of any recent and superficial deposits beneath the proposed development areas;
- Depth to and information on the solid geology to allow characterisation of the bedrock;
- The strength and stiffness of the underlying soils and bedrock;
- Chemical composition of soils for buried concrete design; and
- Determination of the existing groundwater levels.

The scope of ground investigation works undertaken at the site involved the following:

- 10 no. machine excavated trial pits to a maximum depth of 2.70 metres below ground level (mbgl);
- 6 no. cable percussive boreholes to a maximum depth of 2.10 mbgl with in situ testing;
- 6 no. rotary cored drillholes to a maximum depth of 11.0 mbgl;
- 10 no. plate load tests to determine in situ California Bearing Ratio;
- 10 no. dynamic cone penetrometer tests;
- Geophysical survey (in situ resistivity);
- Groundwater monitoring of 6 no. installations.

Groundwater monitoring standpipes were installed in all six of the rotary cored holes with groundwater levels monitored across the site post installation. In-situ testing comprising standard penetration tests were performed in the cable percussive boreholes to derive N values. The N values presented in the exploratory logs are uncorrected for energy ratio.

The following geotechnical laboratory tests were carried out on select samples obtained from the site.

- Moisture Content;
- Atterberg Limits (Liquid / Plastic Limits);
- Particle Size Distribution;
- Moisture Condition Value;
- Soil geochemical testing to BRE Test Suite D;
- Point Load Strength Index; and
- Uniaxial Compressive Strength testing.

Groundwater standpipes were installed in all six rotary holes with groundwater levels monitored across the site post installation.

4. GEOTECHNICAL FINDINGS

The ground conditions encountered during the 2022 IGSL Ltd investigation typically consisted of topsoil which was underlain by predominantly firm to very stiff cohesive soils (considered to be Till) which in turn were underlain by limestone bedrock (considered to be the Lucan Formation). Localised Made Ground were encountered on the western edge of the site, adjacent to the existing building structures, which was recorded as CI.804 stone fill. A summary of the ground conditions encountered is presented in Table 4.1. For detailed engineering descriptions please refer to the IGSL exploratory hole logs presented in Appendix 1.

Table 4-1: Summary of ground conditions encountered

Strata	Description	Depth to Base (mbgl)	Thickness (where proven) (metres)
Topsoil	Not available.	0.30 to 0.50	0.30 to 0.50
Localised Made Ground (TP06 and BH03)	Comprising CI.804 stone fill.	0.30 to 0.50	0.30
Probable Till Deposits	Predominantly Firm becoming stiff or very stiff with depth, light brown or dark brown sandy SILT/ CLAY with some cobbles and occasional boulders. Gravel is angular	1.50 to 3.0	1.0 to 3.0
Weathered Rockhead	Possible weathered bedrock, recovered as grey sandy clayey angular GRAVEL with cobbles and occasional boulders.	1.90 to >3.50	0.30 to >3.50
Bedrock (Limestone)	Medium strong to very strong, thinly to thickly bedded, thinly laminated where fissile mudstone/shale, grey/dark grey/black, fine grained, LIMESTONE. Argillaceous limestone grading regularly (every approximately 0.10 to 0.50 m) into calci- siltite limestone with subordinate MUDSTONE, local stylolites, pyrite present, slightly weathered where intact, very locally moderately weathered at fissile mudstone/shale zones. Many incipient zones throughout.	>10.0	Not Proven

4.1 Topsoil

Topsoil was encountered in all trial pits during the investigation and typically ranged in thickness from 0.3 metres to 0.5 metres. No topsoil was recorded within boreholes.

No in situ or geotechnical testing was performed on the topsoil given that the material will be stripped prior to construction.

4.2 Made Ground

Granular fill (described as CI.804 stone) was encountered in TP06 and BH03 located in the vicinity of the western site boundary near/adjacent to the existing structures in the southwest of the site. At trial pit TP06, the fill was recorded underlying the topsoil to a depth of 0.5mbgl, whereas in BH03 the fill was recorded from ground level with a recorded thickness of 0.30 metres.

In Situ Testing

No in situ testing was undertaken within the Made Ground.

Geotechnical Laboratory Testing

No geotechnical laboratory testing was undertaken within the Made Ground.

4.3 Probable Till Deposits

Underlying the topsoil, cohesive soils interpreted to be Till were encountered site wide at depths ranging between 0.10 mbgl and 0.60 mbgl. The stratum varied in thickness from 1.30 metres to 3.0 metres. Given the engineering descriptions, particularly the cobble and boulder inclusions, the soils are considered to have been deposited in a glacial environment and have therefore been classified as Till deposits within this assessment. The base of the stratum was proven within both the trial pits and drillholes, whilst the cable percussive boreholes terminated in the stratum due to

the presence of cobbles and boulders. Where the base was proven, lateral variations in thickness and depth to base of the cohesive soils were recorded, with the depth to the base ranging between 1.50 mbgl in TP08 to 3.0 mbgl in RC06.

The Till deposits predominantly comprised fine grained soils with coarse grained secondary inclusions. Engineering descriptions from the 2022 IGSL investigation, recorded the stratum as being, firm increasing to stiff and very stiff with depth, brown, light or dark brown sandy gravelly clay or silt / clay with varying cobble and boulder content.

In situ Testing

A total of twelve penetration tests were performed at one metre intervals within the cohesive soils, recording uncorrected N values ranging from 15 (blows per 300mm penetration) to refusal (i.e. 50 blows for less than 300mm penetration). Test refusals were recorded at the base of the cable percussive boreholes and are considered to be either due to encountering either cobbles / boulders or due to the presence of the underlying limestone bedrock. Excluding the upper bound test refusals recorded at the base of the boreholes the mean N value was calculated to be 20, correlating to a soil of medium to high strength.

A total of ten plate load tests (PLT) using a 450mm diameter plate were carried out at each trial pit location at test depths of between 0.3 mbgl and 0.4 mbgl and are therefore considered to be at the interface between the topsoil and Till. Two load cycle tests were performed in accordance with BS 1377, Part 9. Results of the PLT's recorded CBR values ranging from 0.6% to 31.4%, with an average value of 5.3%. Low CBR values i.e. CBR values of less than 2.5%, were recorded in PT01, PT02, PT04, PT06 to PT08 and PT10. Modulus of subgrade reaction, k, values ranged from 11 MPa/m to 106 MPa/m.

Geotechnical Laboratory Testing

Various geotechnical laboratory tests were carried out on select samples which included natural moisture content, Atterberg Limit tests, particle size distribution, moisture condition value at natural moisture content (MCV) and thermal resistivity / conductivity. Due to the secondary granular content within the cohesive soils no high quality undisturbed samples were obtained during the investigation and therefore laboratory strength or consolidation testing has not been possible.

In addition to the geotechnical tests, geochemical tests were performed to determine the aggressive nature of the soils in relation to buried concrete design.

The geotechnical laboratory test results are summarised in Table 4-2.

Test	Possible Superficial	Deposits
	Range of Results	Mean
Moisture Content (%)	14.6 to 26.7	17.7
Plasticity Index (%)	17 to 23	19
Liquid Limit (%)	33 to 41	37
Plastic Limit (%)	15 to 21	18
MCV	6.3 to 14.9	10.8
Bulk Density (Mg/m ³)	1.55 to 2.05	1.74
Dry Density (Mg/m ³)	1.34 to 1.69	1.47
Porosity	0.36 to 0.49	0.44
Thermal Conductivity, K (W/m.k)	0.80 to 1.33	1.07
Thermal Resistivity, R (m K/W)	0.77 to 1.25	0.97
Water Soluble Sulphate SO ₄ (g/l)	<0.010	0.010
Total Sulphur %	0.048 to 0.095	0.07
рН	8.6 to 9.1	8.8

Table 4-2: Summary of geotechnical test results - Possible Till Deposits

Results of the Atterberg Limit tests characterise the cohesive soils as being of intermediate plasticity, whilst modified plasticity index derived from the tests classifying the soils as typically being of low volume change potential, locally non-shrinkable.

4.4 Weathered Rock Deposits

Underlying the cohesive Till, a layer of coarse grained material considered to be weathered rockhead was encountered within both the machine excavated trial pits (with the exception of TP10) and rotary drillholes. The stratum was generally encountered site wide at depths ranging between 1.9 mbgl to 3.5 mbgl, with thickness varying from 0.30 metres to 1.0 metres. The base of the stratum was only proven within the rotary cored drillholes whilst the machine excavated trial pits were recorded as terminating within this stratum. Generally, the base of the weathered rock was at approximately 3.5 mbgl towards the southern edge of the site rising to circa 2.5mbgl within the north part of the site. Based on the findings of the 2022 IGSL investigation, the weathered rock deposits were recorded as being, grey sandy clayey angular gravel with occasional boulders.

In situ Testing

No in situ testing was undertaken within stratum.

Geotechnical Laboratory Testing

A limited number of geotechnical laboratory tests were carried out on select samples which included a single grading and thermal resistivity / conductivity. In addition to the geotechnical tests, geochemical tests were performed to determine the aggressive nature of the weathered rock materials in relation to buried concrete design. The geotechnical laboratory test results are summarised in Table 4-3

 Table 4-3: Summary of geotechnical test results – Weathered Rock Deposits

Test	Weathered Rock Deposits	
	Test Result	
Moisture Content (%)	13.9	
Bulk Density (Mg/m ³)	1.69	
Dry Density (Mg/m ³)	1.48	
Porosity	0.44	
Thermal Conductivity, K (W/m.k)	1.06	
Thermal Resistivity, R (m K/W)	0.95	
Water Soluble Sulphate SO ₄ (g/l)	<0.010	
Total Sulphur %	0.054	
рН	8.7	

4.5 Limestone Bedrock

Bedrock comprising limestone with subordinate mudstone bedrock was encountered underlying either the Till or weathered bedrock deposits within the rotary drillholes. The depth to the top of the intact bedrock was typically recorded at a depth of circa 3.0m (RC01, RC02, RC04 and RC05) with the exception of RC03 at 3.5mbgl (69.82mOD) and RC06 where intact bedrock was recorded at a depth of 4.20mbgl (68.91mOD).

The IGSL rotary cored logs describe the bedrock as typically being, medium strong to very strong, thinly to thickly bedded and thinly laminated (where fissile mudstone/shale), grey, dark grey / black, fine grained, argillaceous limestone (grading every 0.10m to 0.50m into calci-silite limestone with subordinate mudstone, local stylolites, pyrite present). Slightly weathered where intact, locally very moderately weathered at fissile mudstone/shale zones with many incipient zones throughout. Discontinuities are widely to closely spaced, smooth to locally rough, planar to locally curviplanar. Apertures are tight to locally moderately open, locally clay smeared, locally calcite-veined (1mm to 12mm thick). Subhorizontal and subvertical at 30° to 40° and locally 70°. Based on the description the bedrock is considered to be the Lucan Formation of the Carboniferous.

In situ Testing

No in situ testing was carried out within the limestone bedrock.

Geotechnical Laboratory Testing

Sub samples of the intact bedrock were subject to point load strength index tests and unconfined compressive strength (UCS) tests to derive the uniaxial compressive strength of the bedrock. A total of thirty diametral point load strength tests were undertaken at various depths with calculated values ranging from 8 MPa to 120 MPa with an average value of 69 MPa (based on a correlation K value of 20). In addition to the point load tests, six UCS tests were performed on core subsamples taken from the rock. The subsamples were taken at depths ranging from 4.3 mbgl to 8.8 mbgl and produced UCS results ranging from 28 MPa to 102 MPa. For further information on the test results the reader should refer to the IGSL factual report contained within Appendix A.

5. GROUNDWATER

No groundwater strikes were recorded during drilling, however seepages were encountered in BH01, BH03 and BH06 at 1.70m, 1.50m and 1.90mbgl respectively. Further seepages were recorded at circa 2.0m depth within trial pits TP06 to TP10 located within the southern section of the site.

Standpipes were installed in all rotary drillholes to allow groundwater levels to be monitored. The water levels were recorded 5 minutes after end of drilling. At the time of writing a single round of post fieldwork monitoring had been carried out on 31/08/22 which recorded groundwater at levels ranging from 70.99 mOD and 71.65 mOD. The results are presented in Table 5-1.

RC No.	Level (mOD)	Date of Reading	Depth of Reading (mbgl)	Level of Reading (mOD)
RC01	73.76	31/08/2022	2.77	70.99
RC02	74.20	31/08/2022	2.56	71.64
RC03	73.32	31/08/2022	2.03	71.29
RC04	73.52	31/08/2022	1.87	71.65
RC05	73.11	31/08/2022	1.67	71.44
RC06	73.11	31/08/2022	1.77	71.34

Table 5-1: Groundwater monitoring results

6. DERIVATION OF GEOTECHNICAL PARAMETERS

The data presented in this section is based upon the results of the 2022 IGSL investigation designed by Ramboll.

The characteristic values of geotechnical parameters and ground model recommendations provided have been selected for the purposes of permanent works design. If these parameters are to be adopted for any temporary works design the Temporary Works Designer should be satisfied that the parameter selected is appropriate for the load case being considered.

The derivation of characteristic values of geotechnical parameters is described for the soils that are expected to be encountered. Where direct measurement of parameters has not been carried out, established correlations with measured properties have been used to derive values for design.

Characteristic values are defined as a cautious estimate of the value affecting the occurrence of a limit state based on Clause 2.4.5.2, from BS EN 1997-1: 2004 (Eurocode 7). Characteristic values should be used with appropriate partial factors or to achieve appropriate factors of safety, as required.

Weight Density

Adopted characteristic weight density values for the superficial deposits have been based on laboratory test data and empirical values presented in Figure 1 and Figure 2 from BS 8002:2015.

Bedrock values have been derived from the laboratory tests performed as part of the 2022 IGSL Ltd Investigation.

Strength

Cohesive Soils – Undrained Strength Parameters

Characteristic undrained shear strength (c_u) for the over consolidated cohesive soils will be assessed from in situ testing and from material descriptions from boreholes, based on British Standard (BS) 5930: 2015 and BS EN: 1997 (2007).

For over consolidated cohesive soils, the characteristic undrained shear strength, c_u can be derived from SPT N values (where available) using the correlation recommended by Stroud and Butler (1975):

$c_u = f_1 \times N_{60} (kN/m^2)$

Where:

 N_{60} is the SPT N corrected for hammer energy;

 f_1 is dependent on Plasticity Index as per Figure 3 reproduced by Tomlinson, 2001. Based on the data obtained during the 2022 investigation and the Till generally being of intermediate plasticity, an f_1 value of 4.4 has been adopted.



Figure 1: Relationship between plasticity index and undrained shear strength of fine grained soils, reproduced from Tomlinson, 2001

Data from the SPTs generally indicates to the cohesive soils being of medium to high strength with an increase in N values recorded at depth corresponding to an increase in granular content or grain size (i.e. presence of cobbles and boulders). Therefore when deriving the undrained shear strength upper bound values have been discounted and a characteristic SPT N value of 18 adopted.

Cohesive Soils - Effective Stress Strength Parameters

Effective stress (drained) strength parameters for cohesive soils are determined from interpretation of the relationship between ϕ' and PI proposed by Kenney (1959). A conservative value of ϕ' will be derived based on an upper bound value of PI.

The characteristic angle of internal friction determined for the Till based on plasticity index is 27°.

In the absence of effective stress strength tests undertaken on cohesive soils a drained cohesion (c') of 0 kN/m² has been recommended for design.

Stiffness and Compressibility

Cohesive Soils

Where determination of settlement of foundations on cohesive soils is required then stiffness will be assessed from SPT N values using the relationship described in CIRIA Report 143 (1995).

Stiffness based on Young's Modulus (E) has been assessed using:

For normally consolidated cohesive material (following Bowles):

- $E_u = c_u \times 250 \text{ (kN/m}^2 \text{) for undrained stiffness}$
- $E' = E_u \times 0.6$ (kN/m²) for drained stiffness

For overconsolidated cohesive material (following Bowles):

- $E_u = c_u \times 750 \text{ (kN/m}^2 \text{) for undrained stiffness}$
- $E' = E_u \times 0.6$ (kN/m²) for drained stiffness

The settlements calculated from soil modulus values interpreted following the guidance in CIRIA Report 143 are likely to represent conservative settlements.

Bedrock

The Hoek-Brown Classification for the Intact Modulus of the bedrock has been derived using the software RocLab. The values were derived using the UCS, GSI, mi and MR. For the intact rock a UCS of 53 MPa was adopted as the characteristic value based on the UCS and point load test data presented in the 2022 IGSL Ltd Report. In addition to the UCS value a mi value of 8 and an MR (modulus ratio) of 700 was used to derive the Intact Modulus.

6.1 Geotechnical Parameters

Table 6-1 provides a summary of the recommended characteristic values for the geotechnical soil parameters for the site.

Stratum	Geotechnical Parameters								
	Bulk Density	ilk Undrained ensity Shear		Young's Modulus (MPa)		UCS (MN/m ²)			
	(kN/m²)	Strength (kN/m²)	Resistance (Φ´)	Eu	E'				
Till	19	75	27	56	34	-			
Weathered Bedrock (granular soil)	19	-	36	-	18	-			
Intact Limestone	26	-	26	-	37000	53			

Table 6-1: Recommended characteristic values for the geotechnical soil parameters

* Where 'z' is depth below top of stratum

7. RECOMMENDATIONS

The following section outlines the recommendations for the proposed development based on data obtained during the IGSL Ltd investigation. At the time of writing no structural loadings have been provided and therefore the following sections only provide outline recommendations.

7.1 Foundations

Due to the absence of design loadings for the structures, no specific recommendation as to the foundation type that should be adopted is provided, particularly given the type and number of structures requiring foundations. Any foundation design should be carried out in accordance with Eurocode 7 and the corresponding National Annex to obtain the appropriate partial factors.

When the design structural load takedown has been calculated, a detailed analysis into the suitability of shallow foundations should be undertaken. Should shallow spread foundations be deemed suitable these would typically be supported by either the cohesive Till deposits or granular soils where encountered at shallow depths. Given the variation in the geology, the design should consider differential settlements where foundations are in differing geology/strata. Where the foundations are required to support higher imposed loads, spread foundations should be founded on the underlying Lucan Formation, where a deepening of foundation excavations will be required. The commercial viability of founding in the limestone will need to be considered taking into account the depth of dig (circa 3.0m) and volume of material for disposal.

Based on the formation soils comprising medium strength cohesive soils with an undrained shear strength of 75kPa at a depth 1.0m, for a 1m square pad foundation the ultimate design bearing resistance, R, (under Design Approach 1, Combination 2) has been estimated to be 340 kPa using the method proposed in Annex D of Eurocode 7 Geotechnical Design, Part 1: General Rules (BS EN 1997-1:2004+A1:2013). In terms of Serviceability Limit State (SLS) allowing for total settlements to be in the order of 25mm to 30mm, then a safe gross bearing pressure of 150 kPa to 175 kPa is recommended. Where the founding stratum is weathered rock, it is recommended that these bearing pressures be adopted.

Modified plasticity values for the near surface cohesive soils indicate to these being shrinkable in nature and of low volume change potential. Where a shallow foundation solution is adopted guidance given in Chapter 4.2 of the NHBC Standards 2016 should be adhered to in relation to minimum founding depth, void dimensions (where applicable) and existing trees / new planting.

Where the structural loads cannot utilise the use of spread foundations, then the proposed structures should be supported by piled foundations. A piled foundation solution would involve a socketed pile into the limestone bedrock, typically up to 3.00 metres penetration into the rock (or a minimum of at least twice the socketed pile diameter), where the strength of the material would be adequate to support the structural loads.

The key risks associated with the piled foundation include, but are not limited to:

- Pile refusal on buried obstructions or hard strata;
- Variable soft/hard material causing flighting/affecting the integrity of the pile shaft through the infilled ground; and,
- Required penetration (rock socket) into the bedrock.

To reduce the risk of the above bored cast in place concrete piles would be the most suitable option, utilising a specialised hard rock cutter to penetrate the limestone bedrock layer. Driven piles are likely to be unsuitable for use within the Till given the presence of cobbles and boulders which have the potential to limit the depth of pile penetration, unless other plant was available on-site to remove the obstructions. In addition to this, driven piles would not be suitable for use in the limestone bedrock.

The piles will be supported by a combination of end bearing on the rock and shaft friction from the rock socket and overburden soils.

7.2 Floor Slabs

In areas of high strength homogeneous cohesive Till at near surface, ground bearing floor slabs are likely to perform satisfactorily subject to meeting any particular settlement criteria for the structure concerned. Estimations of the modulus of subgrade reaction, *K*, for the near surface soils have been derived from the in situ plate load tests with *K* values typically greater than 15 MPa/m with the exception of PT04, PT08 and PT10 which recorded a *K* value of 14, 11 and 13 MPa/m respectively were recorded. Liquid limit results of less than 50% were recorded as part of the Atterberg Limit tests and these results would correlate to a 'poor' subgrade classification and an assumed *K* value of 27MPa/m. Where a higher value of *K* is required, enhanced values can be achieved by the placement of a granular sub-base of minimum 150mm thickness.

Should floor slabs span material of variable composition then damaging differential settlement may occur and consideration to a suspended slab should be given.

7.3 Pavement Design

A total of ten plate load tests (PLT) using a 450mm diameter plate were carried out at test depths ranging from 0.4 mbgl to 0.6 mbgl and are therefore considered to be at the interface between the base of the topsoil and the upper zone of the Till deposits. Results of the PLT's recorded CBR values ranging from 0.6% to 31.4% with an average value of 5.3%. Localised zones of weaker soils (i.e a CBR value of less than 2.5%) were recorded at test location PT01, PT02, PT04, PT06 to PT08 and PT10.

In addition, a series of dynamic cone penetrometer (DCP) tests were also undertaken from ground level to a depth of 0.9 mbgl at each trial pit location (in accordance with the TRL recommended procedure) to estimate CBR values of the near surface soils. Results from the DCP tests recorded CBR values ranging between 15% and 55% with an average value of 27.8%.

Generally, the CBR values derived from in situ testing across the site were greater than 2.5%, however, localised weaker zones are likely to be encountered during construction. Where identified these localised zones will require improvement by means such as excavate and replace.

7.4 Buried Concrete

Chemical laboratory tests were undertaken on near surface samples of the Till deposits across the site, to determine the aggressivity of the ground against buried concrete. Characteristic values for the soil have been derived based on the size of the data set and guidance given in BRE Special Digest 1:2005 – Concrete in Aggressive Ground (3rd Edition).

The geochemical test results for the Till recorded pH values ranging from 8.6 to 9.1, with water soluble sulphate results <0.010 g/l.

The design ACEC class has been derived based on Table C1 Greenfield Site from the BRE Special Digest 1 and taking groundwater to be mobile. Considering the data set a characteristic value has been calculated based on the mean of the highest two results (where data set of five to nine tests). Findings from the IGSL investigation indicate to the near surface soils (Till) having an ACEC classification of AC-1.

7.5 Earthworks / Material Re-use

Any earthworks operations should be completed in accordance with a suitable earthworks specification. Where earthwork filling is required placement and compaction of fill should be designed to not negatively impact foundation construction, i.e. induce downdrag with respect to any future pile installation.

Data from the IGSL investigation indicates that site won Till material is likely to conform to a Class 2 general fill with the removal of any cobble or boulder inclusions. A single grading undertaken on the weathered bedrock indicates that the material comprised 37% fines and therefore based on this test result the material will also be classified as a Class 2 general fill, however further suitability testing should be undertaken on all soils to verify these classifications in areas where placement of fill are identified. MCV tests undertaken as part of the IGSL investigation produced a wide range of results ranging from 6.3 to 14.9. With the exception of a single test result from BH01 (which recorded 6.3), all other tests recorded MCV values greater than the minimum MCV value of 8 which is typically required for Class 2 soils to be used in earthworks. Considering the existing data set, site won soils are likely to be suitable for reuse, however localised improvement (potentially with the addition of lime) maybe required if all site won cohesive soils are to be reused.

7.6 Stability of Excavations

Information obtained during the investigation recorded the trial pits to be subject to seepages during excavation and therefore if a shallow foundation solution is adopted measures to deal with groundwater inflow may need to be implemented during excavation to maintain stability and prevent softening of cohesive formation soils.

Where excavations are required to a significant depth and it is not possible to batter excavation slopes, or if groundwater is encountered, temporary support; for example using trench sheeting or trench boxes should be considered. For temporary works the contractor should also make his own assessment as to the safety of excavations, particularly if/where man access is required.

8. GEOTECHNICAL RISK REGISTER

Risk	Description	l mpact (1-5)	Probability (1-5)	Level of Risk	Mitigation
Unexpected/ unfavourable ground	Risk of variable depth to rockhead across the site – variable length of	3	2	6	Ensure foundations are constructed to a sufficient depth to be stable in all possible geologies.
conditions	adopted.				Designer contacted immediately if ground conditions differ from what was anticipated.
					Use experienced site geotechnical personnel to provide advanced warning of potential problems.
Obstructions within the superficial	Plant / equipment damaged during foundation installation	2	2	4	Design to be based on the ground investigation data.
deposits					Utilise suitable foundation system (e.g. bored piles)
Encountering uncharted buried services	Risk of delay where uncharted services are encountered. Costs of repair, injury to personnel.	4	1	4	If, during foundation construction, an unexpected obstruction is discovered, cease immediately until it can be established what the obstruction is. CAT scanning must take place during foundation construction to mitigate this risk. Walkover surveys and stats searches will also lessen the likelihood of unknown services.
Unexpectedly high groundwater levels	Groundwater encountered shallower than anticipated resulting	4	2	8	Utilise suitable foundation system (e.g. increase founding depth).
adversely affecting foundation/	in a decrease in working pile capacity/ reduction in FoS, or				Dependent upon site observations Designer contacted immediately if ground conditions differ from what was
formation levels	reduced bearing capacity for shallow foundations bearing on granular soils.				anticipated
Geological features, fissures, faults, dissolution features, etc which impact on design/ construction	Prescence of uplifted limestone rafts reduces shear strength of glacial deposits, resulting in lower FoS for foundations bearing capacity.	4	2	8	Use experienced site geotechnical personnel to provide advanced warning of potential problems. Contact designer in the event of encountering limestone void.
	Risk of dissolution features – online mapping indicates to Drogheda being in a area of medium risk in relation to subsidence				

Risk	Description	Impact (1-5)	Probability (1-5)	Level of Risk	Mitigation
Pavement design	Risk of low strength formation soils.	3	2	6	In situ testing indicates that CBR greater than 2.5% can be anticipated across the site although localised weaker zones maybe encountered which will require improvement (probable excavate and replace with compact granular fill). Recommendation for further testing to be undertaken during construction to verify design CBR.
Contaminated ground/ groundwater	Environmental risks and / or H&S risk to operatives / public. Delay to programme while material is disposed of / remediated.	3	2	6	Refer to Ramboll Geo-environmental report
Shrink Swell effects from clays present.	Structural damage unlikely as laboratory test results indicates low volume change potential.	3	1	3	Foundations to be designed in accordance with NHBC guidelines Chapter 4.2 'Building near trees'. Where new planting is proposed Designer to consider choice of shrub/ sapling and adhere to guidance in Chapter 4.2.
Sulphates in ground attacking and weakening concrete	Reduction in strength of below ground concrete structures - potential failure of foundations.	3	2	6	Existing geochemical data indicates the near surface soils to be of AC-1 in accordance with Table C1 of BRE SD1. Concrete to be designed in accordance with guidelines given in BRE Special Digest1.
					Chemical data currently limited to near surface soils. Engineers descriptions record pyrite within bedrock - potential for sulphates within Lucan Formation and therefore further testing recommended should a deep foundation solution be adopted.
					Designer to be notified should contamination 'hot spots' been countered during construction which may require ACEC classification to be reassessed.

		Probability (P)						
		1 2 3 4 5						
-	1	1	2	3	4	5		

	Impact	Probability
1	Very Low	Highly Unlikely
2	Low	Unlikely

Doc ID REH2022N01645-RAM-RP-00048 / Version 0.2

Ramboll - Vantage Dublin Data Centers DUB-13

2	2	4	6	8	10
3	3	6	9	12	15
4	4	8	12	16	20
5	5	10	15	20	25

3	Medium	Possible	
4	High	Likely	
5	Very High	Highly Likely	



LOW - Normal Risk (rectified through standard procedures)

MEDIUM - Requires Special Attention / Measures

HIGH - Unacceptable Risk

9. REFERENCES

BGS, Geological Survey of Ireland 1:63,630 geological map drift series Sheet 111, 1901
BRE Special Digest 1:2005 Concrete in Aggressive Ground 3rd Edition
Geological Survey of Ireland Interactive Map, 2022
BS 8004:2015 Code of Practice for Foundations
BS 5930:2015 Code of Practice for Ground Investigations
BS EN 1997-1:2004 Eurocode 7: Geotechnical design – Part 1: General Rules
BS EN 1997-1:2004 Eurocode 7: Geotechnical design – Part 2: Ground Investigation and Testing
IGSL Ltd Factual Report (ref: 24149)
CIRIA C143 The Standard Penetration Test (SPT): Methods and Use
CIRIA C504 Engineering in Glacial Tills

Ramboll - Vantage Dublin Data Centers DUB-13

APPENDIX A IGSL FACTUAL REPORT **IGSL Ltd**

Data Centre Project 3 Profile Park

Ground Investigation Report FACTUAL

Project No. 24188

September 2022



M7 Business Park Naas Co. Kildare Ireland

T: +353 (45) 846176 E: info@igsl.ie W: www.igsl.ie

Distribution	Report Status	Rev	Date of Issue	Prepared By:	Approved By:
Ramboll	DRAFT PDF by email	0	09-09-2022	John Lawler BSc MSc PGeo EurGeol FGS	Paul Quigley BEng CEng MICE MIEI FGS RoGEP Adviser
Ramboll	PDF by email	1	23-09-2022	John Lawler	Paul Quigley

DOCUMENT ISSUE REGISTER

TABLE OF CONTENTS

Foreword

1. Introduction

2. Fieldworks

2.1 General

2.2 Trial Pits

2.3 Cable Percussion Boring

2.4 Rotary Core Drillholes

2.5 Dynamic Cone Penetrometer

2.6 Plate Bearing Tests

2.7 Resistivity Survey

2.8 Groundwater Monitoring

2.9 Surveying of Exploratory Hole Locations

3. Laboratory Testing

Bibliography

FIGURES

Figure 1

- Site Location Plan

APPENDICES

Appendix 1	- Trial Pit Logs & Photographs
Appendix 2	- Cable Percussion Borehole Logs
Appendix 3	- Rotary Core Drillhole Logs & Photographs
Appendix 4	- Dynamic Cone Penetrometer Records
Appendix 5	- Plate Bearing Test Records
Appendix 6	- Resistivity Survey
Appendix 7	- Groundwater Monitoring Records
Appendix 8	- Geotechnical Laboratory Results (Soil)
Appendix 9	- Chemical / Environmental Laboratory Results (Soil)
Appendix 10	- Geotechnical Laboratory Results (Rock)
Appendix 11	- Exploratory Hole Location Plan

FOREWORD

The following conditions and notes on the geotechnical site investigation procedures should be read in conjunction with this report.

Standards

The ground investigation works for this project (**Data Centre Project 3 – Profile Park**) have been carried out by IGSL in accordance with Eurocode 7 - Part 2: Ground Investigation & Testing (EN 1997-2:2007). This has been used together with complementary documents such as Engineers Ireland Specification for Ground Investigation (2nd Ed, 2016), BS 5930 (2015+A1:2020) and BS 1377 (Parts 1 to 9) and the following European Norms:

- EN 1997-2 Eurocode 7: 2007 Geotechnical Design Part 2: Ground Investigation & Testing
- EN ISO 22475-1:2006 Geotechnical Investigation and Sampling Sampling Methods & Groundwater Measurements
- EN ISO 14688-1:2017 Geotechnical Investigation and Testing Identification and Classification of Soil, Part 1: Identification and Description
- EN ISO 14688-2:2017 Geotechnical Investigation and Testing Identification and Classification of Soil, Part 2: Principles for a classification
- EN ISO 14689-1:2017 Geotechnical Investigation and Testing Identification, description & classification of rock

The Eurocode 7, Part 2 – Ground Investigation and Testing GI specification shall be read in conjunction with the Specification and Related Documents for Ground Investigation in Ireland, 2nd Edition, published by Engineers Ireland in 2016.

Reporting

No responsibility can be held by IGSL Ltd for ground conditions between exploratory hole locations. The engineering logs provide ground profiles and configuration of strata relevant to the investigation depths achieved and caution should be taken when extrapolating between exploratory points. No liability is accepted for ground conditions extraneous to the investigation points. Unless specifically stated, no account has been taken of possible subsidence due to mineral extraction, mining works or karstification below or close to the site.

This report has been prepared for F1 Enzo Properties and Ramboll and the information should not be used without their prior written permission. IGSL Ltd accepts no responsibility or liability for this document being used other than for the purposes for which it was intended.

Boring Procedures

Where required, 'shell and auger' or cable percussive boring technique is employed as defined by Section 6.3 of IS EN ISO 22475-1:2006. The boring operations, sampling and in-situ testing meet with the recommendations set out in IS EN 1997-2:2007 and BS 1377:1990 and EN ISO 22476-3:2005. The shell and auger boring technique allows for continuous sampling in clay and silt above the water table and sand and gravel below the water table (Table 2 of IS EN ISO 22475-1:2006).

It is highlighted that some disturbance and variation is unavoidable in particular ground (e.g. blowing sands, gravel / cobble dominant glacial deposits etc). Attention is drawn to this condition, whenever it is suspected. Where cobbles and boulders are recorded, no conclusion should be drawn concerning the size, presence, lithological nature, or numbers per unit volume of ground.

In-Situ Testing

Where required, Standard Penetration Tests (SPT's) are conducted strictly in accordance with Section 4.6 of IS EN 1997-2:2007. The SPT equipment (hammer energy test) has been calibrated in accordance with EN ISO 22476-3:2005 and the Energy Ratio (E_r). A calibration certificate is

available upon request. The E_r is defined as the ratio of the actual energy E_{meas} (measured energy during calibration) delivered to the drive weight assembly into the drive rod below the anvil, to the theoretical energy (E_{theor}) as calculated from the drive weight assembly. The measured number of blows (N) reported on the engineering logs are uncorrected. In sands, the energy losses due to rod length and the effect of the overburden pressure should be taken into account (see IS EN ISO 22476-3:2005).

Soil Sampling

Three categories of sampling methods are outlined in EN ISO 22475-1:2006. The categories are referenced A, B and C for any given ground conditions and are shown in Tables 1 and 2 of EN ISO 22475-1:2006. Reference should be made to EN 1997-2:2002 for guidelines on sample class and quality for strength and compressibility testing. Samples of quality classes 1 or 2 can only be obtained by using Category A sampling methods.

Class 1 thin wall undisturbed tube samples (UT100) were obtained in fine grained soils and strictly meet the requirements of EN 1997-2:2002 and EN ISO 22475-1:2006. Soil samples for laboratory tests are divided into five classes with respect to the soil properties that are assumed to remain unchanged during sampling, handling transport and storage. The minimum sample quality required for testing purposes to Eurocode 7 compatibility (EN 1997-2:2002) is shown in Table A.

EN 1997 Clause	Test	Minimum Sample Quality Class	
5.5.3	Water Content	3	
5.5.4	Bulk Density	2	
5.5.5	Particle Density	N/S	
5.5.6	Particle Size Analysis	N/S	
5.5.7	Consistency Limits	4	
5.5.8	Density Index	N/S	
5.5.9	Soil Dispersivity	N/S	
5.5.10	Frost Susceptibility	N/S	
5.6.2	Organic Content	4	
5.6.3	Carbonate Content	3	
5.6.4	Sulphate Content	3	
5.6.5	рН	3	
5.6.6	Chloride Content	3	
5.7	Strength Index	1	
5.8	Strength Tests	1	
5.9	Compressibility Tests	1	
5.10	Compaction Tests	N/S	
5.11	Permeability	2	

Table A – Details of Sample Quality Requirements

N/S – not stated. Presume a representative sample of appropriate size.

Samples recovered from trial pits or trenches meet the requirements of IS EN ISO 22475-1. It is highlighted that unforeseen circumstances such as variations in geological strata may lead to lower quality sample classes being obtained.

Groundwater

The depth of entry of any influx of groundwater is recorded during the course of boring operations. However, the normal rate of boring does not usually permit the recording of an equilibrium level for any one water strike. Where possible, drilling is suspended for a period of twenty minutes to monitor the subsequent rise in water level. Groundwater conditions observed in the borings or pits are those appertaining to the period of investigation. It should be noted however, that groundwater levels are subject to diurnal, seasonal and climatic variations and can also be affected by drainage conditions, tidal variations etc.

Engineering Logging

Soil and rock identification has been based on the examination of the samples recovered and conforms with IS EN ISO 14688-1:2017 and IS EN ISO 14688-2:2017. Rock weathering classification conforms to IS EN ISO 14689-1:2017 along with discontinuities (bedding planes, joints, cleavages, faults etc) as classified in Section 6.4 of IS EN ISO 14689-1:2017 and Annex C of same. Rock mechanical indices (TCR, SCR, RQD) are defined in accordance with IS EN ISO 22475-1:2006.

Where peat has been encountered, samples have been logged in accordance with the Von Post Classification (ref. Von Post, L. 1992. Sveriges Gologiska Undersoknings torvinventering och nogra av dess hittils vunna resultat (SGU peat inventory and some preliminary results) Svenska Mosskulturforeningens Tidskrift, Jonkoping, Swedden, 36, 1-37 and Hobbs N. B. Mire morphology and the properties of some British and foreign peats. QJEG, Vol. 19, 1986.

Retention of Samples

After satisfactory completion of all the scheduled laboratory tests on any sample, the remaining material will be discarded. Unless a period of retention of samples is agreed, it is our normal practice to discard all soil samples one month after submission of our final report.

1. INTRODUCTION

IGSL has undertaken a programme of geotechnical ground investigation works at a greenfield site in the existing Profile Park. The Park is located on the western fringe of Dublin off the Nangor Road (R134), Dublin 22. It is host to a number of data centre buildings. The ground investigation (GI) works were conducted to inform the design for a proposed Data Centre, termed 'Data Centre 3'.

The site comprises former agricultural lands with some indication of there being a yardspace and some small-scale buildings having occupied the site. The predominantly grassland site is punctuated by a number of mature linear hedgerows. It is bound to the north by the Nangor Road, and beyond to Kilcarbery Park industrial estate. The expanse of Profile Park forms its boundary on all other sides with an internal estate road, Falcon Avenue, running along its southeastern aspect.



Figure 1 – Site Location Plan

Fig 1 reproduced from Google Earth Professional 4/2021

The investigation comprised rotary core drillholes, cable percussion boring, dynamic cone penetrometer testing, machine-dug trial pits and in situ plate bearing testing. A resistivity survey was undertaken by Minerex Geophysics Limited. The investigations were executed in accordance with BS 5930 Code of Practice for Site Investigations (2015+A1:2020) and EN 1997-2 Eurocode 7 Part 2 Ground Investigation & Testing and supervised by an IGSL geotechnical engineer.

Geotechnical, chemical and environmental laboratory testing was scheduled on a range of soil samples. The geotechnical testing included moisture contents, Atterberg Limits, PSD gradings and

Moisture Condition Value [MCV] testing. Chemical testing was undertaken to BRE SD-1 on the soil samples. Environmental tests were undertaken on soil samples (WAC '*Rilta*' suite) to assess suitability for off-site disposal to landfill and/or Soil Recovery Facility.

Rock strength testing in the form of Point Load Strength Index [PLSI] and Uniaxial Compressive Strength [UCS] testing was performed on cores recovered from site.

This report presents the factual geotechnical data acquired from the 2022 investigation. The exploratory hole locations are plotted on the site plan in Appendix 11.

2. FIELDWORKS

2.1 General

The geotechnical investigations were carried out in July and August 2022 and comprised the following:

- Trial Pits (10 No.)
- Cable Percussion Boring (6 No.)
- Rotary Core Drillholes (6 No.)
- Dynamic Cone Penetrometer (10 No.)
- Plate Bearing Testing (10 No.)
- Resistivity Survey
- o Groundwater Monitoring
- Surveying of Exploratory Hole Locations

2.2 Trial Pits

Trial pitting was undertaken at ten locations across the site. The trial pits were excavated, logged and sampled under the direction of an IGSL geotechnical engineer in accordance with BS 5930 (2015+A1:2020). Bulk disturbed samples (typically 20 to 30kg) were taken as the pits progressed. In each pit, a plate bearing test was conducted with a dynamic cone penetrometer performed in the surficial soils alongside.

The bulk samples were placed in heavy-duty polyethylene bags and sealed before being transported to Naas for laboratory testing. Environmental samples, collected in 60ml and 250ml glass jars as well as plastic tubs (500ml), were dispatched to the environmental laboratory (Chemtest UK). The trial pits were backfilled with the as-dug arisings and reinstated to the satisfaction of IGSL's site geotechnical engineer. The trial pit logs together with pit photographs are presented in Appendix 1. The logs include descriptions of the soils encountered, groundwater conditions and stability of the pit sidewalls.

2.3 Cable Percussion Boreholes

Cable percussion boring (200mm diameter) was undertaken at six locations using a Dando 2000 rig. The boreholes extended to depths of between 1.90m and 2.0m below ground level. Boring commenced through pre-dug services inspection pits. Each service pit was excavated only after undertaking careful CAT [Cable Avoidance Tool] survey and following consultation of all available utility plans. Disturbed bulk samples were recovered at 1m intervals or change of strata during boring and these are denoted 'B' on the engineering logs.

Standard Penetration Tests (SPT's) were performed in the boreholes and given the nature of the soils, a solid cone was used. It is noted that the SPT N-Values reported are the number of blows for 300mm increment penetration (e.g. BH01 at 1.0m where N=19). These exclude the seating blow values, which represent the initial 150mm depth of penetration. Where partial penetration was achieved during testing, the number of blows is shown for the actual penetration depth achieved (e.g. BH02 at 2.0m where N=50/75mm). In accordance with Eurocode 7, the SPT hammer has been calibrated and the energy ratio (Er) value is incorporated on the engineering logs. It is highlighted that the SPT N-Values reported on the engineering logs are uncorrected for energy ratio.

Descriptions of the soils encountered and samples recovered are presented on the borehole records in Appendix 2. Details of groundwater strikes and hard strata boring (i.e. chiselling) are also presented on the aforementioned records.

2.4 Rotary Core Drillholes

Rotary core drilling was carried out (holes denoted RC_) using a tracked Beretta T44 top-drive rig. At each location, symmetrex drilling was utilized within the superficial deposits with coring
techniques used in the underlying bedrock. The rotary drilling in bedrock produced 78mm diameter cores.

The cores were placed in 3m capacity timber boxes and logged by an IGSL engineering geologist. This included photography of the cores with a digital camera. Where rock core was recovered, a graphic fracture log is also presented alongside the mechanical indices. This illustrates the fracture state of the rock cores and allows easy identification of highly fractured / non-intact zones and discontinuity spacings. It should be noted that no correction for dip of the joints has been made and that the spacings shown are successive joint / core intersections within the core.

Groundwater monitoring standpipes were installed in all six coreholes. The standpipes consisted of 50mm diameter HDPE pipework with proprietary 1mm slots and incorporated a pea gravel filter pack and cement / bentonite grout seal. Protective headwork covers were concreted in place.

The core log records are presented in Appendix 3 and this includes engineering geological descriptions, details of the bedding / discontinuities and mechanical indices (TCR, SCR and RQD's) for each core run (to be included in a future version of this report). Core photographs are also presented in Appendix 3 and these illustrate the structure and fracture state of the bedrock.

2.5 Dynamic Cone Penetrometer Testing

In-situ dynamic cone penetrometer tests were carried out at each trial pit location in accordance with TRL recommended procedure* to estimate CBR values* of the indigenous subsurface deposits. Testing was carried out from ground level. The test results with CBR values are presented in Appendix 4 of this report.

*CBR values are estimated using the correlation derived by Kleyn and Van Heerden (1983), which is preferred by TRL.

2.6 Plate Bearing Testing

Ten plate bearing tests were conducted at each of the trial pit locations at depths between 0.30m to 0.40m below ground level [bgl]. Plate testing was undertaken to evaluate the modulus of sub-grade reaction (Ks) and equivalent CBR value. A 450mm diameter plate was used for the tests with kentledge provided by a mechanical excavator. Two load cycle tests, in accordance with BS 1377, were performed and the load / settlement plots, Ks and equivalent CBR values are presented in Appendix 5 of the report.

2.7 Resistivity Survey

A resistivity survey was conducted by Minerex Geophysics Limited. It consisted of two different methods. The methodology employed used both Vertical Electrical Sounding (VES) and Soil Resistivity (SR) in the Wenner electrode configuration at a range of electrode spacing agreed with the client prior to the fieldwork. The increase in the electrode spacing leads to an increase in the depth - the VES permitting deeper soundings and Soil Resistivity Tests shallow. The Minerex report is presented in Appendix 6.

2.8 Groundwater Monitoring

Groundwater monitoring was undertaken following the fieldworks period. Groundwater levels were measured using an electric dipmeter with measurements taken from the wells installed in the coreholes on the project. The levels recorded are shown in Appendix 7.

2.9 Surveying of Exploratory Hole Locations

Following completion of the exploratory works, surveying was carried out using GPS techniques. Co-ordinates (x, y) were measured to Irish Transverse Mercator and ground levels (z) established to Malin Head. The co-ordinates and ground levels are shown on the exploratory hole logs with locations shown on the exploratory hole plan in Appendix 11.

3. LABORATORY TESTING

Geotechnical laboratory testing was performed at IGSL's INAB-accredited laboratory in accordance with the methods set out in BS1377; British Standard Methods of Test for Soils for Civil Engineering Purposes; British Standards Institute:1990. Soils testing on disturbed samples included moisture content, Atterberg Limits (Liquid / Plastic Limits), Particle Size Distribution, Moisture Condition Value and thermal resistivity testing. The results from testing on selected trial pit and borehole samples are presented in Appendix 8.

Soil chemical testing to BRE Test Suite D is presented in Appendix 9. It incorporates pH, water soluble, acid soluble sulphate, total sulphur in addition to magnesium, chloride and nitrate testing. Soil samples were also selected from trial pits and subject to the *'Rilta'* WAC Suite of testing. The results can be used to classify the material with regard to its potential for disposal to landfill. Both chemical and environmental results are presented in Appendix 9.

Rock strength testing on selected core specimens comprised Point Load Strength Index [PLSI] testing and Uniaxial Compressive Strength [UCS] testing. The tests were performed in accordance ISRM Suggested Methods for Rock Characterization, Testing and Monitoring and the results are presented in Appendix 10.

BIBLIOGRAPHY

- **1.0** BS 5930 (2015 + A1:2020) Code of Practice for Site Investigation, British Standards Institution (BSI).
- 2.0 BS 1377 (1990). Methods of Testing of Soils for Civil Engineering Purposes, BSI.
- **3.0** CEN (2018A). Geotechnical Investigation and Testing Identification and classification of soil Part 1: Identification and description (ISO 14688-1:2017)
- **4.0** CEN (2018B). Geotechnical Investigation and Testing Identification and classification of soil Part 2: Principles for a classification (ISO 14688-2:2017)
- **5.0** CEN (2018C). Geotechnical Investigation and Testing Identification, description & classification of rock (EN ISO 14689-1:2017)
- 6.0 EN 1997-2 (2007). Eurocode 7: Geotechnical design. Part 2: Ground Investigation & Testing
- **7.0** International Society of Rock Mechanics (ISRM) (1981). Rock Characterisation, Testing and Monitoring; ISRM Suggested Method. Oxford, UK: Pergamon Press.
- **8.0** Kleyn, E. & Van Heerden, M.J. (1983, July). Using DCP Soundings to Optimize Pavement Rehabilitation. Paper presented at the Annual Transportation Convention, Milner Park Showgrounds, Johannesburg.
- **9.0** Site Investigation Practice: Assessing BS 5930 (1986), Geological Society Special Publication, No. 2.

Appendix 1

Trial Pit Logs & Photographs

	An									REPORT N	JMBER	
	BSL	Т	RIAL PIT I	RECO	RD					24 ⁻	188	
CON	TRACT	Data Centre Projects 3 - Profile Pa	ark						IT NO.	TP0	1	
LOG	GED BY	MB	CO-ORDINAT	ËS	703,82 730,8	25.57 E 58.11 N		DATE S	TARTED) 19/07 TED 19/07	7/2022 7/2022	
CLIE		F1 Enzo Properties	GROUND LE	VEL (m)	73.70			EXCAVA METHO	ATION D	Hitac	hi 8.5	
ENG		Kamboli							Sampla			Ē
							0		Sample	.5	KPa)	romete
		Geotechnical Description		Legend	Depth (m)	Elevation	Water Strike	Sample Ref	Type	Depth	Vane Test (Hand Penet (KPa)
0.0	TOPSO	IL		<u><u><u>x</u></u>, <u>x</u>, <u>x</u>, <u>y</u>, <u>y</u>, <u>y</u>, <u>y</u>, <u>y</u>, <u>y</u>, <u>y</u>, <u>y</u></u>								
-				$\frac{1}{\sqrt{l_2}} \cdot \frac{\sqrt{l_2}}{\sqrt{l_2}} \cdot \frac{\sqrt{l_2}}$								
-	Firm gre	ey sandy gravelly CLAY with occasio	nal cobbles		0.40	73.30						
-								180437	В	0.60-0.70		
-												
1.0												
-												
-												
-	Croves	ndy alayoy angular CRAVEL with as	acional		1.70	72.00		100/20	D	1 70 1 90		
-	boulder	s (possible weathered rock)	casional	0-0-0-0				100430	D	1.70-1.00		
2.0												
-	End of	Frial Pit at 2.20m		1.0 · 1.0 /	2.20	71.50						
-												
-												
-												
3.0												
-												
-												
-												
-												
Grou Dry p	undwater bit	Conditions						<u> </u>		I		
5												
Stab Good	ility d											
Gene	eral Rema	rks										
2												

E		т		RECO	RD					REPORT NU	JMBER	
CON	TRACT Data Cent	re Projects 3 - Profile Pa	ırk					TRIAL P	IT NO.	TP0	2	
LOG	GED BY MB	-	CO-ORDINAT	ËS	703,87 730,84	72.43 E 17.06 N		DATE S	TARTED	Shee 0 19/07 TFD 19/07	t 1 of 1 7/2022	
CLIE ENGI	NT F1 Enzo P NEER Ramboll	Properties	GROUND LE	VEL (m)	74.07			EXCAVA	ATION D	Hitac	hi 8.5	1
									Sample	s	Pa)	ometer
	Geo	otechnical Description		Legend	Depth (m)	Elevation	Water Strike	Sample Ref	Type	Depth	Vane Test (K	Hand Penetr (KPa)
0.0 - - -	TOPSOIL			$\frac{\frac{\sqrt{1}}{\sqrt{1}} \frac{\sqrt{1}}{\sqrt{1}}}{\frac{\sqrt{1}}{\sqrt{1}} \frac{\sqrt{1}}{\sqrt{1}}}$	0.40	70.07						
-	Firm brown sandy C Firm grey sandy gra	LAY velly CLAY with occasio	nal cobbles		0.40	73.67		180435	В	0.70-0.80		
- - - - - -												
2.0	Grey sandy clayey a boulders (possible v	ngular GRAVEL with oc veathered rock)	casional		1.80	72.27		180436	В	1.80-1.90		
-	End of Trial Pit at 2.	20m			2.20	71.87						
- 3.0 - -												
Grou	ndwater Conditions											
Dry p	bit											
Good	ility វ											
Gene	eral Remarks											

-Arm							REPORT N	JMBER	
IGSL	TRIAL PIT RECO	ORD					24	188	
CONTRACT Data Centre Projects 3 - Profile	Park				TRIAL P	IT NO.	TP0	3	
	CO-ORDINATES	703,8	00.44 E		DATE ST	TARTED	Shee 15/07	t 1 of 1 7/2022	
DGGED BY MB		730,8	27.39 N		DATE C	OMPLE	TED 15/07	/2022	
LIENT F1 Enzo Properties	GROUND LEVEL (M)	73.39			EXCAVA METHO	ATION D	Hitac	hi 8.5	
						Sample	s)a)	mete
Geotechnical Description				trike				ist (KI	enetro
	gend	oth	vatio	ter S	nple	е	oth	Je Te	Pe Pe
	Leç	(n) Del	Ele	Wa	Sar Ref	Тур	Del	Var	Hai
	$\frac{\sqrt{2}}{1/2} \cdot \frac{\sqrt{2}}{\sqrt{2}}$	<u>2</u>							
		2.							
		<u>+</u> - 0.50	72.89						
Stiff greyish brown sandy gravelly CLAY w cobbles	ith ocaassional				180428	в	0.60-0.70		
0		-							
		-							
		-							
Grey sandy clayey angular GRAVEL with	occasional	- 1.80	71.59						
boulders (possible weathered rock)					180429	В	2.00-2.10		
		2							
		2							
		- 260	70 79						
End of Trial Pit at 2.60m		2.00							
0									
roundwater Conditions ry pit									
tability									
ood									
eneral Remarks									

A				חס					REPORT NU	JMBER	
JGS	31			KD					24	188	
CONTR	ACT Data Centre Project	ts 3 - Profile Park					TRIAL P	IT NO.	TP04	4 t 1 of 1	
.OGGE	ED BY MB	CO-ORI	DINATES	703,8 730,8	49.11 E 17.54 N		DATE S	TARTED	18/07 TED 18/07	7/2022 7/2022	
	F F1 Enzo Properties	GROUN	ID LEVEL (m)	73.72			EXCAVA METHO	ATION D	Hitacl	hi 8.5	
								Sample	s	a)	neter
	Geotechnica	I Description	agend	epth (r	evation	'ater Strike	ample ef	/be	epth	ane Test (KP	and Penetror
.0 T	TOPSOIL			<u>م</u> ج		\$	ŮŘ.	f	Ō	>	Ĩ
F	Firm brown sandy CLAY			0.30	73.42						
F	- Firm grey sandy gravelly CLA	Y with occasional cobbl	es 0	0.60	73.12		180432	В	0.50-0.60		
				-			180433	В	0.80-0.90		
D											
				-							
G	Grey sandy clayey angular G boulders (possible weathered	RAVEL with occasional I rock)		1.60	72.12		180434	В	1.60-17.00		
B E	Boulders ät 1.80m End of Trial Pit at 1.90m			1.90	71.82						
.0											
0											
round	water Conditions										
ry pit											
tability	у										
00u											
eneral	al Remarks										

An								REPORT N	JMBER	
IGSL		TRIAL PIT REC	ORD					24	188	
CONTRACT	Data Centre Projects 3 - Profile	e Park				TRIAL P	IT NO.	TP0	5	
LOGGED B	Y MB	CO-ORDINATES	703,8 730,8	85.38 E 05.46 N		DATE S	TARTEI	Shee 18/07 TED 18/07	t 1 of 1 7/2022 7/2022	
CLIENT	F1 Enzo Properties	GROUND LEVEL (m) 74.04			EXCAVA		Hitac	hi 8.5	
ENGINEER	Ramboll					METHO				
							Sample	s)a)	meter
	Geotechnical Descriptic	n geng	epth (r	evation	/ater Strike	ample ef	/pe	epth	ane Test (KI	and Penetro
0.0 TOPS	SOIL	۲. <u>۲. ۲. ۲. ۲.</u>	<u> </u>	Ξ	3	ů ř.	ŕ	ă	>	Ϊč
Firm g	greyish brown sandy gravelly CLAN	with occasional	0.50	73.54						
1.0			الملوا بالهكانا يمطرب الكها بلطوا			180430	В	0.70-0.80		
Grey : 2.0 bould	sandy clayey angular GRAVEL witl ers (possible weathered rock)	n occasional		72.14		180431	В	2.00-2.10		
End o	f Trial Pit at 2.30m	h=7.0	2.30	71.74						
3.0										
Groundwate	er Conditions			1		1				
Dry pit										
Stability Good										
General Rer	narks									

ર્ટ	J.SL		TRIAL PIT	RECO	RD					REPORT NU 24	jmber 188	
CONT	FRACT	Data Centre Projects 3 - Profile	Park					TRIAL P	PIT NO.	TP0	6 t 1 of 1	
LOGO	GED BY	MB F1 Enzo Properties	CO-ORDINAT	'ES VEL (m)	703,77 730,78 73.28	77.23 E 30.74 N		DATE S DATE C EXCAVA	TARTED OMPLE ⁻ ATION	15/07 TED 15/07 Hitac	7/2022 7/2022 hi 8.5	
ENGI	NEER	Ramboll							Sampla			er
		Geotechnical Description		egend	epth n)	levation	/ater Strike	ample ef	anple	epth	ane Test (KPa)	and Penetromet
0.0		L BROLIND (granular fill)			0.20	ш 73.08	5	S R	<u> </u>		>	Ξ
.0	Firm bro boulders	wnish grey sandy gravelly CLAY v	vith occasional		0.50	72.78		180426	В	0.50-0.60		
.0	Grey sar boulders	ndy clayey angular GRAVEL with (s (possible weathered rock)	occasional		1.80	71.48		180427	В	1.80-1.90		
	End of T	rial Pit at 2.10m			2.10	71.18	(SIOW)					
.0												
low	ndwater C ingress at	Conditions t 2.0m										
tabi Good	lity											
iene	ral Rema	rks										

a Array							REPORT NI	JMBER	
IGSL	TRIAL PIT RECO	RD					24	188	
CONTRACT Data Centre Projects 3 - Profile	Park				TRIAL P	IT NO.	TP0	7	
OGGED BY MB	CO-ORDINATES	703,8	16.50 E		DATE S	TARTED) 14/07	7/2022	
	GROUND LEVEL (m)	73.29	/ 1. 4 / IN		DATE C		TED 14/07 Hitac	7/2022 hi 8 5	
NGINEER Ramboll		1	1	1	METHO	D			1
						Sample	s	a)	meter
Geotechnical Description	n edeud	Depth n)	levation	Vater Strike	àample Ref	ype	Jepth	/ane Test (KF	land Penetro
D TOPSOIL			ш	>	012			>	-
	$\frac{\sqrt{t_2}}{\sqrt{t_2}}, \frac{\sqrt{t_2}}{\sqrt{t_2}}$								
Firm brown sandy CLAY	/ <u>////////////////////////////////////</u>	0.40	72.89		190420	Р	0.50.0.60		
	 	0.70	72.59		180420	В	0.50-0.60		
Firm grey sandy gravelly CLAY									
0									
	<u></u>				180421	В	1.40-1.50		
Grey sandy clayey angular GRAVEL with	occasional	1.60	71.69	1					
boulders (possible weathered rock)		1 00	71 30	(Seepage)	180423	В	1.80-1.90		
End of Trial Pit at 1.90m		1.50	11.55						
0									
low ingress at 1.80m									
t ability ood									
eneral Remarks									

E	т	RIAL PIT	RECO	RD					REPORT N	jmber 188	
CON.	דאכר Data Centre Projects 3 - Profile Pa	ark					TRIAL P	IT NO.	TP0	8	
LOG	GED BY MB	CO-ORDINAT	ES	703,85 730,76	57.84 E 53.52 N		DATE S	TARTED OMPLE	Shee 0 15/07 TED 15/07	t 1 of 1 7/2022 7/2022	
CLIE Engi	NT F1 Enzo Properties	GROUND LE	VEL (m)	73.49			EXCAVA METHO	ATION D	Hitac	hi 8.5	
								Sample	s)a)	meter
	Geotechnical Description		Legend	Depth (m)	Elevation	Water Strike	Sample Ref	Type	Depth	Vane Test (K	Hand Penetro (KPa)
0.0	TOPSOIL		$\frac{\sqrt[3]{l_{Z}}}{l_{Z}} \frac{\sqrt[3]{l_{Z}}}{\sqrt[3]{l_{Z}}} \sqrt[3]$	0.50	70.00						
1.0	Firm brownish grey sandy gravelly CLAY with cobbles	h occasional	ן לא יילא לא אין וא ל ו אין יאן אין אין אין	0.50	72.99		180424	В	0.70-0.80		
	Grey sandy clayey angular GRAVEL with oc boulders (possible weathered rock)	casional		1.50	71.99		180425	В	1.70-1.80		
2.0	End of Trial Pit at 2.00m			2.00	71.49	(Slow)					
3.0											
Grou Slow	indwater Conditions ingress at 2.0m					<u> </u>					L
Stabi Good	ility 1										
Gene	eral Remarks										

Chr.		т		RECO	RD					REPORT NU	JMBER 188	
	TRACT	Data Centre Projects 3 - Profile Pa	ark					TRIAL P	IT NO.	TP0	9	
LOG	GED BY	МВ	CO-ORDINAT	ËS	703,82 730,72	20.02 E 26.32 N		- SHEET DATE S DATE C	TARTE	Shee D 14/07 TED 14/07	t 1 of 1 7/2022 7/2022	
	INEER	F1 Enzo Properties Ramboll	GROUND LEV	VEL (m)	73.12			EXCAVA METHO	ATION D	Hitac	hi 8.5	
			1						Sample	es	(F	leter
		Geotechnical Description		egend)epth m)	elevation	Vater Strike	sample Ref	ype	Jepth	/ane Test (KPa	land Penetrom KPa)
0.0 - - - - - -	TOPSO	L y sandy gravelly CLAY with occasio	nal cobbles		0.40	72.72	~	180418	В	0.50-0.60		
- - - - - - - - - - - - - - - - - - -	Grey sai boulders End of T	ndy clayey angular GRAVEL with oc s (possible weathered rock) rial Pit at 1.80m	casional		1.60	71.52 71.32	پ (Sīow)	180419	В	1.60-1.70		
- - - - - - - - - - - - - -												
Grou Slow	indwater (ringress a	Conditions t 1.80m										
Gene	eral Rema	rks										

E IG	SL.		TRIAL PIT	RECO	RD					REPORT NU 24	jmber 188	
CONT	RACT	Data Centre Projects 3 - Profile F	Park					TRIAL P	PIT NO.	TP1	0	
LOGG	ED BY	MB	CO-ORDINAT	TES	703,79 730,69	59.48 E 92.48 N		DATE S DATE C	TARTED	Shee 19/07 TED 19/07	t 1 of 1 7/2022 7/2022	
	NT NEER	F1 Enzo Properties Ramboll	GROUND LE	VEL (m)	73.08			EXCAVA METHO	ATION D	Hitac	hi 8.5	
									Sample	s	a)	meter
		Geotechnical Description		Legend	Depth (m)	Elevation	Water Strike	Sample Ref	Type	Depth	Vane Test (KF	Hand Penetro (KPa)
0.0	TOPSOI	L y sandy gravelly CLAY with occasi	onal cobbles		0.40	72.68		180439	В	0.50-0.60		
- 1.0	Stiff to v and occa	ery stiff greyish black gravelly CLA asional boulders	Y with cobbles		1.40	71.68	₹ (Slow)	180440	В	1.50-1.60		
	End of T	rial Pit at 2.70m			2.70	70.38		180441	В	2.50-2.60		
3.0												
Groun	ndwater (Conditions										
Slow i	ngress a	t 2.0m										
Stabil Slighty	ity y unstabl	e										
Gener	ral Rema	rks										



<u>TP01 – 1 of 3</u>

<u>TP01 – 2 of 3</u>



<u>TP01 – 3 of 3</u>





<u>TP02 – 1 of 3</u>

<u>TP02 – 2 of 3</u>





<u>TP02 – 3 of 3</u>

<u>TP03 – 1 of 3</u>

<u>TP03 – 2 of 3</u>





<u>TP03 – 3 of 3</u>



<u>TP04 – 1 of 3</u>

<u>TP04 – 2 of 3</u>



<image>

<u>TP04 – 3 of 3</u>

<u>TP05 – 1 of 3</u>



<u>TP05 – 2 of 3</u>



<u>TP05 – 3 of 3</u>





<u>TP06 – 1 of 3</u>



<u>TP06 – 3 of 3</u>



<u>TP07 – 1 of 3</u>

<u>TP07 – 2 of 3</u>



<u>TP07 – 3 of 3</u>



<u>TP08 – 1 of 3</u>

<u>TP08 – 2 of 3</u>



IGSL Ltd



<u>TP08 – 3 of 3</u>

<u>TP09 – 1 of 3</u>



<u>TP09 – 2 of 3</u>



<u>TP09 – 3 of 3</u>





<u>TP10 – 1 of 3</u>

<u>TP10 – 2 of 3</u>





<u>TP10 – 3 of 3</u>

Appendix 2

Cable Percussion Borehole Logs

\IGSL/

GEOTECHNICAL BORING RECORD

REPORT NUMBER

24188

7													
co	NTRACT	Data Centre	e Projects 3 - Profile	Park						BOREH SHEET	IOLE NO	9. BH01 Sheet 1 of 1	
CO GR	-ORDINAT OUND LE\	ES 703 730 /EL (m AOD)	3,829.90 E),853.84 N 73.76	RIG TYP BOREHO BOREHO	PE OLE DIAM OLE DEPT	ETER (n H (m)	ו זי (חות	Dando 20 200 1.90	000	DATE (DATE (COMMEN	ICED18/07/2022TED18/07/2022	
CLI ENC	ent Gineer	F1 Enzo Pr Ramboll	operties	SPT HAI	MMER REI Y RATIO (%	F. NO. %)				BORED PROCE) BY ESSED B	W.Cahill Y F.C	1
ē						_	Ê		San	nples			U
Depth (n		C	Description		Legend	Elevation	Depth (m	Ref. Number	Sample Type	Depth (m)	Recovery	Field Test Results	Standpip Details
	Very stiff cobbles Obstructi End of B	dark brown sandy sional cobble	o m	AY with		72.06	1.70	AA171725	В	1.00		N = 19 (3, 4, 4, 5, 6) N = 50/75 mm (25, 50)	
HA	RD STRA	TA BORING/C	HISELLING		\A/ata			Cooled	Dia		W	ATER STRIKE DET	AILS
Fror	n (m) To	(m) (h)	Comments		Strike	eDe	epth	At		((min)	Comments	
1	.7 1.	.9 1.5			1.70) 1.	70	No	No		20	Seepage	
							Hole	Casing	De	nth to	GR	OUNDWATER PRO	GRES
INS	TALLATIC Date Ti	DETAILS	op RZ Base	Туре	Dat	e [Depth	Depth	W	ater	Comme	ents	
P				avoidance t			0						
RE	di	ug inspection	pit carried out	avoidance t	ooij with h	and	D - Small B - Bulk I LB - Larg	Disturbed (tub) Disturbed e Bulk Disturbe	u d	⊦Vial + Tuk	UT - I Samp P - U W - V	Undisturbed 100mm Diameter ole ndisturbed Piston Sample Vater Sample	


REPORT NUMBER

<u> </u>		/														
COI	NTRAC	CT Da	ata Centre	Projects 3 -	Profile Park							BOREH SHEET	IOLE N	IO.	BH02 Sheet 1 of 1	
CO- GR		NATES	703, 730, m AOD)	364.31 E 347.41 N 74.20	RIG T BORE BORE	(PE HOLE DIAN HOLE DEP	NETER TH (m)	R (mi)	m) 2	Dando 20 200 2.00	000	DATE (ENC .ete	ED 18/07/2022 ED 18/07/2022	
CLI ENC	ENT GINEEF	F1 R Ra	Enzo Pro amboll	perties	SPT H ENER	AMMER RE GY RATIO (EF. NC %)).				BORED PROCE	BY SSED	BY	W.Cahill F.C	
									$\widehat{}$		Sam	ples				d)
Depth (m			De	scription		Legend		Elevation	Depth (m	Ref. Number	Sample Type	Depth (m)	Pacovany	Necovery	Field Test Results	Standpipe Details
0 - - - - - - - - - - - - - - - -	Stiff of Stiff t	dark brov	vn sandy S iff dark bro	ILT/CLAY w	ith angular grave			10	1.10	AA171726	в	1.00			N = 22 (4, 4, 5, 5, 6, 6)	
	with a	angular c	cobbles				14 1911 - 14 191	20	2.00	_					N = 50/75 mm (25-50)	
	End	of Boreh	ole at 2.00	m												
4																
HA		RATA B	ORING/CH	ISELLING										WA	TER STRIKE DET	AILS
Fron	n (m)	To (m)	lime (h)	Comments		Wat Strik	er ke	Casi	ing S	At	Rise	e /	i ime min)	Co	omments	
1	.8	2	1.5				-							N	lo water strike	
								-					G	RO	UNDWATER PRO	GRESS
INS	TALLA Date	Tip De	ETAILS	p RZ Base	Туре	Da	ite		lole epth	Casing Depth	De W	oth to ater	Comn	nent	ls	
REN	MARK	3 Location dug inst	on scanne spection p	d using CAT t carried out	[cable avoidance	e tool] with H	nand		Samp D - Small B - Bulk D LB - Large Env - Envi	le Legen Disturbed (tub) Disturbed Bulk Disturbe ironmental San	d d nple (Jar +	+ Vial + Tub	UT Sa P - W	- Und mple - Undis	tisturbed 100mm Diameter sturbed Piston Sample er Sample	

-
\IGSL/

REPORT NUMBER

~		/													
со	NTRAC	CT Da	ata Centre	Projects 3 -	Profile Pa	rk						BOREH SHEET	OLE NO	D. BH03 Sheet 1 of	1
CO GR	ORDII	NATES LEVEL (703, 730, m AOD)	784.97 E 779.34 N 73.32		RIG TYP BOREH BOREH	Pe Ole diam Ole dept	ETER (r H (m)	nm)	Dando 20 200 1.90	000	DATE C DATE C	ommei omple	NCED 14/07/2022 TED 14/07/2022	
CL EN	IENT GINEEF	F1 २ Ra	Enzo Pro amboll	perties		SPT HA	MMER RE	F. NO. %)				BORED	BY SSED E	W.Cahill BY F.C	
											Sam	nples			
Depth (m			De	scription			Legend	Elevation	Depth (m	Ref. Number	Sample Type	Depth (m)	Recovery	Field Test Results	Standpipe Details
- 0	MAD	E GROU	ND (Com	vrised of CL	804 stone	fill)		73.02	0.30						
	Light Stiff t	brown s to very st some col	andy SILT, iff dark bro bbles and	CLAY with o wn sandy s occasional b	occasional ilty gravelly	l gravel y CLAY		72.62	0.70						
- - - - -										AA171722	B	1.00		N = 24 (4, 6, 6, 7, 5, 6)	
	Obst	ruction						71.42	1.90	_				N = 50/75 mm (25, 50)	
		TRATA B	ORING/CH	IISELLING			Wate	er Ca	sing	Sealed	Rise	e T	v ime	VATER STRIKE DE	TAILS
Fro	m (m)	To (m)	(h)	Comments			Strik	e De	epth	At	To	e 1 (r	nin)	Comments	
1	1.7	1.9	1.5				1.50) 1	.50	No	No		20	Seepage	005555
2									Hole	Costa		مغام ا	GF	KOUNDWATER PR	UGRESS
	Date	Tip De	ETAILS	p RZ Base	ту	pe	Dat	te	Hole Depth	Depth	De W	pth to ater	Comme	ents	
	MARK	S Locati dug in	on scanne spection p	d using CA1	[cable av t	oidance t	ool] with h	and	Sam D - Sma B - Bulk LB - Lar Env - Er	Il Disturbed (tub) Disturbed (tub) Disturbed ge Bulk Disturbe wironmental Sar	d) ed mple (Jar +	+ Vial + Tub)	UT - Sam P - L W - '	Undisturbed 100mm Diameter Iple Judisturbed Piston Sample Water Sample	



REPORT NUMBER

		/															
co	NTRAC	CT Da	ata Centre F	Projects 3 -	Profile Park								BOREH SHEET	IOLE	NO.	BH04 Sheet 1 of 1	
CO GR	-ordii Ound	NATES	703,8 730,7 m AOD)	51.21 E 67.13 N 73.52	RIG BOR BOR	TYPE REHOL REHOL	LE DIAM	ETE H (m	R (m ı)	m) 2	Dando 20 200 2.00	00	DATE (IENC LETE	ED 14/07/2022 ED 14/07/2022	
		F1 R Ba	Enzo Prop	erties	SPT	HAM	MER REI	F. NO	Э.				BORE) BY	BY	W.Cahill	
		(1(0						/ 0)				Sam	noles	LOOLL		1.0	
Depth (m)			Des	scription			Legend		Elevation	Depth (m)	Ref. Number	Sample Type	Depth		Recovery	Field Test Results	Standpipe Details
	Very occa:	stiff dark sional co ruction of Boreho	brown san bbles	dy silty grav	/elly CLAY with			72.	02	1.50	AA171721	В	1.00			N = 15 (3, 4, 4, 3, 4, 4) N = 50/75 mm (25, 50)	
HA	RD ST	RATA B	ORING/CHI	SELLING								D .			WA	TER STRIKE DET	AILS
Fror	n (m)	To (m)	(h)	Comments			Wate	er	Cas Dei	ing S oth	At	Ris To	e .	I Ime (min)	Co	omments	
1	.8	2	1.5												N	lo water strike	
<u>}</u>											Casing	De	nth to		GRO	UNDWATER PRO	GRESS
INS	TALLA Date	Tip De	pth RZ Top	RZ Base	Туре		Dat	te		epth	Depth	W	pth to ater	Com	ment	ts	
	MARK	b Location dug inst	on scanned spection pit	using CAT carried out	[cable avoidan	ice too	ol] with h	and	1	D - Small B - Bulk D LB - Large Env - Env	Le Legen Disturbed (tub) Disturbed Bulk Disturbe ironmental San	d d nple (Jar +	⊦ Vial + Tub	L	JT - Und Sample P - Undis V - Wate	listurbed 100mm Diameter sturbed Piston Sample er Sample	

\IGSL/

REPORT NUMBER

7	205	/												
CON	NTRAC	T Da	ata Centre	Projects 3 -	Profile Park						BOREH SHEET	IOLE NO	0. BH05 Sheet 1 of	1
CO- GRO	ordin Dund L	ATES _EVEL (I	703, 730, m AOD)	826.61 E 726.78 N 73.11	RIG TY BOREH BOREH	PE IOLE DIAM IOLE DEPT	ETER (I H (m)	mm)	Dando 20 200 1.90	000	DATE O	COMME	NCED 13/07/2022 ETED 13/07/2022	
CLIE	ENT SINEER	F1 Ra	Enzo Pro Imboll	perties	SPT HA	MMER RE	F. NO. %)				BORED PROCE) BY SSED E	W.Cahill BY F.C	
_										San	nples			0
Depth (m			De	escription		Legend	Elevation	Depth (m	Ref. Number	Sample Type	Depth (m)	Recovery	Field Test Results	Standpipe Details
	Stiff to with sr Obstru End o	o very sti ome cob uction f Boreho	iff dark bro bles and ble at 1.90	own sandy gi boulders	ravelly silty CLAY		71.41	1.70	AA171723	в	1.00		N = 23 (4, 5, 5, 6, 5, 7) N = 50/75 mm (25, 50)	
HA	RD STI	RATA B	ORING/CH	ISELLING								V	NATER STRIKE DE	TAILS
From	n (m)	To (m)	Time (h)	Comments		Wate	er Ca	asing epth	Sealed At	Ris To	e (Time min)	Comments	
1.	.7	1.9	1.5					<u> </u>					No water strike	
								11.2				G	ROUNDWATER PR	OGRESS
INS ⁻	TALLA Date	TION DE	PTAILS	p RZ Base	Туре	Dat	te	Hole Depth	Casing Depth	De W	pth to ater	Comm	ents	
REN	MARKS	Locatio dug ins	on scanne spection p	d using CAT it carried out	[cable avoidance	tool] with h	and	Samp D - Small B - Bulk LB - Larg Env - Env	Die Legen Disturbed (tub) Disturbed ge Bulk Disturbee vironmental Sar	d) mple (Jar -	+ Vial + Tub)	UT - Sam P - U W -	- Undisturbed 100mm Diameter nple Undisturbed Piston Sample Water Sample	

\IGSL/

REPORT NUMBER

~		/															
со	NTRAC	CT Da	ata Centr	e Projects 3	- Profile Pa	ark							Boreho Sheet	OLE NO	0.	BH06 Sheet 1 of 1	
CO GR	-ordii Ound	NATES LEVEL (703 730 m AOD)	3,762.42 E),688.71 N 73.11		RIG TYP BOREHO BOREHO	'E DLE DIAM DLE DEPT	ETER (Ἡ (m)	mm)	2 2 2	0ando 20 200 2.10	00	DATE CO DATE CO	OMME OMPLE	NCEI) 15/07/2022) 15/07/2022	
CLI	ENT	F1	Enzo Pr	operties		SPT HAI		F. NO.					BORED	BY		W.Cahill	
ENG	SINEE	K Ra	amboll			ENERGY	r Ratio (S	%) 	_			Sam	PROCE	SSEDE	3Y	F.C	
Depth (m)			C	escription			Legend	Flevation		Depth (m)	Ref. Number	Sample Type	(m)	Recovery		Field Test Results	Standpipe Details
	Firm grave	stiff dark stiff dark cobbles	wn sandy	andy silty gra	avelly CLA	Y with		71.91	1.	20	AA171726	В	1.00			N = 17 (4, 4, 3, 4, 4, 6) N = 50/75 mm (25, 50)	
HA	RD ST	RATA B	ORING/C	HISELLING										V	NATE	R STRIKE DET	AILS
Fror	n (m)	To (m)	1 ime (h)	Comments	s		Wate Strik	er Ca e_ D	asıng)epth	s	At	Rise To	e Ti (n	ıme nin)	Com	iments	
							1.90)	1.90		No	No		20	Se	epage	
									11-1		Casim			G	ROUI	NDWATER PRO	GRESS
INS	TALLA Date	Tip De	ETAILS	op RZ Bas	e Ty	pe	Dat	ie	Hole Dept	e th	Casing Depth	De W	oth to ater	Comm	ents		
REI	MARK	S Location	on scann spection	ed using CA pit carried or	T [cable av	voidance te	ool] with h	and	Sa D - B - LB En	Small I Small I Bulk Di - Large v - Envir	e Legeni Disturbed (tub) isturbed Bulk Disturber ronmental Sam	d d nple (Jar +	+ Vial + Tub)	UT - San P - I W -	- Undistu nple Undistur Water S	urbed 100mm Diameter bed Piston Sample Sample	

Appendix 3

Rotary Core Drillhole Logs & Photographs



REPORT NUMBER

	\sim	/																
со	NTR	ACT	D	ata (Centre Pro	ojects 3 -	Profi	le Par	k				DRII SHE	LHOLE	E NO	RC She	D1 et 1 of 1	
CO GR			TES	<u>(m</u> O	703,829 730,853 D)	9.90 E 3.84 N <u>73.</u> 76			RIG TYPE FLUSH		BT-44 Air/Mi	l st	DAT DAT	E COMI E COMI		D 10/0 D 11/0	8/2022 8/2022	
CL EN	ient Gine	ER	F	1 En lamb	zo Propei oll	rties			INCLINATION CORE DIA	ON (deg) METER (m	-90 m) 78	51	DRI	LED B	Y Y	IG D	iSL - JK .O'Shea	
Downhole Depth (m)	Core Run Depth (m)	T.C.R.%	S.C.R.%	R.Q.D.%	Frac Spac Lc (mi	ture cing og m) 500	Non-intact Zone	Legend			Descrip	tion			Depth (m)	Elevation	Standpipe Details	SPT (N Value)
- 1	3.00								SYMMETI as returns SYMMETI as returns	RIX DRILL of CLAY RIX DRILL of clayey (ING: No red ING: No red GRAVEL	covery, ob: covery, ob:	served by o	driller driller	1.50	72.26		
- 3	4.50	100	50	18					Very stron thinly lami grey/black limestone calci-siltite stylolites, very locall mudstone 7.31-7.350	g to mediu nated whe s, fine-grain grading re limestone pyrite prese y moderate /shale zone m).	m strong, t re fissile m ned, LIMES gularly (eve with subor ent), slight ely weather es at (3.59-	hickly to th udstone/sh TONE (arg ery approx dinate MU y weathere ed at fissil 3.64m, 6.4	inly bedde nale), grey/ gillaceous 0.10-0.50r IDSTONE, ed where ir e 42-6.45m 8	d (to dark n) into local itact,				
- 5	6.00	100	86	76					Discontinu locally rou tight to loc locally call locally 70°	uities are w ligh, planar cally moder cite-veined	idely to clo to locally c ately open, (1-12mm t	sely space urviplanar locally cla hick). Dips	ed, smooth Apertures ay smeared are 30-40	to are , ° &				
- 7	7.50	100	81	67		6	09.9999											
- 8	9.00	100	91	88		1(070										0 0 0 0 0 0 0 0 0	
(22	10.00	100	91	61							140.00				10.00	63.76	0 0 0 0	
≝ RE	IVIAR	KS	0.00	0.00					End	Water	e at 10.00 n	Sealed	Piec	Time	WA	IER ST	RIKED	ETAILS
4188.GPJ IGSL.GDT	le ca:	sed ().00-(3.00r	n.					Strike	Depth	Sealed At	To	(min)	Co N	mmen o wate	ts er strike	recorded
	TA1	ידאו								Data	Hole	Casing	Depth t	0 000				
	Date -08-2	22	<u>Tip D</u> 10.0	epth	RZ Top 1.00	RZ Base 10.00		Typ 50mi	e m SP	11-08-22	Depth 10.00	<u>Depth</u> 3.00	Water 8.80	Wate drillir	r level re ng.	s corded 5	mins after	end of
∠∟							1						1					



REPORT NUMBER

	\sim	/																
CO	NTR	ACT	D	ata (Centre Pro	ojects 3 -	Profi	ile Par	rk				DRIL SHE	.lhole et	NO	RC She	02 et 1 of 1	1
CO-				(mO)	703,864 730,84	4.31 E 7.41 N 74 20			RIG TYPE		BT-44	ļ.	DAT			D 09/0	8/2022	
				1 En	zo Propo	74.20			FLUSH		Air/M	st			/			
ENG	GINE	ER	R	ambo	20 FTOPEI oll	lies			CORE DIA	ON (deg) METER (m	-90 m) 78		LOG	GED B	Y	D	O'She	a
_	_				<u> </u>						, , , , ,		1-00		-			
Downhole Depth (m	Core Run Depth (m	T.C.R.%	S.C.R.%	R.Q.D.%	Frac Spac Lc (mi	ture cing og m) 500	Non-intact Zone	Legend			Descrip	tion			Depth (m)	Elevation	Standpipe Details	SPT (N Value)
. 0									SYMMETI	RIX DRILL	ING: No re	covery, obs	served by c	driller				
-									as returns	of CLAY								
																	\mathbb{S}	
1																		
															1 50	72 70		
									SYMMET	RIX DRILL	ING: No re	covery, obs	served by c	Iriller	1.00	12.70	ľΞΊ	
								°₽	as returns	of clayey	GRAVEL						°∃°	
2																	₀⊟₀	
								$\frac{2}{2}$									LE.	
	3.00							0-7	SYMMETI		ING: No re	covery obs	served by c	Iriller	2.80	71.40	ľΞΊ	
3	0.00					Z	\$λ/		as returns	of ROCK				/			°₿°	
							\ 4 λ /		Very stron	ig to mediu	im strong, i re fissile m	nedium to udstone/sh	thinly bedo	led (to dark			∘∃∘	
		100	62	48					grey/black	, fine-grain	ned, LIMES	TONE (arg	illaceous	Jan			₀∃₀	
4									limestone calci-siltite	grading re limestone	gularly (eve with subo	ery approx dinate MU	0.10-0.50r DSTONE	n) into local				
	4.50					-			stylolites,	pyrite pres	ent), slightl	y weathere	d where in	tact,			ГЩ	
						F			mudstone	y moderate /shale zon	ely weather es at (4.52·	ed at fissile 4.56m & 5	e .95-6.00m)				°∃°	
5							άλ/		Many incip	pient fractu	ires throug	nout.	,				• =•	
		100	66	59					Discontinu	uities are n	nedium to c	losely spac	ced, smoot	h to			。目。	
									locally rou	igh, planar ally mode	to locally c	urviplanar. locally cla	Apertures	are led (
	6.00					_ =			at 3.23-3.0	39m), loca	ally calcite-	eined (1-1	0mm thick). Dips			ГЕ́І	
3									are 30-40	& locally	70°.						°∃°	
					Г	K-											o <u>∃</u> o	
		100	61	30													。目。	
'																		
	7.50																ľВ	
						F											°₿°	
3						4											₀₿₀	
		100	65	47			NA XA										。 目。	
						N. 1	a: 17N											
,	9.00	<u> </u>	<u> </u>	-		E											°₿°	
-						+											°₽	
		100	78	69		ı F											。 目 。	
	10.00														10.00	64.20	1日	
REI	MAR	KS		2 00-	~				End	ot Borehole	e at 10.00 r	n Sealed I	Rise	Timo	WAT	TER ST	FRIKE 	DETAILS
-101	e ca	seu (5.00-0	3.UUI						Strike	Depth	At	То	(min)	Co	mmen	ts	roordad
																U Wale	TI SUIKE	
_											·				GRO		VATER	DETAILS
NS	TAL	LATI		ETA	ILS					Date	Hole	Casing	Depth t	O Con	nment	S		
	Date	-	Tip D	epth	RZ Top	RZ Base		Тур)e	10-08-22	10.00	3.00	8.80	Wate	r level re	corded 5	i mins afte	er end of
10	-08-2	22	10.0	00	1.00	10.00		50m	m SP					ariiin	y.			



REPORT NUMBER

СО	NTR/	ACT	D	ata C	Centre Pro	ojects 3 -	Prof	ile Par	rk				DRIL		NO	RC	03	2
co	-ORE		TES		703,78 730,779	4.97 E 9.34 N			RIG TYPE		BT-44		DATI			D 15/0	8/2022	2
CL	IENT GINE		F R	1 En: ambo	zo Propei bli	73.32 rties			FLUSH INCLINATION CORE DIAI	ON (deg) METER (m	Air/Mi -90 m) 78	st	DAII	LED B	(((<u>16/0</u> וס D	8/2022 SL - J .O'She	<u> </u>
Downhole Depth (m)	Core Run Depth (m)	T.C.R.%	S.C.R.%	R.Q.D.%	Frac Spac Lc (mi	:ture cing 9g m) 500	Non-intact Zone	Legend			Descript	tion			Depth (m)	Elevation	Standpipe Details	SPT (N Value)
- 0									SYMMETI as returns	RIX DRILL of clayey	ING: No rec	overy, obs	erved by d	riller	3.00	70.32		
- 4	3.50 4.50	100	8	0	E-				Very stron thinly lami grey/black limestone calci-siltite	g to mediu nated whe fine-grain grading re limestone	im strong, the re fissile muned, LIMES ingularly (even with subor	nickly to thi udstone/sha TONE (argi ery approx (dinate MUI	nly beddeo ale), grey/o illaceous).10-0.50n OSTONE,	l (to lark n) into ocal	3.50	69.82	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
5	5.50	100	34	12		-			Many incip	y moderate /shale zon pient fractu	ent), slightly ely weather es at (5.50- ires through	-5.64m & 7 out.	.05-7.10m).				
- 6	6.50	100	53	22					locally rou tight to loc locally cale subhorizor	gh, planar ally moder cite-veinec ntal, 30-40	to locally curves rately open, I (1-70mm t ° & locally 7	locally clay hick). Dips	Apertures smeared are	are			0 0 0 0 0 0	
- 7	8.00	100	63	29			/										0 0 0 0 0 0	
22 • • • • • • • • • • • • • • • • • • •	9.50	100	85	74			330											
	MAR le cas	KS sed ()	0.00-3	3.50r	n.					Water	Casing	Sealed	Rise	Time	WA	TER S		DETAILS
CGPJ IGSL.GD1				2.001						Strike	Depth	At	To	(min)	N	o wate	ıs er strike	e recorded
24186															GRO		VATEF	DETAILS
	STAL	LATI	ON D	ETA	ILS					Date	Hole Depth	Casing Depth	Depth to Water	Com	nment	s		
IGSL RC F	Date -08-2	22	ip D 11.0	epth)0	RZ Top 1.00	RZ Base 11.00	9	Typ 50m	m SP									

/	A	$\overline{}$													R	EPORT		BER
	5/ GS	ر ل			C	GEOT	ECH	INIC	CAL COP	RE LOG	RECO	RD				2	418	8
со	NTR	ACT	D	ata C	Centre Pr	ojects 3	· Prof	le Pa	rk				DRIL	LHOLE	NO	RC	03	
со	-ORD	DINA ⁻	TES		703,78	4.97 E							SHE	ET		Shee	et 2 of	2
GR	OUN	DLE	VEL	(mOI	730,775))	9.34 N 73.32			RIG TYPE		BT-44		DAT	e comm E compi	ENCE	D 15/0	8/2022 8/2022))
CLI	ENT		F	1 Enz	zo Prope	rties			INCLINATI	ON (deg)	Air/Mi -90	st	DRIL	LED BY		IG	iSL - JI	ĸ
EN	GINE	ER	R	ambo	oll I				CORE DIA	METER (mr	n) 78		LOG	GED BY		D.	O'She	a
Downhole Depth (m)	Core Run Depth (m)	T.C.R.%	S.C.R.%	R.Q.D.%	Frac Spa Lc (m	ture cing bg m) 500	Non-intact Zone	Legend			Descript	ion			Depth (m)	Elevation	Standpipe Details	SPT (N Value)
- 10		100	90	68					-									
-							11											
11	11.00								End o	of Borehole	at 11.00 m	1			11.00	62.32		
-																		
- 10																		
12																		
13																		
- 14																		
15																		
16																		
- 47																		
17																		
-																		
18																		
19																		
-																		
RE	MAR	KS							I		<u> </u>	0	D.		WA	TER ST	RIKE	DETAILS
Hol	e cas	sed ().00-3	3.50n	n.					vvater Strike	Depth	At	Rise To	(min)	Co	mmen	ts	
															N	lo wate	er strike	e recorded
											Hole	Casing	Depth t		GRO	DUNDV	VATEF	DETAILS
INS	Date	LATI(DN D	ETAI	LS BZ Top	RZ Base	9	Tv)e	Date	Depth	Depth	Water	Com	ment	S corded 5	mins aft	er end of
16	-08-2	22	11.0	0	1.00	11.00	-	50m	im SP	10-00*22	11.00	0.00	0.10	drilling			io all	



REPORT NUMBER

СС	ONTR	ACT	D	ata (Centre Pro	ojects 3 -	Profile	e Park	κ				DRII	LHOLE	NO	RC	04	
СС	-ORE	DINA	TES		703,85	1.21 E							SHE	ET		She	et 1 of	1
GF	OUN	ID LE	VEL	(mOl	730,76 ⁻ D)	7.13 N 73.52			RIG TYPE FLUSH		BT-44 Air/M	1 ist	DAT	E COMR		011/0 12/0 ס	8/2022 8/2022	
CL	IENT		F	1 En	zo Prope	rties			INCLINATI	ON (deg)	-90	51	DRI	LED B	(IG	SL - JI	<
EN	GINE	ER	R	ambo					CORE DIA	METER (m	m) 78		LOG	IGED B		D.	.O'She	a
Downhole Depth (m)	Core Run Depth (m)	T.C.R.%	S.C.R.%	R.Q.D.%	Frac Spac Lc (mi	ture cing g m)	Non-intact Zone	Legend			Descrip	tion			Depth (m)	Elevation	Standpipe Details	SPT (N Value)
- 0									SYMMETH as returns		ING: No re	covery, ob	served by o	driller				
- 1									SYMMETH as returns	RIX DRILL of gravelly RIX DRILL	ING: No re / CLAY ING: No re	covery, ob	served by o	driller	<u>1.50</u> 2.40	72.02		
Ē	3.00						F		as returns of ROCK						3.00	70.52		
- 3	4.50	100	29	25					Very stron thinly lami grey/black limestone calci-siltite stylolites, very locall mudstone, 5 76-5 78	g to mediu nated whe , fine-grain grading re limestone pyrite pres y moderate /shale zon m 6.06-6.0	im strong, f re fissile m hed, LIMES gularly (ev with subo ent), slightl ely weather es at (3.42)9m, 7, 23-7	hickly to th udstone/sl TONE (arg ery approx dinate ML y weathere ed at fissil -3.48m, 5.	inly bedde nale), grey/ gillaceous 0.10-0.50r IDSTONE, ed where ir e 28-5.31m, 5-8 17m &	d (to dark n) into local itact,				
- 5	6.00	100	59	37					9.65-9.67r Many incip Discontinu locally rou tight to loc locally cale	n). pient fractu uities are w gh, planar ally moder cite-veinec	ridely to clo to locally c ately open I (1-10mm	nout. sely space urviplanar , locally cla thick). Dips	ed, smooth Apertures ay smeared s are 30-40	to are , ° &			0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
- 7	7.50	100	74	53		67			locally sub	ohorizontal	& 70°.						0 0 0 0 0 0	
8	9.00	100	83	47	È												0 0 0 0 0 0 0 0	
/22 	10.00	100	82	71											10.00	63.52	0 0 0	
6/9 1 L L	REMARKS									f Borehole Water	e at 10.00 r	n Sealed	Rice	Timo	WA	TER ST	FRIKE I	DETAILS
4188.GPJ IGSL.GDT										Strike	Depth	At	To	(min)	Co N	mmen o wate	ts er strike	
	STAL	LATI		ETA	ILS					Date	Hole	Casing	Depth t	0 Con	ment	S		DETAILO
GSL RC FI	INSTALLATION DETAILS Date Tip Depth RZ Top RZ Base Typ 12-08-22 10.00 1.00 10.00 50mi							Type 50mn	e n SP	12-08-22	10.00	3.00	8.40	Wate	r level re g.	- corded 5	i mins afte	er end of



REPORT NUMBER

	\sim	/																	
со	NTR	ACT	D	ata (Centre Pro	ojects 3 -	Profi	ile Par	ŕk				DRII SHE	LHOLE	E NO	RC She	05 et 1 of 1	l	
CO-ORDINATES 703,826.61 E 730,726.78 N 730,726.78 N GROUND LEVEL (mOD) 73.11 CLIENT F1 Enzo Properties ENGINEER Bamboli									RIG TYPE		BT-44 Air/Mi	l st	DAT	E COMI E COMI		nenced 12/08/2022 Pleted 15/08/2022			
CLI	IENT GINE	ER	F	1 En ambo	zo Propei oll	rties			INCLINATION CORE DIAL	ON (deg) METER (m	-90 m) 78		DRI	LED B	Y Y	IG D	iSL - JK .O'Shea	(1	
Downhole Depth (m)	Core Run Depth (m)	T.C.R.%	S.C.R.%	R.Q.D.%	Frac Spac Lc (mi	ture cing g m)	Non-intact Zone	Legend	Description						Depth (m)	Elevation	Standpipe Details	SPT (N Value)	
2	3.00								SYMMETI as returns SYMMETI as returns Very stron thinly lami	RIX DRILLI of CLAY RIX DRILLI of gravelly RIX DRILLI of ROCK of ROCK in the diu nated whe	NG: No ree NG: No ree CLAY	covery, ob: covery, ob: covery, ob: nedium to udstone/st	served by o served by o served by o thinly bedo aale), grey/	driller driller driller led (to dark	1.50 2.70 3.00	71.61 70.41 70.11			
- 4	4.50	100	44	44					grey/black limestone calci-siltite stylolites, very locall mudstone 5.53-5.56i 9.15-9.19i Many incip Discontinu	k, fine-grain grading re b limestone pyrite prese y moderate /shale zone m, 5.96-6.0 m). oient fractu uities are m	ed, LIMES gularly (eve with subor ent), slightl sly weather es at (3.44 0m, 6.23-6 res through redium to c	TONE (arg ery approx dinate MU y weathere ed at fissil -3.51m, 5. 3.28m, 6.72 nout.	gillaceous 0.10-0.50r IDSTONE, ed where ir e 37-5.40m, 2-6.75m & ced. smoot	n) into local itact,					
- - - - - - - - - - - - - - - - - - -	6.00	100	67	47					locally rou tight to loc locally cal	gh, planar cally moder cite-veined	to locally c ately open (1-7mm th	urviplanar. locally cla ick). Dips	Apertures y smeared are 30-40°	are , & 70°.					
- 8	9.00	100	81	61															
	10.00	100	81	61											10.00	63 11	° 0		
RE	MAR	KS	1				,		End	of Borehole	e at 10.00 r	n			WA	TER ST	RIKE D	ETAILS	
4188.GPJ IGSL.GDT 16	Hole cased 0.00-3.00m.									Water Strike	Casing Depth	Sealed At	Rise To	Time (min)		mmen o wate	ts er strike	recorded	
∾ Σ	l										Hole	Casino	Denth t	0 -	GRU		VAICH	DETAILS	
INS HC H 101	INSTALLATION DETAILS Date Tip Depth RZ Top RZ Base Type 15-08-22 10.00 1.00 10.00 50mm						ne m SP	Date 15-08-22	10.00 10.00	Depth 3.00	2.70	Wate drillir	nment er level re ng.	S corded 5	mins after	r end of			
<u>ଅ</u>																			



REPORT NUMBER

CON	TRA	СТ	D	ata (Centre Pro	ojects 3 -	Profi	ile Par	rk				DRII	LHOLE	NO	RC	06	
co-c	RDI	NAT	ES		703,762	2.42 E							SHE	ET		She	et 1 of	1
GRO	UND	LE۱	/EL	(mOl	730,688 D)	8.71 N 73.11			RIG TYPE FLUSH		BT-44 Air/Mi	st	DAT DAT	E COMN E COMP	IENCE LETEI	D 08/0 D 09/0	8/2022 8/2022	
		R	F	1 En: ambo	zo Propei	rties				ON (deg) METER (mi	-90 m) 78		DRI		(IG D	SL - JI	K
Ê	=										ing 70		200		•			a
Downhole Depth (r	Core Hun Deptn (n	T.C.R.%	S.C.R.%	R.Q.D.%	Frac Spac Lo (mi	ture cing 9g m) 500	Non-intact Zone	Legend			Descript	ion			Depth (m)	Elevation	Standpipe Details	SPT (N Value)
0									SYMMETI as returns	RIX DRILL	NG: No rec	overy, obs	erved by o	driller				
- 1																		
2																	0 0 0 0 0 0	
3									SYMMETI as returns	RIX DRILL	NG: No rec GRAVEL	overy, obs	erved by c	driller	3.00	70.11		
• 4 4.	20								SYMMETI as returns	RIX DRILL	NG: No rec	overy, obs	erved by o	driller	3.60 4.20	69.51	0	
5	70	00	67	29					Very stron thinly lami grey/black limestone calci-siltite stylolites, very locall mudstone	g to mediu nated when s, fine-grain grading re b limestone pyrite press y moderate (shale zone	m strong, n re fissile mu led, LIMES gularly (eve with subor ent), slightly ely weather se at (5.42	nedium to t udstone/sh TONE (arg ry approx dinate MUI weathere ed at fissile	thinly bedc ale), grey/ illaceous 0.10-0.50r DSTONE, d where in e	led (to dark n) into local itact,			0 0 0 0 0	
6 7 7.	20	00	59	45					Discontinu locally rou tight to loc	m, 8.58-8.6 pient fractu uities are m gh, planar ally moder cite-veined	nedium to cl to locally cu ately open, (1-20mm t	8.72m). out. osely spac urviplanar. locally clay hick). Dips	eed, smoot Apertures y smeared are 30-40	h to are , ° &				
8 8.	70	00	73	37			/ / /		70°.								0 0 0 0 0 0 0 0	
9	.00	00	75	51											10.00	63.11	0 0 0 0 0 0	
REMARKS									End	of Borehole	e at 10.00 m) Caalad	Diag	Time	WA	TER S	RIKE	DETAILS
Hole	Hole cased 0.00-4.20m.									vvater Strike 7.60	Depth 4.20	Sealed At N/S	кıse To	(min)	Co	ommen Slow	ts	
											Hole	Casing	Dopth +	0	GRO)UND	VATER	DETAILS
INST Da 09-0	ALL/ ate 8-22		ip De 10.0	eTA epth 0	RZ Top 1.00	RZ Base 10.00		Typ 50m	oe m SP	Date 09-08-22	10.00	United Search 19 19 19 19 19 19 19 19 19 19 19 19 19	2.90	Con Wate drillin	r level re g.	S corded 5	5 mins afte	er end of

RC01 Box 1 of 3 - 3.00-6.00m



RC01 Box 2 of 3 - 6.00-9.00m



RC01 Box 3 of 3 – 9.00-10.00m



RC02 Box 1 of 3 - 3.00-6.00m



RC02 Box 2 of 3 - 6.00-9.00m



RC02 Box 3 of 3 - 9.00-10.00m



RC03 Box 1 of 3 - 3.50-6.50m



RC03 Box 2 of 3 - 6.50-9.50m



RC03 Box 3 of 3 - 9.50-11.00m



<u>RC04 Box 1 of 3 – 3.00-6.00m</u>



RC04 Box 2 of 3 - 6.00-9.00m



RC04 Box 3 of 3 – 9.00-10.00m



RC05 Box 1 of 3 - 3.00-6.00m



RC05 Box 2 of 3 - 6.00-9.00m



RC05 Box 3 of 3 - 9.00-10.00m



RC06 Box 1 of 2 - 4.20-7.20m



RC06 Box 2 of 2 - 7.20-10.00m



Appendix 4

Dynamic Cone Penetrometer Records























Contract	t	Profile Park			Date:	15/07/2022		Test N	lo. 6
Client		Ramboll				Pooding	40	mm	
ocation	1	Profile Park, D	ublin 22		Dur zen		40		
Soil Des	n cripti	ion Grave	I (MADE GRC	DUND)	Approxin	nate Chainage	0	MBGL	
Vo of			Reading	No of	Total	Reading	No of	Total	Reading
Blows 0		Total Blows	40	Blows	Blows	mm	Blows	Blows	mm
1		1	70						
1		3	110						
1		4 5	120 130						
1		6	140						
1		8	160						
1 1		9 10	168 178						
5		15	200						
5		20 25	240						
5 5		30 35	260 270						
5		40	290						
5 5		45 50	320						
	는 Depth (m BGL) 	-50 100 150 200 250 300 0	10	20	• a No. of	0 40 Blows	•	50	60
		Depth range (r Blows	mm)			Penetration 178 11	mm / blow 16.18		
RRL RN	18:	Log10 (CBR) =	= 2.48-1.057*	Log10 (mm/	blow)				
	L	og10(CBR) =	1.202						
		CBR =	15.924						

















Appendix 5

Plate Bearing Test Records








































Appendix 6

Resistivity Survey

Profile Park Data Centre Co. Dublin Electrical Resistivity Testing

> Report Status: Draft MGX Project Number: 6631 MGX File Ref: 6631p-005.doc 29th of July 2022

Confidential Report To:

IGSL Unit F M7 Business Park Newhall Naas, Co. Kildare

Report submitted by: Minerex Geophysics Limited

Issued by:

Unit F4, Maynooth Business Campus Maynooth, Co. Kildare Ireland Tel.: 01-6510030 Fax.: 01-6510033 Email: info@mgx.ie Hartmut Krahn (Senior Geophysicist)



Subsurface Geophysical Investigations

CONTENTS

	INTRODUCTION1
1.1	Background1
1.2	Objectives1
1.3	Site Description1
1.4	Report1
2.	TESTING ON SITE
2.1	Methodology
2.1 2.2	Methodology 2 Measurements 2
2.1 2.2 2.4	Methodology 2 Measurements 2 Site Work 3
2.1 2.2 2.4 3 .	Methodology 2 Measurements 2 Site Work 3 RESULTS 4

List of Tables, Maps and Figures:

Title	Pages	Document Reference
Table 1: VES Ground Resistivity Testing Results	4 x A4	6631p-Tab1.xls
Table 2: Soil Resistivity Testing Results	4 x A4	6631p-Tab2.xls
Map 1: Location Map	1 x A3	6631p_Map.dwg
Figure 1: Resistivity Testing using the Wenner Array	In Text	In Text

1. INTRODUCTION

1.1 Background

Minerex Geophysics Ltd. (MGX) carried out Resistivity Testing using the Wenner electrode configuration with two different methods for the Profile Park Data Centre in Kilcarbery. The survey was commissioned by IGSL who are the main ground investigation contractor for the project. Two deep vertical electrical sounding (VES) and 2 shallow soil resistivity (SR) tests were carried out. The coordinate system used on this site was Irish Transverse Mercator (ITM).

The test sequence was conducted as part of the overall ground investigation programme for the development of the data center. The purpose of the survey was to provide information to be used in the design and construction phases of the project.

These tests are conducted in order to increase the knowledge of the resistivity of the soil and rock and to assist with the design and installation of earthing systems and underground cabling systems. Soil resistivity depends on a number of factors like soil type, mineral content, temperature, moisture, salt content and compaction.

The methodology specified here encompasses onsite in-situ measurements and the presentation of the results, but does not include the design of the earthing or cabling system.

1.2 Objectives

The main objective of the geophysical survey was:

• To determine the electrical resistivity at a range of depths for each location

1.3 Site Description

The site is shown on Map 1 and the area consists of agricultural land.

1.4 Report

This report includes a location map of the resistivity testing locations and two tables of results. The client provided maps of the site and the digital versions were used as the background map in this report.

The indirect nature and the non-invasive survey methods must be taken into account when considering the results of this survey and Minerex Geophysics Limited, while using appropriate practice to execute the measurements and to present the data, give no guarantees in relation to the existing subsurface.

2. TESTING ON SITE

2.1 Methodology

The methodology consisted of using Vertical Electrical Sounding (VES) and Soil Resistivity (SR) in the Wenner electrode configuration at a range of electrode spacing agreed with the client prior to the fieldwork. The increase in the electrode spacing leads to an increase in the depth.

Two different electrical resistivity tests were used:

1 VES - Vertical Electrical Sounding – Deep

Objective:	Determine the resistivity for ground, soil and rock to a depth around 50m below ground level
	(bgl) and also as two tests in two directions (check for anisotropy).

- Purpose: This test is generally done to deliver values for the design of an earthing or grounding system
- Test Method: Four probe array in Wenner electrode configuration with expanding electrode spacing

Spacings: 1, 2, 3, 4, 5, 7, 10, 15, 20, 30, 40 and 50m

- Directions: There are two tests done at each location in two orthogonal directions
- Instrument: Tigre Resistivity Meter (high power)

Comment: This test includes the 'Soil Resistivity Test – Shallow' intrinsically

2 SR - Soil Resistivity Test – Shallow

- Objective: Determine the shallow soil around 1 3m bgl. In one direction
- Purpose: This test is generally done to deliver values for the design of the cable system
- Test Method: Four probe array in Wenner electrode configuration with three electrode spacings

Spacings: 1, 2 and 3m

- Directions: The test is done in one direction
- Instrument: Tigre or Megger Resistivity Meter

2.2 Measurements

Two Vertical Electrical Soundings were conducted at one location on the site.

All measurements were acquired in accordance with Minerex Geophysics Ltd. procedures, protocols, QC procedures and in compliance with appropriate IEEE and British Standards. The relevant IEEE standard is Std 81-2012 Part 1 – Guide to Measuring Earth Resistivity, Ground Impedance, and Earth Surface Potentials of Ground Systems (IEEE Std 81-2012) for the resistivity testing (IEEE Std81, 2012).

The Vertical Electrical Sounding (VES) and the soil resistivity (SR) was conducted using a Tigre Resistivity Meter with variable current input, a suite of four cables and four stainless steel electrodes. This 'four probe array' is called a Wenner Array as the spacing (A) between the four electrodes was the same for each measurement. At each electrode spacing, the test resistance in Ohms (Ω) was recorded in a detailed field sheet for later office-based computing of ground resistivities.

Figure 1: Resistivity Testing using the Wenner Array.



2.3 Testing Equipment

All equipment used was portable and intrinsically safe. The methods were non-destructive and non-intrusive. Only low voltage power requirements of 12 Volts or less were needed on site and were supplied by batteries. The following equipment was used:

- An ALLIED Tigre Resistivity Meter
- A suite of cables with 4 reels and distance marks for resistivity readings
- Stainless Steel Electrodes
- Measuring tapes
- Handheld GPS

Equipment checks and QC procedures were applied prior to the commencement of data acquisition.

2.4 Site Work

The data acquisition was carried out on the 27th of July 2022 in good weather conditions. Health and safety standards were adhered to at all times.

3. RESULTS

The recorded test resistance in Ω allows for the calculation of the resistivity value in Ω m for each individual electrode spacing.

The resistivity at a given electrode spacing was calculated using the following formula:

 $\rho = 2^*\pi * A * R$

Where;

- $\rho = \text{Resistivity in }\Omega m$
- $\pi = Pi = 3.141592$

A = electrode spacing in m

R = Measured Resistance value in Ω

The survey results with electrode spacing, resistances and resistivities are displayed in Table 1 for the VES and in Table 2 for the SR.

The resistivity values recorded at given electrode spacing can be allocated to approximate depth values. For the Wenner array the average resistivity taken at a particular A-spacing is equal to the average resistivity for a depth range between the ground surface and the A-spacing. Therefore, the average resistivity value recorded in the last column of Table 1 and 2 corresponds to the depth range between 0m bgl and the value in the first column. The depth mentioned in this report is given for visualisation purpose but may change when using the resistivity values in the design of the earthing system.

4. **REFERENCES**

 IEEE Std81, 2012. IEEE Std. 83-2012. IEEE Guide for Measuring Earth Resistivity, Ground Impedance, and Earth Surface Potential of a Ground System. IEEE Power and Energy Society. The Institute of Electrical and Electronics Engineers Inc.

Location:	Direction:	ITM Coordinates East:	ITM Coordinates North:	Elevation:	Date:
Location.	Direction.	TIM COORDINALES LASI.	TTW Coordinates North.		Date.
VES 1	N-S	703849	730812	73.67 mOD	27/07/2022
Wenner Electrode Spacing a (m)	Inner Electrode P Distance to Centre (m)	Outer Electrode C Distance to Centre (m)	Total Distance (m)	Measured Resistance (Ω)	Apparent Resistivity (Ωm)
1	0.5	1.5	3	13.11	82
2	1	3	6	7.16	90
3	1.5	4.5	9	5.455	103
4	2	6	12	5.012	126
5	2.5	7.5	15	4.487	141
7	3.5	10.5	21	3.771	166
10	5	15	30	2.874	181
15	7.5	22.5	45	2.127	200
20	10	30	60	1.643	206
30	15	45	90	1.217	229
40	20	60	120	1.018	256
50	25	75	150	0.819	257

Table 1: VES Ground Resistivity Testing Results

Location:	Direction:	ITM Coordinates East:	ITM Coordinates North:	Elevation:	Date:
Location.	Direction.	The obordinates Last.	The Coordinates North.	Elevation.	Bate.
VES 2	E-W	703849	730812	73.67 mOD	27/07/2022
Wenner Electrode Spacing a (m)	Inner Electrode P Distance to Centre (m)	Outer Electrode C Distance to Centre (m)	Total Distance (m)	Measured Resistance (Ω)	Apparent Resistivity (Ωm)
1	0.5	1.5	3	12.1	76
2	1	3	6	7.341	92
3	1.5	4.5	9	5.748	108
4	2	6	12	5.062	127
5	2.5	7.5	15	4.528	142
7	3.5	10.5	21	3.791	167
10	5	15	30	3.005	189
15	7.5	22.5	45	1.996	188
20	10	30	60	1.744	219
30	15	45	90	1.452	274
40	20	60	120		Fence
50	25	75	150		Fence

Table 1: VES Ground Resistivity Testing Results

Test Name:	Elevation:	ITM Coordinates East:	ITM Coordinates North:	Date:	Instrument:
SR1	74.12 mOD	703864	730845	27/07/2022	Tigre
Wenner Electrode Spacing a (m)	Inner Electrode P Distance to Centre (m)	Outer Electrode C Distance to Centre (m)	Total Distance (m)	Measured Resistance (Ω)	Apparent Resistivity (Ωm)
1	0.5	1.5	3	10.38	65
2	1	3	6	5.657	71
3	1.5	4.5	9	4.507	85
Test Name:	Elevation:	ITM Coordinates East:	ITM Coordinates North:	Date:	Instrument:
Test Name: SR2	Elevation: 73.3 mOD	ITM Coordinates East: 703825	ITM Coordinates North: 730755	Date: 27/07/2022	Instrument: Tigre
Test Name: SR2 Wenner Electrode Spacing a (m)	Elevation: 73.3 mOD Inner Electrode P Distance to Centre (m)	ITM Coordinates East: 703825 Outer Electrode C Distance to Centre (m)	ITM Coordinates North: 730755 Total Distance (m)	Date: 27/07/2022 Measured Resistance (Ω)	Instrument: Tigre Apparent Resistivity (Ωm)
Test Name: SR2 Wenner Electrode Spacing a (m) 1	Elevation: 73.3 mOD Inner Electrode P Distance to Centre (m) 0.5	ITM Coordinates East: 703825 Outer Electrode C Distance to Centre (m) 1.5	ITM Coordinates North: 730755 Total Distance (m) 3	Date: 27/07/2022 Measured Resistance (Ω) 11.09	Instrument: Tigre Apparent Resistivity (Ωm) 70
Test Name: SR2 Wenner Electrode Spacing a (m) 1 2	Elevation: 73.3 mOD Inner Electrode P Distance to Centre (m) 0.5 1	ITM Coordinates East: 703825 Outer Electrode C Distance to Centre (m) 1.5 3	ITM Coordinates North: 730755 Total Distance (m) 3 6	Date: 27/07/2022 Measured Resistance (Ω) 11.09 4.992	Instrument: Tigre Apparent Resistivity (Ωm) 70 63

Table 2: Soil Resistivity Testing Results



Appendix 7

Groundwater Monitoring Records

Project No.	24188		GROUNDW	ATER MON	ITORING DA	ATA SHEET		IGSL Ltd
Project: Engineer:	Profile Park							
Exploratory Hole No.	Hole Depth (m bgl)	Response Zone Top (m bgl)	Response Zone Base (m bgl)	Groundwater Level (m bgl) 31/08/2022	Groundwater Level (m bgl)	Groundwater Level (m bgl)	Comments	
RC01 RC02 RC03 RC04 RC05 RC06	10.00 10.00 11.00 10.00 10.00	1.00 1.00 1.00 1.00 1.00	10.00 10.00 10.00 10.00 10.00	2.77 2.56 2.03 1.87 1.67 1.77				
Remarks:	Water levels r	measured using ele	ctric dipmeter					

BH - denotes cable percussion borehole RC - denotes rotary core drillhole

Appendix 8

Geotechnical Laboratory Results (Soil)

IGSL Ltd Materials Laboratory Unit J5, M7 Business Park Newhall, Naas Co. Kildare 045 846176 Report No. R137530 Contrac Customer Ramboll Samples Received: 15/08/22 Date Te				Contract Date Tes	Deter Tested in No. sted:	rmination accordance 24188 (4) 15/08/22	T of Moistu	est Rep ure Conte 377:Part 2 Contract N	oort ent, Liqui 1990, clau Name:	d & Plast uses 3.2, 4. Profile Pa	ic Limits 3, 4.4 & 5.3 rk - Date C	3** entre Site	4	DETAILED IN SCOPE REG NO. 1331
BH/TP*	Sample No.	Depth* (m)	Lab. Ref	Sample Type*	Moisture Content %	Liquid Limit %	Plastic Limit %	Plasticity Index	% <425µm	Preparation	Liquid Limit Clause	Classification (BS5930)	Description	
BH01	AA171725	1.0	A22/4606	B	14	38	18	20	63	WS	4.4	CI	Brown sandy gravelly CLAY	
BH02	AA171756	1.0	A22/4607	В	17	38	18	20	67	WS	4.4	CI	Brown slightly sandy, s	lightly gravelly, CLAY
BH03	AA171722	1.0	A22/4608	В	17	39	21	18	45	WS	4.4	CI	Brown sandy gravelly	CLAY
BH04	AA171721	1.0	A22/4609	В	15	34	17	17	70	WS	4.4	CL	Brown slightly sandy, g	ravelly, CLAY
BH05	AA171723	1.0	A22/4610	В	10	41	18	23	34	WS	4.4	CI	Brown sandy gravelly	CLAY
BH06	AA171728	1.0	A22/4611	В	20	39	18	21	69	WS	4.4	CI	Brown slightly sandy, s	lightly gravelly, CLAY
TP04	AA180433	0.8	A22/4616	В	10	37	20	17	48	WS	4.4	CI	Brown sandy gravelly	CLAY
TP07	AA180421	1.4	A22/4620	В	15	36	19	17	57	WS	4.4	CI	Brown sandy gravelly	CLAY
TP08	AA180424	0.7	A22/4621	В	11	36	17	19	63	WS	4.4	CI	Brown sandy gravelly	CLAY
TP09	AA180418	0.5	A22/4622	В	13	37	17	20	62	WS	4.4	CI	Brown sandy gravelly	CLAY
TP10	AA180439	0.5	A22/4623	В	12	39	18	21	64	WS	4.4	CI	Brown sandy gravelly	CLAY
TP10	AA180441	2.5	A22/4624	В	12	33	15	18	62	WS	4.4	CL	Grey slightly sandy, gr	avelly, CLAY
	Preparation:	WS - Wet sieved			Sample Type:	B - Bulk Distu	ırbed	Remarks:						
	Liquid Limit Clause:	AR - As received NP - Non plastic 4.3 Cone Penetro 4.4 Cone Penetro	meter definitive	method t method		U - Undisturb	ed	Results relate NOTE: **Thes Opinions and This report sha	only to the spe e clauses hav interpretations all not be repro	ecimen tested,ir e been superce are outside the oduced except ir	as received co ded by EN 178 scope of accre n fullwithout writ	ondition unless 92-1 and EN17 ditation. * deno ten approval fr	otherwise noted. 7892-12. otes Customer supplied om the Laboratory.	information.
			- 1- 5		Persons autho	rized to appro	ve reports			Approved	by		Date	Page
IG	SL Ltd M	aterials La	boratory			H Byrne (La	aboratory I	Manager)		AB	1 pm		05/09/22	1 of 1

		TEST REPORT etermination of Particle Size Distribution in accordance with: BS1377:Part2:1990, clause 9.2 & 9.5** (note: Sedimentation stage not accredited)					
particle	%		Contract No. 24188 Report No. R138016				
size	passing		Contract Name : Profile Park - Data Centre Site 4 Results relate only to the specimen tested in as received				
75	100		BH/TP*: BH02 condition unless otherwise noted. * denotes Customer				
63	100	CODDLES	Sample No.* AA171726 Lab. Sample No. A22/4607 supplied information. Opinions and interpretations are				
50	100		Sample Type: B outside the scope of accreditation.				
37.5	97		Depth* (m) 1.00 Customer: Ramboll This report shall not be reproduced except in full withour				
28	97		Date Received 15/08/2022 Date Testing started 15/08/2022 the written approval of the Laboratory.				
20	91		Description: Brown slightly sandy, slightly gravelly, CLAY				
14	88						
10	84	GRAVEL	Remarks Note: **Clause 9.2 and Clause 9.5 of BS1377:Part 2:1990 have been superseded by IS017892-4:2016.				
6.3	80						
5	78						
3.35	75						
2	71		90				
1.18	68						
0.6	64						
0.425	63	SAND					
0.3	61		⁸ 50				
0.15	57						
0.063	53						
0.037	47						
0.026	43						
0.017	37						
0.010	30	SIL I / CLAT					
0.007	25		0.0001 0.001 0.01 0.1 1 10 100				
0.005	20		CLAY SILT Sieve size (mm) SAND GRAVEL				
0.002	14						
			td Materiale Laboratory Approved by: Date: Page no:				
	IGSL LTO Materials Laboratory 05/09/22 1 of 1						
			Persons authorised to approve report: J Barrett (Quality Manager) H Byrne (Laboratory Manager				


		D Testec	TEST REPORT etermination of Particle Size Distribution in accordance with: BS1377:Part2:1990 , clause 9.2 & 9.5** (note: Sedimentation stage not accredited)	ISO 17025 ISO 17025 ACCREDITED TESTING DETAILED IN SCOPE REG NO. 1397			
particle	%		Contract No. 24188 Report No. R138015	-			
size	passing		Contract Name : Profile Park - Data Centre Site 4	Results relate only to the specimen tested in as received			
75	100		BH/TP*: BH06	condition unless otherwise noted. * denotes Customer			
63	100	CORRES	Sample No.* AA171726 Lab. Sample No. A22/4611	supplied information. Opinions and interpretations are			
50	100		Sample Type: B	outside the scope of accreditation.			
37.5	98		Depth* (m) 1.00 Customer: Ramboll	This report shall not be reproduced except in full without			
28	96		Date Received 15/08/2022 Date Testing started 15/08/202	2 the written approval of the Laboratory.			
20	90		Description: Brown slightly sandy, slightly gravelly, CLAY				
14	86						
10	84	GRAVEL	Remarks Note: **Clause 9.2 and Clause 9.5 of BS1377:Part 2:1990 have been superseded by IS017892-	4:2016 .			
6.3	82		8 <u>5</u> 2 3	പ			
5	81		0.0331.11	2 3.3 6.3 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7			
3.35	80						
2	78		90				
1.18	76		80				
0.6	73		§ 70				
0.425	72	SAND	60				
0.3	70						
0.15	65						
0.063	59						
0.037	49						
0.027	43		20				
0.017	38		10				
0.010	31	SILT/CLAY					
0.007	28	0.	0.0001 0.001 0.01 1	10 100			
0.005	24		CLAY SILT Sieve size (mm) SAND	GRAVEL			
0.002	17						
			Approved by:	Date: Page no:			
		IGSE L	to materials Laboratory	05/09/22 1 of 1			
	Persons authorised to approve report: J Barrett (Quality Manager) H Byrne (Laboratory Manager)						

		D Testec	TEST REPORT etermination of Particle Size Distribution in accordance with: BS1377:Part2:1990 , clause 9.2 & 9.5** (note: Sedimentation stage not accredited)	ISO 17025 NACREDIED TESTING DETAILED IN SCOPE REG NO. (1337)				
particle	%		Contract No. 24188 Report No. R138014	<u>.</u>				
size	passing		Contract Name : Profile Park - Data Centre Site 4	Results relate only to the specimen tested in as received				
75	100		BH/TP*: TP03	condition unless otherwise noted. * denotes Customer				
63	100	CODDLES	Sample No.* AA180429 Lab. Sample No. A22/4614	supplied information. Opinions and interpretations are				
50	100		Sample Type: B	outside the scope of accreditation.				
37.5	100		Depth* (m) 2.00 Customer: Ramboll	This report shall not be reproduced except in full without				
28	94		Date Received 15/08/2022 Date Testing started 15/08/2022	2 the written approval of the Laboratory.				
20	77		Description: Grey/brown clayey/silty, sandy, GRAVEL					
14	68							
10	52	GRAVEL	Remarks Note: **Clause 9.2 and Clause 9.5 of BS1377:Part 2:1990 have been superseded by IS017892-4	:2016 .				
6.3	37		8 0, 5 m - 2 03					
5	34		0.00.01.00.00.00.00.00.00.00.00.00.00.00	22 23 23 23 23 23 23 23 23 23 23 23 23 2				
3.35	32							
2	29		90					
1.18	26		a ⁸⁰	╶╂┈┼┼┼╫┼┼╴┾╱╫╫┼┨║╎				
0.6	23		8 70					
0.425	22	SAND	ig 60					
0.3	20							
0.15	19							
0.063	17							
		JIL I/ CLAT						
			0.0001 0.001 0.01 1	10 100				
			CLAY SILT Sieve size (mm) SAND	GRAVEL				
	1		Approved by:	Date: Page no:				
		IGSL L	td Materials Laboratory	05/09/22 1 of 1				
	Persons authorised to approve report: J Barrett (Quality Manager) H Byrne (Laboratory Manager)							



IGSL Ltd Materials Laboratory Unit J5,M7 Business Park Naas	Test Report Determination of Moisture Condition Value at Natural Moisture Content		IV ISO 17025 ACCREDIED TESTING			
Co. Kildare Tested in accordance		e with BS1377:Part 4:199	90, clause 5.4	DETAILED IN SCOPE REG NO. 1337		
Report No).	R138004		-		
Contract N	lo.	24188				
Contract N	lame:	Profile Park Data Cent	re Site 4			
Customer:		Ramboll				
BH/TP*		BH03				
Sample No	D.*	AA171722				
Depth* (m))	1.0m				
Sample Ty	vpe:	В				
Lab Samp	le No.	A22/4608				
Source* (if	applicable)	N/A				
Material Ty	ype* (if applicable):	В				
Sample Re	eceived:	15/08/22				
Date Teste	ed:	24/08/22 Not Provided				
Sample Ce	ert:					
Moisture C	Content (%):	17				
% Particles (By dry ma	s > 20mm iss):	50				
MCV:		9.4				
Interpretati	ion of Plot:	Steepest Straight Line				
Description	n of Soil:	Brown sandy gravelly S	SILT/CLAY			
Results relate only to the specimen teste Opinions and interpretations are outside * denotes Customer supplied information This report shall not be reproduced exce	ed, in as received condition unless other the scope of accreditation. n. pt in full without written approval from th	wise noted. ne Laboratory.	Persons authorised to a J Barrett (Q H Byrne (La	approve reports uality Manager) boratory Manager)		
		Approved by	Date	Page		
IGSL Ltd Mater	rials Laboratory	A Byene	05/09/22	1 of 1		

IGSL Ltd Materials Laboratory Unit J5,M7 Business Park Naas	Test Report Determination of Moisture Condition Value at Natural Moisture Content		re			
Co. Kildare 045 899324	Tested in accordance	e with BS1377:Part 4:199	90, clause 5.4	DETAILED IN SCOPE REG NO. 1331		
Report No	·).	R138003				
Contract N	ю.	24188				
Contract N	lame:	Profile Park Data Cent	re Site 4			
Customer:		Ramboll				
BH/TP*		BH01				
Sample No).*	AA171725				
Depth* (m))	1.0m				
Sample Ty	pe:	В				
Lab Sampl	le No.	A22/4606				
Source* (if	applicable)	N/A				
Material Ty	/pe* (if applicable):	В				
Sample Re	eceived:	15/08/22				
Date Teste	ed:	24/08/22				
Sample Ce	ert:	Not Provided				
Moisture C	content (%):	16				
% Particles (By dry ma	s > 20mm iss):	19				
MCV:		6.3				
Interpretati	ion of Plot:	Steepest Straight Line				
Descriptior	n of Soil:	Brown sandy gravelly S	SILT/CLAY			
Results relate only to the specimen teste Opinions and interpretations are outside * denotes Customer supplied informatior This report shall not be reproduced exce	ed, in as received condition unless othen the scope of accreditation. n. pt in full without written approval from th	vise noted. e Laboratory.	Persons authorised J Barre H Byrn	to approve reports tt (Quality Manager) e (Laboratory Manager)		
		Approved by	Dat	e Page		
IGSL Ltd Mater	rials Laboratory	A Byene	05/09	/22 1 of 1		

IGSL Ltd Materials Laboratory Unit J5,M7 Business Park Naas	Test Report Determination of Moisture Condition Value at Natural Moisture Content		ITE			
Co. Kildare 045 899324	Tested in accordance	e with BS1377:Part 4:199	90, clause 5.4	DETAILED IN SCOPE REG NO. 1331		
Report No	·).	R138005				
Contract N	ю.	24188				
Contract N	lame:	Profile Park Data Cent	re Site 4			
Customer:		Ramboll				
BH/TP*		BH05				
Sample No).*	AA171723				
Depth* (m))	1.0m				
Sample Ty	pe:	В				
Lab Sampl	le No.	A22/4610				
Source* (if	applicable)	N/A				
Material Ty	/pe* (if applicable):	В				
Sample Re	eceived:	15/08/22				
Date Teste	ed:	24/08/22				
Sample Ce	ert:	Not Provided				
Moisture C	content (%):	16				
% Particles (By dry ma	s > 20mm iss):	22				
MCV:		8.2				
Interpretati	ion of Plot:	Steepest Straight Line				
Descriptior	n of Soil:	Brown sandy gravelly S	SILT/CLAY			
Results relate only to the specimen teste Opinions and interpretations are outside * denotes Customer supplied informatior This report shall not be reproduced exce	ed, in as received condition unless other the scope of accreditation. n. pt in full without written approval from th	vise noted. e Laboratory.	Persons authorised J Barre H Byrr	d to approve reports ett (Quality Manager) e (Laboratory Manager)		
		Approved by	Da	te Page		
IGSL Ltd Mater	rials Laboratory	A Byene	05/09	9/22 1 of 1		

IGSL Ltd Materials Laboratory Unit J5,M7 Business Park Naas	Test Report Determination of Moisture Condition Value at Natural Moisture Content		ISO 17025 ACREDITO TESTING			
Co. Kildare 045 899324	Tested in accordance	e with BS1377:Part 4:199	90, clause s	5.4	DETAILED IN SCOPE REG NO. 1337	
Report No	-).	R138006				
Contract N	0.	24188				
Contract N	ame:	Profile Park Data Cent	re Site 4			
Customer:		Ramboll				
BH/TP*		TP02				
Sample No).*	AA180435				
Depth* (m))	0.70				
Sample Ty	pe:	В				
Lab Samp	e No.	A22/4612				
Source* (if	applicable)	N/A				
Material Ty	/pe* (if applicable):	В				
Sample Re	eceived:	15/08/22 24/08/22 Not Provided 13				
Date Teste	ed:					
Sample Ce	ert:					
Moisture C	content (%):					
% Particles (By dry ma	s > 20mm ss):	13				
MCV:		13				
Interpretati	on of Plot:	Steepest Straight Line				
Description	n of Soil:	Brown sandy gravelly S	SILT/CLAY			
Results relate only to the specimen teste Opinions and interpretations are outside * denotes Customer supplied information This report shall not be reproduced exce	Results relate only to the specimen tested, in as received condition unless otherwise note Opinions and interpretations are outside the scope of accreditation. • denotes Customer supplied information. This report shall not be reproduced except in full without written approval from the Labora				approve reports uality Manager) boratory Manager)	
		Approved by		Date	Page	
IGSL Ltd Mater	rials Laboratory	A Byene		05/09/22	1 of 1	

IGSL Ltd Materials Laboratory Unit J5,M7 Business Park	Test Report Determination of Moisture Condition Value at Natural Moisture					
Naas		Content		lotaro		
Co. Kildare 045 899324	Co. Kildare Tested in accordance 045 899324		90, clause 5.4	4	GENALLD IN SCOPE REG NO.1331	
Report No).	R138007				
Contract N	lo.	24188				
Contract N	lame:	Profile Park Data Cent	re Site 4			
Customer:		Ramboll				
BH/TP*		TP03				
Sample No	D.*	AA180428				
Depth* (m))	0.60				
Sample Ty	vpe:	В				
Lab Samp	le No.	A22/4613				
Source* (if	applicable)	N/A				
Material Ty	ype* (if applicable):	B 15/08/22 24/08/22				
Sample Re	eceived:					
Date Teste	ed:					
Sample Ce	ert:	Not Provided				
Moisture C	Content (%):	17				
% Particles (By dry ma	s > 20mm iss):	12				
MCV:		11				
Interpretati	ion of Plot:	Steepest Straight Line				
Description	n of Soil:	Brown sandy gravelly S	SILT/CLAY			
Results relate only to the specimen teste Opinions and interpretations are outside * denotes Customer supplied information This report shall not be reproduced exce	ed, in as received condition unless othen the scope of accreditation. n. pt in full without written approval from th	vise noted. e Laboratory.	Persons autho J H	rised to a Barrett (Q Byrne (La	approve reports uality Manager) boratory Manager)	
		Approved by	·	Date	Page	
IGSL Ltd Mater	rials Laboratory	A Byene	с)5/09/22	1 of 1	

IGSL Ltd Materials Laboratory Unit J5,M7 Business Park	Test Report Determination of Moisture Condition Value at Natural Moisture					
Naas		Content			ACCREDITED TESTING DETAILED IN SCOPE REG NO. 1337	
Co. Kildare 045 899324	Observe Tested in accordance 045 899324 Tested in accordance		90, clause 5.4	4		
Report No).	R138008				
Contract N	lo.	24188				
Contract N	lame:	Profile Park Data Cent	re Site 4			
Customer:		Ramboll				
BH/TP*		TP04				
Sample No	D.*	AA180432				
Depth* (m))	0.50				
Sample Ty	vpe:	В				
Lab Samp	le No.	A22/4615				
Source* (if	applicable)	N/A				
Material Ty	ype* (if applicable):	В				
Sample Re	eceived:	15/08/22				
Date Teste	ed:	24/08/22				
Sample Ce	ert:	Not Provided				
Moisture C	Content (%):	22				
% Particles (By dry ma	s > 20mm iss):	1				
MCV:		10.6				
Interpretati	ion of Plot:	Steepest Straight Line				
Description	n of Soil:	Brown sandy gravelly S	SILT/CLAY			
Results relate only to the specimen teste Opinions and interpretations are outside * denotes Customer supplied information This report shall not be reproduced exce	ed, in as received condition unless othen the scope of accreditation. n. pt in full without written approval from th	vise noted. e Laboratory.	Persons author J H	rised to a Barrett (Qı Byrne (La	approve reports Jality Manager) boratory Manager)	
		Approved by	·	Date	Page	
IGSL Ltd Mater	rials Laboratory	AByene	C	5/09/22	1 of 1	

IGSL Ltd Materials Laboratory	Test Report			ISO 17025		
Naas	Determination of Moistu	Content		sture		
Co. Kildare 045 899324	Co. Kildare Tested in accordance		90, clause 5.4	ŀ	DETAILED IN SCOPE REG NO. 1337	
Report No).	R138009				
Contract N	lo.	24188				
Contract N	lame:	Profile Park Data Cent	re Site 4			
Customer:		Ramboll				
BH/TP*		TP05				
Sample No	D.*	AA180430				
Depth* (m))	0.70				
Sample Ty	vpe:	В				
Lab Samp	le No.	A22/4617				
Source* (if	applicable)	N/A				
Material Ty	ype* (if applicable):	В				
Sample Re	eceived:	15/08/22				
Date Teste	ed:	24/08/22 Not Provided 12 13				
Sample Ce	ert:					
Moisture C	Content (%):					
% Particles (By dry ma	s > 20mm iss):					
MCV:		14.9				
Interpretati	ion of Plot:	Steepest Straight Line				
Description	n of Soil:	Brown sandy gravelly S	SILT/CLAY			
Results relate only to the specimen teste Opinions and interpretations are outside * denotes Customer supplied information This report shall not be reproduced exce	ed, in as received condition unless othen the scope of accreditation. n. pt in full without written approval from th	vise noted. e Laboratory.	Persons authori J E H E	ised to a Barrett (Qu Byrne (La	approve reports Jality Manager) boratory Manager)	
		Approved by	·	Date	Page	
IGSL Ltd Mater	rials Laboratory	# Byene	05	5/09/22	1 of 1	

IGSL Ltd Materials Laboratory Unit J5 M7 Business Park	Test Report					
Naas	Determination of Moistu	Content		sture		
Co. Kildare 045 899324	Co. Kildare Tested in accordance		90, clause 5.4	1	DETAILED IN SCOPE REG NO. 1337	
Report No).	R138010				
Contract N	lo.	24188				
Contract N	lame:	Profile Park Data Cent	re Site 4			
Customer:		Ramboll				
BH/TP*		TP06				
Sample No	D.*	AA180426				
Depth* (m))	0.50				
Sample Ty	vpe:	В				
Lab Samp	le No.	A22/4618				
Source* (if	applicable)	N/A				
Material Ty	ype* (if applicable):	В				
Sample Re	eceived:	15/08/22 24/08/22				
Date Teste	ed:					
Sample Ce	ert:	Not Provided				
Moisture C	Content (%):	16				
% Particles (By dry ma	s > 20mm iss):	12				
MCV:		12				
Interpretati	ion of Plot:	Steepest Straight Line				
Description	n of Soil:	Brown sandy gravelly SILT/CLAY				
Results relate only to the specimen teste Opinions and interpretations are outside * denotes Customer supplied information This report shall not be reproduced exce	ed, in as received condition unless otherw the scope of accreditation. n. pt in full without written approval from the	vise noted. e Laboratory.	Persons author J E H I	ised to a Barrett (Qe Byrne (La	approve reports uality Manager) boratory Manager)	
		Approved by	·	Date	Page	
IGSL Ltd Mater	rials Laboratory	A Byene	0	5/09/22	1 of 1	

IGSL Ltd Materials Laboratory Unit J5,M7 Business Park Naas	Test Report Determination of Moisture Condition Value at Natural Moisture Content		ISO 17025 ACCREDITED			
Co. Kildare 045 899324	e with BS1377:Part 4:199	90, clause 5	5.4	DETAILED IN SCOPE REG NO. 1337		
Report No).	R138011				
Contract N	lo.	24188				
Contract N	lame:	Profile Park Data Cent	re Site 4			
Customer:		Ramboll				
BH/TP*		TP07				
Sample No	0.*	AA180420				
Depth* (m)	0.50				
Sample Ty	vpe:	В				
Lab Samp	le No.	A22/4619				
Source* (if	applicable)	N/A				
Material T	ype* (if applicable):	В				
Sample Re	eceived:	15/08/22				
Date Teste	ed:	23/08/22 Not Provided 20				
Sample Ce	ert:					
Moisture C	Content (%):					
% Particle (By dry ma	s > 20mm iss):	0				
MCV:		11				
Interpretat	ion of Plot:	Steepest Straight Line				
Description	n of Soil:	Brown sandy gravelly SILT/CLAY				
Results relate only to the specimen teste Opinions and interpretations are outside * denotes Customer supplied information	ed, in as received condition unless other the scope of accreditation.	wise noted.	Persons auth	norised to a J Barrett (Q H Byrne (La	approve reports uality Manager) boratory Manager)	
This report shall not be reproduced exce	pt in full without written approval from th	e Laboratory. Approved by	 	Date	Page	
IGSL Ltd Mate	rials Laboratory	# Byene		05/09/22	1 of 1	

IGSL Ltd Materials Laboratory Unit J5,M7 Business Park Naas	Test Report Determination of Moisture Condition Value at Natural Moisture Content			ISO 17025 ACREATED TESTING		
Co. Kildare 045 899324	e with BS1377:Part 4:199	0, clause 5	5.4	DETAILED IN SCOPE REG NO. 1337		
Report No	·).	R138012				
Contract N	lo.	24188				
Contract N	lame:	Profile Park Data Centr	re Site 4			
Customer:		Ramboll				
BH/TP*		TP08				
Sample No	D.*	AA180424				
Depth* (m))	0.70				
Sample Ty	vpe:	В				
Lab Samp	le No.	A22/4621				
Source* (if	applicable)	N/A				
Material Ty	ype* (if applicable):	В				
Sample Re	eceived:	15/08/22				
Date Teste	ed:	24/08/22				
Sample Ce	ert:	Not Provided				
Moisture C	Content (%):	13				
% Particles (By dry ma	s > 20mm ass):	8	3			
MCV:		11.9				
Interpretati	ion of Plot:	Steepest Straight Line				
Description	n of Soil:	Brown sandy gravelly SILT/CLAY				
Results relate only to the specimen teste Opinions and interpretations are outside * denotes Customer supplied information This report shall not be reproduced exce	ed, in as received condition unless other the scope of accreditation. n. ept in full without written approval from th	vise noted. e Laboratory.	Persons auth	orised to a J Barrett (Q H Byrne (La	approve reports uality Manager) boratory Manager)	
		Approved by		Date	Page	
IGSL Ltd Mater	rials Laboratory	A Byene		05/09/22	1 of 1	

IGSL Ltd Materials Laboratory Unit J5,M7 Business Park Naas	Determination of Moistu	Test Report re Condition Value at	Natural M	oisture	IV ISO 17025 ACCREDIED
Co. Kildare 045 899324	Tested in accordance	e with BS1377:Part 4:199	90, clause 5	5.4	DETAILED IN SCOPE REG NO. 1337
Report No	·).	R138013			
Contract N	0.	24188			
Contract N	lame:	Profile Park Data Cent	re Site 4		
Customer:		Ramboll			
BH/TP*		TP10			
Sample No).*	AA180439			
Depth* (m))	0.50			
Sample Ty	rpe:	В			
Lab Samp	le No.	A22/4623			
Source* (if	applicable)	N/A			
Material Ty	/pe* (if applicable):	В			
Sample Re	eceived:	15/08/22			
Date Teste	ed:	24/08/22			
Sample Ce	ert:	Not Provided			
Moisture C	content (%):	12			
% Particles (By dry ma	s > 20mm iss):	6			
MCV:		10.4			
Interpretati	ion of Plot:	Steepest Straight Line			
Description	n of Soil:	Brown sandy gravelly S	SILT/CLAY		
Results relate only to the specimen teste Opinions and interpretations are outside * denotes Customer supplied information	ed, in as received condition unless other the scope of accreditation.	wise noted.	Persons auth	norised to a J Barrett (Q H Byrne (La	approve reports uality Manager) boratory Manager)
This report shall not be reproduced exce	pt in rull without written approval from th	Approved by		Date	Page
IGSL Ltd Mater	rials Laboratory	A Byene		05/09/22	1 of 1

IGSL Ltd			Toot D	1000			
Materials Laboratory M7 Business Park				short			
Naas Co. Kildare	Determinatio	on of Therma	al Conductiv Needle F	ity / Resistivi Probe	ty of Soil by	Thermal	
Report No	ė		R137284				
Contract N	O		24188				
Contract N	ame:		Profile Park D	Data Centre			
Client:			Ramboll				
Sample Nc	Ċ		171725				
Location			BH01 1.0m				
Soil descri	otion		Grey slightly	sandy slightly	gravelly SILT/	CLAY	
Preparation Date Teste	c ij		<8mm materia oven dried, an 11/08/2022	ll tamped into c d wetter than a	ontainer at as r s received	eceived Wa	ter content
	Water Content %	Bulk density Mg/m ³	Dry density Mg/m ³	Thermal Conductivity K (W/m k)*	Thermal Resistivity R (m K/W)*	Porosity	
As received	17.1	1.57	1.34	1.0080	0.9920	0.49	
Oven dried	0.0	1.34	1.34	0.2486	4.0511	0.49	
Wetter than as received	22.5	1.82	1.48	1.4311	0.7058	0.44	
	Ther	mal Resist	ivity v Wat	er Content			
4.5000							
4.0000 (W) 3.5000							
۲ 2:5000							
Resis							
 1.5000							
1.0000				,			
0.5000							
0.0	5.0	0	10.0	15.0	20.0	25.0	
			Water Conten	t (%)			
Notes: Water content measur linear measurement. Porosity Density of 2.65. Thermal mea. (manufactured by METER Gro	ed in accordance w calculated (voids ra surements underta oup). *Thermal tes:	ith ISO 17892-1: atio/1+voids ratio) ke using a TEMP t results are an ar	2014. Bulk densi with an assumed OS and TR-3 pro verage of 5 readir	ity measured by d Particle bbe ngs.			
The result relates to the speci	men tested.				Persons auth	lorised to ap J Barrett (Qu H Byrne (Lab	oprove report ality Manager) oratory Manager)
			Approved by			Date	Page
IGSL Materia	ıls Laborat	ory	10	An At		09/09/22	1 of 1

IGSL Ltd			Toet D	troop			
Materials Laboratory				choir			
wr busiless raik Naas Co. Kildare	Determinatio	on of Therma	al Conductiv Needle F	ity / Resistivi Probe	ty of Soil by	Thermal	
Report No			R137285				
Contract N	ō		24188				
Contract N	ame:		Profile Park [Data Centre			
Client:			Ramboll				
Sample No	÷		171722				
Location			BH03 1.0m				
Soil descri	otion		Greyish brow	'n slightly sanc	ły slightly grav	elly SILT/C	ΓАΥ
Preparation Date Teste	с ў		<8mm materia oven dried, an 11/08/2022	ll tamped into c d wetter than a	ontainer at as r s received	eceived Wat	er content
	Water Content %	Bulk density Mg/m ³	Dry density Mg/m ³	Thermal Conductivity K (W/m.k)*	Thermal Resistivity R (m K/W)*	Porosity	
As received	26.7	1.84	1.45	1.1405	0.9049	0.45	
Oven dried	0.0	1.37	1.37	0.1978	5.1415	0.48	
Wetter than as received	38.3	1.69	1.22	1.2773	0.8208	0.54	
	Ther	mal Resist	ivity v Wat	er Content			
6.0000							
U K/M)							
, tivity (n 2000 2000 2000 2000 2000 2000 2000 20							
sis99 la							
herma							
ц. т. 00000 П. т.				, ,	•		
0.0000 - 0.0000 0.0	5.0	0.0 15.0	20.0 25 Water Conten	.0 30.0 t (%)	35.0 40.0	45.0	
Notes: Water content measur linear measurement. Porosity Density of 2.65. Thermal mea (manufactured by METER Group	ed in accordance w calculated (voids r surements underta oup). *Thermal tes	ith ISO 17892-1: atio/1+voids ratio) ke using a TEMP t results are an ar	2014. Bulk dens with an assume OS and TR-3 pro verage of 5 readi	try measured by d Particle bbe ngs.			_
The result relates to the speci	men tested.				Persons auth	orised to ap J Barrett (Qua H Byrne (Lab	pprove report ality Manager) oratory Manager)
IGSL Materia	lls Laborat	ory	Approved by	tt Ve		Date 09/09/22	Page 1 of 1
			<i>,</i>	10-11		10000	-

			1				
Materials Laboratory			lest R(eport			
M/ business Park Naas Co. Kildare	Determinatio	in of Therm	al Conductiv Needle F	ity / Resistiv	ity of Soil by	Thermal	
Report No	÷		R137286				
Contract N	ö		24188				
Contract N	ame:		Profile Park [Data Centre			
Client:			Ramboll				
Sample No	÷		171724				
Location			BH05 1.0m				
Soil descri	otion		Greyish brow	'n slightly sanc	dy slightly grav	elly SILT/C	LAY
Preparatio Date Teste	د بە		<8mm materia oven dried, an 11/08/2022	al tamped into c d wetter than a	ontainer at as r s received	eceived Wa	ter content
	Water Content %	Bulk density Mg/m ³	Dry density Mg/m ³	Thermal Conductivity K (W/m.k)*	Thermal Resistivity R (m K/W)*	Porosity	
As received	21.2	2.05	1.69	1.3385	0.7931	0.36	
Oven dried	0.0	1.52	1.52	0.2543	3.9729	0.42	
Wetter than as received	24.0	1.75	1.41	1.4107	0.7139	0.47	
	Ther	mal Resist	ivity v Wat	er Content			
4.5000							
4.0000 (W) 3.5000							
	<u> </u>						
tivitei							
al Resi 1.5000							
erm.							
 0.5000				<u>}</u>	1		
0.0000	5.0	10.0	15.0	20.0	25.0	30.0	
			Water Conten	t (%)			
Notes: Water content measur linear measurement. Porosity Density of 2.65. Themal mea (manufactured by METER Gr	ed in accordance w calculated (voids re surements underta sup). *Thermal tesi	tith ISO 17892-1 ttio/1+voids ratio/ ke using a TEMF t results are an a	:2014. Bulk dens i with an assume ot and TR-3 proverage of 5 readin	ity measured by d Particle obe ngs.			
The result relates to the speci	nen tested.				Persons auth	orised to ap J Barrett (Quá H Byrne (Lab	pprove report ality Manager) oratory Manager)
IGSL Materia	lls Laborat	ory	Approved by	tt US		Date	Page 1 of 1
)			0000	- 5 -

IGSL Ltd Materials I aboratory			Test Re	sport			
M7 Business Park Naas Co. Kildare	Determinatic	in of Therma	al Conductiv	ity / Resistivi Probe	ty of Soil by	Thermal	
Report No			R137287				
Contract N	ö		24188				
Contract N	ame:		Profile Park D	Jata Centre			
Client:			Ramboll				
Sample Nc	·		180437				
Location			TP01 0.6m				
Soil descriț	otion		Greyish brow	n slightly sand	ly slightly grav	elly SILT/C	LAY
Preparation Date Teste			<8mm materia oven dried, an 09/08/2022	ll tamped into co d wetter than as	ontainer at as r s received	eceived Wat	er content
	W ater Content %	Bulk density Mg/m ³	Dry density Mg/m ³	Thermal Conductivity K (W/m.k)*	Thermal Resistivity R (m K/W)*	Porosity	
As received	14.6	1.56	1.36	0.8820	1.1377	0.49	
Oven dried	0.0	1.32	1.32	0.1778	5.6423	0.50	
Wetter than as received	19.9	1.62	1.35	1.2126	0.8274	0.49	
	Ther	mal Resist	ivity v Wat	er Content			
γivity (ι 							
al Resis							
Therma							
-					-		
0.0	5.0	0	LO.O Water Conten!	15.0 t (%)	20.0	25.0	
Notes: Water content measure linear measurement. Ponsity. Density of 2.65. Thermal mea: (manufactured by METER Gro	ed in accordance w alculated (voids re surements undertal up). *Thermal test	tith ISO 17892-1: tito/1+voids ratio) ke using a TEMP t results are an av	2014. Bulk densi with an assume OS and TR-3 pro	ty measured by 1 Particle be 1gs.			_
The result relates to the speci	nen tested.				Persons auth	orised to ap J Barrett (Qua H Byrne (Lab	pprove report ality Manager) oratory Manager)
IGSI Materia	le l aborat	, AL	Approved by			Date	Page
		())	V	the state		09/09/22	1 of 1

IGSL Ltd Materiale Laboratory			Test Re	sport			
Materials Lador and M7 Business Park Naas Co. Kildare	Determinatio	on of Therma	al Conductiv Needle F	ity / Resistivi Probe	ity of Soil by	Thermal	
Report No	ė		R137288				
Contract N	<u>.</u>		24188				
Contract N	ame:		Profile Park [Data Centre			
Client:			Ramboll				
Sample No	·		180435				
Location			TP02 0.8m				
Soil descri	otion		Brown slightly	y sandy slightl	y gravelly SIL ⁷	T/CLAY	
Preparatio Date Teste	ر :p		<8mm materia oven dried, an 11/08/2022	ll tamped into c d wetter than a	ontainer at as r s received	eceived Wat	er content
	W ater Content %	Bulk density Mg/m ³	Dry density Mg/m ³	Thermal Conductivity K (W/m.k)*	Thermal Resistivity R (m K/W)*	Porosity	
As received	14.7	1.65	1.44	0.9508	1.0589	0.46	
Oven dried	0.0	1.39	1.39	2602.0	4.7922	0.48	
Wetter than as received	27.8	1.72	1.35	1.2433	0.8074	0.49	
	Ther	mal Resist	ivity v Wat	er Content			
m K/W							
stivity (
esisə le							
- T Lherma							
						•	
0.0	5.0	10.0	15.0 Water Conten	20.0 t (%)	25.0	30.0	
Notes: Water content measur linear measurement. Porosity Density of 2.65. Thermal mea (manufactured by METER Gr	ed in accordance w calculated (voids ra surements underta oup). *Thermal tes	rith ISO 17892-1: atio/1+voids ratio) ke using a TEMP t results are an ar	2014. Bulk dens with an assume OS and TR-3 pr verage of 5 readir	ity measured by d Particle be ngs.			_
The result relates to the speci	men tested.				Persons auth	orised to ap J Barrett (Qua H Byrne (Labo	pprove report lity Manager) pratory Manager)
ICSI Matoria	le laborat		Approved by			Date	Page
		OI y	FU	the state		09/09/22	1 of 1

IGSL Ltd				1.0			
Materials Laboratory			I est He	Tiode			
wi pusiness raik Naas Co. Kildare	Determinatio	on of Therma	al Conductiv Needle F	ity / Resistivi Probe	ty of Soil by	Thermal	
Report No	ò		R137289				
Contract N	o.		24188				
Contract N	lame:		Profile Park [Data Centre			
Client:			Ramboll				
Sample No	Ġ		180429				
Location			TP03 2.0m				
Soil descri	ption		Grey slightly	sandy slightly	gravelly SILT/	CLAY	
Preparatio Date Test	u ;bé		<8mm materia oven dried, an 09/08/2022	al tamped into c d wetter than a	ontainer at as r s received	eceived Wat	er content
	Water Content %	Bulk density Mg/m ³	Dry density Mg/m ³	Thermal Conductivity K (W/m.k)*	Thermal Resistivity R (m K/W)*	Porosity	
As received	12.6	1.81	1.61	1.0734	0.9358	0.39	
Oven dried	0.0	1.53	1.53	0.1716	5.8714	0.42	
Wetter than as received	17.4	2.14	1.83	1.4324	0.7227	0.31	
	Ther	mal Resist	ivity v Wat	er Content			
2.0000							
E. 0000 (0.000 (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000) (0.000)							
/ity (m) /ity							
vitsise 		A					
mal R 2.0000			4				
Тhеr 1.000			/				
0.0000		_		,			
0.0	0 2.0 4.(0.9	8.0 10.0 Water Conten	12.0 14.0 t (%)	16.0 18.	0 20.0	
Notes: Water content measur linear measurement. Porosity Density of 2.65. Thermal mea (manufactured by METER Gr	ed in accordance w calculated (voids r surements underla oup). *Thermal tes	rith ISO 17892-1 atio/1+voids ratio/ ke using a TEMF t results are an a	2014. Bulk dens) with an assume OS and TR-3 pro verage of 5 readi	ity measured by d Particle be Jgs.			
income outs of october shrees out					Doreone outh	orie od to ar	
Ine result relates to the speci	men tested.					ט ואפט נט מא J Barrett (Qua H Byrne (Lab	Jurove report ality Manager) oratory Manager)
IGSL Materia	als Laborat	ory	Approved by	the not		Date 09/09/22	Page 1 of 1

IGSL Ltd			Tact B	port			
Materials Laboratory M7 Business Park							
Naas Co. Kildare	Determinatio	on of Therma	al Conductiv Needle F	ity / Resistivi Probe	ity of Soil by	Thermal	
Report No			R137290				
Contract N	ö		24188				
Contract N	ame:		Profile Park [Data Centre			
Client:			Ramboll				
Sample No			180423				
Location			TP04 0.8m				
Soil descrip	otion		Greyish brow	n slightly sanc	ły slightly grav	elly SILT/C	ΓАΥ
Preparation Date Teste	– ip		<8mm materia oven dried, an 09/08/2022	ll tamped into c d wetter than a	ontainer at as r	eceived Wat	ter content
	Water Content %	Bulk density Mg/m ³	Dry density Mg/m ³	Thermal Conductivity K (W/m.k)*	Thermal Resistivity R (m K/W)*	Porosity	
As received	14.7	1.69	1.47	0.9005	1.1167	0.44	
Oven dried	0.0	1.35	1.35	0.1504	6.6750	0.49	
Wetter than as received	28.6	2.02	1.57	1.5055	0.6647	0.41	
	Ther	mal Resist	ivity v Wat	er Content			
8.0000							
√ (w K							
stivity 4 0000	4						
a. 0000							
1 5.0000 7.0000		4					
1.0000					Ī		
0.0000 L	5.0	10.0	15.0 2	0.0 25.0	30.0	35.0	
			Water Conten	t (%)			
Notes: Water content measure linear measurement. Porosity i Density of 2.65. Thermal mea: (manufactured by METER Gro	d in accordance w calculated (voids re surements undertal up). *Thermal tesi	ith ISO 17892-1: ttio/1+voids ratio) ke using a TEMP t results are an ar	2014. Bulk dens with an assume OS and TR-3 pro verage of 5 readi	ity measured by d Particle bbe ngs.			
The result relates to the specir	nen tested.				Persons auth	orised to ap J Barrett (Qua H Byrne (Lab	pprove report ality Manager) oratory Manager)
IGSL Materia	ls Laborat	ory	Approved by	H UE		Date	Page
			0	125-110		03/03/22	- 0 -

IGSL Ltd			Tact Ro	port			
Materials Laboratory M7 Business Park							
Naas Co. Kildare	Determinatio	on of Therma	al Conductiv Needle F	ity / Resistivi Probe	ty of Soil by	Thermal	
Report N	ō		R137291				
Contract 1	Jo.		24188				
Contract 1	Vame:		Profile Park D	Data Centre			
Client:			Ramboll				
Sample N	ō		180430				
Location			TP05 0.7m				
Soil descr	iption		Brown slightly	y sandy slightl	y gravelly SIL ⁷	I/CLAY	
Preparatic Date Test	u ;be		<8mm materia oven dried, an 09/08/2022	ll tamped into c d wetter than a	ontainer at as r s received	eceived Wat	er content
	W ater Content %	Bulk density Mg/m ³	Dry density Mg/m ³	Thermal Conductivity K (W/m.k)*	Thermal Resistivity R (m K/W)*	Porosity	
As received	15.0	1.55	1.34	0.8037	1.2526	0.49	
Oven dried	0.0	1.42	1.42	0.1747	5.7375	0.47	
Wetter than as received	19.4	1.98	1.66	1.5234	0.6586	0.37	
	Ther	mal Resist	ivity v Wat	er Content			
00000							
m) (m							
vitsise							
2.0000							
Тhеп			/				
000000					1		
0	5.0	0	10.0 Water Conteni	15.0 t (%)	20.0	25.0	
Notes: Water content measu linear measurement. Porosity Density of 2.65. Thermal mex (manufactured by ME TE R G	ed in accordance w calculated (voids ra tsurements undertal oup). *Thermal test	ith ISO 17892-1: atio/1+voids ratio) ke using a TEMP t results are an a	2014. Bulk densi with an assumer OS and TR-3 pro	ty measured by d Particle bbe ngs.			_
The result relates to the spec	imen tested.				Persons auth	orised to ap J Barrett (Qua H Byrne (Lab	pprove report ality Manager) oratory Manager)
IGSL Materia	als Laborat	ory	Approved by	H Ve		Date	Page 1 of 1
			7			00,00, FF	-

IGSL Ltd			Toet Be				
Materials Laboratory							
Naas Co. Kildare	Determinatic	on of Therma	al Conductivi Needle F	ty / Resistivi Probe	ty of Soil by	Thermal	
Report No	ė		R137292				
Contract N	lo.		24188				
Contract N	lame:		Profile Park D	lata Centre			
Client:			Ramboll				
Sample No	Ö		180426				
Location			TP06 0.5m				
Soil descri	ption		Greyish brow	n slightly sand	ly slightly grav	elly SILT/C	LAY
Preparatio Date Teste	u ;bi		<8mm materia oven dried, and 09/08/2022	l tamped into co d wetter than as	ontainer at as r s received	eceived Wat	er content
	W ater Content %	Bulk density Mg/m ³	Dry density Mg/m ³	Thermal Conductivity K (W/m.k)*	Thermal Resistivity R (m K/W)*	Porosity	
As received	15.4	1.66	1.44	0.9823	1.0256	0.46	
Oven dried	0.0	1.43	1.43	0.1768	5.6960	0.46	
Wetter than as received	21.2	1.83	1.51	1.3255	0.7670	0.43	
	Ther	mal Resist	ivity v Wat	er Content			
	/						
- 2:0000 2:0000 2:0000 2:0000 2:0000 2:0000 2:00000 2:00000 2:00000 2:00000 2:00000 2:000000 2:00000000							
νity (i							
li Resis							
herma herma			/	_/			
					1		
0.0000.0	5.0		10.0 Water Content	15.0 : (%)	20.0	25.0	
Notes: Water content measur	ed in accordance w	ith ISO 17892-1:	2014. Bulk densi	ty measured by			
linear measurement. Porosity Density of 2.65. Thermal mea (manufactured by METER Gn	calculated (voids ra surements undertal oup). *Thermal tesi	tio/1+voids ratio) ke using a TEMP t results are an a	with an assumec OS and TR-3 pro verage of 5 readir	l Particle be Igs.			
The result relates to the speci	men tested.				Persons auth	orised to ap J Barrett (Quá H Byrne (Lab	pprove report ality Manager) oratory Manager)
IGSL Materia	als Laborat	ory	Approved by	the le		Date 09/09/22	Page 1 of 1

IGSL Ltd			Tact R				
Materials Laboratory							
Naas Naas Co. Kildare	Determinatio	on of Therma	al Conductiv Needle F	ity / Resistiv	ity of Soil by	Thermal	
Report N	-o		R137293				
Contract	No.		24188				
Contract	Name:		Profile Park [Data Centre			
Client:			Ramboll				
Sample N	.0 1		180422				
Location			TP07 1.4m				
Soil descr	ription		Brown slightly	y sandy slightl	y gravelly SIL ⁷	I/CLAY	
Preparati Date Test	on ted:		<8mm materia oven dried, an 11/08/2022	al tamped into c d wetter than a	ontainer at as r s received	eceived Wat	er content
	Water Content %	Bulk density Mg/m ³	Dry density Mg/m ³	Thermal Conductivity K (W/m.k)*	Thermal Resistivity R (m K/W)*	Porosity	
As received	19.3	1.87	1.57	1.3003	0.7728	0.41	
Oven dried	0.0	1.46	1.46	0.1656	6.1295	0.45	
Wetter than as received	25.5	1.90	1.51	1.7019	0.5902	0.43	
1	Ther	mal Resist	ivity v Wat	er Content			
0000							
(M) (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (2000 (200) (2000 (2000 (200) (2000 (200) (2000 (200) (2000 (200) (2000 (2000 (200) (2000 (200) (2000 (200) (2000 (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (200) (2							
ty (m							
w t							
2000 2000 2000 2000 2000		,					
Therr			/				
				/	1		
0	.0 5.0	10.0	15.0 Water Conten	20.0 t (%)	25.0	30.0	
Notes: Water content measu linear measurement. Porosit Density of 2.65. Thermal me (manufactured by METER G	ured in accordance w y calculated (voids ra assurements underta aroup). *Thermal tes	/ith ISO 17892-1 atio/1+voids ratio ke using a TEMF t results are an a	:2014. Bulk dens) with an assume OS and TR-3 pro verage of 5 readii	ity measured by d Particle bbe ngs.			
The result relates to the spe	cimen tested.				Persons auth	orised to ap J Barrett (Qua H Byrne (Labo	pprove report ality Manager) oratory Manager)
IGSL Materi	als Laborat	ory	Approved by	tt ve		Date	Page 1 of 1
			5	10-10		131 N31 22	- 10 -

IGSL Ltd			Tact Ro	port			
Materials Laboratory M7 Business Park							
Naas Co. Kildare	Determinatio	on of Therma	al Conductiv Needle F	ity / Resistivi Probe	ty of Soil by	Thermal	
Report No	-		R137294				
Contract N	O		24188				
Contract N	ame:		Profile Park D	Jata Centre			
Client:			Ramboll				
Sample No	·		180424				
Location			TP08 0.7m				
Soil descri	otion		Brown slightly	/ sandy slightly	y gravelly SIL7	I/CLAY	
Preparatio Date Teste			<8mm materia oven dried, an 11/08/2022	ll tamped into co d wetter than as	ontainer at as r s received	eceived Wat	er content
	Water Content %	Bulk density Mg/m ³	Dry density Mg/m ³	Thermal Conductivity K (W/m.k)*	Thermal Resistivity R (m K/W)*	Porosity	
As received	14.8	1.63	1.42	1.0076	0.9973	0.47	
Oven dried	0.0	1.53	1.53	0.2054	4.9015	0.42	
Wetter than as received	21.1	1.96	1.62	1.2018	0.8488	0.39	
	Ther	mal Resist	ivity v Wat	er Content			
9.0000							
∑.0000							
r) (tivity , , , , , , , , , , , , , , , , , , ,							
risesa la							
, perma				/			
					•		
0.0	5.0		10.0 Water Conteni	15.0 t (%)	20.0	25.0	
Notes: Water content measur linear measurement. Porosity Density of 2.65. Thermal mea (manufactured by METER Gr	ed in accordance w calculated (voids ra surements underta oup). *Thermal tes	ith ISO 17892-1: tito/1+voids ratio) ke using a TEMP t results are an av	2014. Bulk densi with an assumet OS and TR-3 pro	ty measured by a Particle bbe igs.			_
The result relates to the speci	men tested.				Persons auth	orised to ap J Barrett (Quá H Byrne (Lab	pprove report ality Manager) oratory Manager)
IGSL Materia	Ils Laborat	ory	Approved by	the la		Date 09/09/22	Page 1 of 1

IGSL Ltd			Test Re	eport			
Materias Laboratory M7 Business Park Naas Co. Kildare	Determinatic	on of Therma	al Conductiv	ity / Resistivi Probe	ty of Soil by	Thermal	
Report No			R137295				
Contract N	Ö		24188				
Contract N	ame:		Profile Park D	Jata Centre			
Client:			Ramboll				
Sample Nc			180418				
Location			TP09 0.5m				
Soil descrip	otion		Greyish brow	n slightly sand	ly slightly grav	elly SILT/C	LAY
Preparation Date Teste	с ;р		<8mm materia oven dried, an 09/08/2022	ll tamped into co d wetter than as	ontainer at as r s received	eceived Wat	er content
	W ater Content %	Bulk density Mg/m ³	Dry density Mg/m ³	Thermal Conductivity K (W/m.k)*	Thermal Resistivity R (m K/W)*	Porosity	
As received	15.4	1.75	1.52	1.0672	0.9453	0.43	
Oven dried	0.0	1.46	1.46	0.1902	5.2803	0.45	
Wetter than as received	20.6	1.96	1.63	1.2804	0.7823	0.39	
	Ther	mal Resist	ivity v Wat	er Content			
9.0000							
μ K/M)							
, tivity (r							
al Resis							
Lherma							
					•		
0.0	5.0	0	10.0 Water Conteni	15.0 t (%)	20.0	25.0	
Notes: Water content measure linear measurement. Porosity Density of 2.65. Thermal meas (manufactured by METER Gro	ed in accordance w calculated (voids re surements underta up). *Thermal test	ith ISO 17892-1: tito/1+voids ratio) ke using a TEMP t results are an ar	2014. Bulk densi with an assume OS and TR-3 proverage of 5 readir	ty measured by I Particle be 19S.			_
The result relates to the speci	men tested.				Persons auth	orised to ap J Barrett (Qua H Byrne (Lab	pprove report ality Manager) oratory Manager)
		ŝ	Approved by			Date	Page
IGOL MAIERIS	lis Laboral	ory		the la		09/09/22	1 of 1

IGSL Ltd			Tect Re	port			
Materials Laboratory M7 Business Park							
Naas Co. Kildare	Determinatio	on of Therma	al Conductiv Needle F	ity / Resistivi Probe	ty of Soil by	Thermal	
Report No	ė		R137296				
Contract N	lo.		24188				
Contract N	lame:		Profile Park D	Jata Centre			
Client:			Ramboll				
Sample No	Ö		180440				
Location			TP10 1.5m				
Soil descri	ption		Grey slightly	sandy slightly	gravelly SILT/	CLAY	
Preparatio Date Test	u ;bé		<8mm materia oven dried, an 09/08/2022	ll tamped into co d wetter than as	ontainer at as r	eceived W at	er content
	Water Content %	Bulk density Mg/m ³	Dry density Mg/m ³	Thermal Conductivity K (W/m.k)*	Thermal Resistivity R (m K/W)*	Porosity	
As received	17.1	1.95	1.66	1.2291	0.8267	0.37	
Oven dried	0.0	1.50	1.50	0.1885	5.3727	0.43	
Wetter than as received	22.6	1.90	1.55	1.4371	0.7031	0.42	
	Ther	mal Resist	ivity v Wat	er Content			
μ K\M)							
, tivity (r							
siz9A I.		/					
реста 7 г.			/	_/			
0.00 0.0	5.0		10.0 Water Conten	15.0 t (%)	20.0	25.0	
Notes: Water content measur linear measurement. Porosity Density of 2.65. Thermal mea (manufactured by METER Gr	ed in accordance w calculated (voids re surements underta oup). *Thermal tes	tith ISO 17892-1: atio/1+voids ratio) ke using a TEMP t results are an ar	2014. Bulk densi with an assume OS and TR-3 pr verage of 5 readi	ty measured by I Particle be Igs.			_
The result relates to the speci	men tested.				Persons auth	orised to ap J Barrett (Qua H Byrne (Labo	pprove report lity Manager) sratory Manager)
IGSL Materia	als Laborat	orv	Approved by	V. Ve		Date	Page
		6.5	V	the state		09/09/22	1 of 1

Appendix 9

Chemical / Environmental Laboratory Results (Soil)



🔅 eurofins

Chemtest

Eurofins Chemtest Ltd Depot Road Newmarket CB8 0AL Tel: 01638 606070 Email: info@chemtest.com

Report No.:	22-31072-1		
Initial Date of Issue:	23-Aug-2022		
Client	IGSL		
Client Address:	M7 Business Park Naas County Kildare Ireland		
Contact(s):	Darren Keogh		
Project	24188 - Profile Park - Data Centre Site 3 (Ramboll)		
Quotation No.:	Q20-19951	Date Received:	15-Aug-2022
Order No.:		Date Instructed:	15-Aug-2022
No. of Samples:	14		
Turnaround (Wkdays):	7	Results Due:	23-Aug-2022
Date Approved:	23-Aug-2022		
Approved By:			
and			

Details:

Stuart Henderson, Technical Manager

Results - Leachate

Client: IGSL			Chei	mtest J	ob No.:	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072
Quotation No.: Q20-19951		(Chemte	st Sam	ple ID.:	1487830	1487832	1487834	1487836	1487837	1487838	1487839	1487840	1487842
Order No.:			Clier	nt Samp	le Ref.:	AA171726	AA171721	AA171726	180428	180432	180431	180426	180420	180440
			Sa	ample Lo	ocation:	BH02	BH04	BH06	TP03	TP04	TP05	TP06	TP07	TP10
				Sampl	е Туре:	SOIL								
				Top De	oth (m):	1.00	1.00	1.00	0.60	0.50	2.00	0.50	0.50	1.50
Determinand	Accred.	SOP	Туре	Units	LOD									
рН	U	1010	10:1		N/A	8.1	8.2	8.2	8.3	7.8	8.1	8.4	8.0	8.3
Ammonium	U	1220	10:1	mg/l	0.050	0.068	0.070	0.080	< 0.050	0.16	0.051	< 0.050	0.082	0.072
Ammonium	N	1220	10:1	mg/kg	0.10	0.73	0.76	0.87	0.54	1.6	0.54	0.47	0.87	0.80
Boron (Dissolved)	U	1455	10:1	mg/kg	0.01	< 0.01	< 0.01	< 0.01	< 0.01	0.16	< 0.01	< 0.01	< 0.01	< 0.01
Benzo[j]fluoranthene	N	1800	10:1	µg/l	0.010	< 0.010	< 0.010	< 0.010	< 0.010	< 0.010	< 0.010	< 0.010	< 0.010	< 0.010

Results - Soil

Client: IGSL		Ch	emtest .	Job No.:	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072
Quotation No.: Q20-19951		Chem	test San	nple ID.:	1487829	1487830	1487831	1487832	1487833	1487834	1487835	1487836	1487837
Order No.:		Cli	ent Sam	ple Ref.:	AA171725	AA171726	AA171722	AA171721	AA171723	AA171726	180436	180428	180432
		S	Sample I	ocation:	BH01	BH02	BH03	BH04	BH05	BH06	TP02	TP03	TP04
			Samp	ole Type:	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
			Top De	epth (m):	1.00	1.00	1.00	1.00	1.00	1.00	1.80	0.60	0.50
			Asbes	stos Lab:		DURHAM		DURHAM		DURHAM		DURHAM	DURHAM
Determinand	Accred.	SOP	Units	LOD									
АСМ Туре	U	2192		N/A		-		-		-		-	-
Asbestos Identification	U	2192		N/A		No Asbestos Detected		No Asbestos Detected		No Asbestos Detected		No Asbestos Detected	No Asbestos Detected
Moisture	N	2030	%	0.020	11	21	12	14	14	13	11	11	15
pH (2.5:1)	N	2010	,,,	4.0	[A] 8 9		[A] 9 1		[A] 8 6		[A] 8 7		
Boron (Hot Water Soluble)	U	2120	ma/ka	0.40	[, 1] 0.0	[A] < 0.40	[,,],,	[A] < 0.40	[,1] 0.0	[A] < 0.40	[, 1] 0.1	[A] < 0.40	[A] < 0.40
Magnesium (Water Soluble)	N	2120	a/l	0.010	[A] < 0.010	[,] 0.10	[A] < 0.010	[,,] 0.10	[A] < 0.010	[,,] 0.10	[A] < 0.010	[,,] 0.10	[,,] 0.10
Sulphate (2:1 Water Soluble) as SO4	U	2120	g/! a/l	0.010	[A] < 0.010								
Total Sulphur	U	2175	%	0.010	[A] 0 048		[A] 0 095		[A] 0 073		[A] 0 054		
Sulphur (Elemental)	U U	2180	ma/ka	1.0	[7,] 0.0.10	[A] 1 4	[, 1] 0.000	[A] 1 1	[,] 0.010	[A] 1 6	[7,] 0.001	[A] 1 0	[A] 1 3
Chloride (Water Soluble)	U U	2220	a/l	0.010	[A] < 0.010	[·] ···	[A] < 0.010	[-]	[A] < 0.010	[, 1]	[A] < 0.010	[, i]e	[,]
Nitrate (Water Soluble)	N	2220	g/l a/l	0.010	< 0.010		< 0.010		< 0.010		< 0.010		
Cvanide (Total)	U	2300	ma/ka	0.50	0.010	[A] < 0.50	0.010	[A] < 0.50	0.010	[A] < 0.50	0.010	[A] < 0.50	[A] < 0.50
Sulphide (Fasily Liberatable)	N	2325	ma/ka	0.50		[A] 7 4	<u> </u>	[A] 26		[A] 24		[A] 16	[A] 1 2
Ammonium (Water Soluble)	U	2220	a/l	0.00	< 0.01	[/]/	< 0.01	[1] 20	< 0.01	[1] 2 1	< 0.01	[7] 10	[A] 1.2
Sulphate (Acid Soluble)	U	2430	%	0.010	[A] 0 020	[A] 0 026	[A] 0 014	[A] 0 026	[A] 0 017	[A] 0 018	[A] 0 031	[A] 0 019	[A] 0 019
Arsenic	U	2455	ma/ka	0.5	[7.] 0.020	6.8	[,,] 0.0	72	[,] 0.0	14	[,,] 0.001	70	12
Barium	U	2455	ma/ka	0		41		36		92		17	92
Cadmium	U	2455	ma/ka	0.10		12		16		0.61		0.16	32
Chromium	U	2455	ma/ka	0.5		8.7		8.9		37		8.0	16
Molybdenum	U U	2455	ma/ka	0.5		2.5		3.3		3.1		1.3	32
Antimony	N	2455	ma/ka	2.0		< 2.0		< 2.0		< 2.0		< 2.0	< 2.0
Copper	U	2455	ma/ka	0.50		19		22		25		16	30
Mercury	U U	2455	ma/ka	0.05		0.05		< 0.05		0.05		< 0.05	0.05
Nickel	U U	2455	ma/ka	0.50		27	<u> </u>	42		32		23	56
Lead	U U	2455	ma/ka	0.50		22	<u> </u>	11		16		8.9	26
Selenium	U U	2455	ma/ka	0.25		0.57	<u> </u>	0.49		1.0		0.45	1.2
Zinc	U U	2455	ma/ka	0.50		56	<u> </u>	62		71		11	86
Chromium (Trivalent)	N	2490	ma/ka	1.0		87	<u> </u>	8.9		37		8.0	16
Chromium (Hexavalent)	N	2490	ma/ka	0.50		< 0.50	<u> </u>	< 0.50		< 0.50		< 0.50	< 0.50
Mineral Oil (TPH Calculation)	N	2670	ma/ka	10		< 10		< 10		< 10		< 10	< 10
Aliphatic TPH >C5-C6	N	2680	ma/ka	10		[Δ] < 1.0		[A] < 1 0		[Δ] < 1.0		[Δ] < 1.0	[A] < 1 0
Aliphatic TPH >C6-C8	N	2680	mg/kg	1.0		[A] < 1.0	<u> </u>	[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Aliphatic TPH >C8-C10		2680	mg/kg	1.0		[A] < 1.0	<u> </u>	[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Aliphatic TPH >C10-C12	U U	2680	ma/ka	1.0		[A] < 1.0	<u> </u>	[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Aliphatic TPH >C12-C16		2680	mg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Aliphatic TPH $>$ C16-C21		2680	mg/kg	1.0		[A] < 1.0	1	[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Aliphatic TPH $> C21-C35$		2680	mg/kg	1.0		[Λ] < 1.0	1	[Δ] < 1.0		[Δ] < 1.0		[Δ] < 1.0	[Δ] < 1.0
/ inprivato 11 11 - 02 1-000		2000	mg/kg	1.0			1	[7] * 1.0		[7] * 1.0		[7] * 1.0	[7] * 1.0

Results - Soil

Client: IGSL		Ch	emtest .	Job No.:	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072
Quotation No.: Q20-19951		Chem	test San	nple ID.:	1487829	1487830	1487831	1487832	1487833	1487834	1487835	1487836	1487837
Order No.:		Cli	ent Sam	ple Ref.:	AA171725	AA171726	AA171722	AA171721	AA171723	AA171726	180436	180428	180432
		S	Sample L	ocation:	BH01	BH02	BH03	BH04	BH05	BH06	TP02	TP03	TP04
			Samp	le Type:	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
			Top De	epth (m):	1.00	1.00	1.00	1.00	1.00	1.00	1.80	0.60	0.50
			Asbes	tos Lab:		DURHAM		DURHAM		DURHAM		DURHAM	DURHAM
Determinand	Accred.	SOP	Units	LOD									
Aliphatic TPH >C35-C44	N	2680	mg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Total Aliphatic Hydrocarbons	Ν	2680	mg/kg	5.0		[A] < 5.0		[A] < 5.0		[A] < 5.0		[A] < 5.0	[A] < 5.0
Aromatic TPH >C5-C7	Ν	2680	mg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Aromatic TPH >C7-C8	N	2680	mg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Aromatic TPH >C8-C10	U	2680	mg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Aromatic TPH >C10-C12	U	2680	mg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Aromatic TPH >C12-C16	U	2680	mg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Aromatic TPH >C16-C21	U	2680	mg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Aromatic TPH >C21-C35	U	2680	mg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Aromatic TPH >C35-C44	Ν	2680	mg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Total Aromatic Hydrocarbons	Ν	2680	mg/kg	5.0		[A] < 5.0		[A] < 5.0		[A] < 5.0		[A] < 5.0	[A] < 5.0
Total Petroleum Hydrocarbons	Ν	2680	mg/kg	10.0		[A] < 10	[A] < 10						
Benzene	U	2760	µg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Toluene	U	2760	µg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Ethylbenzene	U	2760	µg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
m & p-Xylene	U	2760	µg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
o-Xylene	U	2760	µg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Methyl Tert-Butyl Ether	U	2760	µg/kg	1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0		[A] < 1.0	[A] < 1.0
Naphthalene	Ν	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Acenaphthylene	Ν	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Acenaphthene	Ν	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Fluorene	Ν	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Phenanthrene	Ν	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Anthracene	N	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Fluoranthene	N	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Pyrene	N	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Benzo[a]anthracene	N	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Chrysene	Ν	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Benzo[b]fluoranthene	Ν	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Benzo[k]fluoranthene	Ν	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Benzo[a]pyrene	Ν	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Indeno(1,2,3-c,d)Pyrene	N	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Dibenz(a,h)Anthracene	Ν	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Benzo[g,h,i]perylene	N	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Coronene	N	2800	mg/kg	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010	[A] < 0.010
Total Of 17 PAH's	N	2800	mg/kg	0.20		[A] < 0.20		[A] < 0.20		[A] < 0.20		[A] < 0.20	[A] < 0.20
PCB 28	N	2815	mg/kg	0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010	[A] < 0.0010
PCB 52	Ν	2815	mg/kg	0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010	[A] < 0.0010

<u>Results - Soil</u>

Client: IGSL		Ch	emtest .	Job No.:	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072
Quotation No.: Q20-19951		Chem	test Sar	nple ID.:	1487829	1487830	1487831	1487832	1487833	1487834	1487835	1487836	1487837
Order No.:		Cli	ent Sam	ple Ref.:	AA171725	AA171726	AA171722	AA171721	AA171723	AA171726	180436	180428	180432
		S	Sample I	Location:	BH01	BH02	BH03	BH04	BH05	BH06	TP02	TP03	TP04
			Samp	ole Type:	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
			Top De	epth (m):	1.00	1.00	1.00	1.00	1.00	1.00	1.80	0.60	0.50
			Asbes	stos Lab:		DURHAM		DURHAM		DURHAM		DURHAM	DURHAM
Determinand	Accred.	SOP	Units	LOD									
PCB 90+101	N	2815	mg/kg	0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010	[A] < 0.0010
PCB 118	N	2815	mg/kg	0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010	[A] < 0.0010
PCB 153	N	2815	mg/kg	0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010	[A] < 0.0010
PCB 138	N	2815	mg/kg	0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010	[A] < 0.0010
PCB 180	N	2815	mg/kg	0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010	[A] < 0.0010
Total PCBs (7 congeners)	N	2815	mg/kg	0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010		[A] < 0.0010	[A] < 0.0010
Total Phenols	U	2920	mg/kg	0.10		< 0.10		< 0.10		< 0.10		< 0.10	< 0.10

Results - Soil

Client: IGSL		Ch	emtest .	Job No.:	22-31072	22-31072	22-31072	22-31072	22-31072
Quotation No.: Q20-19951		Chem	test Sar	nple ID.:	1487838	1487839	1487840	1487841	1487842
Order No.:		Cli	ent Sam	ple Ref.:	180431	180426	180420	180418	180440
		ç	Sample I	Location:	TP05	TP06	TP07	TP09	TP10
			Samp	ole Type:	SOIL	SOIL	SOIL	SOIL	SOIL
			Top De	epth (m):	2.00	0.50	0.50	0.50	1.50
			Asbes	stos Lab:	DURHAM	DURHAM	DURHAM		DURHAM
Determinand	Accred.	SOP	Units	LOD					
АСМ Туре	U	2192		N/A	-	-	-		-
Asbestos Identification	U	2192		N/A	No Asbestos Detected	No Asbestos Detected	No Asbestos Detected		No Asbestos Detected
Moisture	N	2030	%	0.020	16	8.9	14	9.3	9.2
pH (2.5:1)	N	2010		4.0				[A] 8.8	
Boron (Hot Water Soluble)	U	2120	mg/kg	0.40	[A] < 0.40	[A] < 0.40	[A] < 0.40		[A] < 0.40
Magnesium (Water Soluble)	N	2120	g/l	0.010				[A] < 0.010	
Sulphate (2:1 Water Soluble) as SO4	U	2120	g/l	0.010				[A] < 0.010	
Total Sulphur	U	2175	%	0.010				[A] 0.047	
Sulphur (Elemental)	U	2180	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] 1.5		[A] 1.3
Chloride (Water Soluble)	U	2220	g/l	0.010				[A] < 0.010	
Nitrate (Water Soluble)	N	2220	g/l	0.010				< 0.010	
Cyanide (Total)	U	2300	mg/kg	0.50	[A] < 0.50	[A] < 0.50	[A] < 0.50		[A] < 0.50
Sulphide (Easily Liberatable)	N	2325	mg/kg	0.50	[A] 7.0	[A] 39	[A] 1.4		[A] 0.65
Ammonium (Water Soluble)	U	2220	g/l	0.01				< 0.01	
Sulphate (Acid Soluble)	U	2430	%	0.010	[A] 0.014	[A] 0.017	[A] 0.021	[A] 0.021	[A] 0.010
Arsenic	U	2455	mg/kg	0.5	4.8	4.0	8.4		8.9
Barium	U	2455	mg/kg	0	14	16	39		21
Cadmium	U	2455	mg/kg	0.10	0.14	0.40	0.87		0.47
Chromium	U	2455	mg/kg	0.5	7.7	6.0	14		6.5
Molybdenum	U	2455	mg/kg	0.5	2.7	1.8	1.7		3.5
Antimony	Ν	2455	mg/kg	2.0	< 2.0	< 2.0	< 2.0		< 2.0
Copper	U	2455	mg/kg	0.50	15	13	16		18
Mercury	U	2455	mg/kg	0.05	< 0.05	< 0.05	< 0.05		0.60
Nickel	U	2455	mg/kg	0.50	32	20	28		24
Lead	U	2455	mg/kg	0.50	7.6	9.0	15		43
Selenium	U	2455	mg/kg	0.25	1.9	0.48	0.56		1.5
Zinc	U	2455	mg/kg	0.50	12	18	59		41
Chromium (Trivalent)	Ν	2490	mg/kg	1.0	7.7	6.0	14		6.5
Chromium (Hexavalent)	Ν	2490	mg/kg	0.50	< 0.50	< 0.50	< 0.50		< 0.50
Mineral Oil (TPH Calculation)	Ν	2670	mg/kg	10	< 10	< 10	< 10		< 10
Aliphatic TPH >C5-C6	N	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Aliphatic TPH >C6-C8	Ν	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Aliphatic TPH >C8-C10	U	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Aliphatic TPH >C10-C12	U	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Aliphatic TPH >C12-C16	U	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Aliphatic TPH >C16-C21	U	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Aliphatic TPH >C21-C35	U	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0

Results - Soil

Client: IGSL		Ch	emtest	Job No.:	22-31072	22-31072	22-31072	22-31072	22-31072
Quotation No.: Q20-19951		Chem	test Sar	nple ID.:	1487838	1487839	1487840	1487841	1487842
Order No.:		Cli	ent Sam	ple Ref.:	180431	180426	180420	180418	180440
		5	Sample I	_ocation:	TP05	TP06	TP07	TP09	TP10
			Sam	ole Type:	SOIL	SOIL	SOIL	SOIL	SOIL
			Top D	epth (m):	2.00	0.50	0.50	0.50	1.50
			Asbe	stos Lab:	DURHAM	DURHAM	DURHAM		DURHAM
Determinand	Accred.	SOP	Units	LOD					
Aliphatic TPH >C35-C44	N	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Total Aliphatic Hydrocarbons	N	2680	mg/kg	5.0	[A] < 5.0	[A] < 5.0	[A] < 5.0		[A] < 5.0
Aromatic TPH >C5-C7	N	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Aromatic TPH >C7-C8	N	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Aromatic TPH >C8-C10	U	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Aromatic TPH >C10-C12	U	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Aromatic TPH >C12-C16	U	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Aromatic TPH >C16-C21	U	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Aromatic TPH >C21-C35	U	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Aromatic TPH >C35-C44	N	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Total Aromatic Hydrocarbons	N	2680	mg/kg	5.0	[A] < 5.0	[A] < 5.0	[A] < 5.0		[A] < 5.0
Total Petroleum Hydrocarbons	N	2680	mg/kg	10.0	[A] < 10	[A] < 10	[A] < 10		[A] < 10
Benzene	U	2760	µg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Toluene	U	2760	µg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Ethylbenzene	U	2760	µg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
m & p-Xylene	U	2760	µg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
o-Xylene	U	2760	µg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Methyl Tert-Butyl Ether	U	2760	µg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		[A] < 1.0
Naphthalene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Acenaphthylene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Acenaphthene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Fluorene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Phenanthrene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Anthracene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	1	[A] < 0.010
Fluoranthene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Pyrene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Benzo[a]anthracene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Chrysene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Benzo[b]fluoranthene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Benzo[k]fluoranthene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Benzo[a]pyrene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Indeno(1,2,3-c,d)Pyrene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Dibenz(a,h)Anthracene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Benzo[g,h,i]perylene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Coronene	N	2800	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010		[A] < 0.010
Total Of 17 PAH's	N	2800	mg/kg	0.20	[A] < 0.20	[A] < 0.20	[A] < 0.20		[A] < 0.20
PCB 28	N	2815	mg/kg	0.0010	[A] < 0.0010	[A] < 0.0010	[A] < 0.0010		[A] < 0.0010
PCB 52	N	2815	mg/kg	0.0010	[A] < 0.0010	[A] < 0.0010	[A] < 0.0010		[A] < 0.0010
<u>Results - Soil</u>

Project: 24188 - Profile Park - Data Centre Site 3 (Ramboll)

Client: IGSL		Ch	emtest .	Job No.:	22-31072	22-31072	22-31072	22-31072	22-31072
Quotation No.: Q20-19951	Chemtest Sample ID.:			1487838	1487839	1487840	1487841	1487842	
Order No.:	Client Sample Ref.:		180431	180426	180420	180418	180440		
	Sample Location:			TP05	TP06	TP07	TP09	TP10	
			Samp	ole Type:	SOIL	SOIL	SOIL	SOIL	SOIL
	Top Depth (m):			2.00	0.50	0.50	0.50	1.50	
	Asbestos Lab:		DURHAM	DURHAM	DURHAM		DURHAM		
Determinand	Accred.	SOP	Units	LOD					
PCB 90+101	N	2815	mg/kg	0.0010	[A] < 0.0010	[A] < 0.0010	[A] < 0.0010		[A] < 0.0010
PCB 118	Ν	2815	mg/kg	0.0010	[A] < 0.0010	[A] < 0.0010	[A] < 0.0010		[A] < 0.0010
PCB 153	N	2815	mg/kg	0.0010	[A] < 0.0010	[A] < 0.0010	[A] < 0.0010		[A] < 0.0010
PCB 138	N	2815	mg/kg	0.0010	[A] < 0.0010	[A] < 0.0010	[A] < 0.0010		[A] < 0.0010
PCB 180	N	2815	mg/kg	0.0010	[A] < 0.0010	[A] < 0.0010	[A] < 0.0010		[A] < 0.0010
Total PCBs (7 congeners)	Ν	2815	mg/kg	0.0010	[A] < 0.0010	[A] < 0.0010	[A] < 0.0010		[A] < 0.0010
Total Phenols	U	2920	mg/kg	0.10	< 0.10	< 0.10	< 0.10		< 0.10

Project: 24100 - Prome Park - Data Centre Site 5 (Ramboli)

Chemtest Job No:	22-31072		Landfill \	Naste Acceptanc	e Criteria			
Chemtest Sample ID:	1487830				Limits			
Sample Ref:	AA171726					Stable, Non-		
Sample ID:						reactive		
Sample Location:	BH02					hazardous	Hazardous	
Top Depth(m):	1.00				Inert Waste	waste in non-	Waste	
Bottom Depth(m):					Landfill	hazardous	Landfill	
Sampling Date:						Landfill		
Determinand	SOP	Accred.	Units					
Total Organic Carbon	2625	U	%	[A] 0.32	3	5	6	
Loss On Ignition	2610	U	%	2.4			10	
Total BTEX	2760	U	mg/kg	[A] < 0.010	6			
Total PCBs (7 congeners)	2815	N	mg/kg	[A] < 0.0010	1			
TPH Total WAC	2670	U	mg/kg	[A] < 10	500			
Total Of 17 PAH's	2800	N	mg/kg	[A] < 0.20	100			
рН	2010	U		8.5		>6		
Acid Neutralisation Capacity	2015	N	mol/kg	0.036		To evaluate	To evaluate	
Eluate Analysis	10:1 Eluate			10:1 Eluate	Limit values	for compliance leaching test		
			mg/l	mg/kg	using B	S 10 I/kg		
Arsenic	1455	U	0.0007	0.0073	0.5	2	25	
Barium	1455	U	< 0.005	< 0.050	20	100	300	
Cadmium	1455	U	< 0.00011	< 0.0011	0.04	1	5	
Chromium	1455	U	< 0.0005	< 0.0050	0.5	10	70	
Copper	1455	U	0.0007	0.0074	2	50	100	
Mercury	1455	U	< 0.00005	< 0.00050	0.01	0.2	2	
Molybdenum	1455	U	0.0051	0.051	0.5	10	30	
Nickel	1455	U	< 0.0005	< 0.0050	0.4	10	40	
Lead	1455	U	< 0.0005	< 0.0050	0.5	10	50	
Antimony	1455	U	< 0.0005	< 0.0050	0.06	0.7	5	
Selenium	1455	U	< 0.0005	< 0.0050	0.1	0.5	7	
Zinc	1455	U	0.003	0.027	4	50	200	
Chloride	1220	U	< 1.0	< 10	800	15000	25000	
Fluoride	1220	U	0.50	5.0	10	150	500	
Sulphate	1220	U	1.8	18	1000	20000	50000	
Total Dissolved Solids	1020	Ν	65	650	4000	60000	100000	
Phenol Index	1920	U	< 0.030	< 0.30	1	-	-	
Dissolved Organic Carbon	1610	U	7.2	72	500	800	1000	

Solid Information	
Dry mass of test portion/kg	0.090
Moisture (%)	21

Waste Acceptance Criteria

Project: 24100 - Prome Park - Data Centre Site 5 (Ramboli)

Chemtest Job No:	22-31072		Landfill V	Naste Acceptanc	e Criteria				
Chemtest Sample ID:	1487832					Limits			
Sample Ref:	AA171721					Stable, Non-			
Sample ID:						reactive			
Sample Location:	BH04					hazardous	Hazardous		
Top Depth(m):	1.00				Inert Waste	waste in non-	Waste		
Bottom Depth(m):					Landfill	hazardous	Landfill		
Sampling Date:						Landfill			
Determinand	SOP	Accred.	Units						
Total Organic Carbon	2625	U	%	[A] 0.52	3	5	6		
Loss On Ignition	2610	U	%	2.4			10		
Total BTEX	2760	U	mg/kg	[A] < 0.010	6				
Total PCBs (7 congeners)	2815	N	mg/kg	[A] < 0.0010	1				
TPH Total WAC	2670	U	mg/kg	[A] < 10	500				
Total Of 17 PAH's	2800	N	mg/kg	[A] < 0.20	100				
pH	2010	U		8.6		>6			
Acid Neutralisation Capacity	2015	N	mol/kg	0.055		To evaluate	To evaluate		
Eluate Analysis	e Analysis 10:1 Eluate			10:1 Eluate	Limit values	for compliance	or compliance leaching test		
			mg/l	mg/kg	using B	S 10 l/kg			
Arsenic	1455	U	0.0004	0.0038	0.5	2	25		
Barium	1455	U	< 0.005	< 0.050	20	100	300		
Cadmium	1455	U	< 0.00011	< 0.0011	0.04	1	5		
Chromium	1455	U	< 0.0005	< 0.0050	0.5	10	70		
Copper	1455	U	0.0005	0.0051	2	50	100		
Mercury	1455	U	< 0.00005	< 0.00050	0.01	0.2	2		
Molybdenum	1455	U	0.0063	0.063	0.5	10	30		
Nickel	1455	U	< 0.0005	< 0.0050	0.4	10	40		
Lead	1455	U	< 0.0005	< 0.0050	0.5	10	50		
Antimony	1455	U	< 0.0005	< 0.0050	0.06	0.7	5		
Selenium	1455	U	< 0.0005	< 0.0050	0.1	0.5	7		
Zinc	1455	U	< 0.003	< 0.025	4	50	200		
Chloride	1220	U	1.0	10	800	15000	25000		
Fluoride	1220	U	0.32	3.2	10	150	500		
Sulphate	1220	U	1.0	10	1000	20000	50000		
Total Dissolved Solids	1020	N	62	620	4000	60000	100000		
Phenol Index	1920	U	< 0.030	< 0.30	1	-	-		
Dissolved Organic Carbon	1610	U	8.6	86	500	800	1000		

Solid Information	
Dry mass of test portion/kg	0.090
Moisture (%)	14

Waste Acceptance Criteria

Project: 24100 - Prome Park - Data Centre Site 5 (Ramboli)

Chemtest Job No:	22-31072				Landfill \	Naste Acceptanc	e Criteria
Chemtest Sample ID:	1487834				Limits		
Sample Ref:	AA171726					Stable, Non-	
Sample ID:						reactive	
Sample Location:	BH06					hazardous	Hazardous
Top Depth(m):	1.00				Inert Waste	waste in non-	Waste
Bottom Depth(m):					Landfill	hazardous	Landfill
Sampling Date:						Landfill	
Determinand	SOP	Accred.	Units				
Total Organic Carbon	2625	U	%	[A] 0.63	3	5	6
Loss On Ignition	2610	U	%	2.7			10
Total BTEX	2760	U	mg/kg	[A] < 0.010	6		
Total PCBs (7 congeners)	2815	N	mg/kg	[A] < 0.0010	1		
TPH Total WAC	2670	U	mg/kg	[A] < 10	500		
Total Of 17 PAH's	2800	N	mg/kg	[A] < 0.20	100		
рН	2010	U		8.6		>6	
Acid Neutralisation Capacity	2015	N	mol/kg	0.093		To evaluate	To evaluate
Eluate Analysis	Analysis 10:1 Eluate			10:1 Eluate	Limit values	for compliance	eaching test
			mg/l	mg/kg	using B	S 10 l/kg	
Arsenic	1455	U	0.0003	0.0032	0.5	2	25
Barium	1455	U	< 0.005	< 0.050	20	100	300
Cadmium	1455	U	< 0.00011	< 0.0011	0.04	1	5
Chromium	1455	U	< 0.0005	< 0.0050	0.5	10	70
Copper	1455	U	0.0008	0.0083	2	50	100
Mercury	1455	U	< 0.00005	< 0.00050	0.01	0.2	2
Molybdenum	1455	U	0.0067	0.067	0.5	10	30
Nickel	1455	U	0.0005	0.0050	0.4	10	40
Lead	1455	U	< 0.0005	< 0.0050	0.5	10	50
Antimony	1455	U	< 0.0005	< 0.0050	0.06	0.7	5
Selenium	1455	U	< 0.0005	< 0.0050	0.1	0.5	7
Zinc	1455	U	< 0.003	< 0.025	4	50	200
Chloride	1220	U	< 1.0	< 10	800	15000	25000
Fluoride	1220	U	0.36	3.6	10	150	500
Sulphate	1220	U	< 1.0	< 10	1000	20000	50000
Total Dissolved Solids	1020	N	59	580	4000	60000	100000
Phenol Index	1920	U	< 0.030	< 0.30	1	-	-
Dissolved Organic Carbon	1610	U	6.0	60	500	800	1000

Solid Information							
Dry mass of test portion/kg	0.090						
Moisture (%)	13						

Waste Acceptance Criteria

Project: 24100 - Prome Park - Data Centre Site 5 (Ramboli)

Chemtest Job No:	22-31072		Landfill V	Naste Acceptanc	e Criteria			
Chemtest Sample ID:	1487836				Limits			
Sample Ref:	180428					Stable, Non-		
Sample ID:						reactive		
Sample Location:	TP03					hazardous	Hazardous	
Top Depth(m):	0.60				Inert Waste	waste in non-	Waste	
Bottom Depth(m):					Landfill	hazardous	Landfill	
Sampling Date:						Landfill		
Determinand	SOP	Accred.	Units					
Total Organic Carbon	2625	U	%	[A] 0.26	3	5	6	
Loss On Ignition	2610	U	%	1.3			10	
Total BTEX	2760	U	mg/kg	[A] < 0.010	6			
Total PCBs (7 congeners)	2815	N	mg/kg	[A] < 0.0010	1			
TPH Total WAC	2670	U	mg/kg	[A] < 10	500			
Total Of 17 PAH's	2800	N	mg/kg	[A] < 0.20	100			
рН	2010	U		8.7		>6		
Acid Neutralisation Capacity	2015	N	mol/kg	0.037		To evaluate	To evaluate	
Eluate Analysis	10:1 Eluate			10:1 Eluate	Limit values	for compliance leaching test		
			mg/l	mg/kg	using B	S 10 I/kg		
Arsenic	1455	U	0.0003	0.0028	0.5	2	25	
Barium	1455	U	< 0.005	< 0.050	20	100	300	
Cadmium	1455	U	< 0.00011	< 0.0011	0.04	1	5	
Chromium	1455	U	0.0006	0.0056	0.5	10	70	
Copper	1455	U	0.0007	0.0065	2	50	100	
Mercury	1455	U	< 0.00005	< 0.00050	0.01	0.2	2	
Molybdenum	1455	U	0.0031	0.031	0.5	10	30	
Nickel	1455	U	< 0.0005	< 0.0050	0.4	10	40	
Lead	1455	U	< 0.0005	< 0.0050	0.5	10	50	
Antimony	1455	U	< 0.0005	< 0.0050	0.06	0.7	5	
Selenium	1455	U	< 0.0005	< 0.0050	0.1	0.5	7	
Zinc	1455	U	< 0.003	< 0.025	4	50	200	
Chloride	1220	U	1.3	13	800	15000	25000	
Fluoride	1220	U	0.39	3.9	10	150	500	
Sulphate	1220	U	< 1.0	< 10	1000	20000	50000	
Total Dissolved Solids	1020	Ν	60	600	4000	60000	100000	
Phenol Index	1920	U	< 0.030	< 0.30	1	-	-	
Dissolved Organic Carbon	1610	U	5.9	59	500	800	1000	

Solid Information					
Dry mass of test portion/kg	0.090				
Moisture (%)	11				

Waste Acceptance Criteria

Project: 24100 - Prome Park - Data Centre Site 5 (Ramboli)

Chemtest Job No:	22-31072				LandfIII Waste Acceptance Criteria		
Chemtest Sample ID:	1487837					Limits	
Sample Ref:	180432					Stable, Non-	
Sample ID:						reactive	
Sample Location:	TP04					hazardous	Hazardous
Top Depth(m):	0.50				Inert Waste	waste in non-	Waste
Bottom Depth(m):					Landfill	hazardous	Landfill
Sampling Date:						Landfill	
Determinand	SOP	Accred.	Units				
Total Organic Carbon	2625	U	%	[A] 1.1	3	5	6
Loss On Ignition	2610	U	%	3.2			10
Total BTEX	2760	U	mg/kg	[A] < 0.010	6		
Total PCBs (7 congeners)	2815	N	mg/kg	[A] < 0.0010	1		
TPH Total WAC	2670	U	mg/kg	[A] < 10	500		
Total Of 17 PAH's	2800	N	mg/kg	[A] < 0.20	100		
рН	2010	U		8.2		>6	
Acid Neutralisation Capacity	2015	N	mol/kg	0.0030		To evaluate	To evaluate
Eluate Analysis	10:1 Eluate mg/l			10:1 Eluate	Limit values for compliance leaching		eaching test
				mg/kg	using BS EN 12457 at L/S 10 l/kg		
Arsenic	1455	U	0.0041	0.041	0.5	2	25
Barium	1455	U	< 0.005	< 0.050	20	100	300
Cadmium	1455	U	0.00014	0.0014	0.04	1	5
Chromium	1455	U	0.0042	0.042	0.5	10	70
Copper	1455	U	0.0089	0.089	2	50	100
Mercury	1455	U	< 0.00005	< 0.00050	0.01	0.2	2
Molybdenum	1455	U	0.0015	0.015	0.5	10	30
Nickel	1455	U	0.0086	0.086	0.4	10	40
Lead	1455	U	0.0020	0.020	0.5	10	50
Antimony	1455	U	0.0006	0.0060	0.06	0.7	5
Selenium	1455	U	0.0007	0.0072	0.1	0.5	7
Zinc	1455	U	0.026	0.26	4	50	200
Chloride	1220	U	1.7	17	800	15000	25000
Fluoride	1220	U	0.17	1.7	10	150	500
Sulphate	1220	U	3.1	31	1000	20000	50000
Total Dissolved Solids	1020	N	60	600	4000	60000	100000
Phenol Index	1920	U	< 0.030	< 0.30	1	-	-
Dissolved Organic Carbon	1610	U	16	160	500	800	1000

Solid Information	
Dry mass of test portion/kg	0.090
Moisture (%)	15

Waste Acceptance Criteria

Project: 24100 - Prome Park - Data Centre Site 5 (Ramboli)

Chemtest Job No:	22-31072				LandfIII Waste Acceptance Criteria		
Chemtest Sample ID:	1487838					Limits	
Sample Ref:	180431					Stable, Non-	
Sample ID:						reactive	
Sample Location:	TP05					hazardous	Hazardous
Top Depth(m):	2.00				Inert Waste	waste in non-	Waste
Bottom Depth(m):					Landfill	hazardous	Landfill
Sampling Date:						Landfill	
Determinand	SOP	Accred.	Units				
Total Organic Carbon	2625	U	%	[A] 0.39	3	5	6
Loss On Ignition	2610	U	%	2.6			10
Total BTEX	2760	U	mg/kg	[A] < 0.010	6		
Total PCBs (7 congeners)	2815	N	mg/kg	[A] < 0.0010	1		
TPH Total WAC	2670	U	mg/kg	[A] < 10	500		
Total Of 17 PAH's	2800	N	mg/kg	[A] < 0.20	100		
рН	2010	U		8.6		>6	
Acid Neutralisation Capacity	2015	N	mol/kg	0.071		To evaluate	To evaluate
Eluate Analysis	10:1 Eluate mg/l			10:1 Eluate	Limit values for compliance leaching		eaching test
				mg/kg	using BS EN 12457 at L/S 10 l/kg		
Arsenic	1455	U	0.0003	0.0031	0.5	2	25
Barium	1455	U	< 0.005	< 0.050	20	100	300
Cadmium	1455	U	< 0.00011	< 0.0011	0.04	1	5
Chromium	1455	U	< 0.0005	< 0.0050	0.5	10	70
Copper	1455	U	< 0.0005	< 0.0050	2	50	100
Mercury	1455	U	< 0.00005	< 0.00050	0.01	0.2	2
Molybdenum	1455	U	0.0044	0.044	0.5	10	30
Nickel	1455	U	< 0.0005	< 0.0050	0.4	10	40
Lead	1455	U	< 0.0005	< 0.0050	0.5	10	50
Antimony	1455	U	< 0.0005	< 0.0050	0.06	0.7	5
Selenium	1455	U	0.0007	0.0073	0.1	0.5	7
Zinc	1455	U	< 0.003	< 0.025	4	50	200
Chloride	1220	U	< 1.0	< 10	800	15000	25000
Fluoride	1220	U	0.33	3.3	10	150	500
Sulphate	1220	U	2.0	20	1000	20000	50000
Total Dissolved Solids	1020	Ν	58	580	4000	60000	100000
Phenol Index	1920	U	< 0.030	< 0.30	1	-	-
Dissolved Organic Carbon	1610	U	3.6	< 50	500	800	1000

Solid Information	
Dry mass of test portion/kg	0.090
Moisture (%)	16

Waste Acceptance Criteria

Project: 24100 - Prome Park - Data Centre Site 5 (Ramboli)

Chemtest Job No:	22-31072				Landfill \	Naste Acceptanc	e Criteria
Chemtest Sample ID:	1487839				Limits		
Sample Ref:	180426					Stable, Non-	
Sample ID:						reactive	
Sample Location:	TP06					hazardous	Hazardous
Top Depth(m):	0.50				Inert Waste	waste in non-	Waste
Bottom Depth(m):					Landfill	hazardous	Landfill
Sampling Date:						Landfill	
Determinand	SOP	Accred.	Units				
Total Organic Carbon	2625	U	%	[A] 0.40	3	5	6
Loss On Ignition	2610	U	%	1.1			10
Total BTEX	2760	U	mg/kg	[A] < 0.010	6		
Total PCBs (7 congeners)	2815	N	mg/kg	[A] < 0.0010	1		
TPH Total WAC	2670	U	mg/kg	[A] < 10	500		
Total Of 17 PAH's	2800	N	mg/kg	[A] < 0.20	100		
рН	2010	U		8.8		>6	
Acid Neutralisation Capacity	2015	N	mol/kg	0.053		To evaluate	To evaluate
Eluate Analysis	10:1 Eluate mg/l			10:1 Eluate	Limit values for compliance leaching		eaching test
				mg/kg	using B	S EN 12457 at L/	S 10 I/kg
Arsenic	1455	U	0.0003	0.0031	0.5	2	25
Barium	1455	U	< 0.005	< 0.050	20	100	300
Cadmium	1455	U	< 0.00011	< 0.0011	0.04	1	5
Chromium	1455	U	< 0.0005	< 0.0050	0.5	10	70
Copper	1455	U	< 0.0005	< 0.0050	2	50	100
Mercury	1455	U	< 0.00005	< 0.00050	0.01	0.2	2
Molybdenum	1455	U	0.0072	0.072	0.5	10	30
Nickel	1455	U	< 0.0005	< 0.0050	0.4	10	40
Lead	1455	U	< 0.0005	< 0.0050	0.5	10	50
Antimony	1455	U	< 0.0005	< 0.0050	0.06	0.7	5
Selenium	1455	U	0.0006	0.0055	0.1	0.5	7
Zinc	1455	U	< 0.003	< 0.025	4	50	200
Chloride	1220	U	1.4	14	800	15000	25000
Fluoride	1220	U	0.36	3.6	10	150	500
Sulphate	1220	U	1.4	14	1000	20000	50000
Total Dissolved Solids	1020	N	54	540	4000	60000	100000
Phenol Index	1920	U	< 0.030	< 0.30	1	-	-
Dissolved Organic Carbon	1610	U	15	150	500	800	1000

Solid Information	
Dry mass of test portion/kg	0.090
Moisture (%)	8.9

Waste Acceptance Criteria

Project: 24100 - Prome Park - Data Centre Site 5 (Ramboli)

Chemtest Job No:	22-31072				LandfIII Waste Acceptance Criteria		
Chemtest Sample ID:	1487840					Limits	
Sample Ref:	180420					Stable, Non-	
Sample ID:						reactive	
Sample Location:	TP07					hazardous	Hazardous
Top Depth(m):	0.50				Inert Waste	waste in non-	Waste
Bottom Depth(m):					Landfill	hazardous	Landfill
Sampling Date:						Landfill	
Determinand	SOP	Accred.	Units				
Total Organic Carbon	2625	U	%	[A] 0.99	3	5	6
Loss On Ignition	2610	U	%	2.3			10
Total BTEX	2760	U	mg/kg	[A] < 0.010	6		
Total PCBs (7 congeners)	2815	N	mg/kg	[A] < 0.0010	1		
TPH Total WAC	2670	U	mg/kg	[A] < 10	500		
Total Of 17 PAH's	2800	N	mg/kg	[A] < 0.20	100		
рН	2010	U		8.5		>6	
Acid Neutralisation Capacity	2015	N	mol/kg	0.012		To evaluate	To evaluate
Eluate Analysis	10:1 Eluate mg/l			10:1 Eluate	Limit values	for compliance	eaching test
				mg/kg	using BS EN 12457 at L/S 10 l/kg		
Arsenic	1455	U	0.0038	0.038	0.5	2	25
Barium	1455	U	< 0.005	< 0.050	20	100	300
Cadmium	1455	U	0.00011	0.0011	0.04	1	5
Chromium	1455	U	0.0029	0.029	0.5	10	70
Copper	1455	U	0.0050	0.051	2	50	100
Mercury	1455	U	< 0.00005	< 0.00050	0.01	0.2	2
Molybdenum	1455	U	0.0026	0.026	0.5	10	30
Nickel	1455	U	0.0061	0.061	0.4	10	40
Lead	1455	U	0.0021	0.021	0.5	10	50
Antimony	1455	U	0.0006	0.0063	0.06	0.7	5
Selenium	1455	U	0.0009	0.0086	0.1	0.5	7
Zinc	1455	U	0.016	0.16	4	50	200
Chloride	1220	U	1.8	18	800	15000	25000
Fluoride	1220	U	0.47	4.7	10	150	500
Sulphate	1220	U	2.0	20	1000	20000	50000
Total Dissolved Solids	1020	N	65	650	4000	60000	100000
Phenol Index	1920	U	< 0.030	< 0.30	1	-	-
Dissolved Organic Carbon	1610	U	23	230	500	800	1000

Solid Information						
Dry mass of test portion/kg	0.090					
Moisture (%)	14					

Waste Acceptance Criteria

Project: 24100 - Prome Park - Data Centre Site 5 (Ramboli)

Chemtest Job No:	22-31072				Landfill V	Naste Acceptanc	e Criteria	
Chemtest Sample ID:	1487842					Limits		
Sample Ref:	180440					Stable, Non-		
Sample ID:						reactive		
Sample Location:	TP10					hazardous	Hazardous	
Top Depth(m):	1.50				Inert Waste	waste in non-	Waste	
Bottom Depth(m):					Landfill	hazardous	Landfill	
Sampling Date:						Landfill		
Determinand	SOP	Accred.	Units					
Total Organic Carbon	2625	U	%	[A] 0.80	3	5	6	
Loss On Ignition	2610	U	%	2.2			10	
Total BTEX	2760	U	mg/kg	[A] < 0.010	6			
Total PCBs (7 congeners)	2815	N	mg/kg	[A] < 0.0010	1			
TPH Total WAC	2670	U	mg/kg	[A] < 10	500			
Total Of 17 PAH's	2800	N	mg/kg	[A] < 0.20	100			
рН	2010	U		8.7	>6			
Acid Neutralisation Capacity	2015	N	mol/kg	0.038		To evaluate	To evaluate	
Eluate Analysis			10:1 Eluate	10:1 Eluate	Limit values for compliance leachin		eaching test	
			mg/l	mg/kg	using B	using BS EN 12457 at L/S 10 I/kg		
Arsenic	1455	U	0.0002	0.0021	0.5	2	25	
Barium	1455	U	< 0.005	< 0.050	20	100	300	
Cadmium	1455	U	< 0.00011	< 0.0011	0.04	1	5	
Chromium	1455	U	< 0.0005	< 0.0050	0.5	10	70	
Copper	1455	U	0.0006	0.0056	2	50	100	
Mercury	1455	U	< 0.00005	< 0.00050	0.01	0.2	2	
Molybdenum	1455	U	0.0079	0.079	0.5	10	30	
Nickel	1455	U	< 0.0005	< 0.0050	0.4	10	40	
Lead	1455	U	< 0.0005	< 0.0050	0.5	10	50	
Antimony	1455	U	< 0.0005	< 0.0050	0.06	0.7	5	
Selenium	1455	U	0.0013	0.013	0.1	0.5	7	
Zinc	1455	U	< 0.003	< 0.025	4	50	200	
Chloride	1220	U	< 1.0	< 10	800	15000	25000	
Fluoride	1220	U	0.31	3.1	10	150	500	
Sulphate	1220	U	1.0	10	1000	20000	50000	
Total Dissolved Solids	1020	N	54	540	4000	60000	100000	
Phenol Index	1920	U	< 0.030	< 0.30	1	-	-	
Dissolved Organic Carbon	1610	U	6.0	60	500	800	1000	

Solid Information	
Dry mass of test portion/kg	0.090
Moisture (%)	9.2

Waste Acceptance Criteria

Deviations

In accordance with UKAS Policy on Deviating Samples TPS 63. Chemtest have a procedure to ensure 'upon receipt of each sample a competent laboratory shall assess whether the sample is suitable with regard to the requested test(s)'. This policy and the respective holding times applied, can be supplied upon request. The reason a sample is declared as deviating is detailed below. Where applicable the analysis remains UKAS/MCERTs accredited but the results may be compromised.

Sample:	Sample Ref:	Sample ID:	Sample Location:	Sampled Date:	Deviation Code(s):	Containers Received:
1487829	AA171725		BH01		A	Amber Glass 250ml
1487829	AA171725		BH01		A	Plastic Tub 500g
1487830	AA171726		BH02		A	Amber Glass 250ml
1487830	AA171726		BH02		A	Plastic Tub 500g
1487831	AA171722		BH03		A	Amber Glass 250ml
1487831	AA171722		BH03		A	Plastic Tub 500g
1487832	AA171721		BH04		A	Amber Glass 250ml
1487832	AA171721		BH04		A	Plastic Tub 500g
1487833	AA171723		BH05		A	Amber Glass 250ml
1487833	AA171723		BH05		А	Plastic Tub 500g
1487834	AA171726		BH06		A	Amber Glass 250ml
1487834	AA171726		BH06		A	Plastic Tub 500g
1487835	180436		TP02		A	Amber Glass 250ml
1487835	180436		TP02		A	Plastic Tub 500g
1487836	180428		TP03		A	Amber Glass 250ml
1487836	180428		TP03		A	Plastic Tub 500g
1487837	180432		TP04		A	Amber Glass 250ml
1487837	180432		TP04		A	Plastic Tub 500g
1487838	180431		TP05		A	Amber Glass 250ml
1487838	180431		TP05		A	Plastic Tub 500g
1487839	180426		TP06		A	Amber Glass 250ml
1487839	180426		TP06		A	Plastic Tub 500q

Deviations

In accordance with UKAS Policy on Deviating Samples TPS 63. Chemtest have a procedure to ensure 'upon receipt of each sample a competent laboratory shall assess whether the sample is suitable with regard to the requested test(s)'. This policy and the respective holding times applied, can be supplied upon request. The reason a sample is declared as deviating is detailed below. Where applicable the analysis remains UKAS/MCERTs accredited but the results may be compromised.

Sample:	Sample Ref:	Sample ID:	Sample Location:	Sampled Date:	Deviation Code(s):	Containers Received:
1487840	180420		TP07		A	Amber Glass 250ml
1487840	180420		TP07		A	Plastic Tub 500g
1487841	180418		TP09		A	Amber Glass 250ml
1487841	180418		TP09		A	Plastic Tub 500g
1487842	180440		TP10		A	Amber Glass 250ml
1487842	180440		TP10		A	Plastic Tub 500g

Test Methods

SOP	Title	Parameters included	Method summary
1010	pH Value of Waters	pH	pH Meter
1020	Electrical Conductivity and Total Dissolved Solids (TDS) in Waters	Electrical Conductivity and Total Dissolved Solids (TDS) in Waters	Conductivity Meter
1220	Anions, Alkalinity & Ammonium in Waters	Fluoride; Chloride; Nitrite; Nitrate; Total; Oxidisable Nitrogen (TON); Sulfate; Phosphate; Alkalinity; Ammonium	Automated colorimetric analysis using 'Aquakem 600' Discrete Analyser.
1455	Metals in Waters by ICP-MS	Metals, including: Antimony; Arsenic; Barium; Beryllium; Boron; Cadmium; Chromium; Cobalt; Copper; Lead; Manganese; Mercury; Molybdenum; Nickel; Selenium; Tin; Vanadium; Zinc	Filtration of samples followed by direct determination by inductively coupled plasma mass spectrometry (ICP-MS).
1610	Total/Dissolved Organic Carbon in Waters	Organic Carbon	TOC Analyser using Catalytic Oxidation
1800	Speciated Polynuclear Aromatic Hydrocarbons (PAH) in Waters by GC-MS	Acenaphthene; Acenaphthylene; Anthracene; Benzo[a]Anthracene; Benzo[a]Pyrene; Benzo[b]Fluoranthene; Benzo[ghi]Perylene; Benzo[k]Fluoranthene; Chrysene; Dibenz[ah]Anthracene; Fluoranthene; Fluorene; Indeno[123cd]Pyrene; Naphthalene; Phenanthrene; Pyrene	Pentane extraction / GCMS detection
1920	Phenols in Waters by HPLC	Phenolic compounds including: Phenol, Cresols, Xylenols, Trimethylphenols Note: Chlorophenols are excluded.	Determination by High Performance Liquid Chromatography (HPLC) using electrochemical detection.
2010	pH Value of Soils	pН	pH Meter
2015	Acid Neutralisation Capacity	Acid Reserve	Titration
2030	Moisture and Stone Content of Soils(Requirement of MCERTS)	Moisture content	Determination of moisture content of soil as a percentage of its as received mass obtained at <37°C.
2040	Soil Description(Requirement of MCERTS)	Soil description	As received soil is described based upon BS5930
2120	Water Soluble Boron, Sulphate, Magnesium & Chromium	Boron; Sulphate; Magnesium; Chromium	Aqueous extraction / ICP-OES
2175	Total Sulphur in Soils	Total Sulphur	Determined by high temperature combustion under oxygen, using an Eltra elemental analyser.
2180	Sulphur (Elemental) in Soils by HPLC	Sulphur	Dichloromethane extraction / HPLC with UV detection
2192	Asbestos	Asbestos	Polarised light microscopy / Gravimetry
2220	Water soluble Chloride in Soils	Chloride	Aqueous extraction and measuremernt by 'Aquakem 600' Discrete Analyser using ferric nitrate / mercuric thiocyanate.
2300	Cyanides & Thiocyanate in Soils	Free (or easy liberatable) Cyanide; total Cyanide; complex Cyanide; Thiocyanate	Allkaline extraction followed by colorimetric determination using Automated Flow Injection Analyser.
2325	Sulphide in Soils	Sulphide	Steam distillation with sulphuric acid / analysis by 'Aquakem 600' Discrete Analyser, using N,N–dimethyl-p-phenylenediamine.
2430	Total Sulphate in soils	Total Sulphate	Acid digestion followed by determination of sulphate in extract by ICP-OES.
2490	Hexavalent Chromium in Soils	Chromium [VI]	Soil extracts are prepared by extracting dried and ground soil samples into boiling water. Chromium [VI] is determined by 'Aquakem 600' Discrete Analyser using 1,5-diphenylcarbazide.
2610	Loss on Ignition	loss on ignition (LOI)	Determination of the proportion by mass that is lost from a soil by ignition at 550°C.
2625	Total Organic Carbon in Soils	Total organic Carbon (TOC)	Determined by high temperature combustion under oxygen, using an Eltra elemental analyser.

Test Methods

SOP	Title	Parameters included	Method summary
2670	Total Petroleum Hydrocarbons (TPH) in Soils by GC-FID	TPH (C6–C40); optional carbon banding, e.g. 3- band – GRO, DRO & LRO*TPH C8–C40	Dichloromethane extraction / GC-FID
2680	TPH A/A Split	Aliphatics: >C5–C6, >C6–C8,>C8–C10, >C10–C12, >C12–C16, >C16–C21, >C21– C35, >C35–C44Aromatics: >C5–C7, >C7–C8, >C8–C10, >C10–C12, >C12–C16, >C16–C21, >C21–C35, >C35–C44	Dichloromethane extraction / GCxGC FID detection
2760	Volatile Organic Compounds (VOCs) in Soils by Headspace GC-MS	Volatile organic compounds, including BTEX and halogenated Aliphatic/Aromatics.(cf. USEPA Method 8260)*please refer to UKAS schedule	Automated headspace gas chromatographic (GC) analysis of a soil sample, as received, with mass spectrometric (MS) detection of volatile organic compounds.
2800	Speciated Polynuclear Aromatic Hydrocarbons (PAH) in Soil by GC-MS	Acenaphthene*; Acenaphthylene; Anthracene*; Benzo[a]Anthracene*; Benzo[a]Pyrene*; Benzo[b]Fluoranthene*; Benzo[ghi]Perylene*; Benzo[k]Fluoranthene; Chrysene*; Dibenz[ah]Anthracene; Fluoranthene*; Fluorene*; Indeno[123cd]Pyrene*; Naphthalene*; Phenanthrene*; Pyrene*	Dichloromethane extraction / GC-MS
2815	Polychlorinated Biphenyls (PCB) ICES7Congeners in Soils by GC-MS	ICES7 PCB congeners	Acetone/Hexane extraction / GC-MS
2920	Phenols in Soils by HPLC	Phenolic compounds including Resorcinol, Phenol, Methylphenols, Dimethylphenols, 1- Naphthol and TrimethylphenolsNote: chlorophenols are excluded.	60:40 methanol/water mixture extraction, followed by HPLC determination using electrochemical detection.
640	Characterisation of Waste (Leaching C10)	Waste material including soil, sludges and granular waste	ComplianceTest for Leaching of Granular Waste Material and Sludge

Key

- U UKAS accredited
- M MCERTS and UKAS accredited
- N Unaccredited
- S This analysis has been subcontracted to a UKAS accredited laboratory that is accredited for this analysis
- SN This analysis has been subcontracted to a UKAS accredited laboratory that is not accredited for this analysis
- T This analysis has been subcontracted to an unaccredited laboratory
- I/S Insufficient Sample
- U/S Unsuitable Sample
- N/E not evaluated
- < "less than"
- > "greater than"
- SOP Standard operating procedure
- LOD Limit of detection

Comments or interpretations are beyond the scope of UKAS accreditation The results relate only to the items tested

Uncertainty of measurement for the determinands tested are available upon request None of the results in this report have been recovery corrected

All results are expressed on a dry weight basis

The following tests were analysed on samples as received and the results subsequently corrected to a dry weight basis TPH, BTEX, VOCs, SVOCs, PCBs, Phenols

For all other tests the samples were dried at < 37°C prior to analysis

All Asbestos testing is performed at the indicated laboratory

Issue numbers are sequential starting with 1 all subsequent reports are incremented by 1

Sample Deviation Codes

- A Date of sampling not supplied
- B Sample age exceeds stability time (sampling to extraction)
- C Sample not received in appropriate containers
- D Broken Container
- E Insufficient Sample (Applies to LOI in Trommel Fines Only)

Sample Retention and Disposal

All soil samples will be retained for a period of 30 days from the date of receipt All water samples will be retained for 14 days from the date of receipt Charges may apply to extended sample storage

If you require extended retention of samples, please email your requirements to: <u>customerservices@chemtest.com</u>

Appendix 10

Geotechnical Laboratory Test Results (Rock)

		(Diametrial)	POINT LOAD S	TRENGTH	INDEX TEST DATA				ata
Contract: D Date of test:	ata Centre P - Profile Par 12/09/20	rojects 3 k)22	Sample Type: Contract no. 24	Core 4188					IGSL
RC No.	Depth	D (Diameter)	P (failure load)	F	Is (index strength)	ls(50) (index	*UCS		
	m	mm	kN		Мра	strength) Mpa	MPa	Туре	Orienation
RC01	3.9	78	26.0	1.222	4.27	5.22	104	d	//
	5.5	78	14.0	1.222	2.30	2.81	56	d	//
	7.4	78	25.0	1.222	4.11	5.02	100	d	//
	8.5	78	30.0	1.222	4.93	6.02	120	d	//
	9.3	78	6.0	1.222	0.99	1.20	24	d	//
RC02	3.6	78	22.0	1.222	3.62	4.42	88	d	//
	5.9	78	21.0	1.222	3.45	4.22	84	d	
	7.2	78	4.0	1.222	0.66	0.80	16	d	
	8.9	78	12.0	1.222	1.97	2.41	48	d	//
	9.8	78	18.0	1.222	2.96	3.61	72	d	//
RC03	4.7	78	2.0	1.222	0.33	0.40	8	d	//
	5.4	78	26.0	1.222	4.27	5.22	104	d	//
	8.1	78	14.0	1.222	2.30	2.81	56	d	//
	9.4	78	20.0	1.222	3.29	4.02	80	d	//
	10.8	78	15.0	1.222	2.47	3.01	60	d	11
RC04	3.3	78	19.0	1.222	3.12	3.81	76	d	//
	4.7	78	8.0	1.222	1.31	1.61	32	d	//
	7.7	78	10.0	1.222	1.64	2.01	40	d	//
	8.9	78	20.0	1.222	3.29	4.02	80	d	//
	9.9	78	21.0	1.222	3.45	4.22	84	d	//
								d	//
								d	//
Sta	tistical Sumn	nary Data	ls(50)	UCS*	*UCS Normal	Distribution Cur	ve	Ab	breviations
Number of S	amples Teste	d	20	20	0.3			i	irregular
Minimum			0.40	8	0.25			а	axial
Average			3.34	67	0.23			b	block
Maximum			6.02	120	0.2 + / \			d	diametral
Standard Dev	v.		1.57	31	0.15 + /				
Upper 95% Confidence Limit 6.42 128.48			0.1	\		appro	ox. orientation		
Lower 95% Confidence Limit 0.26 5.24				\backslash		to	planes of		
					0.05	\mathbf{X}		weak	ness/bedding
Comments:					0 ++			U	unknown
*UCS taken a	as k x Point L	oad ls(50): k=		20	0 10	0 200	300	Р	perpendicular
								//	parallel

		(Diametrial)	POINT LOAD S	TRENGTH	INDEX TEST DATA				ato
Contract: D	ata Centre P - Profile Par : 12/09/20	rojects 3 k)22	Sample Type: Contract no. 24	Core 4188					IGSL
RC No.	Depth	D (Diameter)	P (failure load)	F	Is (index strength)	ls(50) (index	*UCS		
	m	mm	` kN ´		Мра	strength) Mpa	MPa	Туре	Orienation
RC05	3.2	78	22.0	1.222	3.62	4.42	88	d	//
	4.8	78	18.0	1.222	2.96	3.61	72	d	11
	7.7	78	14.0	1.222	2.30	2.81	56	d	11
	8.9	78	20.0	1.222	3.29	4.02	80	d	11
	9.9	78	26.0	1.222	4.27	5.22	104	d	11
RC06	4.7	78	4.0	1.222	0.66	0.80	16	d	11
	5.7	78	22.0	1.222	3.62	4.42	88	d	//
	6.7	78	26.0	1.222	4.27	5.22	104	d	//
	8.4	78	8.0	1.222	1.31	1.61	32	d	//
	9.4	78	24.0	1.222	3.94	4.82	96	d	//
				1000					
Sta Number of S	itistical Sumn	nary Data	IS(50)	10		Distribution Cur	ve	- A0 - :	breviations
Minimum	amples reste	u	10	10					avial
			3 69	7/	0.12			a h	block
Maximum			5 22	104	0.1			d	diametral
Standard De	v.		1.51	30	0.08		_	Ĩ	alaniociai
Upper 95% (Upper 95% Confidence Limit 6.66 133.16			133.16	0.06	+ + - + - + - + - + - + - + - + - + + - + + - + + + - + + + + + + + + + + + + + + + + + + + +		appro	x. orientation
Lower 95% Confidence Limit 0.73 14.62			0.04 + /	\uparrow		to	planes of		
				-	0.02 +/	\rightarrow		weak	ness/beddina
Comments:					0 /			U	unknown
*UCS taken a	as k x Point L	oad ls(50): k=		20	0 10	0 200	300	Р	perpendicular
								//	parallel

Uniaxial C	ompression	Test Report Sh	eet	I.G.S.L.	
Sample Identification					
Contract Name: Job Number: Hole No: Depth (m):	Data Centre Projects 24188 RC01 4.70m	5 3 - Profile Park			
Sample Description					
Colour: Grain size: Weathering Grade: Rock Type:	Dark grey Fine-grained Fresh LIMESTONE				
Weathering Grade Criteria I. Fresh: Unchanged from original state II. Slightly weathered: Slight discolouration, slight weakening III. Moderately weathered: Considerable weakening, penetrative discolouration IV. Highly weathered: Considerable weakening, penetrative discolouration, breaks in hand					
<u>Sample Measurements</u>			<u>Sketch of Fail</u>	ire Surfaces	
Length Diameter (Ø) Testing	200 78.1]mm			
Load Rate Load at Failure (P)	4.3 134	kN/min kN			
Strength Calculations					
Uniaxial Compressive Strength	=	<u> </u>	0 385		
	=	1000 x P ∏ x (Ø/2)^2	_		
	=	27.97	(Mpa)		
Bulk Density	=	2.72	(Mg/m ³)		
<u>Notes:</u>					

Uniaxial C	ompression	Test Report She	et	I.G.S.L.	
Sample Identification					
Contract Name: Job Number: Hole No: Depth (m):	Data Centre Projects 24188 RC02 5.20m	s 3 - Profile Park			
Sample Description					
Colour: Grain size: Weathering Grade: Rock Type:	Dark grey Fine-grained Fresh LIMESTONE				
Weathering Grade Criteria I. I. Fresh: Unchanged from original state II. Slightly weathered: Slight discolouration, slight weakening III. Moderately weathered: Considerable weakening, penetrative discolouration IV. Highly weathered: Considerable weakening, penetrative discolouration, breaks in hand					
Sample Measurements			<u>Sketch of Fail</u>	ire Surfaces	
Length Diameter (Ø) Testing	199 78]mm			
Load Rate Load at Failure (P)	4.3 322	kN/min kN			
Strength Calculations					
Uniaxial Compressive Strength	=	<u> </u>	4	-	
	=	1000 x P ∏ x (Ø/2)^2	-		
	=	67.39] (Mpa)		
Bulk Density	=	2.69] (Mg/m ³)		
<u>Notes:</u>					

Uniaxial C	compression ⁻	Test Report She	et	I.G.S.L.	
Sample Identification					
Contract Name: Job Number:	Data Centre Projects 24188	s 3 - Profile Park			
Hole No: Depth (m):	RC03 8.80m				
Sample Description					
Colour:	Dark grey				
Grain size:	Fine-grained				
Weathering Grade:	Fresh				
Rock Type:	LIMESTONE				
Weathering Grade Criteria I. Fresh: II. Slightly weathered: III. Moderately weathered: IV. Highly weathered:	Slight discolouratio Considerable weakening Considerable we	Unchanged from original stat on, slight weakening g, penetrative discolouration eakening, penetrative discolou	te uration, breaks in ha	nd	
<u>Sample Measurements</u>			<u>Sketch of Fail</u>	ure Surfaces	
Length Diameter (Ø)	199 78	mm			
<u>Testing</u> Load Rate	4.3	kN/min			
Load at Failure (P)	134	KN	<u></u>		
_Strength Calculations					
Uniaxial Compressive Strength	1 =	<u> </u>	1		
	=	1000 x P ∏ x (Ø/2)^2	-		
	=	28.04	(Mpa)		
Bulk Density	=	2.67) (Mg/m ³)		
Nataa					
NOLES:					

Uniaxial C	ompression	Test Report She	et	I.G.S.L.
Sample Identification				
Contract Name: Job Number: Hole No: Depth (m):	Data Centre Projects 24188 RC04 6.30m	s 3 - Profile Park		
Sample Description				
Colour: Grain size: Weathering Grade: Rock Type:	Dark grey Fine-grained Fresh LIMESTONE			
Weathering Grade Criteria I. Fresh: II. Slightly weathered: III. Moderately weathered: IV. Highly weathered:	Slight discolouratio Considerable weakening Considerable we	Unchanged from original stat on, slight weakening g, penetrative discolouration eakening, penetrative discolou	te uration, breaks in ha	nd
Sample Measurements			<u>Sketch of Fail</u>	ire Surfaces
Length Diameter (Ø) <u>Testing</u>	203 78]]mm		
Load Rate Load at Failure (P)	4.3 434	kN/min kN		
<u>Strength Calculations</u>				
Uniaxial Compressive Strength	=	<u>434000</u> 4775.94	4	
	=	<u>1000 x P</u> ∏ x (Ø/2)^2	-	
	=	90.83	(Mpa)	
Bulk Density	=	2.65] (Mg/m ³)	
<u>Notes:</u>				

Uniaxial C	ompression ⁻	Test Report She	et	I.G.S.L.
Sample Identification				
Contract Name: Job Number: Hole No:	Data Centre Projects 24188 RC05	3 - Profile Park		
Depth (m):	4.30m			
Sample Description				
Colour:	Dark grey			
Grain size:	Fine-grained			
Weathering Grade:	Fresh			
Rock Type:	LIMESTONE			
<u>Weathering Grade Criteria</u> I. Fresh: II. Slightly weathered: III. Moderately weathered: IV. Highly weathered:	Slight discolouratio Considerable weakening Considerable we	Unchanged from original sta on, slight weakening g, penetrative discolouration eakening, penetrative discolou	te uration, breaks in ha	nd
<u>Sample Measurements</u>		_	<u>Sketch of Fail</u>	ire Surfaces
Length	202			
Load Rate Load at Failure (P)	4.3 490	_mm _kN/min _kN		
<u>Strength Calculations</u>				
Uniaxial Compressive Strength	=	<u>490000</u> 4775.94	4	
	=	<u>1000 x P</u> ∏ x (Ø/2)^2	-	
	=	102.55	(Mpa)	
Bulk Density	=	2.68	(Mg/m ³)	
Notes:				

Uniaxial C	compression	Test Report She	et	I.G.S.L.
Sample Identification				
Contract Name:	Data Centre Projects	3 - Profile Park		
Hole No.	RC06			
Depth (m):	5.80m			
<u>Sample Description</u>				
Colour:	Dark grey			
Grain size:	Fine-grained			
Weathering Grade:	Fresh			
Rock Type:	LIMESTONE			
Weathering Grade Criteria I. Fresh: II. Slightly weathered: III. Moderately weathered: IV. Highly weathered:	Slight discolouratio Considerable weakening Considerable we	Unchanged from original sta on, slight weakening g, penetrative discolouration eakening, penetrative discolou	te uration, breaks in ha	nd
<u>Sample Measurements</u>		_	<u>Sketch of Failu</u>	ire Surfaces
Length	188	_		
Diameter (Ø) <u>Testing</u> Load Rate Load at Failure (P)	4.3 229	_mm _kN/min _kN		
<u>Strength Calculations</u>				
Uniaxial Compressive Strength	1 =	229000 4775.94	4	
	=	1000 x P ∏ x (Ø/2)^2	-	
	=	47.92	(Mpa)	
Bulk Density	=	2.64] (Mg/m ³)	
<u>Notes:</u>				

Appendix 11

Exploratory Hole Location Plan



Technical Appendix 12.2: Contaminated Land Interpretative Report

Volume 3: Technical Appendices Technical Appendix 12.2: Contaminated Land Interpretative Report Intended for Vantage Data Centers DUB11 Limited Date September 2022

Project Number 1620014883

VANTAGE DUBLIN DATA CENTERS DUB13 CONTAMINATED LAND INTERPRETATIVE REPORT



VANTAGE DUBLIN DATA CENTERS DUB-13 CONTAMINATED LAND INTERPRETATIVE REPORT

Project Name	Vantage Dublin Data Centers DUB-13
Project No.	1620014883
Recipient	Vantage Data Centers DUB 11 Limited
Issue No.	P01
Document type	Report
Date	16/09/2022
Made by	Viktoriya Grygoryshchak
Checked by	Hazel Comyn
Approved by	Phil Studds
Document no.	1620014883-CLIR-01
Intended for	For Information
purpose	

Made

by: 11 Comm

Checked/Approved by:

Disclaimer

This report is produced by Ramboll at the request of the client for the purposes detailed herein. This report and accompanying documents are intended solely for the use and benefit of the client for this purpose only and may not be used by or disclosed to, in whole or in part, any other person without the express written consent of Ramboll. Ramboll neither owes nor accepts any duty to any third party and shall not be liable for any loss, damage or expense of whatsoever nature which is caused by their reliance on the information contained in this report.

Version Control Log

Revision	Date	Made by	Checked by	Approved by	Description
P01	14/10/2022	VG	НС	PS	Final issue

Ramboll UK Limited 1 Broad Gate The Headrow Leeds LS1 8EQ United Kingdom T 0113 245 7552 www.ramboll.co.uk

CONTENTS

1.	INTRODUCTION	4
1.1	Brief	4
1.2	Previous Reports	4
1.3	Proposed Development	4
1.4	Objectives	4
1.5	Scope of Works	5
1.6	General Limitations and Reliance	5
2.	SITE SETTING	6
2.1	Site details	6
2.2	Potential sources of contamination	6
3.	GROUND INVESTIGATION	7
3.1	Investigation Design	7
3.2	Ground Investigation Activities	7
4.	GROUND CONDITIONS ENCOUNTERED	8
4.1	Ground Conditions	8
4.2	Groundwater	8
4.3	Field Evidence of Contamination	8
5.	HUMAN HEALTH ASSESSMENT	9
5.1	Assessment Approach	9
5.2	Results	9
6.	WATER ENVIRONMENT ASSESSMENT	10
6.1	Assessment Approach	10
6.2	Water Analytical Results	10
7.	SOURCE-PATHWAY-RECEPTOR RISK ASSESSMENT	11
8.	SOIL WASTE MANAGEMENT	12
8.1	Methodology	12
8.2	Soils Assessment	12
8.3	Landfill Acceptance Criteria Testing	12
8.4	Summary	12
9.	CONCLUSIONS AND RECOMMENDATIONS	13
9.1	Conclusions	13
9.2	Recommendations	13

APPENDICES

Appendix 1 FIGURES AND DRAWINGS

Appendix 2 GENERIC QUANTITATIVE RISK ASSESSMENT SCREENING SHEETS

Appendix 3 HAZWASTEONLINE[™] WASTE CLASSIFICATION

1. INTRODUCTION

1.1 Brief

Ramboll UK Limited (Ramboll) has been appointed by Vantage Data Centers DUB 11 Ltd (hereby referred to as Vantage, the Client) to support the proposed development of a data center (the 'proposed development') on the Profile Park Site, Kilcarbery (the 'site'), situated within the jurisdiction of South Dublin County Council (SDCC).

This report provides an assessment of risks associated with ground contamination. This report does not cover any issues other than those relating to contaminated land. For example, no geotechnical, ecological or archaeological studies are included in the scope of this report.

1.2 Previous Reports

An Environmental Impact Assessment Report (EIAR) has been prepared for Vantage - in accordance with the statutory procedures set out in the Planning and Development Act 2000 (as amended)¹ (the 'Act') and the Planning and Development Regulations 2001 (as amended)² (the 'Regulations') – to accompany an application (the 'application') seeking permission (also known as 'full permission') for a proposed data center (the 'proposed development') on the Profile Park Site, Kilcarbery (the 'site').

Geology and soils (and contamination) desk study information has been provided in Chapter 6 of the EIAR covering ground conditions and site history which allowed an initial indication of potential ground contamination risks at the site. A ground investigation was completed by IGSL Ltd. in September 2022 to provide data on ground conditions and quantify any ground contamination impacts in soils and groundwater/surface water at the site. This was provided to Ramboll in the following document: IGSL Ltd, 2022. Data Centre Project 3 Profile Park Ground Investigation Report Factual Project No 24188 (Draft).

This contaminated land risk assessment is based on the factual information provided by IGSL Ltd, 2022.

1.3 Proposed Development

In summary, the proposed development would comprise the following:

- Demolition of the existing double-story dwelling and three outbuildings/sheds;
- Erection of DUB-13 along with associated emergency generators and flues with a gross floor area of approximately 12,893 m²;; and
- Provision of 60 car parking spaces and 26 bicycle parking spaces provision.

DUB-13 would comprise a two-storey data center of 12,893 m². The data storage facility would also include data storage rooms; associated electrical and mechanical plant rooms; loading bay; maintenance and storage space; office administration areas; plant at roof level; 13 double stacked standby generators with integral fuel tanks for emergency power to the data halls, admin and ancillary spaces with associated flues, each 22.3 m in height (95.95 m AOD) located to the south of the building; a house generator with integral fuel tanks that would provide emergency power to the admin and ancillary spaces; and a fuelling area to serve the proposed emergency generators.

1.4 Objectives

The objective of this report is to identify potential contaminated land risks and constraints associated with the ground conditions in the context of the proposed development, in accordance with current relevant legislation and guidance.

¹ Government of Ireland, 2000. Planning and Development Act 2000 (as amended). ISB. S.I. No. 30/2000.

² Government of Ireland, 2001-2019. Planning and Development Regulations 2001 (as amended). S.I. No. 600 of 2001. ISB.

1.5 Scope of Works

The scope of works includes:

- Review of the IGSL Ltd, 2022 report to provide a discussion of environmental ground conditions across the site;
- Interpretation of the IGSL Ltd, 2022 data to provide a Generic Quantitative Risk Assessment which provides an initial screen of potential ground contamination risks associated with the proposed development;
- Provide comment on soil waste management;
- Present a refined Conceptual Site Model (CSM) and qualitative risk assessment based on the findings of the ground investigations and data interpretation using the source-pathwayreceptor methodology; and
- Present recommendations based on the findings of the ground investigation and the refined CSM.

1.6 General Limitations and Reliance

This report has been prepared by Ramboll exclusively for the intended use by the Client in accordance with the agreement between Ramboll and the Client defining, among others, the purpose, the scope and the terms and conditions for the services. No other warranty, expressed or implied, is made as to the professional advice included in this report or in respect of any matters outside the agreed scope of the services or the purpose for which the report and the associated agreed scope were intended or any other services provided by Ramboll.

In preparation of the report and performance of any other services, Ramboll has relied upon publicly available information, information provided by the client and information provided by third parties. Accordingly, the conclusions in this report are valid only to the extent that the information provided to Ramboll was accurate, complete and available to Ramboll within the reporting schedule.

Ramboll's services are not intended as legal advice, nor an exhaustive review of site conditions and/ or compliance. This report and accompanying documents are initial and intended solely for the use and benefit of the client for this purpose only and may not be used by or disclosed to, in whole or in part, any other person without the express written consent of Ramboll. Ramboll neither owes nor accepts any duty to any third party, unless formally agreed by Ramboll through that party entering into, at Ramboll's sole discretion, a written reliance agreement.

The site investigation works were undertaken during a discrete period of time. The findings and conclusions presented in this report are accordingly factually limited by these circumstances and, unless stated otherwise in the report, are preliminary. The field investigations were restricted to a level of detail necessary to meet the stated objectives of the services. The results of any measurements taken may vary spatially or with time and further confirmatory measurements should be made after any significant period of time has elapsed since the sampling took place. The interpretation of the geological and environmental quality conditions is based on extrapolation from point-source data in a heterogeneous environment. Accordingly, more detailed investigation may be appropriate dependent upon the client objectives.

2. SITE SETTING

2.1 Site details

The site is located at Irish grid reference O 03911 30784, within Profile Park, as shown in Figure 1 in Appendix 1. Geographically, the site is located in Profile Park, approximately 10 kilometres (km) to the south-west of Dublin city centre, within South Dublin County.

The site is a roughly rectangular parcel of agricultural land, with a residential dwelling located in the north-west corner of the site. The site covers a total area of 3.79 ha and lies at an elevation between approximately 74 and 75 m Above Ordnance Datum (m AOD).

The site boundaries are defined by:

- New Nangor Road (R134) to the north;
- Falcon Avenue, Equinix and Grange Castle Golf Club to the east;
- Falcon Avenue to the south; and
- The consented Vantage data centre development (planning reference SD21A/0241) to the west, currently agricultural fields.

The site consists of mostly flat agricultural land, with a residential property present towards the north-west of the site and outbuildings in the south-east. A track is present providing entrance to the field from the northern site boundary and towards the outbuildings.

The site's surrounding context predominantly comprises Profile Park and industrial development to the north, Grange Castle Golf Club to the east beyond which are residential properties, agricultural land and industrial development to the south and the consented Vantage data center development to the west, beyond which is Bolands Car Garage and further data centers (refer to Figure 2 in Appendix 1). The existing Baldonnel stream runs adjacent to the southern boundary of the site and enters the southern section of the site, orientated in a north-west to south-east direction, flowing towards the east.

The site can currently be accessed from three access points, two from the north off New Nangor Road (R134), and one from Falcon Avenue on the eastern border, which leads to a roundabout on the R134 New Nangor Road.

2.2 Potential sources of contamination

Due to the lack of development at the site and the historical agricultural use, the risk of contaminated soils being present onsite is considered low. There is a potential risk, albeit low, associated with migration of contaminants from the adjacent Bolands Garage, although it is noted that this land use is hydraulically down/cross gradient from the site.

A ground investigation was designed and completed to establish the presence of and quantify any ground contamination risks.

3. GROUND INVESTIGATION

3.1 Investigation Design

A ground investigation strategy was developed by Ramboll in consultation with the client and based on the findings of our previous Phase I ESA and proposed development design information. The investigation comprised of geotechnical and environmental ground investigation works. Ramboll appointed IGSL LTD, a Ramboll approved supplier, to undertake specific aspects of the intrusive investigation works.

The results of the geotechnical assessment are not discussed in this report.

3.2 Ground Investigation Activities

The ground investigation was undertaken by IGSL between July and August 2022. All works completed are detailed in the below referenced factual report which should be read in conjunction with this interpretative report:

• IGSL Ltd, 2022. Data Center Project 3 Profile Park. Ground Investigation Report – Factual. Project No 24188 (September 2022).

In summary the ground investigation works comprised:

- Trial pits (10 No.) advanced to between 1.8 m and 2.7 m below ground level (bgl);
- Cable percussive boreholes (6 No.) advanced to between 1.90 m and 2.0 mbgl with in-situ Standard Penetration Tests (SPTs);
- Rotary core drillholes (6 No.) all installed with groundwater monitoring wells;
- Plate load tests (10 No.);
- Geophysical survey (in-situ resistivity);
- Groundwater monitoring; and
- Surveying of exploratory locations.

Soil samples were submitted to Chemtest UK for laboratory testing of a range of determinands. No particular types of potential contaminants were identified from the current and historical use of the site, and therefore the 2022 ground investigation carried out by IGSL included a typical contaminated land chemical testing suite comprising of; heavy metals, total petroleum hydrocarbons (TPHs), asbestos, organic contaminants such as polycyclic aromatic hydrocarbons (PAHs) and polychlorinated biphenyls (PCBs).

All factual data including exploratory hole logs, and laboratory certificates are provided within the aforementioned IGSL Ltd, 2022.

Exploratory hole and sampling locations are shown on Figure 3, reproduced in Appendix 1.

4. GROUND CONDITIONS ENCOUNTERED

4.1 Ground Conditions

The ground conditions encountered on site during the ground investigation (IGSL Ltd, 2022) are described in Table 4.1 below.

Table 4.1: Summary of encountered ground conditions

Stratum	Typical Description	Range of Depth encountered (m bgl – below ground level)	Range of Thickness Encountered (m)
Topsoil	Topsoil	Ground level	0 – 0.50
Made Ground	Granular fill Encountered in TP06, BH03 (part of track leading to the outbuildings in the south-west of the site).	Ground level – 0.20	0 - 0.30
Glacial deposits	Firm to stiff brown and grey sandy and gravelly SILT/CLAY with occasional cobbles	0.30 – 0.50	1.00 - 1.40
Limestone	Grey sandy clayey angular GRAVEL with occasional boulders (possible weathered rock) Encountered in trial pits TP01	1.50 – 1.90	Not proven
	to TP10, with no known base.		

The ground conditions encountered across the site are generally comparable to the geology described on the GSI map for the area which indicates that the site is underlain by the undifferentiated Dublin Calp Limestone.

4.2 Groundwater

Groundwater strikes were noted as following as seepages or slow ingress in TP06 to TP10 between 1.80 m and 2.0 mbgl.

During IGSL's groundwater monitoring visit, the groundwater resting level was recorded to be between 1.67 m bgl (in RC05, south of the site) and 2.77 m bgl (RC01, north of the site).

4.3 Field Evidence of Contamination

No visual or olfactory observations of contamination noted in either soil or groundwater.

5. HUMAN HEALTH ASSESSMENT

The guidance document entitled 'Guidance on the Management of Contaminated Land and Groundwater at EPA Licensed Sites', published by the Environmental Protection Agency of the Republic of Ireland³ has been referred to when assessing the results of the chemical analyses.

5.1 Assessment Approach

There are no statutory thresholds in Ireland for the assessment of soil contamination. For human health, the EPA recommends the use of GAC (generic assessment criteria), based on the UK Environment Agency Contaminated Land Exposure Assessment (CLEA) model, either produced by the UKEA itself or values generated using the CLEA model by reputable third-party organisations. Where GAC have not been published or if practitioners do not use human health GAC publications, values should be generated by appropriately qualified and experienced professionals using the CLEA model for consistency with the EPA approach.

Ramboll has derived GAC for the interpretation of soil and groundwater chemical analyses. The GAC are threshold-based screening criteria, below which a significant risk is not considered to be present. Contaminants at concentrations above the GAC do not infer an unacceptable risk; rather that further assessment is required to more fully understand potential contamination risks.

The Ramboll GAC for human health assessment are based on the generic scenarios outlined in the CLEA methodology and guidance documents, and include inhalation, ingestion, dermal contact of/with soil and dust and inhalation of volatiles as pathways for commercial and residential scenarios, as well as ingestion of homegrown produce for residential with gardens scenario. These have been calculated by use of CLEA Version 1.071.

Exceedances detected during the GAC screening are assessed further in the context of a qualitative source-pathway-receptor risk assessment presented in Section 7. This assessment has considered risk to human health in the context of the development of the Site for commercial / industrial purposes. As such, Ramboll has referred to GAC for commercial / industrial site use.

5.2 Results

The soil analytical results obtained during the ground investigations have been screened against the Ramboll GAC for commercial/industrial end use suitable for assessment of the proposed data centre use.

A total of nine soil samples were analysed for a range of metals PAHs, TPH and PCBs. The results have been screened against the appropriate GAC; the full screening sheets can be found in Appendix 2 showing all data and comparison to the GAC.

All measured concentrations were below the GAC indicating no significant risks to human health from soils for the proposed site use. PAHs, TPH and PCBs were also all laboratory below detection limits.

³ Available at

https://www.epa.ie/pubs/advice/waste/contaminatedland/contaminatedland/Guidance_on_the_Management_of_Contaminated_Land_ and_Groundwater_at_EPA_Licensed_Sites_FINAL.pdf
6. WATER ENVIRONMENT ASSESSMENT

6.1 Assessment Approach

'Guidance on the Management of Contaminated Land and Groundwater at EPA Licensed Sites' indicates that values for screening of the impact on groundwater may come from several sources, including the European Communities Environmental Objectives (Groundwater) Regulations 2010 (S.I. no. 9 of 2010), the EPA's Groundwater Threshold Values (GTVs), the EPA's Interim Guideline Values (IGVs), and drinking water standards or relevant Environmental Quality Standards (EQSs), these latter for when considering a surface water receptor.

Concentrations of determinands (where detected in excess of laboratory reporting limits,) were assessed against the published quality standards for groundwater for initial screening purposes.

Exceedance of screening criteria does not infer that an unacceptable risk is present. In line with the risk-based approach taken in Ireland, the outcome of the screening is qualitatively assessed in the context of the conceptual Site model, to determine whether there is a viable (or potentially viable) source-pathway-receptor (S-P-R) linkage present between the contamination and a receptor.

If there is no S-P-R linkage (for example there is no pathway for the release to migrate, or a receptor is not present) then it can be inferred that the contamination does not pose a risk.

6.2 Water Analytical Results

Nine soil samples were analysed for leachable contaminants including pH, ammonium and metals. No groundwater samples were analysed.

The leachate concentrations are presented in comparison to the GAC protective of potable water supply and surface water environment in Appendix 2.

Nickel and lead were recorded marginally in exceedance of the bioavailable GAC in two samples. In order to calculate the bioavailable fraction from the measured concentrations, additional site specific parameters are needed which were not include in the analytical suite. However, typically the bioaccessible fraction would be less than half, which would suggest the nickel or lead impacts will not pose a significant risk to the water environment.

No significant risk to the water environment has been identified from the available data.

7. SOURCE-PATHWAY-RECEPTOR RISK ASSESSMENT

Sources:

- There are no potentially significant contaminative activities on-site;
- No significant visual or olfactory field evidence of contamination within soils or groundwater has been found on the site;
- Very low levels of soil contamination were recorded typical of a greenfield site at concentrations that do not present a significant risk to potential receptors have been found on-site;
- No asbestos was detected on site; and
- No significant potential off-site contamination sources have been identified.

In summary, no significant soil or groundwater impacts have been identified which may pose a risk to human health or the water environment based on the data available and the currently development proposals.

In the absence of any contamination sources, no further risk assessment is required.

8. SOIL WASTE MANAGEMENT

8.1 Methodology

The assessment has been undertaken using available soil chemical data and HazWasteOnline[™], a web-based tool for classifying waste. The software utilises UK Environment Agency guidance and European regulations to classify samples in line with current requirements.

8.2 Soils Assessment

The analytical results for nine soil samples were entered into HazWasteOnlineTM to provide a preliminary waste classification assessment. The HazWasteOnlineTM output sheets are provided in Appendix 3.

All of the samples were classified as 'non-hazardous'.

8.3 Landfill Acceptance Criteria Testing

Nine soil samples were submitted for indicative laboratory Waste Acceptance Criteria (WAC) testing. The laboratory testing comprises generation of a leachate from the soil sample, which is subsequently analysed for a specific set of determinants against three landfill acceptance criteria. These are: Inert Waste Landfill, Stable Non-reactive Hazardous Waste (in non-hazardous landfill), and Hazardous Landfill.

The results of the WAC testing are presented in IGSL, 2022.

All nine samples analysed do not exceed the 'Inert Waste Landfill' criteria. Should this material be designated for off-site disposal to landfill, the HazWasteOnline[™] classification report and laboratory WAC testing results should be passed for review by the receiving landfill.

8.4 Summary

Based on the information available, the soils on site will be classed as 'non-hazardous'.

Any material different from the encountered material during the ground investigation, and any material with visible contamination should be separated from the remaining soils.

The classification of waste reported above must be confirmed by the receiving landfill prior to disposal, under Duty of Care. Any material to be disposed of as hazardous or inert must have WAC analysis provided to confirm appropriate class of landfill (with the exception of clean natural strata).

WAC testing was completed on nine samples and indicated that these soils may be suitable for acceptance in an inert landfill.

9. CONCLUSIONS AND RECOMMENDATIONS

9.1 Conclusions

9.1.1 Soil and Groundwater Contamination

No significant ground contamination impacts have been identified which may pose a risk to human health or the water environment based on the data available and the current development proposals.

9.1.2 Soil Waste Management

Based on the information available, the Made Ground will be classed as 'non-hazardous'.

Any material different from the encountered material during the ground investigation, and any material with visible contamination should be separated from the remaining soils.

The classification of waste reported above must be confirmed by the receiving landfill prior to disposal, under Duty of Care. Any material to be disposed of as hazardous or inert must have WAC analysis provided to confirm appropriate class of landfill (with the exception of clean natural strata).

Any material to be disposed of as hazardous or inert waste must have WAC analysis provided to confirm appropriate class of landfill. WAC testing completed on 13 samples and indicated that the soil may be suitable for acceptance in an inert landfill.

9.2 Recommendations

Should the reuse of site won material be required, then best practice dictates that the reuse should be carried out in accordance with an appropriately designed Material Management Plan, typically using procedures given in the CL:AIRE, 2011 Definition of Waste: Code of Practice (DoWCoP).

To conform with DoWCoP, the following items will be required:

- Remedial statement/strategy including, *inter alia*, a methodology for the management of unsuspected contamination which may be encountered during works including for consultation with an appropriately qualified environmental consultant, stockpiling and additional chemical testing / assessment prior to re-use;
- Material management plan (earthworks strategy); and
- Production of a Validation Report.

An environmental watching brief by an appropriately qualified environmental consultant is recommended, in particular during the earthworks phases of development, with subsequent validation sampling in accordance with the methodology outlined within the Material Management Plan/Remediation Strategy. This will allow an independent verification report to be prepared which will be required after works are complete.

CONTAMINATED LAND INTERPRETATIVE REPORT Vantage Dublin Data Centers DUB-13

> APPENDIX 1 FIGURES AND DRAWINGS



Reproduced from Ordnance Survey Map Data with the permission of the Controller of HMSO, Crown Copyright Reserved Licence No. ES 100022432

Figure 1: Site Location

CONTAMINATED LAND INTERPRETATIVE REPORT

Vantage Dublin Data Centers DUB-13



Esri, Intermap, NASA, NGA, USGS, Esri UK, Esri, HERE, Garmin, Foursquare, GeoTechnologies, Inc, METI/NASA, USGS

Figure 2: Surrounding Land Uses Plan



Figure 3: Exploratory Hole Location Plan

CONTAMINATED LAND INTERPRETATIVE REPORT Vantage Dublin Data Centers DUB-13

> APPENDIX 2 GENERIC QUANTITATIVE RISK ASSESSMENT SCREENING SHEETS

APPENDIX 2 GROUND INVESTIGATION DESIGN SCOPE

From: James Mayer <james.m@iepinnacle.com> Sent: 13 May 2021 21:06 To: paulquigley@igsl.ie Subject: Profile Park, Grange Castle, Dublin

Hi Paul

We are looking at the above development for our client for an industrial project (refer site location plan below).



Refer attached for a site plan indicating trial pits, borehole and CBR test locations - could you provide us with a price and programme to undertake the site investigation works to include for the following:-

DUB13, Dublin

- 13 No trial Pits across the site as indicated on the attached plan
- 17 No boreholes (with ground water installations)
- 3 No Rotary Boreholes
- CBR test Across the site (trial Pits)
- Allowance should be made for geotechnical testing to confirm bearing pressures across the site to support 2 storey industrial building (up to 4500KN column loads), identification of various strata and testing of soils for reuse within ground works across the site (lime/cement stabilisation is being considered), but also an understanding of their natural properties for reuse
- Logging of ground water across the site
- Environmental sampling of soil and ground water from across the site
- Waste Classification of soil across the site
- Allow for 4No. Infiltration tests (locations to be confirmed)
- Interpretive Geotechnical and Environmental Report

Please could you provide your budget quote and programme on or before Wednesday 20th May, could you also provide a programme for start on site, initial reporting (boreholes and trial pit logs) and timescales for final report based on your current commitments.

Should you have any comments or queries, please do not hesitate to contact us.

Regards

James Mayer MEng MIEI in Director



james.m@iepinnacle.com

Grosvenor Court, 67a Patrick Street, Dun Laoghaire, County Dublin D: +353 1 2311041 M: +353 8 76186300 S: +353 1 2311041 www.pinnacleconsultingengineers.com

NORWICH I LONDON I WELWYN GARDEN CITY I DUBLIN I THE HAGUE I FRANKFURT

DUB13, Dublin

APPENDIX 3 GENERIC QUANTITATIVE RISK ASSESSMENT SCREENING SHEETS

					BH02	BH04	BH06	TP03	TP04	TP05	TP06	TP07	TP10
					SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
Determinand	Туре	Units	DWS	EQS	1.00	1.00	1.00	0.60	0.50	2.00	0.50	0.50	1.50
pН	10:1				8.1	8.2	8.2	8.3	7.8	8.1	8.4	8.0	8.3
Ammonium	10:1	mg/l	0.5	0.3	0.068	0.070	0.080	< 0.050	0.16	0.051	< 0.050	0.082	0.072
Arsenic	10:1	mg/l	0.01	0.0250	0.0007	0.0004	0.0003	0.0003	0.0041	0.0003	0.0003	0.0038	0.0002
Barium	10:1	mg/l			< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005
Cadmium	10:1	mg/l	0.005	0.00008- 0.00025	< 0.00011	< 0.00011	< 0.00011	< 0.00011	0.00014	< 0.00011	< 0.00011	0.00011	< 0.00011
Chromium	10:1	mg/l	0.05	0.03	< 0.0005	< 0.0005	< 0.0005	0.0006	0.0042	< 0.0005	< 0.0005	0.0029	< 0.0005
Copper	10:1	mg/l	2	0.0300	0.0007	0.0005	0.0008	0.0007	0.0089	< 0.0005	< 0.0005	0.0050	0.0006
Mercury	10:1	mg/l	0.001	0.001	< 0.00005	< 0.00005	< 0.00005	< 0.00005	< 0.00005	< 0.00005	< 0.00005	< 0.00005	< 0.00005
Molybdenum	10:1	mg/l			0.0051	0.0063	0.0067	0.0031	0.0015	0.0044	0.0072	0.0026	0.0079
Nickel	10:1	mg/l	0.02	0.004 (bio)	< 0.0005	< 0.0005	0.0005	< 0.0005	0.0086	< 0.0005	< 0.0005	0.0061	< 0.0005
Lead	10:1	mg/l	0.01	0.0012 (bio)	< 0.0005	< 0.0005	< 0.0005	< 0.0005	0.0020	< 0.0005	< 0.0005	0.0021	< 0.0005
Antimony	10:1	mg/l			< 0.0005	< 0.0005	< 0.0005	< 0.0005	0.0006	< 0.0005	< 0.0005	0.0006	< 0.0005
Selenium	10:1	mg/l			< 0.0005	< 0.0005	< 0.0005	< 0.0005	0.0007	0.0007	0.0006	0.0009	0.0013
Zinc	10:1	mg/l	5	0.100	0.003	< 0.003	< 0.003	< 0.003	0.026	< 0.003	< 0.003	0.016	< 0.003
Chloride	10:1	mg/l			< 1.0	1.0	< 1.0	1.3	1.7	< 1.0	1.4	1.8	< 1.0
Fluoride	10:1	mg/l			0.50	0.32	0.36	0.39	0.17	0.33	0.36	0.47	0.31
Sulphate	10:1	mg/l			1.8	1.0	< 1.0	< 1.0	3.1	2.0	1.4	2.0	1.0
DWS	https://www.e	pa.ie/publicat	tions/complian	ceenforcement/drink	ing-water/advi	ceguidance/	european-con	nmunities-drin	king-water-no	-2-regulations	-2007.php		
EQS	https://www.le	egislation.gov	.uk/eudr/2008	/105/annex/l									
	https://www.r	te.ie/documer	nts/news/2017	/08/water-quality-in-ire	land-2010-20 ⁷	15.pdf							
	WFD EU legi	slation											

Project: 24188 - Profile Park - Data Centre Site 3 (Ramboll)

Project: 24188 - Profile Park - Data Centre Site 3 (Ramboll)

Client: IGSL				22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072
Quotation No.: Q20-19951				1487829	1487830	1487831	1487832	1487833	1487834	1487835	1487836	1487837	1487838	1487839	1487840	1487841	1487842
Order No.:				AA171725	AA171726	AA171722	AA171721	AA171723	AA171726	180436	180428	180432	180431	180426	180420	180418	180440
				BH01	BH02	BH03	BH04	BH05	BH06	TP02	TP03	TP04	TP05	TP06	TP07	TP09	TP10
				SOIL													
				1.00	1.00	1.00	1.00	1.00	1.00	1.80	0.60	0.50	2.00	0.50	0.50	0.50	1.50
			GAC commercial /		DURHAM		DURHAM		DURHAM		DURHAM	DURHAM	DURHAM	DURHAM	DURHAM		DURHAM
Determinand	Units	LOD	industrial end use														ĺ
АСМ Туре		N/A			-		-		-		-	-	-	-	-		-
Ashestos Identification		Ν/Δ	Presence?		No Asbestos		No Asbestos		No Asbestos		No Asbestos		No Asbestos				
Aspestos identification		IN/A	T Tesence :		Detected		Detected		Detected		Detected	Detected	Detected	Detected	Detected		Detected
Moisture	%	0.020		11	21	12	14	14	13	11	11	15	16	8.9	14	9.3	9.2
pH (2.5:1)		4.0		[A] 8.9		[A] 9.1		[A] 8.6		[A] 8.7						[A] 8.8	1
Boron (Hot Water Soluble)	mg/kg	0.40			[A] < 0.40		[A] < 0.40										
Magnesium (Water Soluble)	g/l	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010						[A] < 0.010	
Sulphate (2:1 Water Soluble) as SO4	g/l	0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010		[A] < 0.010						[A] < 0.010	
Total Sulphur	%	0.010		[A] 0.048		[A] 0.095		[A] 0.073		[A] 0.054						[A] 0.047	
Sulphur (Elemental)	mg/kg	1.0			[A] 1.4		[A] 1.1		[A] 1.6		[A] 1.0	[A] 1.3	[A] < 1.0	[A] < 1.0	[A] 1.5		[A] 1.3
Chloride (Water Soluble)	g/l	0.010		A < 0.010		[A] < 0.010		[A] < 0.010		A < 0.010						A < 0.010	
Nitrate (Water Soluble)	g/I	0.010		< 0.010	[4] 0.50	< 0.010	[4] 0.50	< 0.010	[4] 0.50	< 0.010	[4] 0.50	[4] 0.50	[A] 0.50	[4] 0.50	[4] 0.50	< 0.010	[A] 0.50
Cyanide (Total)	mg/kg	0.50			[A] < 0.50		[A] < 0.50										
Supride (Easily Liberatable)	mg/kg	0.50		. 0.04	[A] 7.4	. 0. 04	[A] 26	0.04	[A] 24	. 0.04	[A] 16	[A] 1.2	[A] 7.0	[A] 39	[A] 1.4	. 0. 04	[A] 0.65
Ammonium (Water Soluble)	g/i	0.01		< 0.01	[4] 0.000	< 0.01	[4] 0.000	< 0.01	[4] 0.040	< 0.01	[4] 0.040	[4] 0.040	[4] 0 04 4	[4] 0.047	[4] 0 004	< 0.01	[4] 0.040
Arconio	-70 ma/ka	0.010	640	[A] 0.020	[A] 0.026	[A] 0.014	[A] 0.026	[A] 0.017	[A] 0.016	[A] 0.031	T 0.019	[A] 0.019	[A] 0.014	IA 0.017	[A] 0.021	[A] 0.02 I	[A] 0.010
Rarium	mg/kg	0.5	22000		0.0		26		02		17	02	4.0	4.0	20		0.9
Cadmium	mg/kg	0.10	22000		12		16		92		0.16	32	0.14	0.40	0.87		0.47
Chromium	mg/kg	0.10	800		8.7		8.0		37		8.0	16	7.7	6.0	14		6.5
Molybdenum	ma/ka	0.5	18000		2.5		33		31		1.3	3.2	2.7	1.8	17		3.5
Antimony	mg/kg	2.0	7400		< 2.0		< 2.0		< 2.0		< 2.0	< 2.0	< 2.0	< 2.0	< 2.0		< 2.0
Copper	mg/kg	0.50	68000		19		22.0		25		16	30	15	13	16		18
Mercury	ma/ka	0.05	1100		0.05		< 0.05		0.05		< 0.05	0.05	< 0.05	< 0.05	< 0.05		0.60
Nickel	ma/ka	0.50	980		27		42		32		23	56	32	20	28		24
Lead	mg/kg	0.50	2300		22		11		16		8.9	26	7.6	9.0	15		43
Selenium	mg/kg	0.25	12000		0.57		0.49		1.0		0.45	1.2	1.9	0.48	0.56		1.5
Zinc	mg/kg	0.50	730000		56		62		71		11	86	12	18	59		41
Chromium (Trivalent)	mg/kg	1.0			8.7		8.9		37		8.0	16	7.7	6.0	14		6.5
Chromium (Hexavalent)	mg/kg	0.50			< 0.50		< 0.50		< 0.50		< 0.50	< 0.50	< 0.50	< 0.50	< 0.50		< 0.50
Mineral Oil (TPH Calculation)	mg/kg	10			< 10		< 10		< 10		< 10	< 10	< 10	< 10	< 10		< 10
Aliphatic TPH >C5-C6	mg/kg	1.0			[A] < 1.0		[A] < 1.0										
Aliphatic TPH >C6-C8	mg/kg	1.0			[A] < 1.0		[A] < 1.0										
Aliphatic TPH >C8-C10	mg/kg	1.0			[A] < 1.0		[A] < 1.0										
Aliphatic TPH >C10-C12	mg/kg	1.0			[A] < 1.0		[A] < 1.0										
Aliphatic TPH >C12-C16	mg/kg	1.0			[A] < 1.0		[A] < 1.0										
Aliphatic TPH >C16-C21	mg/kg	1.0			[A] < 1.0		[A] < 1.0										
Aliphatic TPH >C21-C35	mg/kg	1.0			[A] < 1.0		[A] < 1.0										
Aliphatic TPH >C35-C44	mg/kg	1.0			[A] < 1.0		A < 1.0										
Arometia TDH - C5 C7	mg/kg	5.0			[A] < 5.0		[A] < 5.0										
Aromatic TPH > C7 C9	mg/kg	1.0			[A] < 1.0		[A] < 1.0										
Aromatic TPH >C8-C10	mg/kg	1.0			[A] < 1.0		[A] < 1.0										
Aromatic TPH >C10-C12	mg/kg	1.0			[A] < 1.0		[A] < 1.0										
Aromatic TPH >C12-C16	ma/ka	1.0			[A] < 1.0		[A] < 1.0										
Aromatic TPH >C16-C21	ma/ka	1.0			[A] < 1.0		[A] < 1.0										
Aromatic TPH >C21-C35	ma/ka	1.0			[A] < 1.0		[A] < 1.0										
Aromatic TPH >C35-C44	ma/ka	1.0			[A] < 1.0		[A] < 1.0										
Total Aromatic Hydrocarbons	mg/kg	5.0			[A] < 5.0		[A] < 5.0										
Total Petroleum Hydrocarbons	mg/kg	10.0			[A] < 10		[A] < 10										
Benzene	µg/kg	1.0			[A] < 1.0		[A] < 1.0										
Toluene	µg/kg	1.0			[A] < 1.0		[A] < 1.0										
Ethylbenzene	µg/kg	1.0			[A] < 1.0		[A] < 1.0										
m & p-Xylene	µg/kg	1.0			[A] < 1.0		[A] < 1.0										
o-Xylene	µg/kg	1.0			[A] < 1.0		[A] < 1.0										
Methyl Tert-Butyl Ether	µg/kg	1.0			[A] < 1.0		[A] < 1.0										
Naphthalene	mg/kg	0.010			[A] < 0.010		[A] < 0.010	ļ	[A] < 0.010		[A] < 0.010		[A] < 0.010				
Acenaphthylene	mg/kg	0.010			[A] < 0.010		[A] < 0.010										
Acenaphthene	mg/kg	0.010			[A] < 0.010		[A] < 0.010	1	[A] < 0.010	1	[A] < 0.010	1	[A] < 0.010				

Client: IGSL			22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072	22-31072
Quotation No.: Q20-19951			1487829	1487830	1487831	1487832	1487833	1487834	1487835	1487836	1487837	1487838	1487839	1487840	1487841	1487842
Order No.:			AA171725	AA171726	AA171722	AA171721	AA171723	AA171726	180436	180428	180432	180431	180426	180420	180418	180440
			BH01	BH02	BH03	BH04	BH05	BH06	TP02	TP03	TP04	TP05	TP06	TP07	TP09	TP10
			SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
			1.00	1.00	1.00	1.00	1.00	1.00	1.80	0.60	0.50	2.00	0.50	0.50	0.50	1.50
		GAC commercial	1	DURHAM		DURHAM		DURHAM		DURHAM	DURHAM	DURHAM	DURHAM	DURHAM		DURHAM
Determinand	Units LOD	industrial end use	1													
Fluorene	mg/kg 0.01)		[A] < 0.010		[A] < 0.010										
Phenanthrene	mg/kg 0.01)		[A] < 0.010		[A] < 0.010										
Anthracene	mg/kg 0.01)		[A] < 0.010		[A] < 0.010										
Fluoranthene	mg/kg 0.01)		[A] < 0.010		[A] < 0.010										
Pyrene	mg/kg 0.01)		[A] < 0.010		[A] < 0.010										
Benzo[a]anthracene	mg/kg 0.01)		[A] < 0.010		[A] < 0.010										
Chrysene	mg/kg 0.01)		[A] < 0.010		[A] < 0.010										
Benzo[b]fluoranthene	mg/kg 0.01)		[A] < 0.010		[A] < 0.010										
Benzo[k]fluoranthene	mg/kg 0.01)		[A] < 0.010		[A] < 0.010										
Benzo[a]pyrene	mg/kg 0.01)		[A] < 0.010		[A] < 0.010										
Indeno(1,2,3-c,d)Pyrene	mg/kg 0.01)		[A] < 0.010		[A] < 0.010										
Dibenz(a,h)Anthracene	mg/kg 0.01)		[A] < 0.010		[A] < 0.010										
Benzo[g,h,i]perylene	mg/kg 0.01)		[A] < 0.010		[A] < 0.010										
Coronene	mg/kg 0.01)		[A] < 0.010		[A] < 0.010										
Total Of 17 PAH's	mg/kg 0.20	1		[A] < 0.20		[A] < 0.20										
PCB 28	mg/kg 0.001	0		[A] < 0.0010		[A] < 0.0010										
PCB 52	mg/kg 0.001	0		[A] < 0.0010		[A] < 0.0010										
PCB 90+101	mg/kg 0.001	0		[A] < 0.0010		[A] < 0.0010										
PCB 118	mg/kg 0.001	0		[A] < 0.0010		[A] < 0.0010										
PCB 153	mg/kg 0.001	0		[A] < 0.0010		[A] < 0.0010										
PCB 138	mg/kg 0.001	0		[A] < 0.0010		[A] < 0.0010										
PCB 180	mg/kg 0.001	0		[A] < 0.0010		[A] < 0.0010										
Total PCBs (7 congeners)	mg/kg 0.001	0		[A] < 0.0010		[A] < 0.0010										
Total Phenols	mg/kg 0.10			< 0.10		< 0.10		< 0.10		< 0.10	< 0.10	< 0.10	< 0.10	< 0.10		< 0.10

DUB13, Dublin

APPENDIX 4 HAZWASTEONLINE[™] WASTE CLASSIFICATION

Waste Classification Report

HazWasteOnline[™] classifies waste as either **hazardous** or **non-hazardous** based on its chemical composition, related legislation and the rules and data defined in the current UK or EU technical guidance (Appendix C) (note that HP 9 Infectious is not assessed). It is the responsibility of the classifier named below to:

- a) understand the origin of the waste
- b) select the correct List of Waste code(s)

RAMBOLL



- d) select and justify the chosen metal species (Appendix B)
- e) correctly apply moisture correction and other available corrections
- f) add the meta data for their user-defined substances (Appendix A)

Company:

Ramboll UK Ltd

1 Broad Gate

The Headrow

Leeds

LS1 8EQ

g) check that the classification engine is suitable with respect to the national destination of the waste (Appendix C)

To aid the reviewer, the laboratory results, assumptions and justifications managed by the classifier are highlighted in pale yellow.

Job name

Dub 13

Description/Comments

Project

Name:

Date:

Site

HazWasteOnline[™] provides a two day, hazardous waste classification course that covers the use of the software and both basic and advanced waste classification techniques. Certification has to be renewed every 3 years.

HazWasteOnline™ Certification:

Course Hazardous Waste Classification

Job summary

0113 204 2880

#	Sample name	Depth [m]	Classification Result	Hazard properties	Page
1	BH02	1.00	Non Hazardous		2
2	BH04	1.00	Non Hazardous		4
3	BH06	1.00	Non Hazardous		6
4	TP03	0.60	Non Hazardous		8
5	TP04	0.50	Non Hazardous		10
6	TP05	2.00	Non Hazardous		12
7	TP06	0.50	Non Hazardous		14
8	TP07	0.50	Non Hazardous		16
9	TP10	1.50	Non Hazardous		18

Related documents

#	Name	Description
1	Ramboll Suite B, asbestos +barium	waste stream template used to create this Job

Report

Created by:	Hazel	Comyn	
-------------	-------	-------	--

Appendices	Page
Appendix A: Classifier defined and non GB MCL determinands	20
Appendix B: Rationale for selection of metal species	21
Appendix C: Version	21



Date

50% complete

Created date: 16 Sep 2022 07:59 GMT

S

16 Sep 2022 07:59 GMT

Classified by

Hazel Comyn

Telephone:



Classification of sample: BH02

Non Hazardous Waste Classified as 17 05 04 in the List of Waste

.

Sample details

Sample name:	LoW Code:
BH02	Chapter:
Sample Depth:	
1.00 m	Entry:
Moisture content:	
21%	
(dry weight correction)	

17: Construction and Demolition Wastes (including excavated soil from contaminated sites)17 05 04 (Soil and stones other than those mentioned in 17 05 03)

Hazard properties

None identified

Determinands

Moisture content: 21% Dry Weight Moisture Correction applied (MC)

#		Determinand EU CLP index EC Number CAS Number	CLP Note	User entered data	Conv. Factor	Compound conc.	Classification value	AC Applied	Conc. Not Used
		number	0					2	
1	4	arsenic { arsenic trioxide }		6.8 mg/kg	1.32	7.42 mg/kg	0.000742 %	\checkmark	
		033-003-00-0 215-481-4 1327-53-3							
2	4	barium { barium chloride }		41 mg/kg	1.516	51.38 mg/kg	0.00514 %	\checkmark	
		056-004-00-8 233-788-1 10361-37-2							
3	4	cadmium { cadmium oxide }		1.2 mg/kg	1.142	1.133 mg/kg	0.000113 %	\checkmark	
		048-002-00-0 215-146-2 1306-19-0							
4	4	chromium in chromium(III) compounds { Chromium(III) oxide (worst case) }		8.7 mg/kg	1.462	10.509 mg/kg	0.00105 %	\checkmark	
		215-160-9 1308-38-9							
5	4	copper { <mark>dicopper oxide; copper (I) oxide</mark> }		19 ma/ka	1.126	17.679 ma/ka	0.00177 %	1	
		029-002-00-X 215-270-7 1317-39-1						ľ	
6	4	lead { lead chromate }	1	22 mg/kg	1.56	28.36 ma/ka	0.00182 %	1	
		082-004-00-2 231-846-0 7758-97-6							
7	4	mercury { mercury dichloride }		0.05 mg/kg	1.353	0.0559 mg/kg	0.00000559 %	\checkmark	
		080-010-00-X 231-299-8 7487-94-7						-	
8	4	nickel { nickel chromate }		27 mg/kg	2.976	66.413 mg/kg	0.00664 %	\checkmark	
		028-035-00-7 238-766-5 14721-18-7							
	4	selenium { selenium compounds with the exception of cadmium sulphoselenide and those specified elsewhere	0.57						
9		in this Annex }		0.57 mg/kg	1.405	0.662 mg/kg	0.0000662 %	\checkmark	
		034-002-00-8							
10	4	zinc { <mark>zinc chromate</mark> }		56 ma/ka	2 774	128.39 ma/ka	0 0128 %	./	
		024-007-00-3 236-878-9 13530-65-9						ľ	
11	4	cyanides { salts of hydrogen cyanide with the exception of complex cyanides such as ferrocyanides, ferricyanides and mercuric oxycyanide and those specified elsewhere in this Annex }		<0.5 mg/kg	1.884	<0.942 mg/kg	<0.0000942 %		<lod< td=""></lod<>
		TPH (C6 to C40) petroleum group							
12	-	TPH		<1 mg/kg		<1 mg/kg	<0.0001 %		<lod< td=""></lod<>
12		naphthalene		<0.01 ma/ka		<0.01 ma/ka	<0.000001.9/		
13		601-052-00-2 202-049-5 91-20-3		<0.01 Ilig/kg		<0.01 Ing/kg	<0.000001 %		
14	8	acenaphthylene 205-917-1 208-96-8		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
15	8	acenaphthene		<0.01 mc///c		<0.01 mg//mg	<0.00001.9/		
13		201-469-6 83-32-9		<0.01 Ilig/kg		<0.01 Ing/kg	<0.000001 %		

Page 2 of 22

#		EU CLP index number	Determinand EC Number	CAS Number	CLP Note	User entered data	Conv Facto	r Compound conc.	Classification value	MC Applied	Conc. Not Used
16	8	fluorene	201 695 5	86 73 7		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< th=""></lod<>
17	0	phenanthrene	201-581-5	85-01-8		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
18	0	anthracene	204-371-1	120-12-7		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< th=""></lod<>
19	0	fluoranthene	205-912-4	206-44-0		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
20	٥	pyrene	204-927-3	129-00-0		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
21		benzo[a]anthracen 601-033-00-9	200-280-6	56-55-3		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
22		chrysene 601-048-00-0	205-923-4	218-01-9		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
23		benzo[b]fluoranthe 601-034-00-4	205-911-9	205-99-2	_	<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
24		benzo[k]fluoranthe 601-036-00-5	205-916-6	207-08-9	-	<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
25		benzo[a]pyrene; be 601-032-00-3	enzo[def]chrysene 200-028-5	50-32-8		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
26	8	indeno[123-cd]pyre	ene 205-893-2	193-39-5		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
27		dibenz[a,h]anthrac 601-041-00-2	ene 200-181-8	53-70-3		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
28	۲	benzo[ghi]perylene	e 205-883-8	191-24-2		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
29		asbestos 650-013-00-6		12001-28-4 132207-32-0 12172-73-5 77536-66-4 77536-68-6 77536-67-5 12001-29-5		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
								Iotal	0.0304 %	1	

Key

1.09	
	User supplied data
	Determinand values ignored for classification, see column 'Conc. Not Used' for reason
	Determinand defined or amended by HazWasteOnline (see Appendix A)
4	Speciated Deteminand - Unless the Determinand is Note 1, the Conversion Factor is used to calculate the compound concentration
<lod< td=""><td>Below limit of detection</td></lod<>	Below limit of detection
ND	Not detected
CLP: Note 1	Only the metal concentration has been used for classification



Classification of sample: BH04

Non Hazardous Waste Classified as 17 05 04 in the List of Waste

.

Sample details

Sample name:	LoW Code:
BH04	Chapter:
Sample Depth:	
1.00 m	Entry:
Moisture content:	
14%	
(dry weight correction)	

17: Construction and Demolition Wastes (including excavated soil from contaminated sites)
17 05 04 (Soil and stones other than those mentioned in 17 05 03)

Hazard properties

None identified

Determinands

Moisture content: 14% Dry Weight Moisture Correction applied (MC)

#		EU CLP index EC Number CAS Number	CLP Note	User entered data	Conv. Factor	Compound conc.	Classification value	MC Applied	Conc. Not Used
1	4	arsenic { arsenic trioxide }		7.2 mg/kg	1.32	8.339 mg/kg	0.000834 %	\checkmark	
2	4	barium { barium chloride }		36 mg/kg	1.516	47.884 mg/kg	0.00479 %	\checkmark	
3	4	cadmium { cadmium oxide }		1.6 mg/kg	1.142	1.603 mg/kg	0.00016 %	\checkmark	
4	4	chromium in chromium(III) compounds { Chromium(III) oxide (worst case) } 215-160-9 1308-38-9		8.9 mg/kg	1.462	11.41 mg/kg	0.00114 %	~	
5	4	copper { dicopper oxide; copper (I) oxide } 029-002-00-X 215-270-7 1317-39-1		22 mg/kg	1.126	21.728 mg/kg	0.00217 %	\checkmark	
6	4	lead { lead chromate } 082-004-00-2 231-846-0 7758-97-6	1	11 mg/kg	1.56	15.051 mg/kg	0.000965 %	\checkmark	
7	4	mercury { mercury dichloride } 080-010-00-X 231-299-8 7487-94-7		<0.05 mg/kg	1.353	<0.0677 mg/kg	<0.0000677 %		<lod< td=""></lod<>
8	4	nickel { nickel chromate } 028-035-00-7 238-766-5 [14721-18-7		42 mg/kg	2.976	109.652 mg/kg	0.011 %	\checkmark	
9	4	selenium { selenium compounds with the exception of cadmium sulphoselenide and those specified elsewhere in this Annex } 034-002-00-8		0.49 mg/kg	1.405	0.604 mg/kg	0.0000604 %	~	
10	4	zinc { zinc chromate } 024-007-00-3 236-878-9 13530-65-9		62 mg/kg	2.774	150.875 mg/kg	0.0151 %	\checkmark	
11	*	cyanides { salts of hydrogen cyanide with the exception of complex cyanides such as ferrocyanides, ferricyanides and mercuric oxycyanide and those specified elsewhere in this Annex } 006-007-00-5		<0.5 mg/kg	1.884	<0.942 mg/kg	<0.0000942 %		<lod< td=""></lod<>
12	8	TPH (C6 to C40) petroleum group		<1 mg/kg		<1 mg/kg	<0.0001 %		<lod< td=""></lod<>
13		naphthalene 601-052-00-2 202-049-5 91-20-3		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
14	۵	acenaphthylene 205-917-1 208-96-8		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
15	8	acenaphthene 201-469-6 83-32-9		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>

Page 4 of 22

#		EU CLP index number	Determinand EC Number	CAS Number	CLP Note	User entered	data	Conv. Factor	Compound conc.	Classification value	MC Applied	Conc. Not Used
16	0	fluorene	201-695-5	86-73-7		<0.01	mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
17	0	phenanthrene	201-581-5	85-01-8		<0.01	mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
18	0	anthracene	204-371-1	120-12-7		<0.01	mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
19	8	fluoranthene	205-912-4	206-44-0		<0.01	mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
20	8	pyrene	204-927-3	129-00-0	_	<0.01	mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
21		benzo[a]anthracen 601-033-00-9	200-280-6	56-55-3		<0.01	mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
22		chrysene 601-048-00-0	205-923-4	218-01-9		<0.01	mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
23		benzo[b]fluoranthe 601-034-00-4	205-911-9	205-99-2	-	<0.01	mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
24		benzo[k]fluoranthe 601-036-00-5	ne 205-916-6	207-08-9	-	<0.01	mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
25		benzo[a]pyrene; be 601-032-00-3	enzo[def]chrysene	50-32-8		<0.01	mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
26	٥	indeno[123-cd]pyre	ene 205-893-2	193-39-5		<0.01	mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
27		dibenz[a,h]anthrac 601-041-00-2	ene 200-181-8	53-70-3		<0.01	mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
28	8	benzo[ghi]perylene	205-883-8	191-24-2		<0.01	mg/kg		<0.01 mg/kg	<0.000001 %	Γ	<lod< td=""></lod<>
29		asbestos 650-013-00-6		12001-28-4 132207-32-0 12172-73-5 77536-66-4 77536-68-6 77536-67-5 12001-29-5		<0.01	mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
									Iotal	0.0364 %	1	

Key

ney	
	User supplied data
	Determinand values ignored for classification, see column 'Conc. Not Used' for reason
	Determinand defined or amended by HazWasteOnline (see Appendix A)
4	Speciated Deteminand - Unless the Determinand is Note 1, the Conversion Factor is used to calculate the compound concentration
<lod< td=""><td>Below limit of detection</td></lod<>	Below limit of detection
ND	Not detected
CLP: Note 1	Only the metal concentration has been used for classification



Classification of sample: BH06

Non Hazardous Waste Classified as 17 05 04 in the List of Waste

.

Sample details

Sample name:	LoW Code:
BH06	Chapter:
Sample Depth:	
1.00 m	Entry:
Moisture content:	
13%	
(dry weight correction)	

17: Construction and Demolition Wastes (including excavated soil from contaminated sites)17 05 04 (Soil and stones other than those mentioned in 17 05 03)

Hazard properties

None identified

Determinands

Moisture content: 13% Dry Weight Moisture Correction applied (MC)

#		Determinand EU CLP index EC Number	LP Note	User entered data	Conv. Factor	Compound conc.	Classification value	1C Applied	Conc. Not Used
		number	ပ					Σ	
1	4	arsenic { arsenic trioxide }		14 ma/ka	1.32	16.358 ma/ka	0.00164 %	1	
		033-003-00-0 215-481-4 1327-53-3		5.5				ľ	
2	4	barium { barium chloride }		92 mg/kg	1.516	123.453 mg/kg	0.0123 %	\checkmark	
		056-004-00-8 233-788-1 10361-37-2							
3	4	cadmium { cadmium oxide }		0.61 mg/kg	1.142	0.617 mg/kg	0.0000617 %	\checkmark	
		048-002-00-0 215-146-2 1306-19-0							
4	4	chromium in chromium(III) compounds { [●] chromium(III) oxide (worst case) }		37 mg/kg	1.462	47.856 mg/kg	0.00479 %	\checkmark	
		215-160-9 1308-38-9							
5	4	copper { <mark>dicopper oxide; copper (I) oxide</mark> }		25 ma/ka	1.126	24.909 ma/ka	0.00249 %	1	
		029-002-00-X 215-270-7 1317-39-1						+	
6	4	lead { lead chromate }	1	16 mg/kg	1.56	22.086 mg/kg	0.00142 %	1	
		082-004-00-2 231-846-0 7758-97-6						-	
7	4	mercury { mercury dichloride }		0.05 mg/kg	1.353	0.0599 mg/kg	0.00000599 %	\checkmark	
		080-010-00-X 231-299-8 7487-94-7							
8	4	nickel { nickel chromate }		32 mg/kg	2.976	84.284 mg/kg	0.00843 %	\checkmark	
		028-035-00-7 238-766-5 14721-18-7							
	4	cadmium sulphoselenide and those specified elsewhere					0.0004.04.0/		
9		in this Annex }		1 mg/kg	1.405	1.243 mg/kg	0.000124 %	\checkmark	
		034-002-00-8							
10	4	zinc { <mark>zinc chromate</mark> }		71 ma/ka	2 774	174.305 ma/ka	0 0174 %	./	
		024-007-00-3 236-878-9 13530-65-9						ľ	
11	4	cyanides { salts of hydrogen cyanide with the exception of complex cyanides such as ferrocyanides, ferricyanides and mercuric oxycyanide and those specified elsewhere in this Annex }		<0.5 mg/kg	1.884	<0.942 mg/kg	<0.0000942 %		<lod< td=""></lod<>
40		TPH (C6 to C40) petroleum group					0.0004.0/		
12		ТРН		<1 mg/кg		<1 mg/kg	<0.0001 %		<lod< td=""></lod<>
12		naphthalene		<0.01 ma/ka		<0.01 ma/ka	<0.000001.9/		
13		601-052-00-2 202-049-5 91-20-3		<0.01 IIIg/kg		<0.01 IIIg/kg	<0.000001 /8		LOD
14		acenaphthylene 205-917-1 208-96-8		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
15	8	acenaphthene		<0.01 ma/ka		<0.01 ma/ka	<0.000001.9/		
10		201-469-6 83-32-9		<0.01 mg/kg		CO.OT ING/Kg	CO.000001 %		

Page 6 of 22

#		EU CLP index number	Determinand EC Number	CAS Number	CLP Note	User entered data	Conv. Facto	. Compound conc.	Classification value	MC Applied	Conc. Not Used
16	0	fluorene	201-695-5	86-73-7		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< th=""></lod<>
17	0	phenanthrene	201-581-5	85-01-8		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
18	۵	anthracene	204-371-1	120-12-7		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< th=""></lod<>
19	۲	fluoranthene	205-912-4	206-44-0		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
20	0	pyrene	204-927-3	129-00-0		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
21		benzo[a]anthracen 601-033-00-9	200-280-6	56-55-3		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
22		chrysene 601-048-00-0	205-923-4	218-01-9	_	<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
23		benzo[b]fluoranthe 601-034-00-4	205-911-9	205-99-2	_	<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
24		benzo[k]fluoranthe 601-036-00-5	205-916-6	207-08-9	_	<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
25		benzo[a]pyrene; be 601-032-00-3	enzo[def]chrysene 200-028-5	50-32-8		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
26	0	indeno[123-cd]pyre	ene 205-893-2	193-39-5		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
27		dibenz[a,h]anthrac 601-041-00-2	ene 200-181-8	53-70-3		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
28	0	benzo[ghi]perylene	e 205-883-8	191-24-2		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
29		asbestos 650-013-00-6		12001-28-4 132207-32-0 12172-73-5 77536-66-4 77536-68-6 77536-67-5 12001-29-5		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
								Total:	0.0489 %		

Key

1.09	
	User supplied data
	Determinand values ignored for classification, see column 'Conc. Not Used' for reason
	Determinand defined or amended by HazWasteOnline (see Appendix A)
4	Speciated Deteminand - Unless the Determinand is Note 1, the Conversion Factor is used to calculate the compound concentration
<lod< td=""><td>Below limit of detection</td></lod<>	Below limit of detection
ND	Not detected
CLP: Note 1	Only the metal concentration has been used for classification



Classification of sample: TP03

Non Hazardous Waste Classified as 17 05 04 in the List of Waste

.

Sample details

Sample name:	LoW Code:
TP03	Chapter:
Sample Depth:	
0.60 m	Entry:
Moisture content:	
11%	
(dry weight correction)	

17: Construction and Demolition Wastes (including excavated soil from contaminated sites)
17 05 04 (Soil and stones other than those mentioned in 17 05 03)

Hazard properties

None identified

Determinands

Moisture content: 11% Dry Weight Moisture Correction applied (MC)

#		EU CLP index EC Number CAS Number	CLP Note	User entered data	Conv. Factor	Compound conc.	Classification value	MC Applied	Conc. Not Used
1	4	arsenic { arsenic trioxide }		7 mg/kg	1.32	8.326 mg/kg	0.000833 %	\checkmark	
2	~	barium { barium chloride }		17 mg/kg	1.516	23.223 mg/kg	0.00232 %	\checkmark	
3	4	cadmium { cadmium oxide } 048-002-00-0 215-146-2 1306-19-0		0.16 mg/kg	1.142	0.165 mg/kg	0.0000165 %	\checkmark	
4	4	chromium in chromium(III) compounds { chromium(III) oxide (worst case) } 215-160-9 1308-38-9		8 mg/kg	1.462	10.534 mg/kg	0.00105 %	~	
5	4	copper { dicopper oxide; copper (I) oxide } 029-002-00-X 215-270-7 1317-39-1		16 mg/kg	1.126	16.229 mg/kg	0.00162 %	\checkmark	
6	~	lead { lead chromate } 082-004-00-2 231-846-0 7758-97-6	1	8.9 mg/kg	1.56	12.507 mg/kg	0.000802 %	\checkmark	
7	~	mercury { mercury dichloride } 080-010-00-X 231-299-8 7487-94-7		<0.05 mg/kg	1.353	<0.0677 mg/kg	<0.0000677 %		<lod< td=""></lod<>
8	4	nickel { nickel chromate } 028-035-00-7 238-766-5 14721-18-7		23 mg/kg	2.976	61.67 mg/kg	0.00617 %	\checkmark	
9	4	selenium { selenium compounds with the exception of cadmium sulphoselenide and those specified elsewhere in this Annex }		0.45 mg/kg	1.405	0.57 mg/kg	0.000057 %	~	
10	4	zinc { zinc chromate } 024-007-00-3 236-878-9 13530-65-9		11 mg/kg	2.774	27.492 mg/kg	0.00275 %	\checkmark	
11	4	cyanides { salts of hydrogen cyanide with the exception of complex cyanides such as ferrocyanides, ferricyanides and mercuric oxycyanide and those specified elsewhere in this Annex }		<0.5 mg/kg	1.884	<0.942 mg/kg	<0.0000942 %		<lod< td=""></lod<>
12	۲	TPH (C6 to C40) petroleum group		<1 mg/kg		<1 mg/kg	<0.0001 %		<lod< td=""></lod<>
13		naphthalene 601-052-00-2 202-049-5 91-20-3		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
14	0	acenaphthylene 205-917-1 208-96-8		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
15	8	acenaphthene 201-469-6 83-32-9		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>

Page 8 of 22

#		EU CLP index number	Determinand EC Number	CAS Number	CLP Note	User entered data	Conv. Facto	. Compound conc.	Classification value	MC Applied	Conc. Not Used
16	0	fluorene	201-695-5	86-73-7		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< th=""></lod<>
17	0	phenanthrene	201-581-5	85-01-8		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
18	0	anthracene	204-371-1	120-12-7		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< th=""></lod<>
19	9	fluoranthene	205-912-4	206-44-0		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
20	٥	pyrene	204-927-3	129-00-0		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
21		benzo[a]anthracen 601-033-00-9	200-280-6	56-55-3		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
22		chrysene 601-048-00-0	205-923-4	218-01-9		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
23		benzo[b]fluoranthe 601-034-00-4	205-911-9	205-99-2	_	<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
24		benzo[k]fluoranthe 601-036-00-5	ne 205-916-6	207-08-9	_	<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
25		benzo[a]pyrene; be 601-032-00-3	enzo[def]chrysene 200-028-5	50-32-8		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
26	8	indeno[123-cd]pyre	ene 205-893-2	193-39-5		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
27		dibenz[a,h]anthrac 601-041-00-2	ene 200-181-8	53-70-3		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
28	8	benzo[ghi]perylene	205-883-8	191-24-2		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
29		asbestos 650-013-00-6		12001-28-4 132207-32-0 12172-73-5 77536-66-4 77536-68-6 77536-67-5 12001-29-5		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
								Iotal:	0.0158 %		

Key

1.09	
	User supplied data
	Determinand values ignored for classification, see column 'Conc. Not Used' for reason
	Determinand defined or amended by HazWasteOnline (see Appendix A)
4	Speciated Deteminand - Unless the Determinand is Note 1, the Conversion Factor is used to calculate the compound concentration
<lod< td=""><td>Below limit of detection</td></lod<>	Below limit of detection
ND	Not detected
CLP: Note 1	Only the metal concentration has been used for classification



Classification of sample: TP04

Non Hazardous Waste Classified as 17 05 04 in the List of Waste

.

Sample details

Sample name:	LoW Code:
TP04	Chapter:
Sample Depth:	
0.50 m	Entry:
Moisture content:	
15%	
(dry weight correction)	

17: Construction and Demolition Wastes (including excavated soil from contaminated sites)
17 05 04 (Soil and stones other than those mentioned in 17 05 03)

Hazard properties

None identified

Determinands

Moisture content: 15% Dry Weight Moisture Correction applied (MC)

#		EU CLP index EC Number CAS Number	CLP Note	User entered data	Conv. Factor	Compound conc.	Classification value	MC Applied	Conc. Not Used
1	4	arsenic { arsenic trioxide }		12 mg/kg	1.32	13.777 mg/kg	0.00138 %	\checkmark	
2	4	barium { barium chloride }		92 mg/kg	1.516	121.306 mg/kg	0.0121 %	\checkmark	
3	4	cadmium { cadmium oxide } 048-002-00-0 215-146-2 1306-19-0		3.2 mg/kg	1.142	3.179 mg/kg	0.000318 %	~	
4	*	chromium in chromium(III) compounds { chromium(III) oxide (worst case) } 215-160-9 1308-38-9		16 mg/kg	1.462	20.335 mg/kg	0.00203 %	~	
5	4	copper { dicopper oxide; copper (I) oxide } 029-002-00-X 215-270-7 1317-39-1		30 mg/kg	1.126	29.371 mg/kg	0.00294 %	\checkmark	
6	4	lead { lead chromate } 082-004-00-2 231-846-0 7758-97-6	1	26 mg/kg	1.56	35.265 mg/kg	0.00226 %	\checkmark	
7	4	mercury { mercury dichloride } 080-010-00-X 231-299-8 7487-94-7		0.05 mg/kg	1.353	0.0588 mg/kg	0.00000588 %	\checkmark	
8	4	nickel { nickel chromate }		56 mg/kg	2.976	144.931 mg/kg	0.0145 %	\checkmark	
9	4	selenium { selenium compounds with the exception of cadmium sulphoselenide and those specified elsewhere in this Annex }		1.2 mg/kg	1.405	1.466 mg/kg	0.000147 %	~	
10	4	zinc { zinc chromate } 024-007-00-3 236-878-9 [13530-65-9		86 mg/kg	2.774	207.458 mg/kg	0.0207 %	\checkmark	
11	*	cyanides { [•] salts of hydrogen cyanide with the exception of complex cyanides such as ferrocyanides, ferricyanides and mercuric oxycyanide and those specified elsewhere in this Annex } 006-007-00-5		<0.5 mg/kg	1.884	<0.942 mg/kg	<0.0000942 %		<lod< td=""></lod<>
12	8	TPH (C6 to C40) petroleum group		<1 mg/kg		<1 mg/kg	<0.0001 %		<lod< td=""></lod<>
13		naphthalene 601-052-00-2 202-049-5 91-20-3		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
14	۲	acenaphthylene 205-917-1 208-96-8		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
15	8	acenaphthene 201-469-6 83-32-9		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>

Page 10 of 22

#		EU CLP index number	Determinand EC Number	CAS Number	CLP Note	User entered data	Conv. Facto	. Compound conc.	Classification value	MC Applied	Conc. Not Used
16	0	fluorene	201-695-5	86-73-7		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< th=""></lod<>
17	0	phenanthrene	201-581-5	85-01-8		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
18	0	anthracene	204-371-1	120-12-7		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< th=""></lod<>
19	0	fluoranthene	205-912-4	206-44-0		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
20	0	pyrene	204-927-3	129-00-0		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
21		benzo[a]anthracen 601-033-00-9	200-280-6	56-55-3		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
22		chrysene 601-048-00-0	205-923-4	218-01-9	_	<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
23		benzo[b]fluoranthe 601-034-00-4	205-911-9	205-99-2	_	<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
24		benzo[k]fluoranthe 601-036-00-5	205-916-6	207-08-9	_	<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
25		benzo[a]pyrene; be 601-032-00-3	enzo[def]chrysene 200-028-5	50-32-8		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
26	۲	indeno[123-cd]pyre	ene 205-893-2	193-39-5		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
27		dibenz[a,h]anthrac 601-041-00-2	:ene 200-181-8	53-70-3		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
28	۲	benzo[ghi]perylene	e 205-883-8	191-24-2		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
29		asbestos 650-013-00-6		12001-28-4 132207-32-0 12172-73-5 77536-66-4 77536-68-6 77536-67-5 12001-29-5		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
								Iotal:	0.0567 %		

Key

1.09	
	User supplied data
	Determinand values ignored for classification, see column 'Conc. Not Used' for reason
	Determinand defined or amended by HazWasteOnline (see Appendix A)
4	Speciated Deteminand - Unless the Determinand is Note 1, the Conversion Factor is used to calculate the compound concentration
<lod< td=""><td>Below limit of detection</td></lod<>	Below limit of detection
ND	Not detected
CLP: Note 1	Only the metal concentration has been used for classification



Classification of sample: TP05

Non Hazardous Waste Classified as 17 05 04 in the List of Waste

.

Sample details

Sample name:	LoW Code:
TP05	Chapter:
Sample Depth:	
2.00 m	Entry:
Moisture content:	
16%	
(dry weight correction)	

17: Construction and Demolition Wastes (including excavated soil from contaminated sites)
17 05 04 (Soil and stones other than those mentioned in 17 05 03)

Hazard properties

None identified

Determinands

Moisture content: 16% Dry Weight Moisture Correction applied (MC)

#		EU CLP index EC Number CAS Number	CLP Note	User entered data	Conv. Factor	Compound conc.	Classification value	MC Applied	Conc. Not Used
		arsenic (arsenic trioxide)	-						
1	•••	033-003-00-0 215-481-4 1327-53-3		4.8 mg/kg	1.32	5.463 mg/kg	0.000546 %	\checkmark	
2	4	barium { barium chloride }		14 mg/kg	1.516	18.301 mg/kg	0.00183 %	\checkmark	
3	4	cadmium { cadmium oxide }		0.14 mg/kg	1.142	0.138 mg/kg	0.0000138 %	\checkmark	
4	4	048-002-00-0 215-146-2 [1306-19-0] chromium in chromium(III) compounds {		7.7 mg/kg	1.462	9.702 mg/kg	0.00097 %	~	
5	4	copper { dicopper oxide; copper (l) oxide } 029-002-00-X 215-270-7 1317-39-1		15 mg/kg	1.126	14.559 mg/kg	0.00146 %	\checkmark	
6	4	lead { lead chromate }	1	7.6 mg/kg	1.56	10.219 mg/kg	0.000655 %	\checkmark	
7	4	mercury { mercury dichloride }		<0.05 mg/kg	1.353	<0.0677 mg/kg	<0.0000677 %		<lod< td=""></lod<>
8	4	nickel { nickel chromate } 028-035-00-7 238-766-5 14721-18-7		32 mg/kg	2.976	82.104 mg/kg	0.00821 %	\checkmark	
9	4	selenium { selenium compounds with the exception of cadmium sulphoselenide and those specified elsewhere in this Annex }		1.9 mg/kg	1.405	2.301 mg/kg	0.00023 %	~	
10	4	zinc { zinc chromate }		12 mg/kg	2.774	28.698 mg/kg	0.00287 %	~	
11	4	cyanides { [•] salts of hydrogen cyanide with the exception of complex cyanides such as ferrocyanides, ferricyanides and mercuric oxycyanide and those specified elsewhere in this Annex }		<0.5 mg/kg	1.884	<0.942 mg/kg	<0.0000942 %		<lod< td=""></lod<>
12	0	TPH (C6 to C40) petroleum group		<1 mg/kg		<1 mg/kg	<0.0001 %		<lod< td=""></lod<>
13		naphthalene 601-052-00-2 202-049-5 91-20-3		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
14	8	acenaphthylene 205-917-1 208-96-8		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
15	0	acenaphthene 201-469-6 83-32-9		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>

Page 12 of 22

#		EU CLP index number	Determinand EC Number	CAS Number	CLP Note	User entered data	Conv. Facto	. Compound conc.	Classification value	MC Applied	Conc. Not Used
16	0	fluorene	201-695-5	86-73-7		<0.01 mg/ł	g	<0.01 mg/kg	<0.000001 %		<lod< th=""></lod<>
17	0	phenanthrene	201-581-5	85-01-8		<0.01 mg/ł	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
18	0	anthracene	204-371-1	120-12-7		<0.01 mg/ł	g	<0.01 mg/kg	<0.000001 %		<lod< th=""></lod<>
19	۵	fluoranthene	205-912-4	206-44-0		<0.01 mg/ł	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
20	0	pyrene	204-927-3	129-00-0		<0.01 mg/ł	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
21		benzo[a]anthracen 601-033-00-9	200-280-6	56-55-3	_	<0.01 mg/ł	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
22		chrysene 601-048-00-0	205-923-4	218-01-9	_	<0.01 mg/ł	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
23		benzo[b]fluoranthe 601-034-00-4	205-911-9	205-99-2	_	<0.01 mg/ł	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
24		benzo[k]fluoranthe 601-036-00-5	205-916-6	207-08-9	_	<0.01 mg/ł	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
25		benzo[a]pyrene; be 601-032-00-3	enzo[def]chrysene 200-028-5	50-32-8		<0.01 mg/ł	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
26	۵	indeno[123-cd]pyre	ene 205-893-2	193-39-5		<0.01 mg/ł	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
27		dibenz[a,h]anthrac 601-041-00-2	200-181-8	53-70-3		<0.01 mg/ł	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
28	۵	benzo[ghi]perylene	e 205-883-8	191-24-2		<0.01 mg/ł	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
29		asbestos 650-013-00-6		12001-28-4 132207-32-0 12172-73-5 77536-66-4 77536-68-6 77536-67-5 12001-29-5		<0.01 mg/ł	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
								Iotal:	0.017 %		

Key

1.09	
	User supplied data
	Determinand values ignored for classification, see column 'Conc. Not Used' for reason
	Determinand defined or amended by HazWasteOnline (see Appendix A)
4	Speciated Deteminand - Unless the Determinand is Note 1, the Conversion Factor is used to calculate the compound concentration
<lod< td=""><td>Below limit of detection</td></lod<>	Below limit of detection
ND	Not detected
CLP: Note 1	Only the metal concentration has been used for classification



Classification of sample: TP06

Non Hazardous Waste Classified as 17 05 04 in the List of Waste

.

Sample details

Sample name:	LoW Code:
TP06	Chapter:
Sample Depth:	
0.50 m	Entry:
Moisture content:	
8.9%	
(dry weight correction)	

17: Construction and Demolition Wastes (including excavated soil from contaminated sites)
17 05 04 (Soil and stones other than those mentioned in 17 05 03)

Hazard properties

None identified

Determinands

Moisture content: 8.9% Dry Weight Moisture Correction applied (MC)

#		Determinand EU CLP index EC Number CAS Number number CAS Number CAS Number	CLP Note	User entered data	Conv. Factor	Compound conc.	Classification value	MC Applied	Conc. Not Used
1	4	arsenic { arsenic trioxide }		4 mg/kg	1.32	4.85 mg/kg	0.000485 %	\checkmark	
2	4	barium { barium chloride }		16 mg/kg	1.516	22.278 mg/kg	0.00223 %	\checkmark	
3	4	cadmium { cadmium oxide } 048-002-00-0 215-146-2 1306-19-0		0.4 mg/kg	1.142	0.42 mg/kg	0.000042 %	\checkmark	
4	4	chromium in chromium(III) compounds { chromium(III) oxide (worst case) }		6 mg/kg	1.462	8.053 mg/kg	0.000805 %	~	
5	4	copper { dicopper oxide; copper (I) oxide } 029-002-00-X 215-270-7 1317-39-1		13 mg/kg	1.126	13.44 mg/kg	0.00134 %	\checkmark	
6	4	lead { lead chromate }	1	9 mg/kg	1.56	12.891 mg/kg	0.000826 %	\checkmark	
7	4	mercury { mercury dichloride } 080-010-00-X 231-299-8 7487-94-7		<0.05 mg/kg	1.353	<0.0677 mg/kg	<0.0000677 %		<lod< td=""></lod<>
8	4	nickel { nickel chromate }		20 mg/kg	2.976	54.661 mg/kg	0.00547 %	\checkmark	
9	4	selenium { selenium compounds with the exception of cadmium sulphoselenide and those specified elsewhere in this Annex }		0.48 mg/kg	1.405	0.619 mg/kg	0.0000619 %	~	
10	4	zinc { zinc chromate }		18 mg/kg	2.774	45.854 mg/kg	0.00459 %	\checkmark	
11	*	cyanides { [•] salts of hydrogen cyanide with the exception of complex cyanides such as ferrocyanides, ferricyanides and mercuric oxycyanide and those specified elsewhere in this Annex } 006-007-00-5	_	<0.5 mg/kg	1.884	<0.942 mg/kg	<0.0000942 %		<lod< td=""></lod<>
12	۵	TPH (C6 to C40) petroleum group		<1 mg/kg		<1 mg/kg	<0.0001 %		<lod< td=""></lod<>
13		naphthalene 601-052-00-2 202-049-5 91-20-3		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
14	۲	acenaphthylene 205-917-1 208-96-8		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
15	8	acenaphthene 201-469-6 83-32-9		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>

Page 14 of 22

#		EU CLP index number	Determinand EC Number	CAS Number	CLP Note	User entered data	Conv. Facto	. Compound conc.	Classification value	MC Applied	Conc. Not Used
16	8	fluorene	201 695 5	86 73 7		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< th=""></lod<>
17	0	phenanthrene	201-581-5	85-01-8		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
18	0	anthracene	204-371-1	120-12-7		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
19	8	fluoranthene	205-912-4	206-44-0		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
20	8	pyrene	204-927-3	129-00-0		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
21		benzo[a]anthracen 601-033-00-9	200-280-6	56-55-3		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
22		chrysene 601-048-00-0	205-923-4	218-01-9	_	<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
23		benzo[b]fluoranthe 601-034-00-4	205-911-9	205-99-2	_	<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
24		benzo[k]fluoranthe 601-036-00-5	ne 205-916-6	207-08-9		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
25		benzo[a]pyrene; be 601-032-00-3	enzo[def]chrysene 200-028-5	50-32-8		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
26	8	indeno[123-cd]pyre	ene 205-893-2	193-39-5		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
27		dibenz[a,h]anthrac 601-041-00-2	ene 200-181-8	53-70-3		<0.01 mg/	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
28	۲	benzo[ghi]perylene	e 205-883-8	191-24-2		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
29		asbestos 650-013-00-6		12001-28-4 132207-32-0 12172-73-5 77536-66-4 77536-68-6 77536-67-5 12001-29-5		<0.01 mg/l	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
								Total:	0.0161 %		

Key

1.09	
	User supplied data
	Determinand values ignored for classification, see column 'Conc. Not Used' for reason
	Determinand defined or amended by HazWasteOnline (see Appendix A)
4	Speciated Deteminand - Unless the Determinand is Note 1, the Conversion Factor is used to calculate the compound concentration
<lod< td=""><td>Below limit of detection</td></lod<>	Below limit of detection
ND	Not detected
CLP: Note 1	Only the metal concentration has been used for classification



Classification of sample: TP07

Non Hazardous Waste Classified as 17 05 04 in the List of Waste

.

Sample details

Sample name:	LoW Code:
TP07	Chapter:
Sample Depth:	
0.50 m	Entry:
Moisture content:	
14%	
(dry weight correction)	

17: Construction and Demolition Wastes (including excavated soil from contaminated sites)
17 05 04 (Soil and stones other than those mentioned in 17 05 03)

Hazard properties

None identified

Determinands

Moisture content: 14% Dry Weight Moisture Correction applied (MC)

#		EU CLP index EC Number CAS Number	CLP Note	User entered data	Conv. Factor	Compound conc.	Classification value	MC Applied	Conc. Not Used
1	4	arsenic { arsenic trioxide }		8.4 mg/kg	1.32	9.729 mg/kg	0.000973 %	\checkmark	
2	4	barium { barium chloride }		39 mg/kg	1.516	51.874 mg/kg	0.00519 %	\checkmark	
3	4	cadmium { cadmium oxide }		0.87 mg/kg	1.142	0.872 mg/kg	0.0000872 %	\checkmark	
4	4	chromium in chromium(III) compounds { chromium(III) oxide (worst case) }		14 mg/kg	1.462	17.949 mg/kg	0.00179 %	~	
5	~	copper { dicopper oxide; copper (I) oxide } 029-002-00-X 215-270-7 1317-39-1		16 mg/kg	1.126	15.802 mg/kg	0.00158 %	\checkmark	
6	4	lead { lead chromate } 082-004-00-2 231-846-0 7758-97-6	1	15 mg/kg	1.56	20.524 mg/kg	0.00132 %	\checkmark	
7	4	mercury { mercury dichloride } 080-010-00-X 231-299-8 7487-94-7		<0.05 mg/kg	1.353	<0.0677 mg/kg	<0.0000677 %		<lod< td=""></lod<>
8	4	nickel { nickel chromate } 028-035-00-7 238-766-5 [14721-18-7		28 mg/kg	2.976	73.101 mg/kg	0.00731 %	\checkmark	
9	4	selenium { selenium compounds with the exception of cadmium sulphoselenide and those specified elsewhere in this Annex }		0.56 mg/kg	1.405	0.69 mg/kg	0.000069 %	~	
10	4	zinc { zinc chromate } 024-007-00-3 236-878-9 13530-65-9		59 mg/kg	2.774	143.574 mg/kg	0.0144 %	\checkmark	
11	4	cyanides { [•] salts of hydrogen cyanide with the exception of complex cyanides such as ferrocyanides, ferricyanides and mercuric oxycyanide and those specified elsewhere in this Annex } 006-007-00-5		<0.5 mg/kg	1.884	<0.942 mg/kg	<0.0000942 %		<lod< td=""></lod<>
12	۲	TPH (C6 to C40) petroleum group		<1 mg/kg		<1 mg/kg	<0.0001 %		<lod< td=""></lod<>
13		naphthalene 601-052-00-2 202-049-5 91-20-3		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
14	8	acenaphthylene 205-917-1 208-96-8		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
15	٥	acenaphthene 201-469-6 83-32-9		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>

Page 16 of 22

#		EU CLP index number	Determinand EC Number	CAS Number	CLP Note	User entered data	Conv. Factor	Compound conc.	Classification value	MC Applied	Conc. Not Used
16	0	fluorene	201-695-5	86-73-7	_	<0.01 mg/kg	1	<0.01 mg/kg	<0.000001 %		<lod< th=""></lod<>
17	0	phenanthrene	201-581-5	85-01-8	_	<0.01 mg/kg	9	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
18	0	anthracene	204-371-1	120-12-7		<0.01 mg/kg	9	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
19	0	fluoranthene	205-912-4	206-44-0		<0.01 mg/kg	1	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
20	8	pyrene	204-927-3	129-00-0		<0.01 mg/kg	1	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
21		benzo[a]anthracen 601-033-00-9	200-280-6	56-55-3	_	<0.01 mg/kg	1	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
22		chrysene 601-048-00-0	205-923-4	218-01-9	_	<0.01 mg/kg	1	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
23		benzo[b]fluoranthe 601-034-00-4	205-911-9	205-99-2	_	<0.01 mg/kg	1	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
24		benzo[k]fluoranthe 601-036-00-5	ne 205-916-6	207-08-9		<0.01 mg/kg	1	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
25		benzo[a]pyrene; be 601-032-00-3	enzo[def]chrysene	50-32-8		<0.01 mg/kg	1	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
26	٥	indeno[123-cd]pyre	ene 205-893-2	193-39-5		<0.01 mg/kg	1	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
27		dibenz[a,h]anthrac 601-041-00-2	ene 200-181-8	53-70-3		<0.01 mg/kg	1	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
28	٥	benzo[ghi]perylene	e 205-883-8	191-24-2	_	<0.01 mg/kg	1	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
29		asbestos 650-013-00-6		12001-28-4 132207-32-0 12172-73-5 77536-66-4 77536-68-6 77536-67-5 12001-29-5		<0.01 mg/kg	1	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
								Iotal:	0.0329 %	1	

Key

ney	
	User supplied data
	Determinand values ignored for classification, see column 'Conc. Not Used' for reason
	Determinand defined or amended by HazWasteOnline (see Appendix A)
4	Speciated Deteminand - Unless the Determinand is Note 1, the Conversion Factor is used to calculate the compound concentration
<lod< td=""><td>Below limit of detection</td></lod<>	Below limit of detection
ND	Not detected
CLP: Note 1	Only the metal concentration has been used for classification



Classification of sample: TP10

Non Hazardous Waste Classified as 17 05 04 in the List of Waste

.

Sample details

Sample name:	LoW Code:
TP10	Chapter:
Sample Depth:	
1.50 m	Entry:
Moisture content:	
9.2%	
(dry weight correction)	

17: Construction and Demolition Wastes (including excavated soil from contaminated sites)
17 05 04 (Soil and stones other than those mentioned in 17 05 03)

Hazard properties

None identified

Determinands

Moisture content: 9.2% Dry Weight Moisture Correction applied (MC)

#		Determinand EU CLP index EC Number CAS Number number CAS Number CAS Number	CLP Note	User entered data	Conv. Factor	Compound conc.	Classification value	MC Applied	Conc. Not Used
1	4	arsenic { arsenic trioxide }		8.9 mg/kg	1.32	10.761 mg/kg	0.00108 %	\checkmark	
2	4	barium { barium chloride }		21 mg/kg	1.516	29.16 mg/kg	0.00292 %	\checkmark	
3	4	cadmium { cadmium oxide }		0.47 mg/kg	1.142	0.492 mg/kg	0.0000492 %	\checkmark	
4	4	chromium in chromium(III) compounds { chromium(III) oxide (worst case) }		6.5 mg/kg	1.462	8.7 mg/kg	0.00087 %	~	
5	æ	copper { dicopper oxide; copper (l) oxide } 029-002-00-X 215-270-7 1317-39-1		18 mg/kg	1.126	18.559 mg/kg	0.00186 %	\checkmark	
6	4	lead { lead chromate } 082-004-00-2 231-846-0 7758-97-6	1	43 mg/kg	1.56	61.421 mg/kg	0.00394 %	\checkmark	
7	4	mercury { mercury dichloride } 080-010-00-X 231-299-8 7487-94-7		0.6 mg/kg	1.353	0.744 mg/kg	0.0000744 %	\checkmark	
8	4	nickel { nickel chromate } 028-035-00-7 238-766-5 14721-18-7		24 mg/kg	2.976	65.412 mg/kg	0.00654 %	\checkmark	
9	4	selenium { selenium compounds with the exception of cadmium sulphoselenide and those specified elsewhere in this Annex }		1.5 mg/kg	1.405	1.93 mg/kg	0.000193 %	~	
10	4	zinc { zinc chromate } 024-007-00-3 236-878-9 13530-65-9		41 mg/kg	2.774	104.158 mg/kg	0.0104 %	\checkmark	
11	4	cyanides { salts of hydrogen cyanide with the exception of complex cyanides such as ferrocyanides, ferricyanides and mercuric oxycyanide and those specified elsewhere in this Annex } 006-007-00-5		<0.5 mg/kg	1.884	<0.942 mg/kg	<0.0000942 %		<lod< td=""></lod<>
12	0	TPH (C6 to C40) petroleum group		<1 mg/kg		<1 mg/kg	<0.0001 %		<lod< td=""></lod<>
13		naphthalene 601-052-00-2 202-049-5 91-20-3		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
14	0	acenaphthylene 205-917-1 208-96-8		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
15	8	acenaphthene 201-469-6 83-32-9		<0.01 mg/kg		<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>

Page 18 of 22

#		EU CLP index number	Determinand EC Number	CAS Number	CLP Note	User entered data	Conv. Factor	Compound conc.	Classification value	MC Applied	Conc. Not Used
16	0	fluorene	201-695-5	86-73-7		<0.01 mg/k	g	<0.01 mg/kg	<0.000001 %		<lod< th=""></lod<>
17	0	phenanthrene	201-581-5	85-01-8		<0.01 mg/k	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
18	0	anthracene	204-371-1	120-12-7		<0.01 mg/k	g	<0.01 mg/kg	<0.000001 %		<lod< th=""></lod<>
19	0	fluoranthene	205-912-4	206-44-0		<0.01 mg/k	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
20	٥	pyrene	204-927-3	129-00-0		<0.01 mg/k	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
21		benzo[a]anthracen 601-033-00-9	200-280-6	56-55-3		<0.01 mg/k	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
22		chrysene 601-048-00-0	205-923-4	218-01-9	_	<0.01 mg/k	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
23		benzo[b]fluoranthe 601-034-00-4	205-911-9	205-99-2	_	<0.01 mg/k	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
24		benzo[k]fluoranthe 601-036-00-5	ne 205-916-6	207-08-9		<0.01 mg/k	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
25		benzo[a]pyrene; be 601-032-00-3	enzo[def]chrysene 200-028-5	50-32-8		<0.01 mg/k	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
26	8	indeno[123-cd]pyre	ene 205-893-2	193-39-5		<0.01 mg/k	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
27		dibenz[a,h]anthrac 601-041-00-2	:ene 200-181-8	53-70-3		<0.01 mg/k	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
28	۲	benzo[ghi]perylene	e 205-883-8	191-24-2		<0.01 mg/k	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
29		asbestos 650-013-00-6		12001-28-4 132207-32-0 12172-73-5 77536-66-4 77536-68-6 77536-67-5 12001-29-5		<0.01 mg/k	g	<0.01 mg/kg	<0.000001 %		<lod< td=""></lod<>
								Total:	0.0281 %		

Key

1.09	
	User supplied data
	Determinand values ignored for classification, see column 'Conc. Not Used' for reason
	Determinand defined or amended by HazWasteOnline (see Appendix A)
4	Speciated Deteminand - Unless the Determinand is Note 1, the Conversion Factor is used to calculate the compound concentration
<lod< td=""><td>Below limit of detection</td></lod<>	Below limit of detection
ND	Not detected
CLP: Note 1	Only the metal concentration has been used for classification

Appendix A: Classifier defined and non GB MCL determinands

• chromium(III) oxide (worst case) (EC Number: 215-160-9, CAS Number: 1308-38-9)

Description/Comments: Data from C&L Inventory Database

Data source: https://echa.europa.eu/information-on-chemicals/cl-inventory-database/-/discli/details/33806

Data source date: 17 Jul 2015 Hazard Statements: Acute Tox. 4; H332 , Acute Tox. 4; H302 , Eye Irrit. 2; H319 , STOT SE 3; H335 , Skin Irrit. 2; H315 , Resp. Sens. 1; H334 , Skin Sens. 1; H317 , Repr. 1B; H360FD , Aquatic Acute 1; H400 , Aquatic Chronic 1; H410

• salts of hydrogen cyanide with the exception of complex cyanides such as ferrocyanides, ferricyanides and mercuric oxycyanide and those specified elsewhere in this Annex

GB MCL index number: 006-007-00-5

Description/Comments: Conversion factor based on a worst case compound: sodium cyanide Additional Hazard Statement(s): EUH032 >= 0.2 % Reason for additional Hazards Statement(s): 20 Nov 2021 - EUH032 >= 0.2 % hazard statement sourced from: WM3, Table C12.2

• TPH (C6 to C40) petroleum group (CAS Number: TPH)

Description/Comments: Hazard statements taken from WM3 1st Edition 2015; Risk phrases: WM2 3rd Edition 2013 Data source: WM3 1st Edition 2015 Data source date: 25 May 2015 Hazard Statements: Flam. Liq. 3; H226 , Asp. Tox. 1; H304 , STOT RE 2; H373 , Muta. 1B; H340 , Carc. 1B; H350 , Repr. 2; H361d , Aquatic Chronic 2; H411

acenaphthylene (EC Number: 205-917-1, CAS Number: 208-96-8)

Description/Comments: Data from C&L Inventory Database

Data source: http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database

Data source date: 17 Jul 2015

Hazard Statements: Acute Tox. 4; H302 , Acute Tox. 1; H330 , Acute Tox. 1; H310 , Eye Irrit. 2; H319 , STOT SE 3; H335 , Skin Irrit. 2; H315

acenaphthene (EC Number: 201-469-6, CAS Number: 83-32-9)

Description/Comments: Data from C&L Inventory Database Data source: http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database Data source date: 17 Jul 2015 Hazard Statements: Eye Irrit. 2; H319 , STOT SE 3; H335 , Skin Irrit. 2; H315 , Aquatic Acute 1; H400 , Aquatic Chronic 1; H410 , Aquatic Chronic 2; H411

• fluorene (EC Number: 201-695-5, CAS Number: 86-73-7)

Description/Comments: Data from C&L Inventory Database Data source: http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database Data source date: 06 Aug 2015 Hazard Statements: Aquatic Acute 1; H400 , Aquatic Chronic 1; H410

• phenanthrene (EC Number: 201-581-5, CAS Number: 85-01-8)

Description/Comments: Data from C&L Inventory Database Data source: http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database Data source date: 06 Aug 2015 Hazard Statements: Acute Tox. 4; H302 , Eye Irrit. 2; H319 , STOT SE 3; H335 , Carc. 2; H351 , Skin Sens. 1; H317 , Aquatic Acute 1; H400 , Aquatic Chronic 1; H410 , Skin Irrit. 2; H315

^a anthracene (EC Number: 204-371-1, CAS Number: 120-12-7)

Description/Comments: Data from C&L Inventory Database Data source: http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database Data source date: 17 Jul 2015 Hazard Statements: Eye Irrit. 2; H319 , STOT SE 3; H335 , Skin Irrit. 2; H315 , Skin Sens. 1; H317 , Aquatic Acute 1; H400 , Aquatic Chronic 1; H410

• fluoranthene (EC Number: 205-912-4, CAS Number: 206-44-0)

Description/Comments: Data from C&L Inventory Database Data source: http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database Data source date: 21 Aug 2015 Hazard Statements: Acute Tox. 4; H302, Aquatic Acute 1; H400, Aquatic Chronic 1; H410

• pyrene (EC Number: 204-927-3, CAS Number: 129-00-0)

Description/Comments: Data from C&L Inventory Database; SDS Sigma Aldrich 2014 Data source: http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database Data source date: 21 Aug 2015 Hazard Statements: Skin Irrit. 2; H315 , Eye Irrit. 2; H319 , STOT SE 3; H335 , Aquatic Acute 1; H400 , Aquatic Chronic 1; H410


indeno[123-cd]pyrene (EC Number: 205-893-2, CAS Number: 193-39-5)

Description/Comments: Data from C&L Inventory Database Data source: http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database Data source date: 06 Aug 2015 Hazard Statements: Carc. 2; H351

• benzo[ghi]perylene (EC Number: 205-883-8, CAS Number: 191-24-2)

Description/Comments: Data from C&L Inventory Database; SDS Sigma Aldrich 28/02/2015 Data source: http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database Data source date: 23 Jul 2015 Hazard Statements: Aquatic Acute 1; H400 , Aquatic Chronic 1; H410

Appendix B: Rationale for selection of metal species

arsenic {arsenic trioxide}

Reasonable case CLP species based on hazard statements/molecular weight and most common (stable) oxide of arsenic. Industrial sources include: smelting; main precursor to other arsenic compounds.

barium {barium chloride}

More likely species

cadmium {cadmium oxide}

Reasonable case CLP species based on hazard statements/molecular weight, very low solubility in water. Industrial sources include: electroplating baths, electrodes for storage batteries, catalysts, ceramic glazes, phosphors, pigments and nematocides. Worst case compounds in CLP: cadmium sulphate, chloride, fluoride & iodide not expected as either very soluble and/or compound's industrial usage not related to site history.

chromium in chromium(III) compounds {chromium(III) oxide (worst case)}

Reasonable case species based on hazard statements/molecular weight. Industrial sources include: tanning, pigment in paint, inks and glass.

copper {dicopper oxide; copper (I) oxide}

Reasonable case CLP species based on hazard statements/molecular weight and insolubility in water. Industrial sources include: oxidised copper metal, brake pads, pigments, antifouling paints, fungicide. Worse case copper sulphate is very soluble and likely to have been leached away if ever present and/or not enough soluble sulphate detected.

lead {lead chromate}

Worst case CLP species based on hazard statements/molecular weight.

mercury {mercury dichloride}

Worst case CLP species based on hazard statements/molecular weight.

nickel {nickel chromate}

Worst case CLP species based on hazard statements/molecular weight.

selenium (selenium compounds with the exception of cadmium sulphoselenide and those specified elsewhere in this Annex)

Harmonised group entry used as most reasonable case. Pigment cadmium sulphoselenide not likely to be present in this soil. No evidence for the other CLP entries: sodium selenite, nickel II selenite and nickel selenide, to be present in this soil.

zinc {zinc chromate}

Worst case CLP species based on hazard statements/molecular weight.

cyanides {salts of hydrogen cyanide with the exception of complex cyanides such as ferrocyanides, ferricyanides and mercuric oxycyanide and those specified elsewhere in this Annex}

Harmonised group entry used as most reasonable case as complex cyanides and those specified elsewhere in the annex are not likely to be present in this soil: [Note conversion factor based on a worst case compound: sodium cyanide].

Appendix C: Version

HazWasteOnline Classification Engine: WM3 1st Edition v1.2.GB - Oct 2021 HazWasteOnline Classification Engine Version: 2022.255.5323.9951 (12 Sep 2022) HazWasteOnline Database: 2022.255.5323.9951 (12 Sep 2022)



This classification utilises the following guidance and legislation: WM3 v1.2.GB - Waste Classification - 1st Edition v1.2.GB - Oct 2021 CLP Regulation - Regulation 1272/2008/EC of 16 December 2008 1st ATP - Regulation 790/2009/EC of 10 August 2009 2nd ATP - Regulation 286/2011/EC of 10 March 2011 3rd ATP - Regulation 618/2012/EU of 10 July 2012 4th ATP - Regulation 487/2013/EU of 8 May 2013 Correction to 1st ATP - Regulation 758/2013/EU of 7 August 2013 5th ATP - Regulation 944/2013/EU of 2 October 2013 6th ATP - Regulation 605/2014/EU of 5 June 2014 WFD Annex III replacement - Regulation 1357/2014/EU of 18 December 2014 Revised List of Waste 2014 - Decision 2014/955/EU of 18 December 2014 7th ATP - Regulation 2015/1221/EU of 24 July 2015 8th ATP - Regulation (EU) 2016/918 of 19 May 2016 9th ATP - Regulation (EU) 2016/1179 of 19 July 2016 10th ATP - Regulation (EU) 2017/776 of 4 May 2017 HP14 amendment - Regulation (EU) 2017/997 of 8 June 2017 13th ATP - Regulation (EU) 2018/1480 of 4 October 2018 14th ATP - Regulation (EU) 2020/217 of 4 October 2019 15th ATP - Regulation (EU) 2020/1182 of 19 May 2020 The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use)(Amendment etc.) (EU Exit) Regulations 2020 - UK: 2020 No. 1567 of 16th December 2020 The Waste and Environmental Permitting etc. (Legislative Functions and Amendment etc.) (EU Exit) Regulations 2020 - UK: 2020 No. 1540 of 16th December 2020 GB MCL List - version 1.1 of 09 June 2021