



APPENDIX 4-6

DRAINAGE DESIGN DRAWINGS

ITION NOTES:

SEWER MANAGEMENT PROCEDURES ARE INTENDED TO ENFORCE
STRICT REQUIREMENTS FOR POLLUTION, SALT AND BRINE,
AND DREDGING AND RECLAMATION ACTIVITIES IN WATERS WILL BE MAINTAINED.
SILT, WATER CANISTER, AND OTHER SOLID WASTE MATERIALS
ARE PROHIBITED FROM DEPARTING EXCAVATIONS.
EXCAVATED SEDIMENT, GROUND, SOIL, OR STONE IS TO BE STORED
IN DESIGNATED STAGING AREAS. TEMPORARY STOCKPILE AREA(S) ARE TO BE LOCATED AS FAR AS POSSIBLE FROM EXCAVATION AREAS.
ALL DRAINAGE DISCHARGE IS TO BE MADE OVER OPEN GROUNDS
OR INTO AN APPROPRIATE POLLUTION AREA. DRAINS ARE TO BE PLACED IN A LINEAL
MANUFACTURED DRAINAGE TRENCH OR DITCH. DRAINS ARE TO BE LOCATED AS FAR AS POSSIBLE FROM EXCAVATION AREAS.
ALL DRAINAGE DISCHARGE IS TO BE MADE OVER OPEN GROUNDS
OR INTO AN APPROPRIATE POLLUTION AREA. DRAINS ARE TO BE PLACED IN A LINEAL
MANUFACTURED DRAINAGE TRENCH OR DITCH. DRAINS ARE TO BE LOCATED AS FAR AS POSSIBLE FROM EXCAVATION AREAS.
TREATMENT IN THESE SEWARS IS NOT REQUIRED. EXCAVATION AREAS ARE TO BE DUG OUT AS NECESSARY TO MAINTAIN A DRY WORKING ENVIRONMENT. EXCAVATION AREAS ARE TO BE DUG OUT AS NECESSARY TO MAINTAIN A DRY WORKING ENVIRONMENT. EXCAVATION AREAS ARE TO BE DUG OUT AS NECESSARY TO MAINTAIN A DRY WORKING ENVIRONMENT.
THE FLOW VELOCITIES OR USE OF SPLASH PLATES, AND
THE USE OF DREDGE SPREADERS ARE PROHIBITED. THIS WILL

The diagram illustrates the spatial distribution of planning application areas for a wind farm. It features a central grey rectangular area labeled 'PLANNING APPLICATION AREA'. Surrounding this central area are several colored rectangles representing different zones:

- Red rectangle (top-left):** Labeled 'EXISTING GROUND SURFACE' and 'CONTOUR (1 M INTERVAL)'.
- Blue rectangle (top-right):** Labeled 'TURBINE AND SWEPT AREA'.
- Orange rectangle (bottom-left):** Labeled 'PROPOSED NEW ROADS'.
- Grey rectangle (bottom-right):** Labeled 'EXISTING ROADS PROPOSED TO BE UPGRADED'.
- Pink rectangle (far bottom-right):** Labeled 'TEMPORARY CONSTRUCTION'.

```

graph TD
    ENTRANCE[ENTRANCE] --> CONSTRUCTION[CONSTRUCTION TYPE]
    CONSTRUCTION --> TEMPORARY[TEMPORARY CONSTRUCTION]
    CONSTRUCTION --> PERMANENT[PERMANENT CONSTRUCTION]
    TEMPORARY --> SPOL[SPOL MANAGEMENT AREA]
    TEMPORARY --> HASTOARD[HASTOARD]
    TEMPORARY --> CABLE[ELectricity CABLE TRUNCH]
    PERMANENT --> CONTRACT[CONTRACT FOR BIDDING]
    PERMANENT --> PLANNING[PLANNING APPLICATION]
    CONTRACT --> BIDDING[BIDDING]
    PLANNING --> APPROVAL[APPROVAL]
    BIDDING --> APPROVAL
  
```

- CUT AREA
- FL. AREA
- DISTANCE FROM THE PROPOSED INFRASTRUCTURE TO THE APLANTATION SITE BOUNDARY
- POTENTIAL GRAVITY FLOW PATHS ARE MODELLED BASED ON DRAINAGE DATA AND DO NOT INDICATE THE PRESENCE OF DRAIN OR WATER-CARVEED BY A MEASURE TO GROUND, AND THERE ARE NO IMPACT NATURAL FEATURES, SUCH AS A CREEK, RIVER, OR STREAM.

The Key Plan diagram illustrates the locations of three dams (D105, D104, and D102) along the U.S. Route 19 corridor. The corridor is represented by a dashed line. Dams D105 and D104 are located upstream, while Dam D102 is located downstream. The diagram also shows the location of the U.S. Route 19 bridge.

DRAWING NOTES:
DRAWINGS ISSUED ARE FOR PLANNING APPLICATION PURPOSES
ONLY.
2. COPYRIGHT, ALL RIGHTS RESERVED. NO PART HEREIN
MAY BE COPIED OR REPRODUCED PARTIALLY OR WHOLLY IN ANY
FORM.

Ordnance Survey Ireland Licence No. 004424
© Ordnance Survey Ireland/Government of Ireland

HYDRO
ELECTRIC



Laur Clavaugh Ltd

Environmental Services


221 Lower Main Street, Dungarvan, Co. Waterford, Ireland.

Tel: +353 (0) 58 44122
Fax: +353 (0) 58 42444
Email: info@environmental.ie
Web: www.environmental.ie


Client:

Job: LAURAVAGH RENEWABLE ENERGY
DEVELOPMENT, CO. GALWAY
Title: PROPOSED DRAINAGE LAYOUT

Figure No:	D103
Drawing No:	P1574-0-0324-A1-D103-000
Sheet Size:	A1
Scale:	1:2000 [A1]
Date:	11/03/2024
Drawn By:	GA
Checked By:	MGM
Project No.:	P1574-0




DETAIL A



INfiltration Area
Schematic - Not to Scale

DETAIL B




TYPICAL UNDER TRACK DRAINAGE
SCALE 1:20

NOTE:
150-300mm diameter HDPE pipes for
existing drainage pathways
to discharge to trackside infiltration
drain or infiltration area.


NOTE:
150-300mm diameter HDPE pipes
discharge to downstream infiltration drain
or infiltration area.

DETAIL C



TYPE X - CHECK DAM DETAIL
SCALE 1:50


DETAIL E



TEMPORARY CONCRETE WASH OUT PIT
SCALE 1:50


TYPE X - CHECK DAM DETAIL
SCALE 1:50

DETAIL D




TYPE COLLECTOR DITCH WITH INFILTRATION
SCALE 1:50

DETAIL B



TYPICAL LAND DRAIN
SCALE 1:20

Date	Description	Chkd	Signed



Project Description:	NOTE
I. Drawings used are for engineering stage only.	2. Drawings are to be used for engineering purposes only. No part of these drawings may be reproduced in whole or in part without the written consent of the author. 3. The author reserves all rights to these drawings. 4. The author is a Hydro Environmental Services Ltd. company. 5. Drawings are to be returned to the author on completion of the project.
	6. Drawings are to be stored for 10 years after completion of the project.
	7. Drawings are to be stored for 10 years after completion of the project.
	8. Drawings are to be stored for 10 years after completion of the project.

Figure No:	D501
Drawing No:	P1-574-0-0324-A1-1501-008
Sheet Size:	A1
Project No:	P1-574-0
Scale:	as shown (A1)
Drawn By:	MCGA
Checked By:	AG
Date:	06/03/2004
Checked By:	AG