



The drawing consists of two parts: a plan view (top) and a typical section (bottom).

**Plan View (Top):** Shows a rectangular area representing the tactile paving zone. Labels include:
 

- 400x400x50 BUFF TACTILE PAVING ZONE, WHERE APPLICABLE
- REAR OF FOOTWAY
- 0.8m TACTILE PAVING DEPTH (1.2m DEEP AT IN-LINE CROSSINGS)
- 2.0m min TACTILE PAVING WIDTH
- TAPER/ INSITU KERB
- STANDARD INSITU KERB
- CENTRAL KERBS TO BE FLUSH WITH CARRIAGEWAY SURFACE AND PAINTED WHITE

**Typical Section (Bottom):** Shows a cross-section of the crossing. Labels include:
 

- FOOTPATH
- 1:20 (gradient)
- 400x400x50 TACTILE PAVIOUR CAST INTO CONCRETE FOOTPATH
- 6mm MAX DIS (upstand)
- CARRIAGEWAY
- INSITU CONCRETE KERB
- VARIABLE WIDTH, SHOULD NOT BE LESS THAN THAT REQUIRED TO ACHIEVE A GRADIENT OF 1:12 MAXIMUM

**UNCONTROLLED DISHED CROSSING WITH TACTILE PAVING**  
SCALE 1:50

**TYPICAL SECTION THROUGH DISHED CROSSING**  
SCALE 1:25

FIGURE 5A

